

Public-law institution jointly founded by the  
federal states and the Federation

**European Technical Assessment Body  
for construction products**



## European Technical Assessment

**ETA-25/0390  
of 17 September 2025**

English translation prepared by DIBt - Original version in German language

### General Part

Technical Assessment Body issuing the  
European Technical Assessment:

Deutsches Institut für Bautechnik

Trade name of the construction product

einZA Schimmelschutz Systemplatte  
einZA Schimmelschutz Laibungsplatte  
einZA Schimmelschutz Keilplatte

Product family  
to which the construction product belongs

Thermal insulation board made of mineral material

Manufacturer

einZA Farben GmbH & Co KG  
Junkersstraße 13  
30179 Hannover  
GERMANY

Manufacturing plant

Werk 3

This European Technical Assessment  
contains

6 pages which form an integral part of this assessment

This European Technical Assessment is  
issued in accordance with Regulation (EU)  
No 305/2011, on the basis of

040012-00-1201

This version replaces

ETA-25/0390 issued on 24 April 2025

The European Technical Assessment is issued by the Technical Assessment Body in its official language. Translations of this European Technical Assessment in other languages shall fully correspond to the original issued document and shall be identified as such.

Communication of this European Technical Assessment, including transmission by electronic means, shall be in full. However, partial reproduction may only be made with the written consent of the issuing Technical Assessment Body. Any partial reproduction shall be identified as such.

This European Technical Assessment may be withdrawn by the issuing Technical Assessment Body, in particular pursuant to information by the Commission in accordance with Article 25(3) of Regulation (EU) No 305/2011.

## Specific part

### 1 Technical description of the product

This European Technical Assessment applies to the factory-made thermal insulation boards made of calcium silicate and cellulose fibres with the designation "einza Schimmelschutz Systemplatte", hereafter referred to as thermal insulation boards.

The thermal insulation boards are high-pressure steam cured (autoclaved).

The surface of the thermal insulation boards can be one-side structured with slots up to approx. 1 mm.

The thermal insulation boards are made of calcium silicate and cellulose fibres and they are not coated or laminated.

The thermal insulation boards are made with the following dimensions:

Nominal thickness: 20 mm to 120 mm

Nominal length: 625 mm and 1250 mm

Nominal widths: 500 mm and 1000 mm

The products "einza Schimmelschutz Laibungsplatte" and "einza Schimmelschutz Keilplatte" sawn out of the above mentioned thermal insulation boards are also covered by the European Technical Assessment.

Nominal dimensions of "einza Schimmelschutz Laibungsplatte": 500 mm x 250 mm x 18 mm

Nominal dimensions of "einza Schimmelschutz Keilplatte": 625 mm x 250 mm x 26/2 mm

The European Technical Assessment has been issued for the product on the basis of agreed data/information, deposited with Deutsches Institut für Bautechnik, which identifies the product that has been assessed. The European Technical Assessment applies only to products corresponding to this agreed data/information.

### 2 Specification of the intended use in accordance with the applicable European Assessment Document

The thermal insulation boards can be used for the following intended uses:

- Internal insulation of ceilings (underside) or roofs
- Internal insulation of floors or bedplates (on the top) below floor screed without protection against noise requirements
- Internal insulation of walls

The performance according to section 3 only applies if the thermal insulation boards are installed according to the manufacture's installation instructions and if they are protected from precipitation, wetting or weathering in built-in state and during transport, storage and installation.

Concerning the application of the thermal insulation boards, also the respective national regulations shall be observed. The design value of the thermal conductivity shall be laid down according to relevant national provisions.

When calculating the thermal resistance, the nominal thickness of the thermal insulation boards shall be applied.

Where the thermal insulation boards are fixed by using adhesives and/or anchors, only such adhesions or anchors shall be used, which are suitable for this purpose. The assessment of these fixings is not subject of this European Technical Assessment.

The verifications and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the thermal insulating boards of at least 50 years.

The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

### 3 Performance of the product and references to the methods used for its assessment

For sampling, conditioning and testing the provisions of the EAD No 040012-00-1201 "Thermal insulation board made of mineral material".

#### 3.1 Safety in case of fire (BWR 2)

Essential characteristic	Performance
<b>Reaction to fire</b> Test acc. to EN ISO 1182:2020 and EN ISO 1716:2018	Class A1 acc. to EN 13501-1:2018 <sup>1</sup>

#### 3.2 Hygiene, health and the environment (BWR 3)

Essential characteristic	Performance
<b>Content and/or release of dangerous substances</b>	The product does not contain or release dangerous substances according to EOTA TR034 (version April 2014).
<b>Water vapour diffusion resistance coefficient</b> Test acc. to EN 12086:2013, climatic condition set A	$\mu = 3$

#### 3.3 Energy economy and heat retention (BWR 6)

Essential characteristic	Performance
<b>Thermal conductivity</b> at mean reference temperature of 10 °C Test acc. to EN 12667:2001	Declared value for a moisture content of the insulation boards at 23 °C and 50 % relative humidity: $\lambda_{D(23,50)} = 0.075 \text{ W/(m} \cdot \text{K)}^2$
Conversion of humidity acc. to EN ISO 10456:2007/AC:2009	
Mass-related moisture content at 23 °C/ 50 % rel. humidity	$u_{23,50} = 0.013 \text{ kg/kg}$
Mass-related moisture content at 23 °C/ 80 % rel. humidity	$u_{23,80} = 0.018 \text{ kg/kg}$
Mass-related moisture conversion coefficient (dry to 23 °C/ 50 % rel. humidity)	$f_{u1} = 1.41$
Mass-related moisture conversion coefficient (23 °C/ 50 % rel. humidity to 23 °C/ 80 % rel. humidity)	$f_{u2} = 1.53$
Moisture conversion factor (dry to 23 °C/ 50 % rel. humidity)	$F_{m1} = 1.02$
Moisture conversion factor (23 °C/ 50 % rel. humidity to 23 °C/ 80 % rel. humidity)	$F_{m2} = 1.01$

<sup>1</sup> The reaction to fire of class A1 according to EN 13501-1 is only proved, if the thermal insulation boards are not supplementary provided with paints, coatings or the like.

<sup>2</sup> The declared value is representative for at least 90 % of the production with a confidence level of 90 % and applies to the density range given in this section 3.3.

Essential characteristic	Performance
<b>Dimensional deviations (individual values)</b>	maximum deviation:
Length and width Test acc. to EN ISO 29465:2022	$\pm 2$ mm class L(2) and W(2) acc. to EN 13163:2012+A2:2016
Thickness Test acc. to EN ISO 29466:2022 (with a load of 250 Pa)	$\pm 2$ mm
Squareness in direction of length and width in direction of thickness Test acc. to EN 824:2013	$S_b \leq 4$ mm/m $S_d \leq 2$ mm
Flatness in direction of length and width Test acc. to EN ISO 29468:2022	$S_{\max} \leq 2$ mm
Water absorption	No performance assessed.
<b>Density (each individual value)</b> Test acc. to EN ISO 29470:2020	Density range: 235 kg/m <sup>3</sup> to 253 kg/m <sup>3</sup>
Bending strength	No performance assessed.
<b>Compressive strength</b> Test acc. to EN ISO 29469:2022	Mean value (individual values may fall below these values up to 10%): 1500 kPa
<b>Dimensional stability at 70° C</b> Test acc. to EN 1604:2013 Conditioning: 48 h, at (70 ± 2) °C	Relative changes in length, width and thickness (maximum): $\leq 0.5\%$
<b>Dimensional stability at 23° C and 90% relative humidity</b> Test acc. to EN 1604:2013 Conditioning: 48 h storage, at (23 ± 2) °C and (90 ± 5) % relative humidity	Relative changes in length, width and thickness (maximum): $\leq 0.5\%$
Tensile strength perpendicular to faces	No performance assessed.
Point load	No performance assessed.
Porosity	No performance assessed.

#### 4 Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base

In accordance with the European Assessment Document EAD 040012-00-1201 the applicable European legal act is: Decision 1999/91/EC of the European Commission

The system to be applied is: 3

In addition, with regard to reaction to fire, the system to be applied is: 1

**5 Technical details necessary for the implementation of the AVCP system, as provided for in the applicable EAD**

Technical details necessary for the implementation of the AVCP system are laid down in the control plan deposited with Deutsches Institut für Bautechnik.

Issued in Berlin on 17 September 2025 by Deutsches Institut für Bautechnik

Frank Iffländer  
Head of Section

Beglaubigt  
Getzlaff