SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

einzA All-Grund, grau
UFI:
QHSC-N1C6-A00E-QUMX

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture
decorative paints/finishes

Uses advised against
No data available.

1.3 Details of the supplier of the safety data sheet

Address
einzA Farben GmbH & Co KG
Junkersstraße 13
30179 Hannover

Telephone no. +49 (0)511 67490-0
Fax no. +49 (0)511 67490-20
e-mail info@einzA.com

Information provided by / telephone
In emergencies, the country-specific emergency number can be found in the corresponding country-specific safety data sheets.

Advice on Safety Data Sheet
sdb_info@umco.de

1.4 Emergency telephone number

+49 (0)40 0511 - 674 90-0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)
Aquatic Chronic 2; H411
Flam. Liq. 3; H226
STOT SE 3; H335
STOT SE 3; H336

Classification information
This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:
Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP
Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms


GHS02


GHS07


GHS09

Signal word

Warning

Hazardous component(s) to be indicated on label:
Hydrocarbons, C9, aromatics

Hazard statement(s)

H226	Flammable liquid and vapour.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Hazard statements (EU)

EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains phthalic-anhydride. May produce an allergic reaction.

Precautionary statement(s)

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P370+P378	In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.
P391	Collect spillage.
P405	Store locked up.
P501	Dispose of contents/container to a facility in accordance with local and national regulations.

UFI:
QHSC-N1C6-A00E-QUMX

2.3 Other hazards

The product does not contain any components > 0.1% that meet the criteria for PBT and vPvB according to Regulation (EC) No. 1907/2006, Annex XIII, or that have been included in the list compiled in accordance with Article 59(1). This product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Hazardous ingredients

No	Substance name		Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration	%
1	**Hydrocarbons, C9, aromatics**		**pls. refer to footnote (2)**	
	64742-95-6 918-668-5 649-356-00-4 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H335 STOT SE 3; H336 Aquatic Chronic 2; H411 Asp. Tox. 1; H304 EUH066	>= 25,00 - < 50,00	wt%
2	**Quartz (SiO2)**			
	14808-60-7 238-878-4 - -	-	>= 10,00 - < 25,00	wt%
3	**phthalic-anhydride**			

	85-44-9 201-607-5 607-009-00-4 01-2119457017-41	Acute Tox. 4; H302 Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335	< 0,50	wt%

Full text of H- and EUH-phrases, if not already mentioned in section 2.2: see section 16.
(2) According to the latest state of knowledge and applying the criteria set out in annex I to Regulation (EC) No 1272/2008 , the aforementioned classification is required. This classification goes beyond the classification set out in table 3, Annex VI to Regulation (CE) No 1272/2008.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	P	-	-	-

Full text for the notes: pls. see section 16 “Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)”.

Acute toxicity estimate (ATE) values			
No	**oral**	**dermal**	**inhalative**
3	1530 mg/kg bodyweight		

SECTION 4: First aid measures

4.1 Description of first aid measures

General information
In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation
Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact
Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact
Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion
If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed
No data available.

4.3 Indication of any immediate medical attention and special treatment needed
No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media
Alcohol resistant foam, CO2, powders, water spray

Unsuitable extinguishing media
water jet.

5.2 Special hazards arising from the substance or mixture
In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO2); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters
Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel
Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders
No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Do not allow to enter drains/watercourses/soil.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling
Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flatting] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

General protective and hygiene measures
Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion
Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions
Comply with legal health and safety regulations; Storage in accordance with the Ordinance on Industrial Safety and Health. Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

Requirements for storage rooms and vessels
Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Incompatible products
Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Stoarge Class according TRGS 510
3 Flammable liquids

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	**Hydrocarbons, C9, aromatics**	**64742-95-6**	**918-668-5**
	TRGS 900		
	Kohlenwasserstoffgemische, Verwendung als Lösemittel (Lösemittelkohlenwasserstoffe), additiv-frei: C9-C15 Aromaten		
	WEL long-term (8-hr TWA reference period)	100 mg/m³	
	Ceiling Limit	2 (II)	
2	**Quartz (SiO2)**	**14808-60-7**	**238-878-4**
	2004/37/EC		
	Respirable crystalline silica dust		
	WEL long-term (8-hr TWA reference period)	0,1 (9) mg/m³	

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name			CAS / EC no	
	Route of exposure	**Exposure time**	**Effect**	**Value**	
1	**Hydrocarbons, C9, aromatics**			**64742-95-6 918-668-5**	
	inhalative	Long term (chronic)	systemic	0,64	mg/m³
	inhalative	Short term (acut)	systemic	1286,4	mg/m³
	inhalative	Long term (chronic)	local	837,5	mg/m³
	inhalative	Short term (acut)	local	1066,67	mg/m³
2	**phthalic-anhydride**			**85-44-9 201-607-5**	
	dermal	Long term (chronic)	systemic	14	mg/kg bw/day
	inhalative	Long term (chronic)	systemic	49,4	mg/m³

DNEL value (consumer)

No	Substance name			CAS / EC no	
	Route of exposure	**Exposure time**	**Effect**	**Value**	
1	**Hydrocarbons, C9, aromatics**			**64742-95-6 918-668-5**	
	inhalative	Long term (chronic)	systemic	0,113	mg/m³
	inhalative	Short term (acut)	systemic	1,152	mg/m³
	inhalative	Long term (chronic)	local	178,57	mg/m³
	inhalative	Short term (acut)	local	640	mg/m³
2	**phthalic-anhydride**			**85-44-9 201-607-5**	
	oral	Long term (chronic)	systemic	5	mg/kg bw/day
	oral	Short term (acut)	systemic	25	mg/kg bw/day
	dermal	Long term (chronic)	systemic	5	mg/kg bw/day
	inhalative	Long term (chronic)	systemic	8,7	mg/m³

PNEC values

No	Substance name		CAS / EC no	
	ecological compartment	**Type**	**Value**	
1	**phthalic-anhydride**		**85-44-9 201-607-5**	
	water	fresh water	1	mg/L
	water	marine water	0,1	mg/L
	water	Aqua intermittent	5,6	mg/L
	water	fresh water sediment	3,8	mg/kg dry weight

	water	marine water sediment	0,38	mg/kg dry weight
	soil	-	0,173	mg/kg dry weight
	sewage treatment plant	-	10	mg/L

8.2 Exposure controls

Appropriate engineering controls
Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection
If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

Eye / face protection
Wear safety googles to protect against splashes. Safety glasses with side protection shield (EN 166)

Hand protection
Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material	In case of short-term contact / splash protection: nitrile rubber		
Material thickness	>	0,4	mm
Breakthrough time	>	120	min
Appropriate Material	In case of prolonged exposure: nitrile rubber		
Material thickness	>	0,4	mm
Breakthrough time	>	480	min

Other
Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls
Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation
liquid

Form
liquid

Colour
according to product name

Odour
like solvents

pH value	
reason for missing pH	substance/mixture is non-soluble (in water)

Boiling point / boiling range			
Value	>	120	°C
Reference substance	solvent mixture		

Melting point/freezing point
No data available

Decomposition temperature
No data available

Flash point			
Value	>=	36	°C
Method	closed cup		

Ignition temperature			
Value	>	200	°C
Reference substance	solvent mixture		

Oxidising properties
Not applicable

Flammability
Not applicable

Lower explosion limit			
Value	>	0,6	% vol
Reference substance	solvent mixture		

Upper explosion limit			
Value	<	7,5	% vol
Reference substance	solvent mixture		

Vapour pressure			
Value	<	100	hPa
Reference temperature		50	°C
Reference substance	solvent mixture		

Relative vapour density
No data available

Relative density
No data available

Density				
Value	1,32	-	1,35	g/cm³
Reference temperature			20	°C
Method	DIN 51757			

Solubility in water	
Comments	immiscible

Solubility
No data available

Partition coefficient n-octanol/water (log value)			
No	**Substance name**	**CAS no.**	**EC no.**
1	**phthalic-anhydride**	**85-44-9**	**201-607-5**
log Pow		1,6	
Source	ECHA		

Kinematic viscosity				
Value	35	-	40	sec
Reference temperature			20	°C
Method	DIN EN 2431 (6 mm)			

Solvent separation test			
Value	<	3	%
Reference temperature		20	°C

Particle characteristics

No data available

Microplastics
This product does not contain synthetic polymer microparticles >= 0.01%.

9.2 Other information

Other information
No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity
Stable under recommended storage and handling conditions (See section 7).

10.2 Chemical stability
Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions
Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid
Heat, naked flames and other ignition sources.

10.5 Incompatible materials
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products
None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity				
No	**Substance name**	**CAS no.**		**EC no.**
1	**phthalic-anhydride**	**85-44-9**		**201-607-5**
LD50		1530		mg/kg bodyweight
Species	rat			
Source	ECHA			

Acute dermal toxicity
No data available

Acute inhalational toxicity				
No	**Substance name**	**CAS no.**		**EC no.**
1	**phthalic-anhydride**	**85-44-9**		**201-607-5**
LC50	>	2,14		mg/l
Duration of exposure		4		h
State of aggregation	mist			
Species	rat			
Method	OECD 403			
Source	ECHA			
Evaluation/classification	Based on available data, the classification criteria are not met (maximum achievable concentration, no mortality).			

Skin corrosion/irritation			
No	**Substance name**	**CAS no.**	**EC no.**
1	**phthalic-anhydride**	**85-44-9**	**201-607-5**
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	irritant		

Serious eye damage/irritation

No	Substance name	CAS no.	EC no.
1	phthalic-anhydride	85-44-9	201-607-5

Species	rabbit
Source	ECHA
Evaluation	Irreversible effects on the eye

Respiratory or skin sensitisation

No	Substance name	CAS no.	EC no.
1	phthalic-anhydride	85-44-9	201-607-5

Route of exposure	respiratory tract
Species	guinea pig
Source	ECHA
Evaluation	sensitizing
Route of exposure	Skin
Species	guinea pig
Method	OECD 406
Source	ECHA
Evaluation	sensitizing

Germ cell mutagenicity

No	Substance name	CAS no.	EC no.
1	phthalic-anhydride	85-44-9	201-607-5

Type of examination	Bacterial Reverse Mutation Test
Species	S. typhimurium TA 1535, TA 1537, TA 98, TA 100 and E. coli WP2
Method	OECD 471
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

Reproduction toxicity

No	Substance name	CAS no.	EC no.
1	phthalic-anhydride	85-44-9	201-607-5

Route of exposure	oral
Species	rat
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

Carcinogenicity

No	Substance name	CAS no.	EC no.
1	phthalic-anhydride	85-44-9	201-607-5

Route of exposure	oral
Species	rat
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

STOT - single exposure

No data available

STOT - repeated exposure

No	Substance name	CAS no.	EC no.
1	phthalic-anhydride	85-44-9	201-607-5

Route of exposure	oral	
NOAEL	500	mg/kg bw/d
Duration of exposure	105	week/s
Species	rat	
Source	ECHA	
Evaluation/classification	Based on available data, the classification criteria are not met.	

Aspiration hazard

No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

11.2 Information on other hazards

Endocrine disrupting properties
No data available

Other information
No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)			
No	**Substance name**	**CAS no.**	**EC no.**
1	**Hydrocarbons, C9, aromatics**	**64742-95-6**	**918-668-5**
LL50		10	mg/l
Duration of exposure		96	h
Species	Oncorhynchus mykiss		
Method	OECD 203		
Source	ECHA		
2	**phthalic-anhydride**	**85-44-9**	**201-607-5**
LC50		560	mg/l
Duration of exposure		168	h
Species	Danio rerio		
Method	OECD 210		
Source	ECHA		

Toxicity to fish (chronic)			
No	**Substance name**	**CAS no.**	**EC no.**
1	**phthalic-anhydride**	**85-44-9**	**201-607-5**
NOEC		10	mg/l
Duration of exposure		60	day(s)
Species	Oncorhynchus mykiss		
Method	OECD 210		
Source	ECHA		

Toxicity to Daphnia (acute)			
No	**Substance name**	**CAS no.**	**EC no.**
1	**Hydrocarbons, C9, aromatics**	**64742-95-6**	**918-668-5**
EL50		4,5	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		
2	**phthalic-anhydride**	**85-44-9**	**201-607-5**
EC50	>	640	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Source	ECHA		

Toxicity to Daphnia (chronic)			
No	**Substance name**	**CAS no.**	**EC no.**
1	**phthalic-anhydride**	**85-44-9**	**201-607-5**
NOEC		16	mg/l

Duration of exposure	21	day(s)
Species	Daphnia magna	
Method	OECD 211	
Source	ECHA	

Toxicity to algae (acute)			
No	**Substance name**	**CAS no.**	**EC no.**
1	**Hydrocarbons, C9, aromatics**	**64742-95-6**	**918-668-5**
EL50	3,1		mg/l
Duration of exposure	72		h
Species	Raphidocelis subcapitata		
Method	OECD 201		
Source	ECHA		
2	**phthalic-anhydride**	**85-44-9**	**201-607-5**
EC50	>= 100		mg/l
Duration of exposure	72		h
Species	Desmodesmus subspicatus		
Method	EU C.3		
Source	ECHA		

Toxicity to algae (chronic)
No data available

Bacteria toxicity			
No	**Substance name**	**CAS no.**	**EC no.**
1	**Hydrocarbons, C9, aromatics**	**64742-95-6**	**918-668-5**
EC50	> 99		mg/l
Duration of exposure	10		min
Species	activated sludge		
Method	OECD 209		
Source	ECHA		

12.2 Persistence and degradability

Biodegradability			
No	**Substance name**	**CAS no.**	**EC no.**
1	**Hydrocarbons, C9, aromatics**	**64742-95-6**	**918-668-5**
Type	BSB		
Value	78		%
Duration	28		d
Method	OECD 301 F		
Source	ECHA		
Evaluation	readily biodegradable		
2	**phthalic-anhydride**	**85-44-9**	**201-607-5**
Type	DOC decrease		
Value	74		%
Duration	30		day(s)
Method	OECD 301 D		
Source	ECHA		
Evaluation	readily biodegradable		

12.3 Bioaccumulative potential

Bioconcentration factor (BCF)			
No	**Substance name**	**CAS no.**	**EC no.**
1	**phthalic-anhydride**	**85-44-9**	**201-607-5**
BCF	3,4		
Method	Calculation model used (Q)SAR		
Source	ECHA		

Partition coefficient n-octanol/water (log value)			
No	**Substance name**	**CAS no.**	**EC no.**
1	**phthalic-anhydride**	**85-44-9**	**201-607-5**
log Pow	1,6		

Source	ECHA

12.4 Mobility in soil

Mobility in soil			
No	**Substance name**	**CAS no.**	**EC no.**
1	**phthalic-anhydride**	**85-44-9**	**201-607-5**
log Koc	0,3 - 1,5		
Method	OECD 106		
Source	ECHA		

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment			
No	**Substance name**	**CAS no.**	**EC no.**
1	**Hydrocarbons, C9, aromatics**	**64742-95-6**	**918-668-5**
PBT assessment	The substance is not PBT.		
vPvB assessment	The substance is not vPvB.		
Source	ECHA		

12.6 Endocrine disrupting properties
No data available.

12.7 Other adverse effects
No data available.

12.8 Other information

Other information
Do not allow to enter drains or water courses.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste code 08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company.
Allow paint/varnish to dry out completely in a well-ventilated area and dispose of in residual waste once completely soldified. Dispose of liquid or non-drying residues separately.
Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN	UN1263
IMDG	UN1263
ICAO-TI / IATA	UN1263

14.2 UN proper shipping name

ADR/RID/ADN	PAINT
IMDG	PAINT
ICAO-TI / IATA	Paint

14.3 Transport hazard class(es)

ADR/RID/ADN - Class	3
Label	3
Classification code	F1

Tunnel restriction code	D/E
Hazard identification no.	30
IMDG - Class	3
Label	3
ICAO-TI / IATA - Class	3
Label	3

14.4 Packing group

ADR/RID/ADN	III
IMDG	III
ICAO-TI / IATA	III

14.5 Environmental hazards

ADR/RID/ADN	Symbol "fish and tree"
IMDG	Symbol "fish and tree"
EmS	F-E+S-E

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)
According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation
According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES	
The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3, 40
The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	

No	Substance name	CAS no.	EC no.	No
1	2-aminoethanol	141-43-5	205-483-3	75
2	2-methylpentane-2,4-diol	107-41-5	203-489-0	75
3	Limestone	1317-65-3	215-279-6	75
4	phthalic-anhydride	85-44-9	201-607-5	75
5	propan-1-ol	71-23-8	200-746-9	75
6	propylene carbonate	108-32-7	203-572-1	75
7	titanium dioxide	13463-67-7	236-675-5	75
8	toluene	108-88-3	203-625-9	75
9	xylene	1330-20-7	215-535-7	75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances	
This product is subject to Part I of Annex I, risk category:	E2, P5c
If the properties of the substance/product give rise to more than one classification, for the purposes of 2012/18/UE, the lowest qualifying quantities set out in Part 1 and Part 2 of Annex I shall apply.	

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)	
VOC content	34,80 %

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products
relevant VOC limit value as referred to in Annex II of Directive 2004/42/CE , Cat. : i, type: lb = 500 g/l Max. VOC content (limit value) of the product in its ready for use condition = < 500 g/l

National regulations

Water Hazard Class (Germany)

Class	2
Source	Classification according to AwSV (Regulation on facilities for handling substances that are hazardous to water).

Other regulations

GISCODE	BSL30	Covering agents, solvent based, containing aromatic substances, labeled

Other national regulations
Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment. For example, TRGS (Technical Rules for Hazardous Substances) and the DGUV (German Social Accident Insurance) rules.

15.2 Chemical safety assessment
A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:
Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.
The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.
Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.
National Threshold Limit Values of the corresponding countries as amended in each case.
Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Classification information
This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:
Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP
Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

P	The harmonised classification as a carcinogen applies unless the full refining history is known and it can be shown that the substance from which it is produced is not a carcinogen, in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.

Creation of the safety data sheet
UMCO GmbH
Georg-Wilhelm-Str. 187, D-21107 Hamburg
Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.
The safety data sheet describes products with a view to safety requirements.
It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:
Alterations to the previous edition are marked in the left-hand margin.

This document is an English translation of the legally compliant safety data sheet of the region Germany. This document, including UFI and emergency telephone number, may only be used for placing on the market in the region Germany.

Copyright-protected document. Any changes or reproductions require the express consent of UMCO GmbH.
Prod-ID 653831