

Product no.: 3940330

Current version: 3.0.0, issued: 26.06.2020 Reglaced version: 2.0.0, issued: 18.05.2020 Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

einzA Aqua-Kompaktlasur, eiche

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

decorative paints/finishes

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

einzA Farben GmbH & Co KG

Junkersstraße 13 30179 Hannover

Telephone no. +49 (0)511 67490-0 Fax no. +49 (0)511 67490-20 e-mail info@einzA.com

Advice on Safety Data Sheet

sdb info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English): +49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

This product does not meet the classification criteria given in the Regulation (EC) No 1272/2008 (CLP).

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms

-

Signal word

_

Hazard statement(s)

-

Hazard statements (EU)

EUH208 Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

Precautionary statement(s)

-

Labelling information

The labelling (EU hazard statements) meets the criteria of annex II of Directive (EC) Nr. 1272/2008 (CLP).

2.3 Other hazards



Trade name: einzA Aqua-Kompaktlasur, eiche

Product no.: 3940330

Current version: 3.0.0, issued: 26.06.2020 Reglaced version: 2.0.0, issued: 18.05.2020 Region: GB

PBT assessment

The components of this product are not considered to be a PBT.

vPvB assessment

The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Hazardous ingredients

No	Substance name		Additio	onal information	
	CAS / EC / Index / REACH no	, , , , , , , , , , , , , , , , , , , ,	Conce	ntration	%
1	(2-METHOXYMETH	YLETHOXY)PROPANOL			
	34590-94-8 252-104-2	-	<	2.50	%-b.w.
	202-104-2				
	01-2119450011-60				
2	2-butoxyethanol				
	111-76-2	Acute Tox. 4; H302	<	2.50	%-b.w.
	203-905-0	Acute Tox. 4; H312			
	603-014-00-0	Acute Tox. 4; H332			
	01-2119475108-36	Eye Irrit. 2; H319			
2	4.0 hamaia athianal	Skin Irrit. 2; H315	nda nad	ion to footpote (4)	
3	1,2-benzisothiazol-	. ,		fer to footnote (1)	24.1
	2634-33-5	Acute Tox. 4*; H302	<	0.05	%-b.w.
	220-120-9	Eye Dam. 1; H318			
	613-088-00-6	Skin Irrit. 2; H315			
	-	Skin Sens. 1; H317			
		Acute Tox. 2; H330			
		Aquatic Acute 1; H400			
		Aquatic Chronic 2; H411			
4	pyridine-2-thiol 1-c				
	3811-73-2	Acute Tox. 4; H302	<	0.10	%-b.w.
	223-296-5	Acute Tox. 4; H332			
	1 _	Aquatic Acute 1; H400			
	-	Aquatic Chronic 2; H411 Eye Dam. 1; H318			

Full Text for all H-phrases and EUH-phrases: pls. see section 16

⁽¹⁾ Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
3	-	Skin Sens. 1; H317: C >= 0.05%	-	-
4	-	-	M = 100	-

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

^(*,**,***,****) Detailed explanation pls. refer to CLP regulation No. 1272/2008, annex VI, 1.2



Trade name: einzA Aqua-Kompaktlasur, eiche

Product no.: 3940330

Current version: 3.0.0, issued: 26.06.2020 Reglaced version: 2.0.0, issued: 18.05.2020 Region: GB

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO2, powders, water spray

Unsuitable extinguishing media

water jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO2); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Due to the organic solvents' content of the mixture: Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding



Product no.: 3940330

Current version: 3.0.0, issued: 26.06.2020 Reglaced version: 2.0.0, issued: 18.05.2020 Region: GB

of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flatting] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.		EC no.	
1	(2-METHOXYMETHYLETHOXY)PROPANOL	34590-94-8		252-104-2	
	2000/39/EC				
	(2-Methoxymethylethoxy)-propanol				
	WEL long-term (8-hr TWA reference period)	308	mg/m³	50	ppm
	Skin resorption / sensibilisation	Skin			
	List of approved workplace exposure limits (WELs) /	EH40			
	(2-Methoxymethylethoxy) propanol				
	WEL long-term (8-hr TWA reference period)	308	mg/m³	50	ppm
	Comments	Sk			
2	2-butoxyethanol	111-76-2		203-905-0	
	2000/39/EC				
	2-Butoxyethanol				
	WEL short-term (15 min reference period)	246	mg/m³	50	ppm
	WEL long-term (8-hr TWA reference period)	98	mg/m³	20	ppm
	Skin resorption / sensibilisation	Skin			
	List of approved workplace exposure limits (WELs) / EH40				
	2-Butoxyethanol				
	WEL short-term (15 min reference period)	246	mg/m³	50	ppm
	WEL long-term (8-hr TWA reference period)	123	mg/m³	25	ppm
	Comments	Sk, BMGV			_

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name			CAS / EC no
	Route of exposure	Exposure time	Effect	Value
1	2-butoxyethanol			111-76-2
				203-905-0



Trade name: einzA Aqua-Kompaktlasur, eiche

Product no.: 3940330

Current version: 3.0.0, issued: 26.06.2020 Region: 2.0.0, issued: 18.05.2020 Region: GB

dermal	Long term (chronic)	systemic	125.00	mg/kg/day
dermal	Short term (acut)	systemic	89.00	mg/kg/day
inhalative	Long term (chronic)	systemic	98.00	mg/m³
inhalative	Short term (acut)	systemic	1091.00	mg/m³
inhalative	Long term (chronic)	local	246.00	mg/m³

DNEL value (consumer)

No	Substance name	Substance name			
	Route of exposure	Exposure time	Effect	Value	
1	2-butoxyethanol			111-76-2	
				203-905-0	
	oral	Long term (chronic)	systemic	6.30	mg/kg/day
	oral	Short term (acut)	systemic	26.70	mg/kg/day
	dermal	Long term (chronic)	systemic	75.00	mg/kg/day
	dermal	Short term (acut)	systemic	89.00	mg/kg/day
	inhalative	Long term (chronic)	systemic	59.00	mg/m³
	inhalative	Short term (acut)	systemic	426.00	mg/m³
	inhalative	Long term (chronic)	local	147.00	mg/m³

PNEC values

No	Substance name		CAS / EC no	
	ecological compartment	Туре	Value	
1	2-butoxyethanol		111-76-2 203-905-0	
	water	fresh water	8.80	mg/L
	water	marine water	0.88	mg/L
	water	fresh water sediment	34.60	mg/kg
	with reference to: dry weight		,	
	water	marine water sediment	3.46	mg/kg
	water	Aqua intermittent	26.4	mg/L
	soil	-	2.33	mg/kg dry weight
	sewage treatment plant	-	463.00	mg/L
	secondary poisoning	-	0.02	g/kg

8.2 Exposure controls

Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

Eye / face protection

Wear safety googles to protect against splashes. Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material In case of short-term contact / splash protection: nitrile rubber

Material thickness > 0.4 mm
Breakthrough time > 120 min



Product no.: 3940330

Current version: 3.0.0, issued: 26.06.2020 Reglaced version: 2.0.0, issued: 18.05.2020 Region: GB

Appropriate Material In case of prolonged exposure: nitrile rubber Material thickness > 0.4 mm
Breakthrough time > 480 min

Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form/Colour
liquid
according to product name

Odour characteristic

Odour threshold
No data available

pH valueValue7.8- 7.8

 Boiling point / boiling range

 Value
 appr.
 100 °C

Melting point / melting range

No data available

Decomposition point / decomposition range

No data available

Flash point
Not applicable

Auto-ignition temperature

No data available

Oxidising properties

Not applicable

Explosive properties

No data available

Flammability (solid, gas)

Not applicable

Lower flammability or explosive limits

No data available

Upper flammability or explosive limits

No data available

Vapour pressure100hPaValue50°C

Vapour density
No data available

Evaporation rate
No data available

Relative density
No data available



Product no.: 3940330

Current version: 3.0.0, issued: 26.06.2020 Reglaced version: 2.0.0, issued: 18.05.2020 Region: GB

Density	
Value	1.03 - 1.06 g/cm³
Reference temperature	20 °C
Method	DIN 51757

Solubility in water	
Comments	miscible

Solubility(ies)
No data available

Part	Partition coefficient: n-octanol/water					
No	Substance name	CAS no.		EC no.		
1	2-butoxyethanol	111-76-2		203-905-0		
log F	Pow		0.81			
Refe	erence temperature		25	°C		
•		ECHA				

Viscosity	
Value	1600 - 1800 Pa*s
Reference temperature	20 °C
Method	DIN 53019

Solvent separation test	
Not applicable	

9.2 Other information

Other information	
No data available.	

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage and handling conditions (See section 7).

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acu	Acute oral toxicity (result of the ATE calculation for the mixture)				
No	Product Name	Product Name			
1	einzA Aqua-Kompaktlasur, eiche				
Com	nments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE oral > 2000 mg/kg).			

Acu	te oral toxicity		
No	Substance name	CAS no.	EC no.



Trade name: einzA Aqua-Kompaktlasur, eiche

Product no.: 3940330

Current version: 3.0.0, issued: 26.06.2020 Replaced version: 2.0.0, issued: 18.05.2020 Region: GB

1 2-butoxyethanol	111-76-2		203-905-0
LD50		1746	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		

Acu	Acute dermal toxicity (result of the ATE calculation for the mixture)				
No	Product Name				
1	einzA Aqua-Kompaktlasur, eiche				
Com	nments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE dermal > 2000 mg/kg).			

Acu	Acute dermal toxicity					
No	Substance name		CAS no.	EC no.		
1	2-butoxyethanol		111-76-2	203-905-0		
LD5	0	>	2000	mg/kg bodyweight		
Spe	cies	guinea pig				
Metl	hod	OECD 402				
Sou	Source					

Acu	Acute inhalational toxicity (result of the ATE calculation for the mixture)				
No	Product Name	Product Name			
1	einzA Aqua-Kompaktlasur, eiche				
Com					

Acute inhalational toxicity	
No data available	

Skir	Skin corrosion/irritation					
No	Substance name		CAS no.	EC no.		
1	2-butoxyethanol		111-76-2	203-905-0		
Dura	ation of exposure		4	h		
Spe	cies	rabbit				
Met	hod	EU B.4				
Source		ECHA				
Eva	Evaluation					

Seri	ous eye damage/irritation				
No	Substance name	CAS no.		EC no.	
1	2-butoxyethanol	111-76-2		203-905-0	
Dura	ation of exposure		24	h	
Spe	cies	rabbit			
Meth	hod	OECD 405			
Soul	rce	ECHA			
Eval	luation	Irritating to eyes			

Res	Respiratory or skin sensitisation				
No	Substance name	CAS no.	EC no.		
1	2-butoxyethanol	111-76-2	203-905-0		
Rou	te of exposure	Skin			
Spe	cies	guinea pig			
Metl	hod	OECD 406			
Source		ECHA			
Eval	luation	non-sensitizing			

Germ cell mutagenicity



Trade name: einzA Aqua-Kompaktlasur, eiche

Product no.: 3940330

Current version: 3.0.0, issued: 26.06.2020 Reglaced version: 2.0.0, issued: 18.05.2020 Region: GB

No	Substance name	CAS no.	EC no.
1	2-butoxyethanol	111-76-2	203-905-0
Meth	nod	OECD 471	
Soul	rce	ECHA	
Evaluation/classification Based on		Based on available data, the classification	n criteria are not met.

Reproduction toxicity

No data available

Card	Carcinogenicity					
No	Substance name	CAS no.	EC no.			
1	2-butoxyethanol	111-76-2	203-905-0			
Spe	cies	rat				
Meth	nod	OECD 451				
Source		ECHA				
Eval	uation/classification	Based on available data, the clas	sification criteria are not met.			

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration hazard

No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

SECTION 12: Ecological information

12.1 Toxicity

Toxi	Toxicity to fish (acute)					
No	Substance name	CAS	no.	EC no.		
1	2-butoxyethanol	111-	76-2	203-905-0		
LC5	0	>	1474	mg/l		
Dura	ation of exposure		96	h		
Spe	cies	Oncorhynchus my	kiss			
Meth	nod	OECD 203				
Soul	rce	ECHA				

Toxi	icity to fish (chronic)					
No	Substance name		CAS no.		EC no.	
1	2-butoxyethanol		111-76-2		203-905-0	
NOE	EC	>		100	mg/l	
Dura	ation of exposure			21	day(s)	
Spe	cies	Danio rerio				
Metl	hod	OECD 204				
Sou	rce	ECHA				

Tox	icity to Daphnia (acute)		
No	Substance name	CAS no.	EC no.
1	2-butoxyethanol	111-76-2	203-905-0
EC5	0	1550	mg/l
Dura	ation of exposure	48	h



Product no.: 3940330

Current version: 3.0.0, issued: 26.06.2020 Replaced version: 2.0.0, issued: 18.05.2020 Region: GB

Species Daphnia magna
Method OECD 202
Source ECHA

	icity to Daphnia (chronic)			
No	Substance name	CAS no.		EC no.
1	2-butoxyethanol	111-76-2		203-905-0
NOE	EC		100	mg/l
Dura	ation of exposure		21	day(s)
Spe	cies	Daphnia magna		
Metl	hod	OECD 211		
Sou	rce	ECHA		

Toxi	city to algae (acute)				
No	Substance name	CAS no.		EC no.	
1	2-butoxyethanol	111-76-2		203-905-0	
EC5	0		911	mg/l	
Dura	ation of exposure		72	h	
Spe	cies	Pseudokirchneriella subcapita	ıta		
Meth	nod	OECD 201			
Soul	rce	ECHA			

Toxicity to algae (chronic)	
No data available	

Bacteria toxicity	
No data available	

12.2 Persistence and degradability

Bio	degradability				
No	Substance name	CAS no.		EC no.	
1	2-butoxyethanol	111-76-2		203-905-0	
Туре	e	aerobic biodegradation			
Valu	e		90.4	%	
Dura	ation		28	day(s)	
Met	hod	OECD 301 B			
Sou	rce	ECHA			
Eva	luation	readily biodegradable			

12.3 Bioaccumulative potential

	2.04.004					
Part	Partition coefficient: n-octanol/water					
No	Substance name	CAS no.		EC no.		
1	2-butoxyethanol	111-76-2		203-905-0		
log F	Pow		0.81			
Refe	erence temperature		25	°C		
Soul	rce	ECHA				

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	The components of this product are not considered to be a PBT.
vPvB assessment	The components of this product are not considered to be a vPvB.

12.6 Other adverse effects

No data available.

12.7 Other information

Other information	
Do not allow to enter drains or water courses.	

SECTION 13: Disposal considerations



Trade name: einzA Aqua-Kompaktlasur, eiche

Product no.: 3940330

Current version: 3.0.0, issued: 26.06.2020 Reglaced version: 2.0.0, issued: 18.05.2020 Region: GB

13.1 Waste treatment methods

Product

Waste code 08 01 11* waste paint and varnish containing organic solvents or other hazardous

substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company.

Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Packaging

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

The product is not subject to ADR/RID/ADN regulations.

14.2 Transport IMDG

The product is not subject to IMDG regulations.

14.3 Transport ICAO-TI / IATA

The product is not subject to ICAO-TI / IATA regulations.

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances requiring authorisation as listed on Annex XVII of the REACH regulation (EC) 1907/2006.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is not subject to Part 1 or 2 of Annex I.

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)VOC content4.80%

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic



Product no.: 3940330

Current version: 3.0.0, issued: 26.06.2020 Reglaced version: 2.0.0, issued: 18.05.2020 Region: GB

solvents in certain paints and varnishes and vehicle refinishing products

relevant VOC limit value as referred to in Annex II of Directive 2004/42/CE, Cat.: e, type: wb = 130 g/l Max. VOC content (limit value) of the product in its ready for use condition = < 130 g/l

National regulations

Other national regulations

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.

EC Directives 2000/39/EC, 2006/15/EC, 2009/161/EU

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin rea

H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.

H330 Fatal if inhaled.
H332 Harmful if inhaled.
H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Department issuing safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 653711