

Trade name: einza mix Aqua-Kompaktlasur, Basis 0**Product no.:** 0171613**Current version :** 3.4.0, issued: 21.12.2023**Replaced version:** 3.3.1, issued: 07.08.2023**Region:** GB**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name

einza mix Aqua-Kompaktlasur, Basis 0**1.2 Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses of the substance or mixture**

decorative paints/finishes

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet**Address**

einza Farben GmbH & Co KG

Junkersstraße 13

30179 Hannover

Telephone no. +49 (0)511 67490-0

Fax no. +49 (0)511 67490-20

e-mail info@einza.com

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification information**

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

This product does not meet the classification criteria given in the Regulation (EC) No 1272/2008 (CLP).

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)****Hazard pictograms**

-

Signal word

-

Hazard statement(s)

-

Hazard statements (EU)

EUH208

Contains adipohydrazide, 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

EUH210

Safety data sheet available on request.

Precautionary statement(s)

-

Labelling information

The labelling (EU hazard statements) meets the criteria of annex II of Directive (EC) Nr. 1272/2008 (CLP).

2.3 Other hazards

Trade name: einza mix Aqua-Kompaktlasur, Basis 0

Product no.: 0171613

Current version : 3.4.0, issued: 21.12.2023

Replaced version: 3.3.1, issued: 07.08.2023

Region: GB

PBT assessment

The components of this product are not considered to be a PBT.

vPvB assessment

The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not applicable. The product is not a substance.

3.2 Mixtures**Hazardous ingredients**

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration
			%
1	(2-METHOXYMETHYLETHOXY)PROPANOL		
	34590-94-8 252-104-2 - 01-2119450011-60	-	< 2.50 wt%
2	2-butoxyethanol		
	111-76-2 203-905-0 603-014-00-0 01-2119475108-36	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Skin Irrit. 2; H315	< 2.50 wt%
3	adipohydrazide		
	1071-93-8 213-999-5 - -	Skin Sens. 1; H317 Aquatic Chronic 2; H411	< 2.50 wt%
4	1,2-benzisothiazol-3(2H)-one		pls. refer to footnote (1)
	2634-33-5 220-120-9 613-088-00-6 -	Acute Tox. 4*; H302 Eye Dam. 1; H318 Skin Irrit. 2; H315 Skin Sens. 1; H317 Acute Tox. 2; H330 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	< 0.05 wt%
5	pyridine-2-thiol 1-oxide, sodium salt		
	3811-73-2 223-296-5 613-344-00-7 -	EUH070 Acute Tox. 4; H302 Acute Tox. 3; H311 Acute Tox. 3; H331 Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Irrit. 2; H319 STOT RE 1; H372 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	< 0.10 wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(*, **, ***, ****) Detailed explanation pls. refer to CLP regulation No. 1272/2008, annex VI, 1.2

(1) Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
4	-	Skin Sens. 1; H317: C >= 0.05%	-	-
5	-	-	M = 100	-

No	Route, target organ, concrete effect
5	H372 -; nervous system; -

Trade name: einza mix Aqua-Kompaktlasur, Basis 0**Product no.:** 0171613**Current version :** 3.4.0, issued: 21.12.2023**Replaced version:** 3.3.1, issued: 07.08.2023**Region:** GB

Acute toxicity estimate (ATE) values			
No	oral	dermal	inhalative
2	1200 mg/kg bodyweight		

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO₂, powders, water spray

Unsuitable extinguishing media

water jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Trade name: einza mix Aqua-Kompaktlasur, Basis 0

Product no.: 0171613

Current version : 3.4.0, issued: 21.12.2023

Replaced version: 3.3.1, issued: 07.08.2023

Region: GB

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage**7.1 Precautions for safe handling****Advice on safe handling**

Due to the organic solvents' content of the mixture: Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flattening] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities**Technical measures and storage conditions**

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limit values**

No	Substance name	CAS no.	EC no.
1	(2-METHOXYMETHYLETHOXY)PROPANOL	34590-94-8	252-104-2
	2000/39/EC		
	(2-Methoxymethylethoxy)-propanol		
	WEL long-term (8-hr TWA reference period)	308 mg/m ³	50 ppm
	Skin resorption / sensibilisation	Skin	
	List of approved workplace exposure limits (WELs) / EH40		
	(2-Methoxymethylethoxy) propanol		
	WEL long-term (8-hr TWA reference period)	308 mg/m ³	50 ppm
	Comments	Sk	
2	2-butoxyethanol	111-76-2	203-905-0
	2000/39/EC		
	2-Butoxyethanol		
	WEL short-term (15 min reference period)	246 mg/m ³	50 ppm
	WEL long-term (8-hr TWA reference period)	98 mg/m ³	20 ppm
	Skin resorption / sensibilisation	Skin	

Trade name: einza mix Aqua-Kompaktlasur, Basis 0

Product no.: 0171613

Current version : 3.4.0, issued: 21.12.2023

Replaced version: 3.3.1, issued: 07.08.2023

Region: GB

List of approved workplace exposure limits (WELs) / EH40				
2-Butoxyethanol				
WEL short-term (15 min reference period)	246	mg/m ³	50	ppm
WEL long-term (8-hr TWA reference period)	123	mg/m ³	25	ppm
Comments	Sk, BMGV			

DNEL, DMEL and PNEC values**DNEL values (worker)**

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	2-butoxyethanol			111-76-2 203-905-0	
	inhalative	Long term (chronic)	systemic	98.00	mg/m ³
	inhalative	Short term (acut)	systemic	1091.00	mg/m ³
	inhalative	Long term (chronic)	local	246.00	mg/m ³

DNEL value (consumer)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	2-butoxyethanol			111-76-2 203-905-0	
	oral	Long term (chronic)	systemic	6.30	mg/kg/day
	oral	Short term (acut)	systemic	26.70	mg/kg/day
	inhalative	Long term (chronic)	systemic	59.00	mg/m ³
	inhalative	Short term (acut)	systemic	426.00	mg/m ³
	inhalative	Long term (chronic)	local	147.00	mg/m ³

PNEC values

No	Substance name		CAS / EC no	
	ecological compartment	Type	Value	
1	2-butoxyethanol		111-76-2 203-905-0	
	water	fresh water	8.80	mg/L
	water	marine water	0.88	mg/L
	water	fresh water sediment	34.60	mg/kg
	with reference to: dry weight			
	water	marine water sediment	3.46	mg/kg
	water	Aqua intermittent	26.4	mg/L
	soil	-	2.33	mg/kg dry weight
	sewage treatment plant	-	463.00	mg/L
	secondary poisoning	-	0.02	g/kg

8.2 Exposure controls**Appropriate engineering controls**

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment**Respiratory protection**

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

Eye / face protection

Wear safety goggles to protect against splashes. Safety glasses with side protection shield (EN 166)

Hand protection

Trade name: einza mix Aqua-Kompaktlasur, Basis 0**Product no.:** 0171613**Current version :** 3.4.0, issued: 21.12.2023**Replaced version:** 3.3.1, issued: 07.08.2023**Region:** GB

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material	In case of short-term contact / splash protection: nitrile rubber		
Material thickness	>	0.4	mm
Breakthrough time	>	120	min
Appropriate Material	In case of prolonged exposure: nitrile rubber		
Material thickness	>	0.4	mm
Breakthrough time	>	480	min

Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation			
liquid			
Form			
liquid			
Colour			
according to product name			
Odour			
characteristic			
pH value			
Value		7.8	- 7.8
Boiling point / boiling range			
Value	appr.	100	°C
Melting point/freezing point			
No data available			
Decomposition temperature			
No data available			
Flash point			
Not applicable			
Ignition temperature			
No data available			
Oxidising properties			
Not applicable			
Flammability			
Not applicable			
Lower explosion limit			
No data available			
Upper explosion limit			
No data available			
Vapour pressure			
Value	<	100	hPa
Reference temperature		50	°C

Trade name: einza mix Aqua-Kompaktlasur, Basis 0

Product no.: 0171613

Current version : 3.4.0, issued: 21.12.2023

Replaced version: 3.3.1, issued: 07.08.2023

Region: GB

Relative vapour density

No data available

Relative density

No data available

Density

Value	1.03	-	1.06	g/cm ³
Reference temperature			20	°C
Method	DIN 51757			

Solubility in water

Comments miscible

Solubility

No data available

Partition coefficient n-octanol/water (log value)

No	Substance name	CAS no.	EC no.
1	2-butoxyethanol	111-76-2	203-905-0
log Pow		0.81	
Reference temperature		25	°C
Source		ECHA	

Kinematic viscosity

Value	1600	-	1800	Pa*s
Reference temperature			20	°C
Method	DIN 53019			

Solvent separation test

Not applicable

Particle characteristics

No data available

9.2 Other information**Other information**

No data available.

SECTION 10: Stability and reactivity**10.1 Reactivity**

Stable under recommended storage and handling conditions (See section 7).

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute oral toxicity (result of the ATE calculation for the mixture)**

No	Product Name
1	einza mix Aqua-Kompaktlasur, Basis 0

Trade name: einza mix Aqua-Kompaktlasur, Basis 0

Product no.: 0171613

Current version : 3.4.0, issued: 21.12.2023

Replaced version: 3.3.1, issued: 07.08.2023

Region: GB

Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE oral > 2000 mg/kg).
----------	---

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	2-butoxyethanol	111-76-2	203-905-0
ATE		1200	mg/kg bodyweight
Species	rat		
Source	1272/2008/EC, Annex VI		

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	2-butoxyethanol	111-76-2	203-905-0
LD50		> 2000	mg/kg bodyweight
Species	guinea pig		
Method	OECD 402		
Source	ECHA		

Acute inhalational toxicity (result of the ATE calculation for the mixture)			
No	Product Name		
1	einza mix Aqua-Kompaktlasur, Basis 0		
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE for inhalation: > 20.000 ppmV (gases), > 20 mg/l (vapours), > 5 mg/l (dusts/mists)).		

Acute inhalational toxicity	
No data available	

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	2-butoxyethanol	111-76-2	203-905-0
Duration of exposure		4	h
Species	rabbit		
Method	EU B.4		
Source	ECHA		
Evaluation	irritant		

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	2-butoxyethanol	111-76-2	203-905-0
Duration of exposure		24	h
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	Irritating to eyes		

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	2-butoxyethanol	111-76-2	203-905-0
Route of exposure	Skin		
Species	guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		

Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	2-butoxyethanol	111-76-2	203-905-0
Method	OECD 471		

Trade name: einza mix Aqua-Kompaktlasur, Basis 0

Product no.: 0171613

Current version : 3.4.0, issued: 21.12.2023

Replaced version: 3.3.1, issued: 07.08.2023

Region: GB

Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

Reproduction toxicity
No data available

Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	2-butoxyethanol	111-76-2	203-905-0
Species		rat	
Method		OECD 451	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

STOT - single exposure
No data available

STOT - repeated exposure			
No	Substance name	CAS no.	EC no.
1	2-butoxyethanol	111-76-2	203-905-0
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Aspiration hazard
No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure	
Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.	

11.2 Information on other hazards

Endocrine disrupting properties

No data available.

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	2-butoxyethanol	111-76-2	203-905-0
LC50		1474	mg/l
Duration of exposure		96	h
Species		Oncorhynchus mykiss	
Method		OECD 203	
Source		ECHA	
Toxicity to fish (chronic)			
No	Substance name	CAS no.	EC no.
1	2-butoxyethanol	111-76-2	203-905-0
NOEC		>	100 mg/l
Duration of exposure		21	day(s)
Species		Danio rerio	
Method		OECD 204	
Source		ECHA	

Trade name: einza mix Aqua-Kompaktlasur, Basis 0

Product no.: 0171613

Current version : 3.4.0, issued: 21.12.2023

Replaced version: 3.3.1, issued: 07.08.2023

Region: GB

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	2-butoxyethanol	111-76-2	203-905-0
EC50		1550	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		

Toxicity to Daphnia (chronic)			
No	Substance name	CAS no.	EC no.
1	2-butoxyethanol	111-76-2	203-905-0
NOEC		100	mg/l
Duration of exposure		21	day(s)
Species	Daphnia magna		
Method	OECD 211		
Source	ECHA		

Toxicity to algae (acute)			
No	Substance name	CAS no.	EC no.
1	2-butoxyethanol	111-76-2	203-905-0
EC50		911	mg/l
Duration of exposure		72	h
Species	Pseudokirchneriella subcapitata		
Method	OECD 201		
Source	ECHA		

Toxicity to algae (chronic)			
No data available			

Bacteria toxicity			
No data available			

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	2-butoxyethanol	111-76-2	203-905-0
Type	aerobic biodegradation		
Value		90.4	%
Duration		28	day(s)
Method	OECD 301 B		
Source	ECHA		
Evaluation	readily biodegradable		

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	2-butoxyethanol	111-76-2	203-905-0
log Pow		0.81	
Reference temperature		25	°C
Source	ECHA		

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	The components of this product are not considered to be a PBT.
vPvB assessment	The components of this product are not considered to be a vPvB.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

Trade name: einzA mix Aqua-Kompaktlasur, Basis 0**Product no.:** 0171613**Current version :** 3.4.0, issued: 21.12.2023**Replaced version:** 3.3.1, issued: 07.08.2023**Region:** GB

No data available.

12.8 Other information**Other information**

Do not allow to enter drains or water courses.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Waste code

08 01 11*

waste paint and varnish containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company. Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

SECTION 14: Transport information**14.1 Transport ADR/RID/ADN**

The product is not subject to ADR/RID/ADN regulations.

14.2 Transport IMDG

The product is not subject to IMDG regulations.

14.3 Transport ICAO-TI / IATA

The product is not subject to ICAO-TI / IATA regulations.

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations****Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

Trade name: einza mix Aqua-Kompaktlasur, Basis 0

Product no.: 0171613

Current version : 3.4.0, issued: 21.12.2023

Replaced version: 3.3.1, issued: 07.08.2023

Region: GB

No	Substance name	CAS no.	EC no.	No
1	1,2-benzisothiazol-3(2H)-one	2634-33-5	220-120-9	75
2	2-butoxyethanol	111-76-2	203-905-0	75
3	formaldehyde	50-00-0	200-001-8	75
4	pyridine-2-thiol 1-oxide, sodium salt	3811-73-2	223-296-5	75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is not subject to Part 1 or 2 of Annex I.

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)

VOC content 4.81 %

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products

relevant VOC limit value as referred to in Annex II of Directive 2004/42/CE , Cat. : e, type: wb = 130 g/l

Max. VOC content (limit value) of the product in its ready for use condition = < 130 g/l

National regulations**Other national regulations**

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

EUH070	Toxic by eye contact.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Trade name: einza mix Aqua-Kompaktlasur, Basis 0

Product no.: 0171613

Current version : 3.4.0, issued: 21.12.2023

Replaced version: 3.3.1, issued: 07.08.2023

Region: GB

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.
Prod-ID 653637