

**Trade name:** einZA Aqua-Kunststoff, RAL 7030 steingrau

**Product no.:** 0171158

**Current version:** 1.0.0, Revision: 28.01.2026

**Replaced version:** -, Revision: -

**Region:**  
GER

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Trade name**

**einZA Aqua-Kunststoff, RAL 7030 steingrau**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

decorative paints/finishes

**Uses advised against**

No data available.

### 1.3 Details of the supplier of the safety data sheet

**Address**

einZA Farben GmbH & Co KG

Junkersstraße 13

30179 Hannover

Telephone no. +49 (0)511 67490-0

Fax no. +49 (0)511 67490-20

e-mail info@einZA.com

**Information provided by / telephone**

In emergencies, the country-specific emergency number can be found in the corresponding country-specific safety data sheets.

**Advice on Safety Data Sheet**

sdb\_info@umco.de

### 1.4 Emergency telephone number

+49 (0)40 0511 - 674 90-0

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification information**

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

This product does not meet the classification criteria given in the Regulation (EC) No 1272/2008 (CLP).

### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)**

**Hazard pictograms**

-

**Signal word**

-

**Hazard statement(s)**

-

**Hazard statements (EU)**

EUH208

Contains adipohydrazide, 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1). May produce an allergic reaction.

EUH210

Safety data sheet available on request.

**Precautionary statement(s)**

Trade name: einza Aqua-Kunststoff, RAL 7030 steingrau

Product no.: 0171158

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:  
GER**Labelling information**

The labelling (EU hazard statements) meets the criteria of annex II of Directive (EC) Nr. 1272/2008 (CLP).

**2.3 Other hazards**

The product does not contain any components > 0.1% that meet the criteria for PBT and vPvB according to Regulation (EC) No. 1907/2006, Annex XIII, or that have been included in the list compiled in accordance with Article 59(1). This product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**SECTION 3: Composition/information on ingredients****3.1 Substances**

Not applicable. The product is not a substance.

**3.2 Mixtures****Hazardous ingredients**

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	<b>barium sulfate, natural</b>		
	7727-43-7 231-784-4 - -	-	>= 5,00 - < 10,00 wt%
2	<b>1-methoxy-2-propanol</b>		
	107-98-2 203-539-1 603-064-00-3 01-2119457435-35	Flam. Liq. 3; H226 STOT SE 3; H336	< 2,50 wt%
3	<b>adipohydrazide</b>		
	1071-93-8 213-999-5 - -	Skin Sens. 1; H317 Aquatic Chronic 2; H411	< 0,50 wt%
4	<b>1,2-benzisothiazol-3(2H)-one</b>		
	2634-33-5 220-120-9 613-088-00-6 -	Acute Tox. 4; H302 Skin Irrit. 2; H315 Skin Sens. 1A; H317 Eye Dam. 1; H318 Acute Tox. 2; H330 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	< 0,10 wt%
5	<b>pyridine-2-thiol 1-oxide, sodium salt</b>		
	3811-73-2 223-296-5 613-344-00-7 -	EUH070 Acute Tox. 4; H302 Acute Tox. 3; H311 Acute Tox. 3; H331 Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Irrit. 2; H319 STOT RE 1; H372 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	< 0,10 wt%
6	<b>reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)</b>		

Trade name: einza Aqua-Kunststoff, RAL 7030 steingrau

Product no.: 0171158

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:  
GER

55965-84-9	Acute Tox. 2; H310	< 0,0015	wt%
-	Acute Tox. 2; H330		
613-167-00-5	Acute Tox. 3; H301		
-	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 Eye Dam. 1; H318 Skin Corr. 1C; H314 Skin Sens. 1A; H317		

Full text of H- and EUH-phrases, if not already mentioned in section 2.2: see section 16.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
4	-	Skin Sens. 1A; H317: C $\geq$ 0,036%	M = 1	M = 1
5	-	-	M = 100	-
6	B	Skin Sens. 1A; H317: C $\geq$ 0,0015% Eye Irrit. 2; H319: C $\geq$ 0,06% Skin Irrit. 2; H315: C $\geq$ 0,06% Skin Corr. 1C; H314: C $\geq$ 0,6% Eye Dam. 1; H318: C $\geq$ 0,6%	M = 100	M = 100

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

No	Route, target organ, concrete effect
5	H372 -; nervous system; -

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

#### After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

#### After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

#### After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

#### After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

No data available.

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Alcohol resistant foam, CO<sub>2</sub>, powders, water spray

#### Unsuitable extinguishing media

water jet.

### 5.2 Special hazards arising from the substance or mixture

**Trade name:** einza Aqua-Kunststoff, RAL 7030 steingrau

**Product no.:** 0171158

**Current version:** 1.0.0, Revision: 28.01.2026

**Replaced version:** -, Revision: -

**Region:**  
GER

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO<sub>2</sub>); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

### 5.3 Advice for firefighters

Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

#### For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

### 6.2 Environmental precautions

If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Do not allow to enter drains/watercourses/soil.

### 6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

### 6.4 Reference to other sections

No data available.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Advice on safe handling

Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flattening] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

#### General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

#### Advice on protection against fire and explosion

No special measures necessary.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Technical measures and storage conditions

Comply with legal health and safety regulations; Storage in accordance with the Ordinance on Industrial Safety and Health. Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep from freezing.

#### Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

#### Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

#### Stoarge Class according TRGS 510

12 Non-combustible liquids that cannot be assigned to any of the above LGKs.

### 7.3 Specific end use(s)

No data available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Trade name: einzA Aqua-Kunststoff, RAL 7030 steingrau

Product no.: 0171158

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:  
GER

**Occupational exposure limit values**

No	Substance name	CAS no.	EC no.
1	<b>barium sulfate, natural</b>	<b>7727-43-7</b>	<b>231-784-4</b>
	<b>2006/15/EC</b>		
	Barium (soluble compounds as Ba)		
	WEL long-term (8-hr TWA reference period)	0,5	mg/m <sup>3</sup>
2	<b>1-methoxy-2-propanol</b>	<b>107-98-2</b>	<b>203-539-1</b>
	<b>TRGS 900</b>		
	1-Methoxy-2-propanol		
	WEL long-term (8-hr TWA reference period)	370	mg/m <sup>3</sup> 100 ml/m <sup>3</sup>
	Ceiling Limit	2(l)	
	Notes	Y	
	<b>2000/39/EC</b>		
	1-Methoxypropanol-2		
	WEL short-term (15 min reference period)	568	mg/m <sup>3</sup> 150 ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m <sup>3</sup> 100 ppm
	Skin resorption / sensibilisation	Skin	

**Biological limit values**

No	Substance name
1	<b>1-methoxy-2-propanol</b>
	<b>TRGS 903</b>
	1-Methoxypropan-2-ol
	parameter
	Value
	Comments
	sample material
	Sampling moment

  

	1-Methoxypropan-2-ol
	15 mg/l
	DFG
	U
	b

**DNEL, DMEL and PNEC values**

**DNEL values (worker)**

No	Substance name	CAS / EC no		
	Route of exposure	Exposure time	Effect	Value
1	<b>1-methoxy-2-propanol</b>	<b>107-98-2</b>	<b>203-539-1</b>	
	dermal	Long term (chronic)	systemic	183 mg/kg/day
	inhalative	Long term (chronic)	systemic	369 mg/m <sup>3</sup>
	inhalative	Short term (acut)	local	553,5 mg/m <sup>3</sup>
	inhalative	Short term (acut)	systemic	553,5 mg/m <sup>3</sup>

**DNEL value (consumer)**

No	Substance name	CAS / EC no		
	Route of exposure	Exposure time	Effect	Value
1	<b>1-methoxy-2-propanol</b>	<b>107-98-2</b>	<b>203-539-1</b>	
	oral	Long term (chronic)	systemic	33 mg/kg/day
	dermal	Long term (chronic)	systemic	78 mg/kg/day
	inhalative	Long term (chronic)	systemic	43,9 mg/m <sup>3</sup>

**PNEC values**

No	Substance name	CAS / EC no	
	ecological compartment	Type	Value
1	<b>1-methoxy-2-propanol</b>	<b>107-98-2</b>	<b>203-539-1</b>
	water	fresh water	10 mg/L
	water	marine water	1 mg/L
	water	Aqua intermittent	100 mg/L
	water	fresh water sediment	52,3 mg/kg

**Trade name:** einza Aqua-Kunststoff, RAL 7030 steingrau

**Product no.:** 0171158

**Current version:** 1.0.0, Revision: 28.01.2026

**Replaced version:** -, Revision: -

**Region:**  
GER

with reference to: dry weight			
water	marine water sediment	5,2	mg/kg
with reference to: dry weight			
soil	-	4,59	mg/kg
with reference to: dry weight			
sewage treatment plant	-	100	mg/L

## 8.2 Exposure controls

### Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

### Personal protective equipment

#### Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

#### Eye / face protection

Wear safety goggles to protect against splashes. Safety glasses with side protection shield (EN 166)

#### Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material In case of short-term contact / splash protection: nitrile rubber

Material thickness > 0,4 mm

Breakthrough time > 120 min

Appropriate Material In case of prolonged exposure: nitrile rubber

Material thickness > 0,4 mm

Breakthrough time > 480 min

#### Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

#### Environmental exposure controls

Do not allow to enter drains or water courses.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

<b>State of aggregation</b>	
liquid	
<b>Form</b>	
liquid	
<b>Colour</b>	
according to product name	
<b>Odour</b>	
characteristic	
<b>pH value</b>	
Value	8,1 - 8,5
<b>Boiling point / boiling range</b>	
Value	appr. 100 °C

Trade name: einzA Aqua-Kunststoff, RAL 7030 steingrau

Product no.: 0171158

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:  
GER

<b>Melting point/freezing point</b>
No data available

<b>Decomposition temperature</b>
No data available

<b>Flash point</b>
Not applicable

<b>Ignition temperature</b>
No data available

<b>Oxidising properties</b>
Not applicable

<b>Flammability</b>
Not applicable

<b>Lower explosion limit</b>
No data available

<b>Upper explosion limit</b>
No data available

<b>Vapour pressure</b>			
Value	<	100	hPa
Reference temperature		50	°C

<b>Relative vapour density</b>
No data available

<b>Relative density</b>
No data available

<b>Density</b>			
Value	1,23	-	1,27
Reference temperature			20
Method	DIN 51757		
			g/cm <sup>3</sup>
			°C

<b>Solubility in water</b>	
Comments	miscible

<b>Solubility</b>
No data available

<b>Partition coefficient n-octanol/water (log value)</b>			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
log Pow	<	1	
Reference temperature		20	°C
with reference to	pH: 6.8		
Method	OECD 117		
Source	ECHA		

<b>Kinematic viscosity</b>			
Value	3000	-	3500
Reference temperature			20
Method	DIN 53019		
			Pa*s
			°C

<b>Solvent separation test</b>
Not applicable

<b>Particle characteristics</b>
No data available

## 9.2 Other information

<b>Other information</b>
--------------------------

Trade name: einza Aqua-Kunststoff, RAL 7030 steingrau

Product no.: 0171158

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:  
GER

No data available.

**SECTION 10: Stability and reactivity****10.1 Reactivity**

Stable under recommended storage and handling conditions (See section 7).

**10.2 Chemical stability**

Stable under recommended storage and handling conditions (See section 7).

**10.3 Possibility of hazardous reactions**

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**10.4 Conditions to avoid**

Heat, naked flames and other ignition sources.

**10.5 Incompatible materials**

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**10.6 Hazardous decomposition products**

None if stored, handled and transported properly. In case of fire: see section 5.

**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
LD50		4016	mg/kg bodyweight
Species	rat		
Method	EC 440/2008, B.1		
Source	ECHA		

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
LD50		> 2000	mg/kg bodyweight
Species	rat		
Method	440/2008/EC B.3.		
Source	ECHA		

Acute inhalational toxicity			
No data available			

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
Species	rabbit		
Method	EC 440/2008, B.4		
Source	ECHA		
Evaluation	non-irritant		

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
Species	rabbit		
Method	2004/73/EEC, B.5		
Source	ECHA		
Evaluation	non-irritant		

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1

Trade name: einzA Aqua-Kunststoff, RAL 7030 steingrau

Product no.: 0171158

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:  
GER

Route of exposure	Skin
Species	guinea pig
Method	440/2008/EC B.6
Source	ECHA
Evaluation	non-sensitizing

<b>Germ cell mutagenicity</b>
No data available

<b>Reproduction toxicity</b>
No data available

<b>Carcinogenicity</b>
No data available

<b>STOT - single exposure</b>
No data available

<b>STOT - repeated exposure</b>
No data available

<b>Aspiration hazard</b>
No data available

<b>Delayed and immediate effects as well as chronic effects from short and long-term exposure</b>
Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

## 11.2 Information on other hazards

<b>Endocrine disrupting properties</b>
No data available

### Other information

No data available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Toxicity to fish (acute)				
No	Substance name	CAS no.		EC no.
1	1-methoxy-2-propanol	107-98-2		203-539-1
LC50		> 4600	- 10000	mg/l
Duration of exposure			96	h
Species	Leuciscus idus			
Method	DIN 38 412, part L15			
Source	ECHA			
Evaluation/classification	Based on available data, the classification criteria are not met.			

<b>Toxicity to fish (chronic)</b>
No data available

Toxicity to Daphnia (acute)				
No	Substance name	CAS no.		EC no.
1	1-methoxy-2-propanol	107-98-2		203-539-1
EC50		21100	- 25900	mg/l
Duration of exposure			48	h
Species	Daphnia magna			

Trade name: einzA Aqua-Kunststoff, RAL 7030 steingrau

Product no.: 0171158

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:  
GER

Method	ESR-ES-15
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

<b>Toxicity to Daphnia (chronic)</b>
No data available

<b>Toxicity to algae (acute)</b>
No data available

<b>Toxicity to algae (chronic)</b>
No data available

<b>Bacteria toxicity</b>
No data available

**12.2 Persistence and degradability**

Biodegradability			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
Type		aerobic biodegradation	
Value		96	%
Duration		28	day(s)
Method		OECD 301 E	
Source		ECHA	
Evaluation		readily biodegradable	

**12.3 Bioaccumulative potential**

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
log Pow		<	1
Reference temperature			20 °C
with reference to		pH: 6.8	
Method		OECD 117	
Source		ECHA	

**12.4 Mobility in soil**

No data available.

**12.5 Results of PBT and vPvB assessment**

No data available.

**12.6 Endocrine disrupting properties**

No data available.

**12.7 Other adverse effects**

No data available.

**12.8 Other information**

<b>Other information</b>
Do not allow to enter drains or water courses.

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

**Product**

Waste code 08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company. Allow paint/varnish to dry out completely in a well-ventilated area and dispose of in residual waste once completely solidified. Dispose of liquid or non-drying residues separately.

**Trade name:** einza Aqua-Kunststoff, RAL 7030 steingrau

**Product no.:** 0171158

**Current version:** 1.0.0, Revision: 28.01.2026

**Replaced version:** -, Revision: -

**Region:**  
GER

Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

**Packaging**

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

## SECTION 14: Transport information

**14.1 UN number or ID number**

Not classified as dangerous in the meaning of transport regulations.

**14.2 UN proper shipping name**

Not classified as dangerous in the meaning of transport regulations.

**14.3 Transport hazard class(es)**

Not classified as dangerous in the meaning of transport regulations.

**14.4 Packing group**

Not classified as dangerous in the meaning of transport regulations.

**14.5 Environmental hazards**

Not classified as dangerous in the meaning of transport regulations.

**14.6 Special precautions for user**

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments**

Not relevant

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulations**

**Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

**REACH candidate list of substances of very high concern (SVHC) for authorisation**

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

**Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES**

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	1,2-benzisothiazol-3(2H)-one	2634-33-5	220-120-9	75
2	2-(2-butoxyethoxy)ethanol	112-34-5	203-961-6	75
3	Calcium carbonate	471-34-1	207-439-9	75
4	diiron trioxide	1309-37-1	215-168-2	75
5	Iron hydroxide oxide yellow	51274-00-1	257-098-5	75
6	Limestone	1317-65-3	215-279-6	75
7	pyridine-2-thiol 1-oxide, sodium salt	3811-73-2	223-296-5	75
8	titanium dioxide	13463-67-7	236-675-5	75
9	triiron-tetraoxide	1317-61-9	215-277-5	75

**Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances**

This product is not subject to Part 1 or 2 of Annex I.

Trade name: einzA Aqua-Kunststoff, RAL 7030 steingrau

Product no.: 0171158

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:  
GER**Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)**

VOC content	3,81 %
-------------	--------

**Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products**

relevant VOC limit value as referred to in Annex II of Directive 2004/42/CE , Cat. : i, type: wb = 140 g/l  
Max. VOC content (limit value) of the product in its ready for use condition = < 140 g/l

**National regulations****Water Hazard Class (Germany)**

Class 2  
Source Classification according to AwSV (Regulation on facilities for handling substances that are hazardous to water).

**Other regulations**

GISCODE BSW30 Covering agents, water based, solvent-containing

**Other national regulations**

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment. For example, TRGS (Technical Rules for Hazardous Substances) and the DGUV (German Social Accident Insurance) rules.

**15.2 Chemical safety assessment**

A chemical safety assessment has not been carried out for this mixture.

**SECTION 16: Other information****Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

**Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)**

EUH070	Toxic by eye contact.
EUH071	Corrosive to the respiratory tract.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

**Classification information**

**Trade name:** einzA Aqua-Kunststoff, RAL 7030 steingrau

**Product no.:** 0171158

**Current version:** 1.0.0, Revision: 28.01.2026

**Replaced version:** -, Revision: -

**Region:**  
GER

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

This product does not meet the classification criteria given in the Regulation (EC) No 1272/2008 (CLP).

**Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)**

B Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

**Creation of the safety data sheet**

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: [umco@umco.de](mailto:umco@umco.de)

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

This document is an English translation of the legally compliant safety data sheet of the region Germany. This document, including UFI and emergency telephone number, may only be used for placing on the market in the region Germany.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.  
Prod-ID 653618