

Product no.: 0076097

Current version: 4.2.0, issued: 21.12.2023 Replaced version: 4.1.0. issued: 07.02.2022 Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier 1 1

Trade name

einzA mix Aqua-PU seidenmatt, Basis 3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

decorative paints/finishes

Uses advised against

No data available

1.3 Details of the supplier of the safety data sheet

Address

einzA Farben GmbH & Co KG

Junkersstraße 13 30179 Hannover

+49 (0)511 67490-0 Telephone no. +49 (0)511 67490-20 Fax no e-mail info@einzA.com

Advice on Safety Data Sheet

sdb info@umco.de

Emergency telephone number

For medical advice (in German and English): +49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

This product does not meet the classification criteria given in the Regulation (EC) No 1272/2008 (CLP).

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms

Signal word

Hazard statement(s)

Hazard statements (EU)

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-

3-one and 2-methyl-2H -isothiazol-3-one (3:1). May produce an allergic reaction.

EUH210 Safety data sheet available on request.

Precautionary statement(s)

Labelling information

The labelling (EU hazard statements) meets the criteria of annex II of Directive (EC) Nr. 1272/2008 (CLP).



Trade name: einzA mix Aqua-PU seidenmatt, Basis 3

Product no.: 0076097

Current version: 4.2.0, issued: 21.12.2023 Replaced version: 4.1.0, issued: 07.02.2022 Region: GB

2.3 Other hazards

PBT assessment

The components of this product are not considered to be a PBT.

vPvB assessment

The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Hazardous ingredients

No	Substance name		Additional information	
	CAS / EC / Index /	Classification (EC) 1272/2008 (CLP)	Concentration	%
	REACH no			
1		YLETHOXY)PROPANOL		
	34590-94-8	-	< 2.50	wt%
	252-104-2		2.00	11170
	-			
	01-2119450011-60			
2	triethylamine			
	121-44-8	Flam. Liq. 2; H225	< 1.00	wt%
	204-469-4	Acute Tox. 4; H302		
	612-004-00-5	Acute Tox. 3; H311		
	01-2119475467-26	Skin Corr. 1A; H314		
		Acute Tox. 3; H331		
		STOT SE 3; H335		
3	1,2-benzisothiazol-		pls. refer to footnote (1)	
	2634-33-5	Acute Tox. 4*; H302	< 0.05	wt%
	220-120-9	Eye Dam. 1; H318		
	613-088-00-6	Skin Irrit. 2; H315		
	-	Skin Sens. 1; H317		
		Acute Tox. 2; H330		
		Aguatic Acute 1; H400		
		Aquatic Chronic 2; H411		
4	pyridine-2-thiol 1-c			
-	3811-73-2	EUH070	< 0.10	wt%
	223-296-5	Acute Tox. 4; H302		
	613-344-00-7	Acute Tox. 3; H311		
	-	Acute Tox. 3; H331		
		Skin Irrit. 2; H315		
		Skin Sens. 1; H317		
		Eye Irrit. 2; H319		
		STOT RE 1; H372		
		Aquatic Acute 1; H400		
		Aquatic Chronic 2; H411		
5	reaction mass of: 5	5-chloro-2-methyl-4-isothiazolin-3-one and 2-		
	methyl-2H -isothia:			
	55965-84-9	Acute Tox. 2; H310	< 0.0015	wt%
	-	Acute Tox. 2; H330		
	613-167-00-5	Acute Tox. 3; H301		
	-	Aquatic Acute 1; H400		
		Aquatic Chronic 1; H410		
		EÚH071		
		Eye Dam. 1; H318		
		Skin Corr. 1C; H314		
<u> </u>		Skin Sens. 1A; H317		
6	propane-1,2-diol			
			•	



Trade name: einzA mix Aqua-PU seidenmatt, Basis 3

Product no.: 0076097

Current version: 4.2.0, issued: 21.12.2023 Reglaced version: 4.1.0, issued: 07.02.2022 Region: GB

57-55-6 200-338-0	-	<	2.50	wt%
01-2119456809-23				

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(*,**,***,****) Detailed explanation pls. refer to CLP regulation No. 1272/2008, annex VI, 1.2

(1) Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
2	-	STOT SE 3; H335: C >= 1%	-	-
3	-	Skin Sens. 1; H317: C >= 0.05%	-	-
4	-	-	M = 100	-
5	В	Skin Sens. 1A; H317: C >= 0.0015% Eye Irrit. 2; H319: C >= 0.06% Skin Irrit. 2; H315: C >= 0.06% Skin Corr. 1C; H314: C >= 0.6% Eye Dam. 1; H318: C >= 0.6%	M = 100	M = 100

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

No	Route, target organ, concrete effect
4	H372
	-; nervous system; -

Acu	Acute toxicity estimate (ATE) values					
No	oral	dermal	inhalative			
2	730 mg/kg bodyweight	580 mg/kg bodyweight				

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO2, powders, water spray

Unsuitable extinguishing media

water jet.



Product no.: 0076097

Current version: 4.2.0, issued: 21.12.2023 Reglaced version: 4.1.0, issued: 07.02.2022 Region: GB

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO2); Toxic pyrolysis products: Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Due to the organic solvents' content of the mixture: Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flatting] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

7.3 Specific end use(s)

No data available.



Product no.: 0076097

Current version: 4.2.0, issued: 21.12.2023 Replaced version: 4.1.0, issued: 07.02.2022 Region: GB

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.		EC no.	
1	(2-METHOXYMETHYLETHOXY)PROPANOL	34590-94-8		252-104-2	
	2000/39/EC				
	(2-Methoxymethylethoxy)-propanol				
	WEL long-term (8-hr TWA reference period)	308	mg/m³	50	ppm
	Skin resorption / sensibilisation	Skin			
	List of approved workplace exposure limits (WELs) / E	EH40			
	(2-Methoxymethylethoxy) propanol				
	WEL long-term (8-hr TWA reference period)	308	mg/m³	50	ppm
	Comments	Sk			
2	propane-1,2-diol	57-55-6		200-338-0	
	List of approved workplace exposure limits (WELs) / E	H40			
	Propane-1,2-diol				
	vapour & particulates				
	WEL long-term (8-hr TWA reference period)	474	mg/m³	150	ppm
	List of approved workplace exposure limits (WELs) / E	EH40			
	Propane-1,2-diol particulates				
	WEL long-term (8-hr TWA reference period)	10	mg/m³		
3	triethylamine	121-44-8		204-469-4	
	2000/39/EC				
	Triethylamine				
	WEL short-term (15 min reference period)	12.6	mg/m³	3	ppm
	WEL long-term (8-hr TWA reference period)	8.4	mg/m³	2	ppm
	Skin resorption / sensibilisation	Skin			
	List of approved workplace exposure limits (WELs) / E	H40			
	Triethylamine				
	WEL short-term (15 min reference period)	17	mg/m³	4	ppm
	WEL long-term (8-hr TWA reference period)	8	mg/m³	2	ppm
	Comments	Sk			

DNEL, DMEL and PNEC values

DNEL values (worker)

	DIVEL VAIACS (WOLKEL)					
No	Substance name			CAS / EC	no	
	Route of exposure	Exposure time	Effect	Value		
1	triethylamine			121-44-8		
	_			204-469-4	ļ	
	dermal	Long term (chronic)	systemic	12.1	mg/kg/day	
	inhalative	Long term (chronic)	systemic	8.4	mg/m³	
	inhalative	Short term (acut)	systemic	12.6	mg/m³	
	inhalative	Long term (chronic)	local	8.4	mg/m³	
	inhalative	Short term (acut)	local	12.6	mg/m³	

PNEC values

No	Substance name	CAS / EC no		
	ecological compartment	Туре	Value	
1	triethylamine		121-44-8	
			204-469-4	
	water	fresh water	0.11	mg/L
	water	marine water	0.011	mg/L
	water	fresh water sediment	1.575	mg/kg dry
				weight
	water	marine water sediment	0.158	mg/kg dry
				weight



Product no.: 0076097

Current version: 4.2.0, issued: 21.12.2023 Replaced version: 4.1.0, issued: 07.02.2022 Region: GB

soil	-	0.25	mg/kg dry weight
sewage treatment plant	•	100	mg/L

8.2 Exposure controls

Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

Eye / face protection

Wear safety googles to protect against splashes. Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific workstation suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material In case of short-term contact / splash protection: nitrile rubber

Material thickness>0.4mmBreakthrough time>120minAppropriate MaterialIn case of prolonged exposure: nitrile rubberMaterial thickness>0.4mmBreakthrough time>480min

Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation						
liquid						
Farm						
Form						
liquid						
Colour						
according to product name						
Odour						
characteristic						
will value						
pH value	_					
Value	8	3.0 -	8.3			
Boiling point / boiling range						
Value	appr.		100	°C		
Malting nation/functions nation	_				_	
Melting point/freezing point						
No data available						



Product no.: 0076097

Current version: 4.2.0, issued: 21.12.2023 Replaced version: 4.1.0, issued: 07.02.2022 Region: GB

Decomposition temperature
No data available

Flash point Not applicable

Ignition temperature No data available

Oxidising properties Not applicable

Flammability	
Not applicable	

Lower explosion limit	
No data available	

Upper explosion limit	
No data available	

Vapour pressure			
Value	<	100	hPa
Reference temperature		50	°C

Relative vapour density	
No data available	
No data avallable	

Relative density	
No data available	

Density			
Value	appr.	1.20	g/cm³
Reference temperature		20	°C
Method	DIN 51757		

Solubility in water		
Comments	miscible	

Solubility	
No data available	

Part	Partition coefficient n-octanol/water (log value)				
No	Substance name	CAS no.		EC no.	
1	triethylamine	121-44-8		204-469-4	
log F	Pow		1.45		
with	reference to	pH: 13			
Sour	ce	ECHA			

Kinematic viscosity		
Value	1900 - 2300 mPa*s	
Reference temperature	20 °C	
Method	DIN 53019	

Solvent separation test	
Not applicable	

Particle characteristics	
No data available	

9.2 Other information

Other information	
No data available.	

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage and handling conditions (See section 7).



Product no.: 0076097

Current version: 4.2.0, issued: 21.12.2023 Replaced version: 4.1.0, issued: 07.02.2022 Region: GB

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acu	Acute oral toxicity				
No	Substance name	CAS no.	EC no.		
1	triethylamine	121-44-8	204-469-4		
LD5	0	73	30 mg/kg bodyweight		
Spe	cies	rat			
Meth	nod	OECD 401			
Soul	rce	ECHA			
Eval	uation/classification	Based on available data, the cla	ssification criteria are met.		

Acu	Acute dermal toxicity (result of the ATE calculation for the mixture)			
No	Product Name			
1	einzA mix Aqua-PU seidenmatt, Basis 3			
Con	Comments The result of the applied calculation method according to the			
	European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Paragraph			
		3 of Annex I is outside the values that imply a classification / labelling		
		of this mixture according to table 3.1.1 defining the respective		
		categories (ATE dermal > 2000 mg/kg).		

Acu	Acute dermal toxicity				
No	Substance name	CAS no.	EC no.		
1	triethylamine	121-44-8	204-469-4		
LD5	0	580	mg/kg bodyweight		
Spe	cies	rabbit			
Meth	nod	OECD 402			
Soul	rce	ECHA			
Eval	uation/classification	Based on available data, the classit	fication criteria are met.		

Acu	Acute inhalational toxicity (result of the ATE calculation for the mixture)			
No	Product Name			
1	einzA mix Aqua-PU seidenmatt, Basis 3			
1 einzA mix Aqua-PU seidenmatt, Basis 3 Comments		The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE for inhalation: > 20.000 ppmV (gases), > 20 mg/l (vapours), > 5 mg/l (dusts/mists).		

Acute inhalational toxicity	
No data available	

Skin corrosion/irritation				
No	Substance name	CAS no.	EC no.	
1	triethylamine	121-44-8	204-469-4	
Spe	cies	rabbit		
		OECD 404		



Product no.: 0076097

Current version: 4.2.0, issued: 21.12.2023 Replaced version: 4.1.0, issued: 07.02.2022 Region: GB

Source EVAIUation Corrosive
Evaluation/classification Based on available data, the classification criteria are met.

Seri	ous eye damage/irritation			
No	Substance name	CAS no.	EC no.	
1	triethylamine	121-44-8	204-469-4	
Spe	cies	rabbit		
Meth	nod	OECD 405		
Soul	rce	ECHA		
Eval	uation	strongly irritant		
Eval	uation/classification	Based on available data, the classification criteria are met.		

Respiratory	or skin	sensitisation
-------------	---------	---------------

No data available

Germ cell mutagenicity

No data available

Reproduction toxicity

No data available

Carcinogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration hazard

No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

11.2 Information on other hazards

Endocrine disrupting properties

No data available.

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Tox	Toxicity to fish (acute)			
No	Substance name	CAS no.		EC no.
1	triethylamine	121-44-8		204-469-4
LC5	0		24	mg/l
Dura	ation of exposure		96	h
Spe	cies	Oryzias latipes		
Met	nod	OECD 203		
Sou	rce	ECHA		
Eva	uation/classification	Based on available data, the	classification	n criteria are not met.

Toxicity to fish (chronic)



Product no.: 0076097

Current version: 4.2.0, issued: 21.12.2023 Replaced version: 4.1.0, issued: 07.02.2022 Region: GB

No data available

Toxicity to Daphnia (acute)

No data available

Toxicity to Daphnia (chronic)

No data available

Toxi	city to algae (acute)				
No	Substance name	CAS no.	EC no.		
1	triethylamine	121-44-8	204-469-4		
EC5	0	8	mg/l		
Dura	ation of exposure	7	72 h		
Spe	Species Pseudokirchneriella subcapitata				
Meth	Method OECD 201				
Sou	rce	ECHA			
Eval	uation/classification	Based on available data, the cla	assification criteria are not met.		

Toxicity to algae (chronic)

No data available

Bacteria toxicity
No data available

12.2 Persistence and degradability

Biod	Biodegradability				
No	Substance name	CAS no.		EC no.	
1	triethylamine	121-44-8		204-469-4	
Туре	e	aerobic biodegradation			
Valu	е		80.3	%	
Dura	ation		29	day(s)	
Meth	nod	OECD 301 B		• • •	
Sou	rce	ECHA			
Eval	uation	readily biodegradable			

12.3 Bioaccumulative potential

Biod	Bioconcentration factor (BCF)			
No	Substance name	CAS no.		EC no.
1	triethylamine	121-44-8		204-469-4
BCF		<	0.5	
Spe	cies	Cyprinus carpio		
Method		OECD 305 C		
Soul	rce	ECHA		

Partition coefficient n-octanol/water (log value)				
No	Substance name	CAS no.		EC no.
1	triethylamine	121-44-8		204-469-4
log Pow			1.45	
with reference to		pH: 13		
Source		ECHA		

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment		
PBT assessment	The components of this product are not considered to be a PBT.	
vPvB assessment	The components of this product are not considered to be a vPvB.	

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.



Trade name: einzA mix Aqua-PU seidenmatt, Basis 3

Product no.: 0076097

Current version: 4.2.0, issued: 21.12.2023 Replaced version: 4.1.0, issued: 07.02.2022 Region: GB

12.8 Other information

Other information

Do not allow to enter drains or water courses.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste code 08 01 11*

waste paint and varnish containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company. Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

The product is not subject to ADR/RID/ADN regulations.

14.2 Transport IMDG

The product is not subject to IMDG regulations.

14.3 Transport ICAO-TI / IATA

The product is not subject to ICAO-TI / IATA regulations.

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No Substance name CAS no. EC no. No



Trade name: einzA mix Aqua-PU seidenmatt, Basis 3

Product no.: 0076097

Current version: 4.2.0, issued: 21.12.2023 Replaced version: 4.1.0, issued: 07.02.2022 Region: GB

1	1,2-benzisothiazol-3(2H)-one	2634-33-5	220-120-9	75	
2	Limestone	1317-65-3	215-279-6	75	
3	pyridine-2-thiol 1-oxide, sodium salt	3811-73-2	223-296-5	75	
4	triethylamine	121-44-8	204-469-4	75	

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is not subject to Part 1 or 2 of Annex I.

Directive 2010/75/EU on industrial emissions	(integrated pollution prevention and control)
VOC content	3.65 %

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products

relevant VOC limit value as referred to in Annex II of Directive 2004/42/CE , Cat. : d, type: wb = 130 g/l Max. VOC content (limit value) of the product in its ready for use condition = < 130 g/l

National regulations

Other national regulations

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

EUH070 Toxic by eye contact.
EUH071 Corrosive to the respiratory tract.

H225 Highly flammable liquid and vapour.
H301 Toxic if swallowed.

H301 Toxic if swallowed.
H302 Harmful if swallowed.
H310 Fatal in contact with skin.
H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.

H330 Fatal if inhaled. H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)



Trade name: einzA mix Aqua-PU seidenmatt, Basis 3

Product no.: 0076097

Current version: 4.2.0, issued: 21.12.2023 Replaced version: 4.1.0, issued: 07.02.2022 Region: GB

В

Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH. Prod-ID 760329