

**Product no.:** 7205031

Current version: 7.4.0. issued: 21.12.2023 Replaced version: 7.3.1, issued: 07.08.2023 Region: GB

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **Product identifier** 1 1

Trade name

## einzA Aqua-Siegel glänzend, farblos

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses of the substance or mixture

decorative paints/finishes

#### Uses advised against

No data available

#### 1.3 Details of the supplier of the safety data sheet

#### Address

einzA Farben GmbH & Co KG

Junkersstraße 13 30179 Hannover

+49 (0)511 67490-0 Telephone no. +49 (0)511 67490-20 Fax no info@einzA.com

#### **Advice on Safety Data Sheet**

sdb info@umco.de

#### **Emergency telephone number**

For medical advice (in German and English): +49 (0)551 192 40 (Giftinformationszentrum Nord)

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

This product does not meet the classification criteria given in the Regulation (EC) No 1272/2008 (CLP).

#### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

### Hazard pictograms

#### Signal word

#### Hazard statement(s)

Hazard statements (EU)

Contains adipohydrazide, 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-**EUH208** 

methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1). May produce an

allergic reaction.

**EUH210** Safety data sheet available on request.

## Precautionary statement(s)

#### Labelling information

The labelling (EU hazard statements) meets the criteria of annex II of Directive (EC) Nr. 1272/2008 (CLP).



Trade name: einzA Aqua-Siegel glänzend, farblos

**Product no.:** 7205031

**Current version : 7.4.0, issued: 21.12.2023 Replaced version: 7.3.1, issued: 07.08.2023 Region: GB** 

## 2.3 Other hazards

PBT assessment

The components of this product are not considered to be a PBT.

vPvB assessment

The components of this product are not considered to be a vPvB.

## **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Not applicable. The product is not a substance.

#### 3.2 Mixtures

**Hazardous ingredients** 

No	Substance name		Additi	Additional information	
	CAS / EC / Index /	Classification (EC) 1272/2008 (CLP)	Conce	entration	%
	REACH no				
1		YLETHOXY)PROPANOL			
	34590-94-8	-	<	5.00	wt%
	252-104-2				
	-				
2	01-2119450011-60				
	adipohydrazide 1071-93-8	Skin Sens. 1; H317	<	2.50	wt%
	213-999-5	Skill Sells. 1, H317	`	2.50	W1%
	_				
	_				
3	triethylamine				
	121-44-8	Flam. Lig. 2; H225	<	1.00	wt%
	204-469-4	Acute Tox. 4; H302			
	612-004-00-5	Acute Tox. 3; H311			
	01-2119475467-26	Skin Corr. 1A; H314			
		Acute Tox. 3; H331			
		STOT SE 3; H335			
4	1,2-benzisothiazol-			efer to footnote (1)	
	2634-33-5	Acute Tox. 4*; H302	<	0.05	wt%
	220-120-9	Eye Dam. 1; H318			
	613-088-00-6	Skin Irrit. 2; H315			
	-	Skin Sens. 1; H317			
		Acute Tox. 2; H330 Aquatic Acute 1; H400			
		Aquatic Acute 1, 1400 Aquatic Chronic 2; H411			
5	pyridine-2-thiol 1-o				
	3811-73-2	EUH070	<	0.10	wt%
	223-296-5	Acute Tox. 4; H302		0.10	11170
	613-344-00-7	Acute Tox. 3; H311			
	-	Acute Tox. 3; H331			
		Skin Irrit. 2; H315			
		Skin Sens. 1; H317			
		Eye Irrit. 2; H319			
		STOT RE 1; H372			
		Aquatic Acute 1; H400			
		Aquatic Chronic 2; H411			
6		-chloro-2-methyl-4-isothiazolin-3-one and 2-			
	methyl-2H -isothiaz	zoi-3-one (3:1)			



**Product no.:** 7205031

Current version: 7.4.0, issued: 21.12.2023 Replaced version: 7.3.1, issued: 07.08.2023 Region: GB

	55965-84-9 - 613-167-00-5 -	Acute Tox. 2; H310 Acute Tox. 2; H330 Acute Tox. 3; H301 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 Eye Dam. 1; H318 Skin Corr. 1C; H314 Skin Sens. 1A; H317	<	0.0015	wt%
7	propane-1,2-diol				
	57-55-6	-	<	5.00	wt%
	200-338-0				
	-				
	01-2119456809-23				

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(\*,\*\*,\*\*\*\*) Detailed explanation pls. refer to CLP regulation No. 1272/2008, annex VI, 1.2

<sup>(1)</sup> Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
3	=	STOT SE 3; H335: C >= 1%	-	-
4	-	Skin Sens. 1; H317: C >= 0.05%	-	-
5	-	-	M = 100	-
6	В	Skin Sens. 1A; H317: C >= 0.0015% Eye Irrit. 2; H319: C >= 0.06% Skin Irrit. 2; H315: C >= 0.06% Skin Corr. 1C; H314: C >= 0.6% Eye Dam. 1; H318: C >= 0.6%	M = 100	M = 100

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

No	Route, target organ, concrete effect
5	H372
	-; nervous system; -

Acu	Acute toxicity estimate (ATE) values					
No	oral	dermal	inhalative			
3	730 mg/kg bodyweight	580 mg/kg bodyweight				

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

#### **General information**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

### After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

#### After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

#### After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

### After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

No data available.



Product no.: 7205031

Current version: 7.4.0, issued: 21.12.2023 Reglaced version: 7.3.1, issued: 07.08.2023 Region: GB

#### 4.3 Indication of any immediate medical attention and special treatment needed

No data available.

## **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

#### Suitable extinguishing media

Alcohol resistant foam, CO2, powders, water spray

## Unsuitable extinguishing media

water jet.

#### 5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO2); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

#### 5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

#### For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

#### 6.2 Environmental precautions

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

#### 6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

#### 6.4 Reference to other sections

No data available.

## **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

#### Advice on safe handling

Due to the organic solvents' content of the mixture: Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flatting] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

#### General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

#### Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

#### 7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions



**Product no.:** 7205031

Current version: 7.4.0, issued: 21.12.2023 Reglaced version: 7.3.1, issued: 07.08.2023 Region: GB

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

#### Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

#### Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

### 7.3 Specific end use(s)

No data available.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

### Occupational exposure limit values

No	Substance name	CAS no.		EC no.		
1	propane-1,2-diol	57-55-6		200-338-0		
	List of approved workplace exposure limits (WELs) / EH40					
	Propane-1,2-diol					
	vapour & particulates					
	WEL long-term (8-hr TWA reference period)	474	mg/m³	150	ppm	
	List of approved workplace exposure limits (WELs) / I	EH40				
	Propane-1,2-diol particulates	-				
	WEL long-term (8-hr TWA reference period)	10	mg/m³			
2	(2-METHOXYMETHYLETHOXY)PROPANOL	34590-94-8		252-104-2		
	2000/39/EC					
	(2-Methoxymethylethoxy)-propanol					
	WEL long-term (8-hr TWA reference period)	308	mg/m³	50	ppm	
	Skin resorption / sensibilisation	Skin				
	List of approved workplace exposure limits (WELs) / EH40					
	(2-Methoxymethylethoxy) propanol					
	WEL long-term (8-hr TWA reference period)	308	mg/m³	50	ppm	
	Comments	Sk				
3	triethylamine	121-44-8		204-469-4		
	2000/39/EC					
	Triethylamine					
	WEL short-term (15 min reference period)	12.6	mg/m³	3	ppm	
	WEL long-term (8-hr TWA reference period)	8.4	mg/m³	2	ppm	
	Skin resorption / sensibilisation	Skin				
	List of approved workplace exposure limits (WELs) / I	EH40				
	Triethylamine					
	WEL short-term (15 min reference period)	17	mg/m³	4	ppm	
	WEL long-term (8-hr TWA reference period)	8	mg/m³	2	ppm	
	Comments	Sk				

#### **DNEL, DMEL and PNEC values**

## **DNEL values (worker)**

No	Substance name			CAS / EC no	
	Route of exposure		Effect	Value	
1	triethylamine			121-44-8	
				204-469-4	
	dermal	Long term (chronic)	systemic	12.1	mg/kg/day
	inhalative	Long term (chronic)	systemic	8.4	mg/m³
	inhalative	Short term (acut)	systemic	12.6	mg/m³
	inhalative	Long term (chronic)	local	8.4	mg/m³
	inhalative	Short term (acut)	local	12.6	mg/m³

**PNEC values** 



**Product no.:** 7205031

Current version: 7.4.0, issued: 21.12.2023 Replaced version: 7.3.1, issued: 07.08.2023 Region: GB

No	Substance name		CAS / EC n	10
	ecological compartment	Туре	Value	
1	triethylamine		121-44-8	
			204-469-4	
	water	fresh water	0.11	mg/L
	water	marine water	0.011	mg/L
	water	fresh water sediment	1.575	mg/kg dry weight
	water	marine water sediment	0.158	mg/kg dry weight
	soil	-	0.25	mg/kg dry weight
	sewage treatment plant	-	100	mg/L

#### 8.2 Exposure controls

#### Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

#### Personal protective equipment

#### Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

#### Eye / face protection

Wear safety googles to protect against splashes. Safety glasses with side protection shield (EN 166)

#### Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material In case of short-term contact / splash protection: nitrile rubber

Material thickness > 0.4 mm

Breakthrough time > 120 min

Appropriate Material In case of prolonged exposure: nitrile rubber

Material thickness > 0.4 mm

Breakthrough time > 480 min

#### Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

#### **Environmental exposure controls**

Do not allow to enter drains or water courses.

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

State of aggregation	
liquid	
Form	

Form	
liquid	

Colour	
according to product name	

Odour	

Solvent separation test

Particle characteristics

Not applicable



Trade name: einzA Aqua-Siegel glänzend, farblos

**Product no.:** 7205031

Current version: 7.4.0, issued: 21.12.2023 Replaced version: 7.3.1, issued: 07.08.2023 Region: GB

EC no.
204-469-4



**Product no.:** 7205031

Current version: 7.4.0, issued: 21.12.2023 Reglaced version: 7.3.1, issued: 07.08.2023 Region: GB

No data available

#### 9.2 Other information

Other information	
No data available.	

## **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

Stable under recommended storage and handling conditions (See section 7).

#### 10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

#### 10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

#### 10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

#### 10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

#### 10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

## **SECTION** 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity					
No	Substance name	CAS no.	EC no.		
1	triethylamine	121-44-8	204-469-4		
LD5	0	730	mg/kg bodyweight		
Spe	cies	rat			
Meth	nod	OECD 401			
Soul	rce	ECHA			
Eval	uation/classification	Based on available data, the class	sification criteria are met.		

Acu	Acute dermal toxicity (result of the ATE calculation for the mixture)				
No	Product Name				
1	einzA Aqua-Siegel glänzend, farblos				
Com	Comments The result of the applied calculation method according to the				
		European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part			
		3 of Annex I is outside the values that imply a classification / labelling			
	of this mixture according to table 3.1.1 defining the respective				
	categories (ATE dermal > 2000 mg/kg).				

Acu	Acute dermal toxicity					
No	Substance name	CAS no.	EC no.			
1	triethylamine	121-44-8	204-469-4			
LD5	0	580	) mg/kg bodyweight			
Spe	cies	rabbit				
Meth	nod	OECD 402				
Soul	rce	ECHA				
Eval	uation/classification	Based on available data, the class	sification criteria are met.			

Acu	Acute inhalational toxicity (result of the ATE calculation for the mixture)		
No	No Product Name		
1	einzA Aqua-Siegel glänzend, farblos		



Trade name: einzA Aqua-Siegel glänzend, farblos

**Product no.:** 7205031

Current version: 7.4.0, issued: 21.12.2023 Reglaced version: 7.3.1, issued: 07.08.2023 Region: GB

Comments	The result of the applied calculation method according to the
	European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part
	3 of Annex I is outside the values that imply a classification / labelling
	of this mixture according to table 3.1.1 defining the respective
	categories (ATE for inhalation: > 20.000 ppmV (gases), > 20 mg/l
	(vapours), > 5 mg/l (dusts/mists).

## Acute inhalational toxicity

No data available

Skin	Skin corrosion/irritation				
No	Substance name	CAS no.	EC no.		
1	triethylamine	121-44-8	204-469-4		
Spec	cies	rabbit			
Meth	nod	OECD 404			
Soul	ce	ECHA			
Eval	uation	corrosive			
Eval	Evaluation/classification Based on available data, the classification criteria are met.				

Seri	Serious eye damage/irritation				
No	Substance name	CAS no.	EC no.		
1	triethylamine	121-44-8	204-469-4		
Spe	cies	rabbit			
Metl	hod	OECD 405			
Sou	rce	ECHA			
Eval	valuation strongly irritant				
Fval	luation/classification	Based on available data, the classification criteria are met.			

#### Respiratory or skin sensitisation

No data available

#### Germ cell mutagenicity

No data available

#### Reproduction toxicity

No data available

## Carcinogenicity

No data available

#### STOT - single exposure

No data available

#### STOT - repeated exposure

No data available

## **Aspiration hazard**

No data available

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

#### 11.2 Information on other hazards

**Endocrine disrupting properties** 

No data available.

#### Other information

No data available.



**Product no.:** 7205031

**Current version : 7.4.0, issued: 21.12.2023 Replaced version: 7.3.1, issued: 07.08.2023 Region: GB** 

## **SECTION 12: Ecological information**

## 12.1 Toxicity

Toxi	Toxicity to fish (acute)				
No	Substance name	CAS no.	EC no.		
1	triethylamine	121-44-8	204-469-4		
LC5	0		24 mg/l		
Dura	ation of exposure		96 h		
Spe	Species Oryzias latipes				
Method OECD 203		OECD 203			
Sou	Source ECHA				
Eval	Evaluation/classification Based on available data, the classification criteria are not met.				

## **Toxicity to fish (chronic)**

No data available

## Toxicity to Daphnia (acute)

No data available

## **Toxicity to Daphnia (chronic)**

No data available

Toxi	Toxicity to algae (acute)				
No	Substance name	CAS no.	EC no.		
1	triethylamine	121-44-8	204-469-4		
EC5	0		8 mg/l		
Dura	Duration of exposure 72 h				
Species Pseudokirchneriella subcapitata			ata		
Meth	nod	OECD 201			
Source   ECHA					
Eval	Evaluation/classification Based on available data, the classification criteria are not met.				

## Toxicity to algae (chronic)

No data available

# Bacteria toxicity No data available

12.2 Persistence and degradability

Biodegradability							
No	Substance name	CAS no.	EC no.				
1	triethylamine	121-44-8	204-469-4				
Туре		aerobic biodegradation					
Value			80.3 %				
Duration			29 day(s)				
Method		OECD 301 B					
Source		ECHA					
Evaluation		readily biodegradable					

12.3 Bioaccumulative potential

Bioconcentration factor (BCF)						
No	Substance name	CAS no.		EC no.		
1	triethylamine	121-44-8	204-469-4			
BCF		<	0.5			
Species		Cyprinus carpio				
Method		OECD 305 C				
Soul	rce	ECHA				

Partition coefficient n-octanol/water (log value)						
No	Substance name	CAS no.		EC no.		
1	triethylamine	121-44-8		204-469-4		
log F	Pow		1.45			
with reference to		pH: 13				
Source		ECHA				



**Product no.:** 7205031

Current version: 7.4.0, issued: 21.12.2023 Replaced version: 7.3.1, issued: 07.08.2023 Region: GB

#### 12.4 Mobility in soil

No data available.

#### 12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment							
PBT assessment	The components of this product are not considered to be a PBT.						
vPvB assessment	The components of this product are not considered to be a vPvB.						

### 12.6 Endocrine disrupting properties

No data available.

#### 12.7 Other adverse effects

No data available.

#### 12.8 Other information

~					4.	
Oth	٥r	ınt	nr	ma	111	Λn

Do not allow to enter drains or water courses.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### **Product**

Waste code 08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company. Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

#### **Packaging**

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

## **SECTION 14: Transport information**

#### 14.1 Transport ADR/RID/ADN

The product is not subject to ADR/RID/ADN regulations.

## 14.2 Transport IMDG

The product is not subject to IMDG regulations.

#### 14.3 Transport ICAO-TI / IATA

The product is not subject to ICAO-TI / IATA regulations.

#### 14.4 Other information

No data available.

#### 14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

### 14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

### 14.7 Maritime transport in bulk according to IMO instruments

Not relevant

#### **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU regulations</u>

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)



Trade name: einzA Aqua-Siegel glänzend, farblos

**Product no.:** 7205031

Current version: 7.4.0, issued: 21.12.2023 Replaced version: 7.3.1, issued: 07.08.2023 Region: GB

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

#### REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

# Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	1,2-benzisothiazol-3(2H)-one	2634-33-5	220-120-9	75
2	2-(2-butoxyethoxy)ethanol	112-34-5	203-961-6	75
3	pyridine-2-thiol 1-oxide, sodium salt	3811-73-2	223-296-5	75
4	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-	55965-84-9	-	75
	one and 2-methyl-2H -isothiazol-3-one (3:1)			
5	triethylamine	121-44-8	204-469-4	75

# Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances This product is not subject to Part 1 or 2 of Annex I.

# Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)VOC content6.41%

# Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products

relevant VOC limit value as referred to in Annex II of Directive 2004/42/CE, Cat. : e, type: wb = 130 g/l Max. VOC content (limit value) of the product in its ready for use condition = < 130 g/l

#### **National regulations**

#### Other national regulations

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

#### 15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

## **SECTION 16: Other information**

#### Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

# Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

EUH070 Toxic by eye contact.
EUH071 Corrosive to the respiratory tract.
H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.
H302 Harmful if swallowed.
H310 Fatal in contact with skin.
H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.



Trade name: einzA Aqua-Siegel glänzend, farblos

**Product no.:** 7205031

Current version: 7.4.0, issued: 21.12.2023 Reglaced version: 7.3.1, issued: 07.08.2023 Region: GB

H319 Causes serious eye irritation. H330 Fatal if inhaled. H331 Toxic if inhaled. H335 May cause respiratory irritation. H372 Causes damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

# Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

В

Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

#### Creation of the safety data sheet

**UMCO GmbH** 

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

#### Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH. Prod-ID 653828