

Trade name: einZA Flüssig-Kunststoff, farblos

Product no.: 5700132

Current version : 2.0.3, issued: 03.01.2024

Replaced version: 2.0.2, issued: 04.07.2023

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

einZA Flüssig-Kunststoff, farblos

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture
decorative paints/finishes

Uses advised against
No data available.

1.3 Details of the supplier of the safety data sheet

Address

einZA Farben GmbH & Co KG
Junkersstraße 13
30179 Hannover

Telephone no. +49 (0)511 67490-0
Fax no. +49 (0)511 67490-20
e-mail info@einZA.com

Advice on Safety Data Sheet
sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):
+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Aquatic Chronic 2; H411
Flam. Liq. 3; H226
STOT SE 3; H335
STOT SE 3; H336

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02



GHS07



GHS09

Signal word

Warning

Hazardous component(s) to be indicated on label:

Hydrocarbons, C9, aromatics

Hazard statement(s)

H226 Flammable liquid and vapour.

Trade name: einZA Flüssig-Kunststoff, farblos

Product no.: 5700132

Current version : 2.0.3, issued: 03.01.2024

Replaced version: 2.0.2, issued: 04.07.2023

Region: GB

H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Hazard statements (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.
 EUH208 Contains methyl-methacrylate, butyl methacrylate, dodecane-1-thiol. May produce an allergic reaction.

Precautionary statement(s)

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P370+P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.
 P391 Collect spillage.
 P405 Store locked up.
 P501 Dispose of contents/container to a facility in accordance with local and national regulations.

2.3 Other hazards

PBT assessment
 The components of this product are not considered to be a PBT.
 vPvB assessment
 The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Hazardous ingredients

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	Hydrocarbons, C9, aromatics		pls. refer to footnote (2)
	64742-95-6 918-668-5 649-356-00-4 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H335 STOT SE 3; H336 Aquatic Chronic 2; H411 Asp. Tox. 1; H304 EUH066	>= 25.00 - < 50.00 wt%
2	1-methoxy-2-propanol		
	107-98-2 203-539-1 603-064-00-3 01-2119457435-35	Flam. Liq. 3; H226 STOT SE 3; H336	>= 5.00 - < 10.00 wt%
3	2-methoxy-1-methylethyl acetate		
	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336	>= 5.00 - < 10.00 wt%
4	methyl-methacrylate		
	80-62-6 201-297-1 607-035-00-6 01-2119452498-28	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335	< 0.50 wt%
5	butyl methacrylate		

Trade name: einZA Flüssig-Kunststoff, farblos

Product no.: 5700132

Current version : 2.0.3, issued: 03.01.2024

Replaced version: 2.0.2, issued: 04.07.2023

Region: GB

	97-88-1 202-615-1 607-033-00-5 01-2119486394-28	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 STOT SE 3; H335	< 0.50	wt%
6	dodecane-1-thiol			
	112-55-0 203-984-1 - 01-2119491318-31	Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	< 0.10	wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(2) According to the latest state of knowledge and applying the criteria set out in annex I to Regulation (EC) No 1272/2008, the aforementioned classification is required. This classification goes beyond the classification set out in table 3, Annex VI to Regulation (CE) No 1272/2008.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	P	-	-	-
4	D	-	-	-
6	-	-	M = 10	M = 10

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO₂, powders, water spray

Unsuitable extinguishing media

water jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Trade name: einZA Flüssig-Kunststoff, farblos

Product no.: 5700132

Current version : 2.0.3, issued: 03.01.2024

Replaced version: 2.0.2, issued: 04.07.2023

Region: GB

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flattening] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Trade name: einzA Flüssig-Kunststoff, farblos

Product no.: 5700132

Current version : 2.0.3, issued: 03.01.2024

Replaced version: 2.0.2, issued: 04.07.2023

Region: GB

Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
	2000/39/EC		
	1-Methoxypropanol-2		
	WEL short-term (15 min reference period)	568 mg/m ³	150 ppm
	WEL long-term (8-hr TWA reference period)	375 mg/m ³	100 ppm
	Skin resorption / sensibilisation	Skin	
	List of approved workplace exposure limits (WELs) / EH40		
	1-Methoxypropan-2-ol		
	WEL short-term (15 min reference period)	560 mg/m ³	150 ppm
	WEL long-term (8-hr TWA reference period)	375 mg/m ³	100 ppm
	Comments	Sk	
2	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
	List of approved workplace exposure limits (WELs) / EH40		
	1-Methoxypropylacetate		
	WEL short-term (15 min reference period)	548 mg/m ³	100 ppm
	WEL long-term (8-hr TWA reference period)	274 mg/m ³	50 ppm
	Comments	Sk	
	2000/39/EC		
	2-Methoxy-1-methylethylacetate		
	WEL short-term (15 min reference period)	550 mg/m ³	100 ppm
	WEL long-term (8-hr TWA reference period)	275 mg/m ³	50 ppm
	Skin resorption / sensibilisation	Skin	

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name	CAS / EC no		
	Route of exposure	Exposure time	Effect	Value
1	Hydrocarbons, C9, aromatics			64742-95-6 918-668-5
	dermal	Long term (chronic)	systemic	12.5 mg/kg/day
	inhalative	Long term (chronic)	systemic	151 mg/m ³
2	1-methoxy-2-propanol			107-98-2 203-539-1
	dermal	Long term (chronic)	systemic	183 mg/kg/day
	inhalative	Long term (chronic)	systemic	369 mg/m ³
	inhalative	Short term (acut)	local	553.5 mg/m ³
	inhalative	Short term (acut)	systemic	553.5 mg/m ³
3	2-methoxy-1-methylethyl acetate			108-65-6 203-603-9
	dermal	Long term (chronic)	systemic	796 mg/kg/day
	inhalative	Long term (chronic)	systemic	275 mg/m ³
	inhalative	Short term (acut)	local	550 mg/m ³

DNEL value (consumer)

No	Substance name	CAS / EC no		
	Route of exposure	Exposure time	Effect	Value
1	Hydrocarbons, C9, aromatics			64742-95-6 918-668-5
	oral	Long term (chronic)	systemic	7.5 mg/kg/day
	dermal	Long term (chronic)	systemic	7.5 mg/kg/day
	inhalative	Long term (chronic)	systemic	32 mg/m ³
2	1-methoxy-2-propanol			107-98-2 203-539-1
	oral	Long term (chronic)	systemic	33 mg/kg/day
	dermal	Long term (chronic)	systemic	78 mg/kg/day
	inhalative	Long term (chronic)	systemic	43.9 mg/m ³

Trade name: einza Flüssig-Kunststoff, farblos

Product no.: 5700132

Current version : 2.0.3, issued: 03.01.2024

Replaced version: 2.0.2, issued: 04.07.2023

Region: GB

3	2-methoxy-1-methylethyl acetate			108-65-6 203-603-9
	oral	Long term (chronic)	systemic	36 mg/kg/day
	oral	Short term (acut)	systemic	500 mg/kg/day
	dermal	Long term (chronic)	systemic	320 mg/kg/day
	inhalative	Long term (chronic)	systemic	33 mg/m ³
	inhalative	Long term (chronic)	local	33 mg/m ³

PNEC values

No	Substance name		CAS / EC no	
	ecological compartment	Type	Value	
1	1-methoxy-2-propanol		107-98-2 203-539-1	
	water	fresh water	10	mg/L
	water	marine water	1	mg/L
	water	Aqua intermittent	100	mg/L
	water	fresh water sediment	52.3	mg/kg
	with reference to: dry weight			
	water	marine water sediment	5.2	mg/kg
	with reference to: dry weight			
	soil	-	4.59	mg/kg
	with reference to: dry weight			
	sewage treatment plant	-	100	mg/L
2	2-methoxy-1-methylethyl acetate		108-65-6 203-603-9	
	water	fresh water	0.635	mg/L
	water	marine water	0.064	mg/L
	water	fresh water sediment	3.29	mg/kg
	with reference to: dry weight			
	water	marine water sediment	0.329	mg/kg
	with reference to: dry weight			
	soil	-	0.29	mg/kg
	with reference to: dry weight			
	sewage treatment plant	-	100	mg/L

8.2 Exposure controls

Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

Eye / face protection

Wear safety goggles to protect against splashes. Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material	In case of short-term contact / splash protection: nitrile rubber		
Material thickness	>	0.4	mm
Breakthrough time	>	120	min

Trade name: einZA Flüssig-Kunststoff, farblos

Product no.: 5700132

Current version : 2.0.3, issued: 03.01.2024

Replaced version: 2.0.2, issued: 04.07.2023

Region: GB

Appropriate Material	In case of prolonged exposure: nitrile rubber
Material thickness	> 0.4 mm
Breakthrough time	> 480 min

Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

State of aggregation	
liquid	
Form	
liquid	
Colour	
according to product name	
Odour	
like solvents	
pH value	
No data available	
Boiling point / boiling range	
Value	> 120 °C
Reference substance	solvent mixture
Melting point/freezing point	
No data available	
Decomposition temperature	
No data available	
Flash point	
Value	45 - 48 °C
Method	closed cup
Ignition temperature	
Value	> 200 °C
Reference substance	solvent mixture
Oxidising properties	
Not applicable	
Flammability	
Not applicable	
Lower explosion limit	
Value	> 0.6 % vol
Reference substance	solvent mixture
Upper explosion limit	
Value	< 7.5 % vol
Reference substance	solvent mixture
Vapour pressure	
Value	< 100 hPa
Reference temperature	50 °C
Reference substance	solvent mixture
Relative vapour density	
No data available	

Trade name: einZA Flüssig-Kunststoff, farblos

Product no.: 5700132

Current version : 2.0.3, issued: 03.01.2024

Replaced version: 2.0.2, issued: 04.07.2023

Region: GB

Relative density	
No data available	

Density	
Value	0.98 - 1.17 g/cm ³
Reference temperature	20 °C
Method	DIN 51757

Solubility in water	
Comments	immiscible

Solubility	
No data available	

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
	log Pow	<	1
	Reference temperature		20 °C
	with reference to	pH: 6.8	
	Method	OECD 117	
	Source	ECHA	
2	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
	log Pow		1.2
	Reference temperature		20 °C
	Method	OECD 117	
	Source	ECHA	

Kinematic viscosity	
Value	40 - 44 sec
Reference temperature	20 °C
Method	DIN EN 2431 (6 mm)

Solvent separation test	
Value	< 3 %
Reference temperature	20 °C

Particle characteristics	
No data available	

9.2 Other information

Other information	
No data available.	

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage and handling conditions (See section 7).

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information

Trade name: einzA Flüssig-Kunststoff, farblos

Product no.: 5700132

Current version : 2.0.3, issued: 03.01.2024

Replaced version: 2.0.2, issued: 04.07.2023

Region: GB

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
LD50	>	3492	mg/kg bodyweight
Species	rat		
Source	ECHA		
2	1-methoxy-2-propanol	107-98-2	203-539-1
LD50	>	4016	mg/kg bodyweight
Species	rat		
Method	EC 440/2008, B.1		
Source	ECHA		
3	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
LD50	>	5155	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
LD50	>	3160	mg/kg bodyweight
Species	rabbit		
Method	OECD 402		
Source	ECHA		
2	1-methoxy-2-propanol	107-98-2	203-539-1
LD50	>	2000	mg/kg bodyweight
Species	rat		
Method	440/2008/EC B.3.		
Source	ECHA		
3	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
LD50	>	5000	mg/kg bodyweight
Species	rat		
Method	OECD 402		
Source	ECHA		

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
LC50	>	6.193	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Method	OECD 403		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	low-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	1-methoxy-2-propanol	107-98-2	203-539-1
Species	rabbit		
Method	EC 440/2008, B.4		
Source	ECHA		
Evaluation	non-irritant		
3	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
Species	rabbit		

Trade name: einzA Flüssig-Kunststoff, farblos

Product no.: 5700132

Current version : 2.0.3, issued: 03.01.2024

Replaced version: 2.0.2, issued: 04.07.2023

Region: GB

Method	OECD 404
Source	ECHA
Evaluation	non-irritant

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
Species		rabbit	
Method		OECD 405	
Source		ECHA	
Evaluation		non-irritant	
2	1-methoxy-2-propanol	107-98-2	203-539-1
Species		rabbit	
Method		2004/73/EEC, B.5	
Source		ECHA	
Evaluation		non-irritant	
3	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
Species		rabbit	
Method		OECD 405	
Source		ECHA	
Evaluation		non-irritant	

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
Route of exposure		Skin	
Species		guinea pig	
Method		OECD 406	
Source		ECHA	
Evaluation		non-sensitizing	
2	1-methoxy-2-propanol	107-98-2	203-539-1
Route of exposure		Skin	
Species		guinea pig	
Method		440/2008/EC B.6	
Source		ECHA	
Evaluation		non-sensitizing	
3	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
Route of exposure		Skin	
Species		guinea pig	
Method		OECD 406	
Source		ECHA	
Evaluation		non-sensitizing	

Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
2	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
Type of examination		in vitro gene mutation study in bacteria	
Method		OECD 471	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Carcinogenicity			
No data available			

STOT - single exposure			

Trade name: einZA Flüssig-Kunststoff, farblos

Product no.: 5700132

Current version : 2.0.3, issued: 03.01.2024

Replaced version: 2.0.2, issued: 04.07.2023

Region: GB

No data available

STOT - repeated exposure

No	Substance name	CAS no.	EC no.
1	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
Route of exposure		oral	
Species		rats (male/female)	
Method		OECD 422	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Aspiration hazard

No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

11.2 Information on other hazards**Endocrine disrupting properties**

No data available.

Other information

No data available.

SECTION 12: Ecological information**12.1 Toxicity**

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
LL50		9.2	mg/l
Duration of exposure		96	h
Species		Oncorhynchus mykiss	
Method		OECD 203	
Source		ECHA	
2	1-methoxy-2-propanol	107-98-2	203-539-1
LC50		> 4600	- 10000
Duration of exposure		96	h
Species		Leuciscus idus	
Method		DIN 38 412, part L15	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
3	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
LC50		100	- 180
Duration of exposure		96	h
Species		Oncorhynchus mykiss	
Method		OECD 203	
Source		ECHA	

Toxicity to fish (chronic)

No data available

Toxicity to Daphnia (acute)

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
EL50		3.2	mg/l

Trade name: einZA Flüssig-Kunststoff, farblos

Product no.: 5700132

Current version : 2.0.3, issued: 03.01.2024

Replaced version: 2.0.2, issued: 04.07.2023

Region: GB

Duration of exposure	48	h
Species	Daphnia magna	
Method	OECD 202	
Source	ECHA	
2	1-methoxy-2-propanol	107-98-2 203-539-1
EC50	21100	- 25900 mg/l
Duration of exposure	48	h
Species	Daphnia magna	
Method	ESR-ES-15	
Source	ECHA	
Evaluation/classification	Based on available data, the classification criteria are not met.	
3	2-methoxy-1-methylethyl acetate	108-65-6 203-603-9
EC50	>	500 mg/l
Duration of exposure	48	h
Species	Daphnia magna	
Method	EU Method C.2	
Source	ECHA	

Toxicity to Daphnia (chronic)

No	Substance name	CAS no.	EC no.
1	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
NOEC	>=	100	mg/l
Duration of exposure		21	day(s)
Species	Daphnia magna		
Method	OECD 211		
Source	ECHA		

Toxicity to algae (acute)

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
EL50		2.9	mg/l
Duration of exposure		72	h
Species	Pseudokirchneriella subcapitata		
Method	OECD 201		
Source	ECHA		
2	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
EC50	>	1000	mg/l
Duration of exposure		96	h
Species	Raphidocelis subcapitata		
Method	OECD 201		
Source	ECHA		

Toxicity to algae (chronic)

No data available

Bacteria toxicity

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
EC50	>	99	mg/l
Duration of exposure		10	min
Species	activated sludge		
Method	OECD 209		
Source	ECHA		
2	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
EC10	>	1000	mg/l
Duration of exposure		30	min
Species	activated sludge		
Method	OECD 209		
Source	ECHA		

12.2 Persistence and degradability**Biodegradability**

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5

Trade name: einzA Flüssig-Kunststoff, farblos

Product no.: 5700132

Current version : 2.0.3, issued: 03.01.2024

Replaced version: 2.0.2, issued: 04.07.2023

Region: GB

Type	BSB		
Value	78	%	
Duration	28	d	
Method	OECD 301 F		
Source	ECHA		
Evaluation	readily biodegradable		
2	1-methoxy-2-propanol	107-98-2	203-539-1
Type	aerobic biodegradation		
Value	96	%	
Duration	28	day(s)	
Method	OECD 301 E		
Source	ECHA		
Evaluation	readily biodegradable		
3	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
Type	aerobic biodegradation		
Value	83	%	
Duration	28	day(s)	
Method	OECD 301 F		
Source	ECHA		
Evaluation	readily biodegradable		

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
log Pow	<	1	
Reference temperature with reference to		20	°C
Method	pH: 6.8 OECD 117		
Source	ECHA		
2	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
log Pow		1.2	
Reference temperature		20	°C
Method	OECD 117		
Source	ECHA		

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	The components of this product are not considered to be a PBT.
vPvB assessment	The components of this product are not considered to be a vPvB.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information
Do not allow to enter drains or water courses.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste code 08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company.

Trade name: einZA Flüssig-Kunststoff, farblos

Product no.: 5700132

Current version : 2.0.3, issued: 03.01.2024

Replaced version: 2.0.2, issued: 04.07.2023

Region: GB

Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class	3
Classification code	F1
Packing group	III
Hazard identification no.	30
UN number	UN1263
Proper shipping name	PAINT
Tunnel restriction code	D/E
Label	3
Environmentally hazardous substance mark	Symbol "fish and tree"

14.2 Transport IMDG

Class	3
Packing group	III
UN number	UN1263
Proper shipping name	PAINT
Technical name	Hydrocarbons, C9, aromatics
EmS	F-E+S-E
Label	3
Marine pollutant mark	Symbol "fish and tree"

14.3 Transport ICAO-TI / IATA

Class	3
Packing group	III
UN number	UN1263
Proper shipping name	Paint
Label	3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

Trade name: einzA Flüssig-Kunststoff, farblos

Product no.: 5700132

Current version : 2.0.3, issued: 03.01.2024

Replaced version: 2.0.2, issued: 04.07.2023

Region: GB

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3, 40

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	butyl methacrylate	97-88-1	202-615-1	75
2	methyl-methacrylate	80-62-6	201-297-1	75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category: E2, P5c

If the properties of the substance/product give rise to more than one classification, for the purposes of 2012/18/UE, the lowest qualifying quantities set out in Part 1 and Part 2 of Annex I shall apply.

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)

VOC content 48.87 %

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products

relevant VOC limit value as referred to in Annex II of Directive 2004/42/CE , Cat. : i, type: Ib = 500 g/l
Max. VOC content (limit value) of the product in its ready for use condition = < 500 g/l

National regulations

Other national regulations

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

D Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words 'non-stabilised'.

Trade name: einzA Flüssig-Kunststoff, farblos

Product no.: 5700132

Current version : 2.0.3, issued: 03.01.2024

Replaced version: 2.0.2, issued: 04.07.2023

Region: GB

P The harmonised classification as a carcinogen applies unless the full refining history is known and it can be shown that the substance from which it is produced is not a carcinogen, in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 653771