# **Trade name:** einzA mix Kompaktlasur Silvershine, Basis ME **Product no.:** 0025856

Current version : 1.1.1. issued: 21.12.2023

Replaced version: 1.1.0, issued: 03.07.2023

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1 **Product identifier**

Trade name

## einzA mix Kompaktlasur Silvershine, Basis ME

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture decorative paints/finishes

**Uses advised against** No data available.

## 1.3 Details of the supplier of the safety data sheet

#### Address

einzA Farben GmbH & Co KG Junkersstraße 13 30179 Hannover

 Telephone no.
 +49 (0)511 67490-0

 Fax no.
 +49 (0)511 67490-20

 e-mail
 info@einzA.com

Advice on Safety Data Sheet sdb\_info@umco.de

#### 1.4 Emergency telephone number

For medical advice (in German and English): +49 (0)551 192 40 (Giftinformationszentrum Nord)

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

#### **Classification information**

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

This product does not meet the classification criteria given in the Regulation (EC) No 1272/2008 (CLP).

## 2.2 Label elements

## Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms

Signal word

Hazard statement(s)

Hazard statements (EU)

EUH210 Safety data sheet available on request.

#### Precautionary statement(s)

## Labelling information

The labelling (EU hazard statements) meets the criteria of annex II of Directive (EC) Nr. 1272/2008 (CLP).

#### 2.3 Other hazards

PBT assessment

Current version : 1.1.1, issued: 21.12.2023

## **Trade name:** einzA mix Kompaktlasur Silvershine, Basis ME

Product no.: 0025856

Replaced version: 1.1.0, issued: 03.07.2023

Region: GB

The components of this product are not considered to be a PBT. vPvB assessment The components of this product are not considered to be a vPvB.

The components of this product are not considered to be a VPVB.

## **SECTION 3: Composition/information on ingredients**

## 3.1 Substances

Not applicable. The product is not a substance.

## 3.2 Mixtures

## Hazardous ingredients

No	Substance name		Additi	onal information		
	CAS / EC / Index /	Classification (EC) 1272/2008 (CLP)	Concentration			%
	REACH no					
1	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics					
	-	Asp. Tox. 1; H304	>=	50.00 - <	70.00	wt%
	918-481-9	EUH066				
	-					
	01-2119457273-39					
2	aluminium powder	(stabilised)				
	7429-90-5	Flam. Sol. 1; H228	<	2.50		wt%
	231-072-3					
	013-002-00-1					
	01-2119529243-45					

Full Text for all H-phrases and EUH-phrases: pls. see section 16

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
2	Т	-	-	-

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

## **General information**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

#### After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

#### After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

#### After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

#### After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

## **4.2 Most important symptoms and effects, both acute and delayed** No data available.

## **4.3** Indication of any immediate medical attention and special treatment needed No data available.

## **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

Current version : 1.1.1, issued: 21.12.2023

## **Trade name:** einzA mix Kompaktlasur Silvershine, Basis ME

## Product no.: 0025856

Replaced version: 1.1.0, issued: 03.07.2023

Region: GB

## Suitable extinguishing media

Alcohol resistant foam, CO2, powders, water spray

## Unsuitable extinguishing media water jet.

## 5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO2); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

## 5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

## **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

#### For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

#### 6.2 Environmental precautions

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

#### 6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

## 6.4 Reference to other sections

No data available.

## **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

#### Advice on safe handling

Due to the organic solvents' content of the mixture: Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flatting] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

## General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

## Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

## 7.2 Conditions for safe storage, including any incompatibilities

## Technical measures and storage conditions

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

#### Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Product no.: 0025856 Current version : 1.1.1, issued: 21.12.2023

Replaced version: 1.1.0, issued: 03.07.2023

Region: GB

## Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

#### 7.3 Specific end use(s) No data available.

## SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

## **Occupational exposure limit values**

No	Substance name	CAS no.		EC no.		
1	aluminium powder (stabilised)	7429-90-5		231-072-3		
	List of approved workplace exposure limits (WELs) / EH40					
	Aluminium metal					
	total inhalable dust					
	WEL long-term (8-hr TWA reference period)	10	mg/m³			
	List of approved workplace exposure limits (WELs) / E	EH40				
	Aluminium metal					
	respirable dust					
	WEL long-term (8-hr TWA reference period)	4	mg/m³			

## DNEL, DMEL and PNEC values

	DNEL values (worker)							
No	Substance name			CAS / EC no				
	Route of exposure	Exposure time	Effect	Value				
1	aluminium powder (stabil	ised)		7429-90-5				
				231-072-3				
	inhalative	Long term (chronic)	local	3.72	mg/m³			
L	IIIIdiduve		local	0.12	mg/m			

DNEL value (consumer)

No	Substance name			CAS / EC no			
	Route of exposure Exposure time Effect			Value			
1	aluminium powder (stabilised)			7429-90-5			
				231-072-3			
	oral	Long term (chronic)	systemic	3.95	mg/kg/day		

	PNEC values						
No	Substance name		CAS / EC no				
	ecological compartment	Туре	Value				
1	aluminium powder (stabilised)		7429-90-5				
			231-072-3				
	water	fresh water	74.9	µg/L			
	sewage treatment plant	-	20	mg/L			

## 8.2 Exposure controls

## Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

## Personal protective equipment

#### **Respiratory protection**

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

## Eye / face protection

Wear safety googles to protect against splashes. Safety glasses with side protection shield (EN 166)

Product no.: 0025856

Current version : 1.1.1, issued: 21.12.2023

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves. Appropriate Material In case of short-term contact / splash protection: nitrile rubber

Replaced version: 1,1,0, issued: 03,07,2023

Appropriate Material	In case of sh	nort-term contact / sp	olash protectio	n: nitrile
Material thickness	>	0.4	mm	
Breakthrough time	>	120	min	
Appropriate Material	In case of pr	olonged exposure: r	itrile rubber	
Material thickness	>	0.4	mm	
Breakthrough time	>	480	min	

#### Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

#### Environmental exposure controls

Do not allow to enter drains or water courses.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

State of aggregation			
liquid			
Form			
liquid			
Colour			
according to product name			
Odour			
characteristic			
pH value No data available			
Boiling point / boiling range		100	20
Value	appr.	100	°C
Melting point/freezing point			
No data available			
Decomposition temperature			
No data available			
Flash point			
Value	>=	62	°C
Method	closed cup		
Ignition temperature			
No data available			
Oxidising properties			
Not applicable			
Flammability			
Not applicable			
Lower explosion limit			
No data available			
Upper explosion limit			
No data available			
Vapour pressure			



Region: GB

## Product no.: 0025856 Current version : 1.1.1, issue

Reference temperature **Relative vapour dens** No data available **Relative density** No data available

Reference temperature

Value

Density Value

Method

; ;	,			
1: 21.12.2023	: 21.12.2023 <b>Replaced version:</b> 1.1.0, issued: 03.07.2023			Region: G
	<	100 50	hPa °C	
ity	·			
	0.84	- 0.89 20	g/cm³ °C	
	DIN 51757			
	immiscible			

#### Solubility in water Comments

Solu	Solubility								
No c	No data available								
Part	Partition coefficient n-octanol/water (log value)								
No	Substance name		CAS no.		EC no.				
1	Hydrocarbons, C10-C13, n-alkanes, isoal	kanes,	-		918-481-9				
	cyclics, <2% aromatics								
log F	Pow	3.17		- 7.22					
Meth	nod	QSAR							
Sou	rce	ECHA							
King	ematic viscosity								
Valu		55	- 65						
	-			sec					
Meth	100	DIN EN 2431	(4 mm)						
Solv	Solvent separation test								
	Not applicable								
Part	icle characteristics								

## No data available

9.2

## Other information

Other information No data available.

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

Stable under recommended storage and handling conditions (See section 7).

## 10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

## 10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

## 10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

## 10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

#### 10.6 Hazardous decomposition products None if stored, handled and transported properly. In case of fire: see section 5.

## **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

#### Product no.: 0025856

Current version : 1.1.1, issued: 21.12.2023

Replaced version: 1.1.0. issued: 03.07.2023

Region: GB

No Substance name CAS no. EC no. 918-481-9 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics LD50 15000 > mg/kg bodyweight Species rat **OECD 401** Method Source **ECHA** Evaluation/classification Based on available data, the classification criteria are not met. Acute dermal toxicity No data available Acute inhalational toxicity No Substance name CAS no. EC no. aluminium powder (stabilised) 7429-90-5 231-072-3 1 LC50 0.888 mg/l Duration of exposure Δ Dust State of aggregation Species rat **ECHA** Source Skin corrosion/irritation No data available Serious eye damage/irritation No data available Respiratory or skin sensitisation No data available Germ cell mutagenicity No Substance name CAS no. EC no. Hydrocarbons, C10-C13, n-alkanes, isoalkanes, 918-481-9 1 cyclics, <2% aromatics Type of examination in vitro gene mutation study in bacteria Species S. typhimurium TA 1535, TA 1537, TA 98 and TA 100S. typhimurium TA 1535, TA 1537, TA 98, TA 100, TA 102 Method **OECD 471** Source **ECHA** Evaluation/classification Based on available data, the classification criteria are not met. Route of exposure oral Type of examination In vivo mammalian somatic cell study: cytogenicity / erythrocyte micronucleus Species mouse **OECD 474** Method Source **ECHA** Evaluation/classification Based on available data, the classification criteria are not met. **Reproduction toxicity** No data available Carcinogenicity No data available STOT - single exposure No data available STOT - repeated exposure No Substance name CAS no. EC no. Hydrocarbons, C10-C13, n-alkanes, isoalkanes, 918-481-9 1 cyclics, <2% aromatics Route of exposure oral NOAEL 500 >= mg/kg bw/d Species rat Method **OECD 408** ECHA Source

## Product no.: 0025856

Current version : 1.1.1. issued: 21.12.2023

Replaced version: 1.1.0. issued: 03.07.2023

Region: GB

Evaluation/classification

Based on available data, the classification criteria are not met.

Aspiration hazard

## No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

## **11.2** Information on other hazards

Endocrine disrupting properties No data available.

Other information No data available.

## **SECTION 12: Ecological information**

## 12.1 Toxicity

Toxicity to fish (acute)
No data available
Toxicity to fish (chronic)
No data available
Toxicity to Daphnia (acute)
No data available
Toxicity to Daphnia (chronic)
No data available
Toxicity to algae (acute)
No data available
Toxicity to algae (chronic)
No data available
Bacteria toxicity
No data available

## 12.2 Persistence and degradability

No data available.

#### 12.3 Bioaccumulative potential

Part	Partition coefficient n-octanol/water (log value)							
No	Substance name		CAS no.			EC no.		
1	Hydrocarbons, C10-C13, n-alkanes, isoalkanes,		-			918-481-9		
	cyclics, <2% aromatics							
log F	Pow	3.17		-	7.22			
Meth	nod	QSAR						
Source		ECHA						

#### 12.4 Mobility in soil

No data available.

## 12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	The components of this product are not considered to be a PBT.
vPvB assessment	The components of this product are not considered to be a vPvB.

Current version : 1.1.1, issued: 21.12.2023

## Trade name: einzA mix Kompaktlasur Silvershine, Basis ME

Product no.: 0025856

Replaced version: 1.1.0. issued: 03.07.2023

12.6 Endocrine disrupting properties

No data available.

## 12.7 Other adverse effects

No data available.

## 12.8 Other information

## Other information

Do not allow to enter drains or water courses.

## SECTION 13: Disposal considerations

## 13.1 Waste treatment methods

 Product
 Waste code
 08 01 11\*
 waste paint and varnish containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company. Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

## Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

## **SECTION 14: Transport information**

## 14.1 Transport ADR/RID/ADN

The product is not subject to ADR/RID/ADN regulations.

## 14.2 Transport IMDG

The product is not subject to IMDG regulations.

## 14.3 Transport ICAO-TI / IATA

The product is not subject to ICAO-TI / IATA regulations.

**14.4 Other information** No data available.

## 14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

## 14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments Not relevant

## **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

## REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

## Product no.: 0025856

Current version : 1.1.1, issued: 21.12.2023

#### Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No	
1	2-(2-butoxyethoxy)ethanol	112-34-5	203-961-6	75	
2	2-methylpentane-2,4-diol	107-41-5	203-489-0	75	
3	aluminium powder (stabilised)	7429-90-5	231-072-3	75	

**Directive 2012/18/EU** on the control of major-accident hazards involving dangerous substances This product is not subject to Part 1 or 2 of Annex I.

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)VOC content57.94

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products

relevant VOC limit value as referred to in Annex II of Directive 2004/42/CE, Cat. : f, type: lb = 700 g/l Max. VOC content (limit value) of the product in its ready for use condition = < 700 g/l

#### National regulations

#### Other national regulations

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

#### 15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

## **SECTION 16: Other information**

#### Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case. The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section. Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case. Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

# Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in thesesections)EUH066Repeated exposure may cause skin dryness or cracking.

EUH066	Repeated exposure may cause skin dryness or cracking
H228	Flammable solid.
H304	May be fatal if swallowed and enters airways.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

Т

This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be included in the safety data sheet.

#### Creation of the safety data sheet

#### UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.



Trade name: einzA mix Kompaktlasur Silvershine, Basis MEProduct no.: 0025856Current version : 1.1.1, issued: 21.12.2023Replaced version

Replaced version: 1.1.0, issued: 03.07.2023

Region: GB

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH. Prod-ID 793283