

Trade name: einzA mix Korral-Top, Basis 4

Product no.: 0078200

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

einzA mix Korral-Top, Basis 4

UFI:

8M4W-Q04C-Y00A-E2WG

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

decorative paints/finishes

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

einzA Farben GmbH & Co KG

Junkersstraße 13

30179 Hannover

Telephone no. +49 (0)511 67490-0

Fax no. +49 (0)511 67490-20

e-mail info@einza.com

Information provided by / telephone

In emergencies, the country-specific emergency number can be found in the corresponding country-specific safety data sheets.

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

+49 (0)40 0511 - 674 90-0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Aquatic Chronic 2; H411

Flam. Liq. 3; H226

STOT SE 3; H336

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02



GHS07



GHS09

Signal word

Warning

Trade name: einzA mix Korral-Top, Basis 4**Product no.:** 0078200**Current version:** 1.0.0, Revision: 28.01.2026**Replaced version:** -, Revision: -**Region:**
GER**Hazardous component(s) to be indicated on label:**

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hazard statement(s)

H226 Flammable liquid and vapour.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Hazard statements (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statement(s)

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P370+P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.
 P391 Collect spillage.
 P405 Store locked up.
 P501 Dispose of contents/container to a facility in accordance with local and national regulations.

UFI:

8M4W-Q04C-Y00A-E2WG

2.3 Other hazards

The product does not contain any components > 0.1% that meet the criteria for PBT and vPvB according to Regulation (EC) No. 1907/2006, Annex XIII, or that have been included in the list compiled in accordance with Article 59(1). This product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not applicable. The product is not a substance.

3.2 Mixtures**Hazardous ingredients**

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	barium sulfate, natural		
	7727-43-7 231-784-4 - -	-	>= 25,00 - < 50,00 wt%
2	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
	64742-48-9 919-857-5 649-327-00-6 01-2119463258-33	Flam. Liq. 3; H226 Asp. Tox. 1; H304 STOT SE 3; H336 EUH066	>= 25,00 - < 50,00 wt%
3	trizinc bis(orthophosphate)		
	7779-90-0 231-944-3 030-011-00-6 01-2119485044-40	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 5,00 - < 10,00 wt%
4	(2-METHOXYMETHYLETHOXY)PROPANOL		

Trade name: einzA mix Korral-Top, Basis 4

Product no.: 0078200

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

	34590-94-8 252-104-2 - 01-2119450011-60	-	< 2,50	wt%
5	n-butyl acetate			
	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	EUH066 Flam. Liq. 3; H226 STOT SE 3; H336	< 2,50	wt%
6	potassium 2-ethylhexanoate			
	3164-85-0 221-625-7 607-230-00-6 01-2119980714-29	Eye Dam. 1; H318 Repr. 2; H361d Skin Irrit. 2; H315	< 0,50	wt%
7	zinc oxide			
	1314-13-2 215-222-5 030-013-00-7 01-2119463881-32	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	< 0,25	wt%

Full text of H- and EUH-phrases, if not already mentioned in section 2.2: see section 16.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
2	P	-	-	-
7	-	-	M = 1	M = 1

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO₂, powders, water spray

Unsuitable extinguishing media

water jet.

Trade name: einzA mix Korral-Top, Basis 4

Product no.: 0078200

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Do not allow to enter drains/watercourses/soil.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flattening] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Comply with legal health and safety regulations; Storage in accordance with the Ordinance on Industrial Safety and Health. Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Incompatible products

Trade name: einza mix Korral-Top, Basis 4

Product no.: 0078200

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Stoarge Class according TRGS 510

3 Flammable liquids

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limit values**

No	Substance name	CAS no.	EC no.
1	barium sulfate, natural	7727-43-7	231-784-4
	2006/15/EC		
	Barium (soluble compounds as Ba)		
	WEL long-term (8-hr TWA reference period)	0,5	mg/m ³
2	(2-METHOXYMETHYLETHOXY)PROPANOL	34590-94-8	252-104-2
	TRGS 900		
	(2-Methoxymethylethoxy)propanol (Isomerengemisch)		
	WEL long-term (8-hr TWA reference period)	310	mg/m ³ 50 ml/m ³
	Ceiling Limit	1(l)	
	2000/39/EC		
	(2-Methoxymethylethoxy)-propanol		
	WEL long-term (8-hr TWA reference period)	308	mg/m ³ 50 ppm
	Skin resorption / sensibilisation	Skin	
3	n-butyl acetate	123-86-4	204-658-1
	TRGS 900		
	n-Butylacetat		
	WEL long-term (8-hr TWA reference period)	300	mg/m ³ 62 ml/m ³
	Ceiling Limit	2(l)	
	Notes	Y	
	EU 2019/1831		
	n-Butyl acetate		
	WEL short-term (15 min reference period)	723	mg/m ³ 150 ppm
	WEL long-term (8-hr TWA reference period)	241	mg/m ³ 50 ppm

DNEL, DMEL and PNEC values**DNEL values (worker)**

DNEL values (worker)					
No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			64742-48-9 919-857-5	
	dermal	Long term (chronic)	systemic	77	mg/kg/day
	inhalative	Long term (chronic)	systemic	871	mg/m³
2	n-butyl acetate			123-86-4 204-658-1	
	dermal	Long term (chronic)	systemic	11	mg/kg/day
	dermal	Short term (acut)	systemic	11	mg/kg/day
	inhalative	Long term (chronic)	systemic	300	mg/m³
	inhalative	Short term (acut)	systemic	600	mg/m³
	inhalative	Long term (chronic)	local	300	mg/m³
	inhalative	Short term (acut)	local	600	mg/m³
3	potassium 2-ethylhexanoate			3164-85-0 221-625-7	
	dermal	Long term (chronic)	systemic	5,95	mg/kg/day
	inhalative	Long term (chronic)	systemic	41,98	mg/m³

DNEL value (consumer)

EU safety data sheet



Trade name: einza mix Korral-Top, Basis 4

Product no.: 0078200

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			64742-48-9 919-857-5	
	oral	Long term (chronic)	systemic	46	mg/kg/day
	dermal	Long term (chronic)	systemic	46	mg/kg/day
	inhalative	Long term (chronic)	systemic	185	mg/m ³
2	n-butyl acetate			123-86-4 204-658-1	
	oral	Long term (chronic)	systemic	2	mg/kg/day
	oral	Short term (acute)	systemic	2	mg/kg/day
	dermal	Long term (chronic)	systemic	6	mg/kg/day
	dermal	Short term (acute)	systemic	6	mg/kg/day
	inhalative	Long term (chronic)	systemic	35,7	mg/m ³
	inhalative	Short term (acute)	systemic	300	mg/m ³
	inhalative	Long term (chronic)	local	35,7	mg/m ³
	inhalative	Short term (acute)	local	300	mg/m ³
3	potassium 2-ethylhexanoate			3164-85-0 221-625-7	
	oral	Long term (chronic)	systemic	2,98	mg/kg/day
	dermal	Long term (chronic)	systemic	2,98	mg/kg/day
	inhalative	Long term (chronic)	systemic	10,35	mg/m ³

PNEC values

No	Substance name		CAS / EC no	
	ecological compartment	Type	Value	
1	trizinc bis(orthophosphate)		7779-90-0 231-944-3	
	water	fresh water	20,6	µg/L
	water	marine water	6,1	µg/L
	water	fresh water sediment	117,8	mg/kg dry weight
	water	marine water sediment	56,5	mg/kg dry weight
	water	fresh water	85	µg/L
	water	marine water	42,5	µg/L
	water	fresh water sediment	867,4	mg/kg dry weight
	water	marine water sediment	957,7	mg/kg dry weight
	soil	-	35,6	mg/kg
	sewage treatment plant	-	100	µg/L
2	n-butyl acetate		123-86-4 204-658-1	
	water	fresh water	0,18	mg/L
	water	marine water	0,018	mg/L
	water	fresh water sediment	0,981	mg/kg dry weight
	water	marine water sediment	0,098	mg/kg dry weight
	soil	-	0,09	mg/kg
	sewage treatment plant	-	35,6	mg/L
3	potassium 2-ethylhexanoate		3164-85-0 221-625-7	
	water	fresh water	0,36	mg/L
	water	Aqua intermittent	0,493	mg/L
	water	fresh water sediment	0,637	mg/kg dry weight
	water	marine water sediment	0,637	mg/kg dry weight
	water	marine water	0,036	mg/L

Trade name: einzA mix Korral-Top, Basis 4**Product no.:** 0078200**Current version:** 1.0.0, Revision: 28.01.2026**Replaced version:** -, Revision: -**Region:**
GER

	soil	-	1,06	mg/kg dry weight
4	zinc oxide		1314-13-2 215-222-5	
	water	fresh water	17,9	µg/L
	with reference to: Zn			
	water	marine water	9	µg/L
	with reference to: Zn			
	water	fresh water sediment	182,8	mg/kg
	water	marine water sediment	201,9	mg/kg
	with reference to: Zn, dry weight			
	soil	-	103,4	mg/kg
	with reference to: Zn, dry weight			
	sewage treatment plant	-	124,5	µg/L

8.2 Exposure controls

Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

Eye / face protection

Wear safety goggles to protect against splashes. Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material In case of short-term contact / splash protection: nitrile rubber

Material thickness > 0,4 mm

Breakthrough time > 120 min

Appropriate Material In case of prolonged exposure: nitrile rubber

Material thickness > 0,4 mm

Breakthrough time > 480 min

Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation

liquid

Form

liquid

Colour

according to product name

Trade name: einzA mix Korral-Top, Basis 4

Product no.: 0078200

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

Odour			
like solvents			
pH value			
reason for missing pH		substance/mixture is non-soluble (in water)	
Boiling point / boiling range			
Value	>	120	°C
Reference substance	solvent mixture		
Melting point/freezing point			
No data available			
Decomposition temperature			
No data available			
Flash point			
Value	>=	30	°C
Method	closed cup		
Ignition temperature			
Value	>	200	°C
Reference substance	solvent mixture		
Oxidising properties			
Not applicable			
Flammability			
Not applicable			
Lower explosion limit			
Value	>	0,6	% vol
Reference substance	solvent mixture		
Upper explosion limit			
Value	<	7,5	% vol
Reference substance	solvent mixture		
Vapour pressure			
Value	<	100	hPa
Reference temperature		50	°C
Reference substance	solvent mixture		
Relative vapour density			
No data available			
Relative density			
No data available			
Density			
Value	appr.	1,36	g/cm³
Reference temperature		20	°C
Method	DIN 51757		
Solubility in water			
Comments	immiscible		
Solubility			
No data available			
Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
log Pow		2,3	
Reference temperature		25	°C
Method	OECD 117		

Trade name: einzA mix Korral-Top, Basis 4

Product no.: 0078200

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

Source	ECHA
--------	------

Kinematic viscosity			
Value	2100	-	2300 mPa*s
Reference temperature		20	°C
Method	DIN 53019		

Solvent separation test			
Value	<	3	%
Reference temperature		20	°C

Particle characteristics	
No data available	

9.2 Other information

Other information
No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage and handling conditions (See section 7).

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	919-857-5
LD50	>	5000	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		
2	trizinc bis(orthophosphate)	7779-90-0	231-944-3
LD50	>	5000	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		
3	n-butyl acetate	123-86-4	204-658-1
LD50		10760	mg/kg bodyweight
Species	rat		
Method	OECD 423		
Source	ECHA		
4	zinc oxide	1314-13-2	215-222-5
LD50	>	5000	mg/kg bodyweight
Species	rat		
Method	OECD 401		

Trade name: einza mix Korral-Top, Basis 4

Product no.: 0078200

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

Source		ECHA	
Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	919-857-5
LD50	>	2000	mg/kg bodyweight
Species	rabbit		
Method	OECD 402		
Source	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
LD50	>	14112	mg/kg bodyweight
Species	rabbit		
Method	OECD 402		
Source	ECHA		
3	zinc oxide	1314-13-2	215-222-5
LD50	>	2000	mg/kg bodyweight
Species	rat		
Method	OECD 402		
Source	ECHA		
Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	trizinc bis(orthophosphate)	7779-90-0	231-944-3
LC50	>	5,41	mg/l
Duration of exposure		4	h
State of aggregation	Dust/mist		
Species	rat		
Method	OECD 403		
Source	ECHA		
2	zinc oxide	1314-13-2	215-222-5
LC50	>	5,7	mg/l
Duration of exposure		4	h
State of aggregation	Dust/mist		
Species	rat		
Method	OECD 403		
Source	ECHA		
Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	919-857-5
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		
2	trizinc bis(orthophosphate)	7779-90-0	231-944-3
Species	rabbit		
Method	OECD 404		
Source	ECHA / Read across		
Evaluation	non-irritant		
3	n-butyl acetate	123-86-4	204-658-1
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		
4	zinc oxide	1314-13-2	215-222-5
Species	Human Skin Model		
Method	OECD 431		
Source	ECHA		
Evaluation	non-irritant		

Trade name: einzA mix Korral-Top, Basis 4

Product no.: 0078200

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	919-857-5
Species		rabbit	
Method		OECD 405	
Source		ECHA	
Evaluation		non-irritant	
2	trizinc bis(orthophosphate)	7779-90-0	231-944-3
Species		rabbit	
Method		OECD 405	
Source		ECHA	
Evaluation		non-irritant	
3	n-butyl acetate	123-86-4	204-658-1
Species		rabbit	
Method		OECD 405	
Source		ECHA	
Evaluation		non-irritant	
4	zinc oxide	1314-13-2	215-222-5
Species		rabbit	
Method		OECD 405	
Source		ECHA	
Evaluation		non-irritant	
Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	919-857-5
Route of exposure		Skin	
Species		guinea pig	
Method		OECD 406	
Source		ECHA	
Evaluation		non-sensitizing	
2	trizinc bis(orthophosphate)	7779-90-0	231-944-3
Route of exposure		Skin	
Species		guinea pig	
Source		ECHA / Read across	
Evaluation		non-sensitizing	
3	zinc oxide	1314-13-2	215-222-5
Route of exposure		Skin	
Species		Guinea pig	
Method		OECD 406	
Source		ECHA	
Evaluation		non-sensitizing	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
2	zinc oxide	1314-13-2	215-222-5
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
2	zinc oxide	1314-13-2	215-222-5
Source		ECHA	

Trade name: einza mix Korral-Top, Basis 4

Product no.: 0078200

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

Evaluation/classification	Based on available data, the classification criteria are not met.
---------------------------	---

Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	zinc oxide	1314-13-2	215-222-5
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

STOT - single exposure	
No data available	

STOT - repeated exposure			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
Route of exposure		inhalational	
NOAEC		500	ppm
Duration of exposure		90	day(s)
Species		rat	
Method		EPA OTS 798.2450	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Aspiration hazard	
No data available	

Delayed and immediate effects as well as chronic effects from short and long-term exposure	
Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.	

11.2 Information on other hazards

Endocrine disrupting properties	
No data available	

Other information
No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	919-857-5
LL50		>	1000 mg/l
Duration of exposure		96	h
Species		Rainbow trout	
Method		OECD 203	
Source		ECHA	
2	n-butyl acetate	123-86-4	204-658-1
LC50		18	mg/l
Duration of exposure		96	h
Species		Pimephales promelas	
Method		OECD 203	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Trade name: einzA mix Korral-Top, Basis 4

Product no.: 0078200

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

Toxicity to fish (chronic)			
No data available			

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	919-857-5
EL50	>	1000	mg/l
Duration of exposure		48	h
Species with reference to	Daphnia magna		
Method	WAF (water accommodated fractions)		
Source	OECD 202		
	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
EC50		44	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Toxicity to Daphnia (chronic)			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
NOEC		23	mg/l
Duration of exposure		21	day(s)
Species with reference to	Daphnia magna		
Method	CAS 110-19-0		
Source	OECD 211		
	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Toxicity to algae (acute)			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	919-857-5
EL50	>	1000	mg/l
Duration of exposure		72	h
Species with reference to	Pseudokirchneriella subcapitata		
Method	WAF (water accommodated fractions)		
Source	OECD 201		
	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
EC50		397	mg/l
Duration of exposure		72	h
Species	Selenastrum capricornutum		
Method	OECD 201		
Source	ECHA		

Toxicity to algae (chronic)			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
NOEC		196	mg/l
Duration of exposure		72	h
Species	Raphidocelis subcapitata		
Method	OECD 201		
Source	ECHA		

Bacteria toxicity			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
IC50		356	mg/l
Duration of exposure		40	h
Species	Tetrahymena pyriformis (Protozoa)		

Trade name: einzA mix Korral-Top, Basis 4

Product no.: 0078200

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

Source | ECHA

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	919-857-5
Method		OECD 301 F	
Source		ECHA	
Evaluation		readily biodegradable	
2	n-butyl acetate	123-86-4	204-658-1
Type		aerobic biodegradation	
Value		83	%
Duration		28	day(s)
Method		OECD 301 D	
Source		ECHA	
Evaluation		readily biodegradable	
Abiotic Degradation			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
Type		Photolysis	
Half-life		3,3	day(s)
Reference temperature		25	°C
Source		ECHA	

12.3 Bioaccumulative potential

Bioconcentration factor (BCF)			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
BCF		15,3	
Method		Calculation model used (Q)SAR	
Source		ECHA	

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
log Pow		2,3	
Reference temperature		25	°C
Method		OECD 117	
Source		ECHA	

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information
Do not allow to enter drains or water courses.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Product

Trade name: einzA mix Korral-Top, Basis 4**Product no.:** 0078200**Current version:** 1.0.0, Revision: 28.01.2026**Replaced version:** -, Revision: -**Region:**
GER

Waste code 08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company. Allow paint/varnish to dry out completely in a well-ventilated area and dispose of in residual waste once completely solidified. Dispose of liquid or non-drying residues separately.

Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

SECTION 14: Transport information**14.1 UN number or ID number**

ADR/RID/ADN	UN1263
IMDG	UN1263
ICAO-TI / IATA	UN1263

14.2 UN proper shipping name

ADR/RID/ADN	PAINT
IMDG	PAINT
ICAO-TI / IATA	Paint

14.3 Transport hazard class(es)

ADR/RID/ADN - Class	3
Label	3
Classification code	F1
Tunnel restriction code	D/E
Hazard identification no.	30
IMDG - Class	3
Label	3
ICAO-TI / IATA - Class	3
Label	3

14.4 Packing group

ADR/RID/ADN	III
IMDG	III
ICAO-TI / IATA	III

14.5 Environmental hazards

ADR/RID/ADN	Symbol "fish and tree"
IMDG	Symbol "fish and tree"
EmS	F-E+S-E

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations**

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)
--

Trade name: einzA mix Korral-Top, Basis 4**Product no.:** 0078200**Current version:** 1.0.0, Revision: 28.01.2026**Replaced version:** -, Revision: -**Region:**
GER

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3, 40

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	2-ethylhexanoic acid	149-57-5	205-743-6	75
2	potassium 2-ethylhexanoate	3164-85-0	221-625-7	75
3	strontium bis(2-ethylhexanoate)	2457-02-5	219-536-3	75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category: E2, P5c

If the properties of the substance/product give rise to more than one classification, for the purposes of 2012/18/UE, the lowest qualifying quantities set out in Part 1 and Part 2 of Annex I shall apply.

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)

VOC content 28,87 %

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products

relevant VOC limit value as referred to in Annex II of Directive 2004/42/CE, Cat. : i, type: lb = 500 g/l

Max. VOC content (limit value) of the product in its ready for use condition = < 500 g/l

National regulations**Water Hazard Class (Germany)**

Class

2

Source

Classification according to AwSV (Regulation on facilities for handling substances that are hazardous to water).

Other regulations

GISCODE BSL20

Covering agents, solvent based, free of aromatic substances, labeled

Other national regulations

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment. For example, TRGS (Technical Rules for Hazardous Substances) and the DGUV (German Social Accident Insurance) rules.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H304

May be fatal if swallowed and enters airways.

H315

Causes skin irritation.

H318

Causes serious eye damage.

Trade name: einzA mix Korral-Top, Basis 4

Product no.: 0078200

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

H361d Suspected of damaging the unborn child.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

P The harmonised classification as a carcinogen applies unless the full refining history is known and it can be shown that the substance from which it is produced is not a carcinogen, in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

This document is an English translation of the legally compliant safety data sheet of the region Germany. This document, including UFI and emergency telephone number, may only be used for placing on the market in the region Germany.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.
Prod-ID 772632