

Trade name: einza Lackspray 96-511, Hammerschlag Silber**Product no.:** 9651101**Current version :** 1.1.0, issued: 07.08.2020**Replaced version:** 1.0.0, issued: 22.05.2019**Region:** GB**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name****einza Lackspray 96-511, Hammerschlag Silber****1.2 Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses of the substance or mixture**

decorative paints/finishes

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet**Address**

einza Farben GmbH & Co KG

Junkersstraße 13

30179 Hannover

Telephone no. +49 (0)511 67490-0

Fax no. +49 (0)511 67490-20

e-mail info@einza.com

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Aerosol 1; H222

Aquatic Chronic 3; H412

Eye Irrit. 2; H319

Skin Irrit. 2; H315

STOT SE 3; H336

Asp. Tox. 1; H304

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)****Hazard pictograms**

GHS02



GHS07

Signal word

Danger

Hazardous component(s) to be indicated on label:

ethyl-acetate

Hazard statement(s)

H222

Extremely flammable aerosol.

H229

Pressurised container: May burst if heated.

H315

Causes skin irritation.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.

H412

Harmful to aquatic life with long lasting effects.

Precautionary statement(s)

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Trade name: einza Lackspray 96-511, Hammerschlag Silber

Product no.: 9651101

Current version : 1.1.0, issued: 07.08.2020

Replaced version: 1.0.0, issued: 22.05.2019

Region: GB

P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P271 Use only outdoors or in a well-ventilated area.
 P405 Store locked up.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/container to a facility in accordance with local and national regulations.

2.3 Other hazards

PBT assessment
 The components of this product are not considered to be a PBT.
 vPvB assessment
 The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not applicable. The product is not a substance.

3.2 Mixtures**Hazardous ingredients**

No	Substance name		Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration	%
1	ethyl-acetate			
	141-78-6 205-500-4 607-022-00-5 -	EUH066 Eye Irrit. 2; H319 Flam. Liq. 2; H225 STOT SE 3; H336	>= 25.00 - < 50.00	%-b.w.
2	butane			
	106-97-8 203-448-7 601-004-00-0 -	Flam. Gas 1; H220 Press. Gas; H280	>= 10.00 - < 25.00	%-b.w.
3	propane			
	74-98-6 200-827-9 601-003-00-5 -	Flam. Gas 1; H220 Press. Gas	>= 10.00 - < 25.00	%-b.w.
4	Naphtha (petroleum), hydrodesulfurized heavy			
	64742-82-1 265-185-4 649-330-00-2 -	Aquatic Chronic 2; H411 Asp. Tox. 1; H304 EUH066 Flam. Liq. 3; H226 STOT SE 3; H336 STOT RE 1; H372	>= 5.00 - < 10.00	%-b.w.
5	xylene			
	1330-20-7 215-535-7 601-022-00-9 -	Acute Tox. 4*; H312 Acute Tox. 4*; H332 Flam. Liq. 3; H226 Skin Irrit. 2; H315	>= 5.00 - < 10.00	%-b.w.
6	aluminium powder (stabilised)			
	7429-90-5 231-072-3 013-002-00-1 -	Flam. Sol. 1; H228 Water-react. 2; H261	< 2.50	%-b.w.
7	ethylbenzene		pls. refer to footnote (1)	
	100-41-4 202-849-4 601-023-00-4 -	Acute Tox. 4; H332 Flam. Liq. 2; H225 Asp. Tox. 1; H304 STOT RE 2; H373 Eye Irrit. 2; H319 Skin Irrit. 2; H315 STOT SE 3; H335	< 2.50	%-b.w.
8	n-butyl acetate			
	123-86-4 204-658-1 607-025-00-1 -	EUH066 Flam. Liq. 3; H226 STOT SE 3; H336	< 2.50	%-b.w.
9	acetone			
	67-64-1	EUH066	< 2.50	%-b.w.

EU safety data sheet



Trade name: einza Lackspray 96-511, Hammerschlag Silber

Product no.: 9651101

Current version : 1.1.0, issued: 07.08.2020

Replaced version: 1.0.0, issued: 22.05.2019

Region: GB

	200-662-2 606-001-00-8 -	Eye Irrit. 2; H319 Flam. Liq. 2; H225 STOT SE 3; H336		
10	butan-1-ol			
	71-36-3 200-751-6 603-004-00-6 -	Acute Tox. 4*; H302 Eye Dam. 1; H318 Flam. Liq. 3; H226 Skin Irrit. 2; H315 STOT SE 3; H335 STOT SE 3; H336	< 2.50	%-b.w.

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(*,**,***,****) Detailed explanation pls. refer to CLP regulation No. 1272/2008, annex VI, 1.2

(1) Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
2	C, U	-	-	-
3	U	-	-	-
4	P	-	-	-
5	C	-	-	-
6	T	-	-	-

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

No	Route, target organ, concrete effect
4	H372 -; central nervous system; -
7	H373 inhalational; hearing; -

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO₂, powders, water spray

Unsuitable extinguishing media

water jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

Trade name: einza Lackspray 96-511, Hammerschlag Silber

Product no.: 9651101

Current version : 1.1.0, issued: 07.08.2020

Replaced version: 1.0.0, issued: 22.05.2019

Region: GB

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Exclude sources of ignition and ventilate the area. Do not inhale vapours/aerosols. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage**7.1 Precautions for safe handling****Advice on safe handling**

The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Do not breathe steams or mist of the product. For personal protection see section 8. Avoid eye, skin and clothing contact.

General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard.

7.2 Conditions for safe storage, including any incompatibilities**Technical measures and storage conditions**

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

Requirements for storage rooms and vessels

Keep the product in the original packing. Keep container tightly closed. Observe label precautions. Official regulations ruling storage of aerosols must be observed.

Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limit values**

No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
	2017/164/EU		
	Ethyl acetate		
	WEL short-term (15 min reference period)	1468	mg/m ³ 400 ppm
	WEL long-term (8-hr TWA reference period)	734	mg/m ³ 200 ppm
	List of approved workplace exposure limits (WELs) / EH40		
	Ethyl acetate		
	WEL short-term (15 min reference period)		400 ppm
	WEL long-term (8-hr TWA reference period)		200 ppm
2	butane	106-97-8	203-448-7
	List of approved workplace exposure limits (WELs) / EH40		
	Butane		
	WEL short-term (15 min reference period)	1810	mg/m ³ 750 ppm
	WEL long-term (8-hr TWA reference period)	1450	mg/m ³ 600 ppm
	Comments	Carc. (only applies if Butane contains more than 0.1% of buta-	

EU safety data sheet



Trade name: einza Lackspray 96-511, Hammerschlag Silber

Product no.: 9651101

Current version : 1.1.0, issued: 07.08.2020

Replaced version: 1.0.0, issued: 22.05.2019

Region: GB

		1,3-diene)			
3	Naphtha (petroleum), hydrodesulfurized heavy		64742-82-1		265-185-4
	List of approved workplace exposure limits (WELs) / EH40				
	WEL long-term (8-hr TWA reference period)	1200	mg/m³		
4	xylene		1330-20-7		215-535-7
	2000/39/EC				
	Xylene, mixed isomers, pure				
	WEL short-term (15 min reference period)	442	mg/m³	100	ppm
	WEL long-term (8-hr TWA reference period)	221	mg/m³	50	ppm
	Skin resorption / sensibilisation	Skin			
	List of approved workplace exposure limits (WELs) / EH40				
	Xylene, o-, m-, p- or mixed isomers				
	WEL short-term (15 min reference period)	441	mg/m³	100	ppm
	WEL long-term (8-hr TWA reference period)	220	mg/m³	50	ppm
	Comments	Sk,BMGV			
5	aluminium powder (stabilised)		7429-90-5		231-072-3
	List of approved workplace exposure limits (WELs) / EH40				
	Aluminium metal				
	total inhalable dust				
	WEL long-term (8-hr TWA reference period)	10	mg/m³		
	List of approved workplace exposure limits (WELs) / EH40				
	Aluminium metal				
	respirable dust				
	WEL long-term (8-hr TWA reference period)	4	mg/m³		
6	ethylbenzene		100-41-4		202-849-4
	2000/39/EC				
	Ethylbenzene				
	WEL short-term (15 min reference period)	884	mg/m³	200	ppm
	WEL long-term (8-hr TWA reference period)	442	mg/m³	100	ppm
	Skin resorption / sensibilisation	Skin			
	List of approved workplace exposure limits (WELs) / EH40				
	Ethylbenzene				
	WEL short-term (15 min reference period)	552	mg/m³	125	ppm
	WEL long-term (8-hr TWA reference period)	441	mg/m³	100	ppm
	Comments	Sk			
7	n-butyl acetate		123-86-4		204-658-1
	List of approved workplace exposure limits (WELs) / EH40				
	Butyl acetate				
	WEL short-term (15 min reference period)	966	mg/m³	200	ppm
	WEL long-term (8-hr TWA reference period)	724	mg/m³	150	ppm
	EU 2019/1831				
	n-Butyl acetate				
	WEL short-term (15 min reference period)	723	mg/m³	150	ppm
	WEL long-term (8-hr TWA reference period)	241	mg/m³	50	ppm
8	acetone		67-64-1		200-662-2
	2000/39/EC				
	Acetone				
	WEL long-term (8-hr TWA reference period)	1210	mg/m³	500	ppm
	List of approved workplace exposure limits (WELs) / EH40				
	Acetone				
	WEL short-term (15 min reference period)	3620	mg/m³	1500	ppm
	WEL long-term (8-hr TWA reference period)	1210	mg/m³	500	ppm
9	butan-1-ol		71-36-3		200-751-6
	List of approved workplace exposure limits (WELs) / EH40				
	Butan-1-ol				
	WEL short-term (15 min reference period)	154	mg/m³	50	ppm
	Comments	Sk			

8.2 Exposure controls

Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Short term: filter apparatus, Filter A

Eye / face protection

Trade name: einza Lackspray 96-511, Hammerschlag Silber

Product no.: 9651101

Current version : 1.1.0, issued: 07.08.2020

Replaced version: 1.0.0, issued: 22.05.2019

Region: GB

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form/Colour			
Aerosol			
according to product name			
Odour			
characteristic			
Odour threshold			
No data available			
pH value			
No data available			
Boiling point / boiling range			
No data available			
Melting point / melting range			
No data available			
Decomposition point / decomposition range			
No data available			
Flash point			
No data available			
Ignition temperature			
Value	490	°C	
Auto-ignition temperature			
No data available			
Oxidising properties			
No data available			
Explosive properties			
No data available			
Flammability (solid, gas)			
No data available			
Lower flammability or explosive limits			
Value	1.5	% vol	
Upper flammability or explosive limits			
Value	13.00	% vol	
Vapour pressure			
Value	3	-	4 bar
Reference temperature		20	°C
Value		10.4	bar
Reference temperature		50	°C
Vapour density			
No data available			
Evaporation rate			
No data available			
Relative density			
No data available			
Density			
Value	0.95	g/cm ³	

Trade name: einZA Lackspray 96-511, Hammerschlag Silber

Product no.: 9651101

Current version : 1.1.0, issued: 07.08.2020

Replaced version: 1.0.0, issued: 22.05.2019

Region: GB

Reference temperature	20 °C
Reference substance	varnish
Solubility in water	
Comments	essentially insoluble
Solubility(ies)	
No data available	
Partition coefficient: n-octanol/water	
No data available	
Viscosity	
No data available	

9.2 Other information

Other information
No data available.

SECTION 10: Stability and reactivity**10.1 Reactivity**

Stable under recommended storage and handling conditions (See section 7).

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

Acute oral toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	einZA Lackspray 96-511, Hammerschlag Silber
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE oral > 2000 mg/kg).

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
LD50		10760	mg/kg bodyweight
Species	rat		
Method	OECD 423		
Source	ECHA		
2	acetone	67-64-1	200-662-2
LD50		5800	mg/kg bodyweight
Species	rat		
Source	ECHA		

Acute dermal toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	einZA Lackspray 96-511, Hammerschlag Silber
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE dermal > 2000 mg/kg).

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
LD50		14112	mg/kg bodyweight

EU safety data sheet



Trade name: einza Lackspray 96-511, Hammerschlag Silber

Product no.: 9651101

Current version : 1.1.0, issued: 07.08.2020

Replaced version: 1.0.0, issued: 22.05.2019

Region: GB

Species	rabbit
Method	OECD 402
Source	ECHA
2	acetone
	67-64-1
	200-662-2
LD50	> 7400 mg/kg bodyweight
Species	rat
Source	ECHA

Acute inhalational toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	einza Lackspray 96-511, Hammerschlag Silber
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE for inhalation: > 20.000 ppmV (gases), > 20 mg/l (vapours), > 5 mg/l (dusts/mists)).

Acute inhalational toxicity	
No	Substance name
1	n-butyl acetate
	123-86-4
	204-658-1
LC50	>= 21 mg/l
Duration of exposure	4 h
State of aggregation	Vapour
Species	rat
Method	OECD 403
Source	ECHA
2	acetone
	67-64-1
	200-662-2
LC50	76 mg/l
Duration of exposure	4 h
State of aggregation	mist
Species	rat
Source	ECHA

Skin corrosion/irritation	
No	Substance name
1	acetone
	67-64-1
	200-662-2
Duration of exposure	24 h
Species	rabbit
Evaluation	low-irritant
Evaluation/classification	Based on available data, the classification criteria are not met.

Serious eye damage/irritation	
No	Substance name
1	acetone
	67-64-1
	200-662-2
Species	rabbit
Method	OECD 405
Source	ECHA
Evaluation	irritant

Respiratory or skin sensitisation	
No	Substance name
1	acetone
	67-64-1
	200-662-2
Route of exposure	Skin
Species	guinea pig
Source	ECHA
Evaluation	non-sensitizing

Germ cell mutagenicity	
No	Substance name
1	acetone
	67-64-1
	200-662-2
Type of examination	Bacterial Reverse Mutation Test
Method	OECD 471
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

Reproduction toxicity	
No data available	

Carcinogenicity	
No data available	

STOT - single exposure	
No data available	

STOT - repeated exposure	
--------------------------	--

Trade name: einza Lackspray 96-511, Hammerschlag Silber

Product no.: 9651101

Current version : 1.1.0, issued: 07.08.2020

Replaced version: 1.0.0, issued: 22.05.2019

Region: GB

No data available

Aspiration hazard

No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation may cause irritations of the respiratory tract, allergic reactions, cough, breathing difficulties, headache, nausea and vomiting.

SECTION 12: Ecological information**12.1 Toxicity**

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	propane	74-98-6	200-827-9
LC50		24.11	mg/l
Duration of exposure		96	h
Species	fish		
Method	QSAR		
Source	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
LC50		18	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	OECD 203		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	acetone	67-64-1	200-662-2
LC50		5540	mg/l
Duration of exposure		96	h
Species	Oncorhynchus mykiss		
Method	OECD 203		
Source	ECHA		

Toxicity to fish (chronic)

No data available

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	propane	74-98-6	200-827-9
EC50		14.22	mg/l
Duration of exposure		48	h
Species	Daphnia		
Method	QSAR		
Source	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
EC50		44	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	acetone	67-64-1	200-662-2
EC50		8800	mg/l
Duration of exposure		48	h
Species	Daphnia pulex		
Source	ECHA		

Toxicity to Daphnia (chronic)

No	Substance name	CAS no.	EC no.
1	acetone	67-64-1	200-662-2
NOEC		2212	mg/l
Duration of exposure		28	day(s)
Species	Daphnia magna		
Method	OECD 211		
Source	ECHA		

Toxicity to algae (acute)

No	Substance name	CAS no.	EC no.
1	propane	74-98-6	200-827-9
EC50		7.71	mg/l
Duration of exposure		96	h
Species	Algae		
Method	QSAR		
Source	ECHA		

Trade name: einza Lackspray 96-511, Hammerschlag Silber

Product no.: 9651101

Current version : 1.1.0, issued: 07.08.2020

Replaced version: 1.0.0, issued: 22.05.2019

Region: GB

2	n-butyl acetate	123-86-4	204-658-1
EC50		647.7	mg/l
Duration of exposure		72	h
Species	Desmodesmus subspicatus		
Source	ECHA		

Toxicity to algae (chronic)			
No	Substance name	CAS no.	EC no.
1	acetone	67-64-1	200-662-2
EC10		530	mg/l
Duration of exposure		8	day(s)
Species	Microcystis aeruginosa (blue-green alga)		
Source	ECHA		

Bacteria toxicity	
No data available	

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	propane	74-98-6	200-827-9
Type	aerobic biodegradation		
Value		100	%
Duration		633	h
Source	ECHA		
Evaluation	readily biodegradable		
2	xylene	1330-20-7	215-535-7
Value			%
3	acetone	67-64-1	200-662-2
Type	aerobic biodegradation		
Value		90	%
Duration		28	day(s)
Source	ECHA		
Evaluation	readily biodegradable		

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	The components of this product are not considered to be a PBT.
vPvB assessment	The components of this product are not considered to be a vPvB.

12.6 Other adverse effects

No data available.

12.7 Other information

Other information	
Do not allow to enter drains or water courses.	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste code 08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company.

Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Hand over only completely emptied aerosol cans for valuable substance recovery!

Packaging

Waste code 15 01 04; 15 01 11* metallic packaging; metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

SECTION 14: Transport information

Trade name: einza Lackspray 96-511, Hammerschlag Silber

Product no.: 9651101

Current version : 1.1.0, issued: 07.08.2020

Replaced version: 1.0.0, issued: 22.05.2019

Region: GB

14.1 Transport ADR/RID/ADN

Class	2
Classification code	5F
UN number	UN1950
Proper shipping name	AEROSOLS
Tunnel restriction code	D
Label	2.1

14.2 Transport IMDG

Class	2
UN number	UN1950
Proper shipping name	AEROSOLS
EmS	F-D, S-U
Label	2.1

14.3 Transport ICAO-TI / IATA

Class	2.1
UN number	UN1950
Proper shipping name	Aerosols, flammable
Label	2.1

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations****Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances requiring authorisation as listed on Annex XVII of the REACH regulation (EC) 1907/2006.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category: P3a

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)

VOC content	67.5	%
VOC-value	675	g/l

National regulations**Other national regulations**

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

Trade name: einza Lackspray 96-511, Hammerschlag Silber

Product no.: 9651101

Current version : 1.1.0, issued: 07.08.2020

Replaced version: 1.0.0, issued: 22.05.2019

Region: GB

National Threshold Limit Values of the corresponding countries as amended in each case.
Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

EUH066	Repeated exposure may cause skin dryness or cracking.
H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H261	In contact with water releases flammable gases.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
P	The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0.1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262- P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3.
T	This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be included in the safety data sheet.
U	When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Creation of the safety data sheet

UMCO GmbH
Georg-Wilhelm-Str. 187, D-21107 Hamburg
Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 671463