

Trade name: einza Lackspray 96-702, Gleit- und Schmiermittel**Product no.:** 9670203**Current version :** 1.1.0, issued: 07.08.2020**Replaced version:** 1.0.0, issued: 08.10.2019**Region:** GB**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name****einza Lackspray 96-702, Gleit- und Schmiermittel****1.2 Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses of the substance or mixture**

decorative paints/finishes

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet**Address**

einza Farben GmbH & Co KG

Junkersstraße 13

30179 Hannover

Telephone no. +49 (0)511 67490-0

Fax no. +49 (0)511 67490-20

e-mail info@einza.com

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Aerosol 1; H222

Eye Irrit. 2; H319

STOT SE 3; H336

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)****Hazard pictograms**

GHS02



GHS07

Signal word

Danger

Hazardous component(s) to be indicated on label:

n-butyl acetate

acetone

Hazard statement(s)

H222

Extremely flammable aerosol.

H229

Pressurised container: May burst if heated.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.

Hazard statements (EU)

EUH066

Repeated exposure may cause skin dryness or cracking.

Precautionary statement(s)

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211

Do not spray on an open flame or other ignition source.

Trade name: einza Lackspray 96-702, Gleit- und Schmiermittel

Product no.: 9670203

Current version : 1.1.0, issued: 07.08.2020

Replaced version: 1.0.0, issued: 08.10.2019

Region: GB

P251 Do not pierce or burn, even after use.
 P271 Use only outdoors or in a well-ventilated area.
 P405 Store locked up.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/container to a facility in accordance with local and national regulations.

2.3 Other hazards

PBT assessment
 The components of this product are not considered to be a PBT.
 vPvB assessment
 The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not applicable. The product is not a substance.

3.2 Mixtures**Hazardous ingredients**

No	Substance name CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Additional information Concentration	%
1	butane			
	106-97-8 203-448-7 601-004-00-0 01-2119474691-32	Flam. Gas 1; H220 Press. Gas liq.; H280	>= 25.00 - < 50.00	%-b.w.
2	n-butyl acetate			
	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	EUH066 Flam. Liq. 3; H226 STOT SE 3; H336	>= 25.00 - < 50.00	%-b.w.
3	acetone			
	67-64-1 200-662-2 606-001-00-8 01-2119471330-49	Eye Irrit. 2; H319 Flam. Liq. 2; H225 STOT SE 3; H336	>= 25.00 - < 50.00	%-b.w.
4	propane			
	74-98-6 200-827-9 601-003-00-5 01-2119486944-21	Flam. Gas 1; H220 Press. Gas liq.; H280	>= 10.00 - < 25.00	%-b.w.
5	ethyl-acetate			
	141-78-6 205-500-4 607-022-00-5 01-2119475103-46	EUH066 Eye Irrit. 2; H319 Flam. Liq. 2; H225 STOT SE 3; H336	< 5.00	%-b.w.

Full Text for all H-phrases and EUH-phrases: pls. see section 16

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	C, U	-	-	-
4	U	-	-	-

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

SECTION 4: First aid measures**4.1 Description of first aid measures****General information**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate

Trade name: einZA Lackspray 96-702, Gleit- und Schmiermittel

Product no.: 9670203

Current version : 1.1.0, issued: 07.08.2020

Replaced version: 1.0.0, issued: 08.10.2019

Region: GB

medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO₂, powders, water spray

Unsuitable extinguishing media

water jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Exclude sources of ignition and ventilate the area. Do not inhale vapours/aerosols. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Do not breathe steams or mist of the product. For personal protection see section 8. Avoid eye, skin and clothing contact.

General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

Requirements for storage rooms and vessels

Keep the product in the original packing. Keep container tightly closed. Observe label precautions. Official regulations ruling storage of aerosols must be observed.

Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Trade name: einza Lackspray 96-702, Gleit- und Schmiermittel

Product no.: 9670203

Current version : 1.1.0, issued: 07.08.2020

Replaced version: 1.0.0, issued: 08.10.2019

Region: GB

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limit values**

No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7
List of approved workplace exposure limits (WELs) / EH40			
	Butane		
	WEL short-term (15 min reference period)	1810 mg/m ³	750 ppm
	WEL long-term (8-hr TWA reference period)	1450 mg/m ³	600 ppm
	Comments	Carc, (only applies if Butane contains more than 0.1% of buta-1,3-diene)	
2	n-butyl acetate	123-86-4	204-658-1
List of approved workplace exposure limits (WELs) / EH40			
	Butyl acetate		
	WEL short-term (15 min reference period)	966 mg/m ³	200 ppm
	WEL long-term (8-hr TWA reference period)	724 mg/m ³	150 ppm
	EU 2019/1831		
	n-Butyl acetate		
	WEL short-term (15 min reference period)	723 mg/m ³	150 ppm
	WEL long-term (8-hr TWA reference period)	241 mg/m ³	50 ppm
3	acetone	67-64-1	200-662-2
2000/39/EC			
	Acetone		
	WEL long-term (8-hr TWA reference period)	1210 mg/m ³	500 ppm
List of approved workplace exposure limits (WELs) / EH40			
	Acetone		
	WEL short-term (15 min reference period)	3620 mg/m ³	1500 ppm
	WEL long-term (8-hr TWA reference period)	1210 mg/m ³	500 ppm
4	ethyl-acetate	141-78-6	205-500-4
2017/164/EU			
	Ethyl acetate		
	WEL short-term (15 min reference period)	1468 mg/m ³	400 ppm
	WEL long-term (8-hr TWA reference period)	734 mg/m ³	200 ppm
List of approved workplace exposure limits (WELs) / EH40			
	Ethyl acetate		
	WEL short-term (15 min reference period)		400 ppm
	WEL long-term (8-hr TWA reference period)		200 ppm

DNEL, DMEL and PNEC values**DNEL values (worker)**

CNEL values (worker)					
No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	n-butyl acetate			123-86-4 204-658-1	
	dermal	Long term (chronic)	systemic	11	mg/kg/day
	dermal	Short term (acut)	systemic	11	mg/kg/day
	inhalative	Long term (chronic)	systemic	300	mg/m³
	inhalative	Short term (acut)	systemic	600	mg/m³
	inhalative	Long term (chronic)	local	300	mg/m³
	inhalative	Short term (acut)	local	600	mg/m³
2	acetone			67-64-1 200-662-2	
	dermal	Long term (chronic)	systemic	186	mg/kg/day
	inhalative	Short term (acut)	local	2420	mg/m³
	inhalative	Short term (acut)	systemic	1210	mg/m³
3	ethyl-acetate			141-78-6 205-500-4	
	dermal	Long term (chronic)	systemic	63	mg/kg/day
	inhalative	Short term (acut)	systemic	1468	mg/m³
	inhalative	Long term (chronic)	local	734	mg/m³
	inhalative	Short term (acut)	local	1468	mg/m³
	inhalative	Long term (chronic)	systemic	734	mg/m³

Trade name: einza Lackspray 96-702, Gleit- und Schmiermittel

Product no.: 9670203

Current version : 1.1.0, issued: 07.08.2020

Replaced version: 1.0.0, issued: 08.10.2019

Region: GB

DNEL value (consumer)

No	Substance name	Route of exposure	Exposure time	Effect	CAS / EC no	Value
1	n-butyl acetate				123-86-4 204-658-1	
	oral		Long term (chronic)	systemic	2	mg/kg/day
	oral		Short term (acut)	systemic	2	mg/kg/day
	dermal		Long term (chronic)	systemic	6	mg/kg/day
	dermal		Short term (acut)	systemic	6	mg/kg/day
	inhalative		Long term (chronic)	systemic	35.7	mg/m ³
	inhalative		Short term (acut)	systemic	300	mg/m ³
	inhalative		Long term (chronic)	local	35.7	mg/m ³
	inhalative		Short term (acut)	local	300	mg/m ³
2	acetone				67-64-1 200-662-2	
	oral		Long term (chronic)	systemic	62	mg/kg/day
	dermal		Long term (chronic)	systemic	62	mg/kg/day
	inhalative		Long term (chronic)	systemic	200	mg/m ³
3	ethyl-acetate				141-78-6 205-500-4	
	oral		Long term (chronic)	systemic	4.5	mg/kg/day
	dermal		Long term (chronic)	systemic	37	mg/kg/day
	inhalative		Short term (acut)	systemic	734	mg/m ³
	inhalative		Long term (chronic)	local	367	mg/m ³
	inhalative		Short term (acut)	local	734	mg/m ³
	inhalative		Long term (chronic)	systemic	367	mg/m ³

PNEC values

No	Substance name	ecological compartment	Type	CAS / EC no	Value
1	n-butyl acetate			123-86-4 204-658-1	
	water		fresh water	0.18	mg/L
	water		marine water	0.018	mg/L
	water		Aqua intermittent	0.36	mg/L
	water		fresh water sediment	0.981	mg/kg dry weight
	water		marine water sediment	0.0981	mg/kg dry weight
	soil		-	0.0903	mg/kg
	sewage treatment plant		-	35.6	mg/L
2	acetone			67-64-1 200-662-2	
	water		fresh water	10.6	mg/L
	water		marine water	1.06	mg/L
	water		Aqua intermittent	21	mg/L
	water		fresh water sediment	30.4	mg/kg
	water		marine water sediment	3.04	mg/kg
	soil		-	29.5	mg/kg
	sewage treatment plant		-	100	mg/L
3	ethyl-acetate			141-78-6 205-500-4	
	water		fresh water	0.24	mg/L
	water		marine water	0.024	mg/L
	water		Aqua intermittent	1.65	mg/L
	water		fresh water sediment	1.15	mg/kg dry weight
	water		marine water sediment	0.115	mg/kg dry weight
	soil		-	0.148	mg/kg dry weight
	sewage treatment plant		-	650	mg/L
	secondary poisoning		-	200	mg/kg

8.2 Exposure controls

Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Short term: filter apparatus, Filter A

Trade name: einza Lackspray 96-702, Gleit- und Schmiermittel

Product no.: 9670203

Current version : 1.1.0, issued: 07.08.2020

Replaced version: 1.0.0, issued: 08.10.2019

Region: GB

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Form/Colour			
Aerosol			
according to product name			
Odour			
characteristic			
Odour threshold			
No data available			
pH value			
No data available			
Boiling point / boiling range			
No data available			
Melting point / melting range			
No data available			
Decomposition point / decomposition range			
No data available			
Flash point			
No data available			
Ignition temperature			
Value	490	°C	
Auto-ignition temperature			
No data available			
Oxidising properties			
No data available			
Explosive properties			
No data available			
Flammability (solid, gas)			
No data available			
Lower flammability or explosive limits			
Value	1.5	% vol	
Upper flammability or explosive limits			
Value	13.00	% vol	
Vapour pressure			
Value	3	- 4	bar
Reference temperature		20	°C
Value		10.4	bar
Reference temperature		50	°C
Vapour density			
No data available			
Evaporation rate			
No data available			
Relative density			
No data available			
Density			

Trade name: einza Lackspray 96-702, Gleit- und Schmiermittel

Product no.: 9670203

Current version : 1.1.0, issued: 07.08.2020

Replaced version: 1.0.0, issued: 08.10.2019

Region: GB

Value	0.95	g/cm³	
Reference temperature	20	°C	
Reference substance	varnish		
Solubility in water			
Comments	essentially insoluble		
Solubility(ies)			
No data available			
Partition coefficient: n-octanol/water			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
log Pow		2.3	
Reference temperature		25	°C
Method	OECD 117		
Source	ECHA		
2	propane	74-98-6	200-827-9
log Pow	appr.	1.8	
Method	QSAR		
Source	ECHA		
3	ethyl-acetate	141-78-6	205-500-4
log Pow		6.8	
Reference temperature		25	°C
Source	ECHA		
Viscosity			
No data available			

9.2 Other information

Other information
No data available.

SECTION 10: Stability and reactivity**10.1 Reactivity**

Stable under recommended storage and handling conditions (See section 7).

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
LD50		10760	mg/kg bodyweight
Species	rat		
Method	OECD 423		
Source	ECHA		
2	acetone	67-64-1	200-662-2
LD50		5800	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		
3	ethyl-acetate	141-78-6	205-500-4
LD50		5600	mg/kg bodyweight
Species	rat		
Source	ECHA		

Trade name: einza Lackspray 96-702, Gleit- und Schmiermittel

Product no.: 9670203

Current version : 1.1.0, issued: 07.08.2020

Replaced version: 1.0.0, issued: 08.10.2019

Region: GB

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
LD50		14112	mg/kg bodyweight
Species	rabbit		
Method	OECD 402		
Source	ECHA		
2	acetone	67-64-1	200-662-2
LD50		15800	mg/kg bodyweight
Species	rabbit		
Source	ECHA		
3	ethyl-acetate	141-78-6	205-500-4
LD50		20000	mg/kg bodyweight
Species	rabbit		
Source	ECHA		
Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	acetone	67-64-1	200-662-2
LC50		76	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Source	ECHA		
2	propane	74-98-6	200-827-9
LC50		800000	ppmV
Duration of exposure		0.25	h
State of aggregation	Gas		
Species	rat		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		
2	ethyl-acetate	141-78-6	205-500-4
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	low-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	non-irritant		
2	ethyl-acetate	141-78-6	205-500-4
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	low-irritant		
Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
Route of exposure	Skin		
Species	guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		
Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7
Type of examination	In vitro Mammalian Chromosomal Aberration Test		

Trade name: einza Lackspray 96-702, Gleit- und Schmiermittel

Product no.: 9670203

Current version : 1.1.0, issued: 07.08.2020

Replaced version: 1.0.0, issued: 08.10.2019

Region: GB

Species	Human Lymphocyte		
Method	OECD 473		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Type of examination	in vitro gene mutation study in bacteria		
Species	Salmonella typhimurium		
Method	OECD 471		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	n-butyl acetate	123-86-4	204-658-1
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	propane	74-98-6	200-827-9
Route of exposure	inhalational		
Species	Salmonella typhimurium		
Method	OECD 471		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7
Route of exposure	inhalational		
Species	rat		
Method	OECD 422		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	n-butyl acetate	123-86-4	204-658-1
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	propane	74-98-6	200-827-9
Route of exposure	inhalational		
Species	rat		
Method	OECD 422		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Carcinogenicity			
No data available			
STOT - single exposure			
No data available			
STOT - repeated exposure			
No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7
Route of exposure	inhalational		
Species	rat		
Method	OECD 422		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	n-butyl acetate	123-86-4	204-658-1
Route of exposure	inhalational		
NOAEC	500		ppm
Duration of exposure	90		day(s)
Species	rat		
Method	EPA OTS 798.2450		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	propane	74-98-6	200-827-9
Route of exposure	inhalational		
Species	rat		
Method	OECD 422		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Aspiration hazard			
No data available			
Delayed and immediate effects as well as chronic effects from short and long-term exposure			
Inhalation may cause irritations of the respiratory tract, allergic reactions, cough, breathing difficulties, headache, nausea and vomiting.			

SECTION 12: Ecological information

Trade name: einza Lackspray 96-702, Gleit- und Schmiermittel

Product no.: 9670203

Current version : 1.1.0, issued: 07.08.2020

Replaced version: 1.0.0, issued: 08.10.2019

Region: GB

12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
LC50		18	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	OECD 203		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	acetone	67-64-1	200-662-2
LC50		5540	mg/l
Duration of exposure		96	h
Species	Oncorhynchus mykiss		
Source	ECHA		
3	ethyl-acetate	141-78-6	205-500-4
LC50		230	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Source	ECHA		

Toxicity to fish (chronic)			
No data available			

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
EC50		44	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	acetone	67-64-1	200-662-2
EC50		8800	mg/l
Duration of exposure		48	h
Species	Daphnia pulex		
Source	ECHA		
3	ethyl-acetate	141-78-6	205-500-4
EC50		1350	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Source	ECHA		

Toxicity to Daphnia (chronic)			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
NOEC		23	mg/l
Duration of exposure		21	day(s)
Species	Daphnia magna		
with reference to	CAS 110-19-0		
Method	OECD 211		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Toxicity to algae (acute)			
No data available			

Toxicity to algae (chronic)			
No data available			

Bacteria toxicity			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
IC50		356	mg/l
Duration of exposure		40	h
Species	Tetrahymena pyriformis (Protozoa)		
Source	ECHA		

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7

Trade name: einza Lackspray 96-702, Gleit- und Schmiermittel

Product no.: 9670203

Current version : 1.1.0, issued: 07.08.2020

Replaced version: 1.0.0, issued: 08.10.2019

Region: GB

Type	aerobic biodegradation		
Value	50	%	
Duration	3.46	d	
Method	QSAR		
Source	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
Type	aerobic biodegradation		
Value	83	%	
Duration	28	day(s)	
Method	OECD 301 D		
Source	ECHA		
Evaluation	readily biodegradable		
3	acetone	67-64-1	200-662-2
Type	aerobic biodegradation		
Value	90.9	%	
Duration	28	day(s)	
Method	OECD 301 B		
Source	ECHA		
Evaluation	readily biodegradable		
4	propane	74-98-6	200-827-9
Type	aerobic biodegradation		
Value	50	%	
Duration	3	d	
Method	QSAR		
Source	ECHA		
Evaluation	readily biodegradable		
5	ethyl-acetate	141-78-6	205-500-4
Source	ECHA		
Evaluation	readily biodegradable		
Abiotic Degradation			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
Type	Photolysis		
Half-life	3.3	day(s)	
Reference temperature	25	°C	
Source	ECHA		

12.3 Bioaccumulative potential

Bioconcentration factor (BCF)			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
BCF		15.3	
Method	Calculation model used (Q)SAR		
Source	ECHA		
Partition coefficient: n-octanol/water			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
log Pow		2.3	
Reference temperature		25	°C
Method	OECD 117		
Source	ECHA		
2	propane	74-98-6	200-827-9
log Pow		appr. 1.8	
Method	QSAR		
Source	ECHA		
3	ethyl-acetate	141-78-6	205-500-4
log Pow		6.8	
Reference temperature		25	°C
Source	ECHA		

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	The components of this product are not considered to be a PBT.
vPvB assessment	The components of this product are not considered to be a vPvB.

12.6 Other adverse effects

Trade name: einza Lackspray 96-702, Gleit- und Schmiermittel**Product no.:** 9670203**Current version :** 1.1.0, issued: 07.08.2020**Replaced version:** 1.0.0, issued: 08.10.2019**Region:** GB

No data available.

12.7 Other information**Other information**

Do not allow to enter drains or water courses.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Waste code 08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company.

Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Hand over only completely emptied aerosol cans for valuable substance recovery!

Packaging

Waste code 15 01 04; 15 01 11* metallic packaging; metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

SECTION 14: Transport information**14.1 Transport ADR/RID/ADN**

Class	2
Classification code	5F
UN number	UN1950
Proper shipping name	AEROSOLS
Tunnel restriction code	D
Label	2.1

14.2 Transport IMDG

Class	2
UN number	UN1950
Proper shipping name	AEROSOLS
EmS	F-D, S-U
Label	2.1

14.3 Transport ICAO-TI / IATA

Class	2.1
UN number	UN1950
Proper shipping name	Aerosols, flammable
Label	2.1

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations****Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Trade name: einza Lackspray 96-702, Gleit- und Schmiermittel

Product no.: 9670203

Current version : 1.1.0, issued: 07.08.2020

Replaced version: 1.0.0, issued: 08.10.2019

Region: GB

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances requiring authorisation as listed on Annex XVII of the REACH regulation (EC) 1907/2006.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:

P3a

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)

VOC content

62.5

%

VOC-value

675

g/l

National regulations**Other national regulations**

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H220

Extremely flammable gas.

H225

Highly flammable liquid and vapour.

H226

Flammable liquid and vapour.

H280

Contains gas under pressure; may explode if heated.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

C

Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

U

When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 671469