

Trade name: einza Härter LawiDox, für Epoxidharz-Grundierung AgBB**Product no.:** 0072725**Current version :** 3.0.0, issued: 17.09.2024**Replaced version:** 2.2.0, issued: 03.11.2021**Region:** GB**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name****einza Härter LawiDox, für Epoxidharz-Grundierung AgBB****1.2 Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses of the substance or mixture**

Epoxy resin

Hardener

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet**Address**

einza Farben GmbH & Co KG

Junkersstraße 13

30179 Hannover

Telephone no. +49 (0)511 67490-0

Fax no. +49 (0)511 67490-20

e-mail info@einza.com

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Acute Tox. 4; H302

Acute Tox. 4; H332

Aquatic Chronic 3; H412

Eye Dam. 1; H318

Skin Corr. 1B; H314

Skin Sens. 1; H317

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)****Hazard pictograms**

GHS05



GHS07

Signal word

Danger

Hazardous component(s) to be indicated on label:

benzyl alcohol

m-phenylenebis(methylamine)

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-Chloro-2,3-epoxypropane, Reaction products with 3-Aminomethyl-3,5,5-trimethylcyclohexylamine

Hazard statement(s)

H302+H332

Harmful if swallowed or if inhaled

H314

Causes severe skin burns and eye damage.

H317

May cause an allergic skin reaction.

Trade name: einza Härter LawiDox, für Epoxidharz-Grundierung AgBB

Product no.: 0072725

Current version : 3.0.0, issued: 17.09.2024

Replaced version: 2.2.0, issued: 03.11.2021

Region: GB

H412	Harmful to aquatic life with long lasting effects.
Precautionary statement(s)	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/eye protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P405	Store locked up.
P501	Dispose of contents/container to a facility in accordance with local and national regulations.

2.3 Other hazards

PBT assessment

The components of this product are not considered to be a PBT.

vPvB assessment

The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Hazardous ingredients

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration
			%
1	benzyl alcohol		
	100-51-6 202-859-9 603-057-00-5 01-2119492630-38	Acute Tox. 4; H302 Acute Tox. 4; H332	>= 25.00 - < 50.00 wt%
2	m-phenylenebis(methylamine)		
	1477-55-0 216-032-5 - 01-2119480150-50	Acute Tox. 4; H332 Acute Tox. 4; H302 Aquatic Chronic 3; H412 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1B; H317 EUH071	>= 10.00 - < 25.00 wt%
3	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)		
	113930-69-1 500-302-4 - -	Acute Tox. 4; H302 Skin Sens. 1; H317	>= 10.00 - < 25.00 wt%
4	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-Chloro-2,3-epoxypropane, Reaction products with 3-Aminomethyl-3,5,5-trimethylcyclohexylamine		
	38294-64-3 - - 01-2119965165-33	Aquatic Chronic 3; H412 Skin Corr. 1B; H314 Skin Sens. 1; H317 Eye Dam. 1; H318	>= 10.00 - < 25.00 wt%
5	salicylic acid		
	69-72-7 200-712-3 607-732-00-5 -	Acute Tox. 4; H302 Eye Dam. 1; H318 Repr. 2; H361d	< 5.00 wt%
6	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia		
	9046-10-0 - - 01-2119557899-12	Skin Corr. 1C; H314 Eye Dam. 1; H318 Aquatic Chronic 3; H412	< 2.50 wt%

Full text of H- and EUH-phrases, if not already mentioned in section 2.2: see section 16.

Trade name: einza Härter LawiDox, für Epoxidharz-Grundierung AgBB**Product no.:** 0072725**Current version :** 3.0.0, issued: 17.09.2024**Replaced version:** 2.2.0, issued: 03.11.2021**Region:** GB

Acute toxicity estimate (ATE) values			
No	oral	dermal	inhalative
1	1230 mg/kg bodyweight		

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. After skin contact immediately wash with water and soap and rinse thoroughly. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Do NOT induce vomiting. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO₂, powders, water spray

Unsuitable extinguishing media

water jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Trade name: einza Härter LawiDox, für Epoxidharz-Grundierung AgBB

Product no.: 0072725

Current version : 3.0.0, issued: 17.09.2024

Replaced version: 2.2.0, issued: 03.11.2021

Region: GB

Due to the organic solvents' content of the mixture: Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flating] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities**Technical measures and storage conditions**

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****DNEL, DMEL and PNEC values****DNEL values (worker)**

No	Substance name			CAS / EC no
	Route of exposure	Exposure time	Effect	Value
1	benzyl alcohol			100-51-6 202-859-9
	dermal	Long term (chronic)	systemic	8 mg/kg/day
	dermal	Short term (acute)	systemic	40 mg/kg/day
	inhalative	Long term (chronic)	systemic	22 mg/m ³
	inhalative	Short term (acute)	systemic	110 mg/m ³
2	m-phenylenebis(methylamine)			1477-55-0 216-032-5
	dermal	Long term (chronic)	systemic	0.33 mg/kg
	inhalative	Long term (chronic)	systemic	1.2 mg/m ³
	inhalative	Long term (chronic)	local	0.2 mg/m ³
3	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia			9046-10-0 -
	dermal	Long term (chronic)	systemic	2.5 mg/kg/day
	inhalative	Long term (chronic)	systemic	5.29 mg/m ³

DNEL value (consumer)

No	Substance name			CAS / EC no
	Route of exposure	Exposure time	Effect	Value
1	benzyl alcohol			100-51-6 202-859-9
	oral	Long term (chronic)	systemic	4 mg/kg/day
	oral	Short term (acute)	systemic	20 mg/kg/day
	dermal	Long term (chronic)	systemic	4 mg/kg/day
	dermal	Long term (chronic)	systemic	20 mg/kg/day
	inhalative	Long term (chronic)	systemic	5.4 mg/m ³
	inhalative	Short term (acute)	systemic	27 mg/m ³

PNEC values

No	Substance name		CAS / EC no
	ecological compartment	Type	Value
1	benzyl alcohol		100-51-6 202-859-9
	water	fresh water	1 mg/L

Trade name: einza Härter LawiDox, für Epoxidharz-Grundierung AgBB

Product no.: 0072725

Current version : 3.0.0, issued: 17.09.2024

Replaced version: 2.2.0, issued: 03.11.2021

Region: GB

	water	marine water	0.1	mg/L
	water	Aqua intermittent	2.3	mg/L
	water	fresh water sediment	5.27	mg/kg dry weight
	water	marine water sediment	0.527	mg/kg dry weight
	soil	-	0.456	mg/kg dry weight
	sewage treatment plant	-	39	mg/L
2	m-phenylenebis(methylamine)		1477-55-0	216-032-5
	water	fresh water	0.094	mg/L
	water	marine water	0.0094	mg/L
	water	fresh water sediment	12.4	mg/kg
	with reference to: dry mass			
	water	marine water sediment	1.24	mg/kg
	with reference to: dry mass			
	soil	-	2.44	mg/kg
	with reference to: dry mass			
	sewage treatment plant	-	10	mg/L
3	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia		9046-10-0	-
	water	fresh water	0.015	mg/L
	water	marine water	0.014	mg/L
	water	fresh water sediment	0.132	mg/kg dry weight
	water	marine water sediment	0.125	mg/kg dry weight
	soil	-	0.018	mg/kg dry weight
	sewage treatment plant	-	7.5	mg/L
	secondary poisoning	-	6.93	mg/kg food

8.2 Exposure controls

Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. Filter A2P2 (DIN EN 14387)

Eye / face protection

Wear safety goggles to protect against splashes. Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material	butyl rubber		
Material thickness		0.7	mm
Breakthrough time	>	480	min
Appropriate Material	nitrile rubber		
Material thickness		0.4	mm
Breakthrough time	>	480	mm

Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation
liquid
Form
Liquid
Colour
yellowish

Trade name: einza Härter LawiDox, für Epoxidharz-Grundierung AgBB

Product no.: 0072725

Current version : 3.0.0, issued: 17.09.2024

Replaced version: 2.2.0, issued: 03.11.2021

Region: GB

Odour			
amine-like			
pH value			
reason for missing pH		substance/mixture is non-soluble (in water)	
Boiling point / boiling range			
Value		205	
Melting point/freezing point			
No data available			
Decomposition temperature			
No data available			
Flash point			
Value		101 °C	
Ignition temperature			
Value		435 °C	
Oxidising properties			
Not applicable			
Flammability			
Not applicable			
Lower explosion limit			
Value		1.3 % vol	
Upper explosion limit			
Value		13 % vol	
Vapour pressure			
Value		0.1 hPa	
Reference temperature		20 °C	
Relative vapour density			
No data available			
Relative density			
No data available			
Density			
Value		1.05 g/cm³	
Reference temperature		20 °C	
Solubility in water			
Comments		partially miscible	
Solubility			
No data available			
Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
log Pow		1.05	
Reference temperature		20	°C
Source		ECHA	
2	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia	9046-10-0	-
log Pow		1.34	
Reference temperature		25	°C
Method		OECD 117	
Kinematic viscosity			
Value		600 - 700 mPa*s	
Reference temperature		20 °C	
Type		dynamic	
Solvent separation test			
Not applicable			
Particle characteristics			
No data available			

9.2 Other information

Other information

Trade name: einza Härter LawiDox, für Epoxidharz-Grundierung AgBB

Product no.: 0072725

Current version : 3.0.0, issued: 17.09.2024

Replaced version: 2.2.0, issued: 03.11.2021

Region: GB

No data available.

SECTION 10: Stability and reactivity**10.1 Reactivity**

Stable under recommended storage and handling conditions (See section 7).

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Acute oral toxicity (result of the ATE calculation for the mixture)			
Product Name			
einza Härter LawiDox, für Epoxidharz-Grundierung AgBB			
ATE (Mixture)	879.99	mg/kg	
Method	Calculation method according Regulation (EC) No 1272/2008, (CLP), annex I, part 3, section 3.1.3.6.		

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
LD50		1230	mg/kg bodyweight
Species	rat		
2	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia	9046-10-0	-
LD50		2885	mg/kg bodyweight
Species	rat (female)		
Method	OECD 401		
Source	ECHA		

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
LD50		2000	mg/kg bodyweight
Species	rabbit		
2	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia	9046-10-0	-
LD50		2979	mg/kg bodyweight
Species	rabbit		
Method	OECD 402		
Source	ECHA		

Acute inhalational toxicity (result of the ATE calculation for the mixture)			
Product Name			
einza Härter LawiDox, für Epoxidharz-Grundierung AgBB			
ATE (Mixture)	19.4004	mg/l	
Route of exposure / physical form	Vapour		
Method	Calculation method according Regulation (EC) No 1272/2008, (CLP), annex I, part 3, section 3.1.3.6.		

Acute inhalational toxicity			
No data available			

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
Species	rabbit		
Method	OECD 404		
Source	ECHA		

Trade name: einza Härter LawiDox, für Epoxidharz-Grundierung AgBB

Product no.: 0072725

Current version : 3.0.0, issued: 17.09.2024

Replaced version: 2.2.0, issued: 03.11.2021

Region: GB

Evaluation		non-irritant	
2	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia		9046-10-0 -
Species		rabbit	
Method		OECD 404	
Source		ECHA	
Evaluation		corrosive	
Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
Species		rabbit	
Method		OECD 405	
Source		ECHA	
Evaluation		non-irritant	
2	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia		9046-10-0 -
Species		rabbit	
Method		OECD 405	
Source		ECHA	
Evaluation		corrosive	
Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
Route of exposure		Skin	
Species		mouse	
Method		OECD 429	
Source		ECHA	
Evaluation		non-sensitizing	
Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
Species		Salmonella typhimurium TA98, TA100, TA1535, TA1537	
Method		OECD 471	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Reproduction toxicity			
No data available			
Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
Route of exposure		oral	
		400	mg/kg bw/d
Species		rat	
Method		OECD 451	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
STOT - single exposure			
No data available			
STOT - repeated exposure			
No data available			
Aspiration hazard			
No data available			
Endocrine disrupting properties			
No data available			
Delayed and immediate effects as well as chronic effects from short and long-term exposure			
Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. Based on the properties of the epoxy constituent(s) and considering toxicological data on similar mixtures, this mixture may be a skin sensitiser and an irritant. It contains low molecular weight epoxy constituents which are irritating to eyes, mucous membrane and skin. Repeated skin contact may lead to irritation and to sensitisation, possibly with cross-sensitisation to other epoxies. Skin contact with the mixture and exposure to spray mist and vapour should be avoided.			

Trade name: einza Härter LawiDox, für Epoxidharz-Grundierung AgBB

Product no.: 0072725

Current version : 3.0.0, issued: 17.09.2024

Replaced version: 2.2.0, issued: 03.11.2021

Region: GB

11.2 Information on other hazards

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
LC50		460	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	EPA OPP 72-1		
Source	ECHA		
2	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia	9046-10-0	-
LC50		>	mg/l
Duration of exposure		15	h
Species	Oncorhynchus mykiss		
Method	OECD 203		
Source	ECHA		
Toxicity to fish (chronic)			
No data available			
Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
EC50		230	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		
2	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia	9046-10-0	-
EC50		80	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		
Toxicity to Daphnia (chronic)			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
NOEC		51	mg/l
Duration of exposure		21	day(s)
Species	Daphnia magna		
Method	OECD 211		
Source	ECHA		
Toxicity to algae (acute)			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
EC50		710	mg/l
Duration of exposure		72	h
Species	Pseudokirchneriella subcapitata		
Method	OECD 201		
Source	ECHA		
2	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia	9046-10-0	-
ErC50		15	mg/l
Duration of exposure		72	h
Species	Pseudokirchneriella subcapitata		
Method	OECD 201		
Source	ECHA		
Toxicity to algae (chronic)			
No data available			
Bacteria toxicity			

Trade name: einza Härter LawiDox, für Epoxidharz-Grundierung AgBB

Product no.: 0072725

Current version : 3.0.0, issued: 17.09.2024

Replaced version: 2.2.0, issued: 03.11.2021

Region: GB

No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
IC50		390	mg/l
Duration of exposure		24	h
Species	Nitrosomonas sp.		
Method	ISO 8192		
Source	ECHA		

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
Value	92	- 96	%
Source	ECHA		
Evaluation	readily biodegradable		
2	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia	9046-10-0	-
Type	aerobic biodegradation		
Value	0		%
Duration	28		day(s)
Method	OECD 301 B		
Source	ECHA		

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
log Pow		1.05	
Reference temperature		20	°C
Source	ECHA		
2	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia	9046-10-0	-
log Pow		1.34	
Reference temperature		25	°C
Method	OECD 117		

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
Product Name	
einza Härter LawiDox, für Epoxidharz-Grundierung AgBB	
PBT assessment	The components of this product are not considered to be a PBT.
vPvB assessment	The components of this product are not considered to be a vPvB.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information
Do not allow to enter drains or water courses.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Waste code 08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company. Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

Trade name: einza Härter LawiDox, für Epoxidharz-Grundierung AgBB

Product no.: 0072725

Current version : 3.0.0, issued: 17.09.2024

Replaced version: 2.2.0, issued: 03.11.2021

Region: GB

SECTION 14: Transport information**14.1 UN number or ID number**

ADR/RID/ADN	UN2735
IMDG	UN2735
ICAO-TI / IATA	UN2735

14.2 UN proper shipping name

ADR/RID/ADN	AMINES, LIQUID, CORROSIVE, N.O.S.
IMDG	AMINES, LIQUID, CORROSIVE, N.O.S.
ICAO-TI / IATA	Amines, liquid, corrosive, n.o.s.

14.3 Transport hazard class(es)

ADR/RID/ADN - Class	8
Label	8
Classification code	C7
Tunnel restriction code	E
Hazard identification no.	80
IMDG - Class	8
Label	8
ICAO-TI / IATA - Class	8
Label	8

14.4 Packing group

ADR/RID/ADN	II
IMDG	II
ICAO-TI / IATA	II

14.5 Environmental hazards

EmS	F-A, S-B
-----	----------

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations****Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3
The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	

No	Substance name	CAS no.	EC no.	No
1	salicylic acid	69-72-7	200-712-3	75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is not subject to Part 1 or 2 of Annex I.

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)

VOC content	40	% weight
-------------	----	----------

National regulations**Other national regulations**

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

Trade name: einza Härter LawiDox, für Epoxidharz-Grundierung AgBB

Product no.: 0072725

Current version : 3.0.0, issued: 17.09.2024

Replaced version: 2.2.0, issued: 03.11.2021

Region: GB

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

EUH071	Corrosive to the respiratory tract.
H302	Harmful if swallowed.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H361d	Suspected of damaging the unborn child.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCÖ GmbH.

Prod-ID 686401