

Trade name: einzA LawiPur 2-K-PU Mattsiegel, Stammlack

Product no.: 0079347

Current version: 1.0.1, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

einzA LawiPur 2-K-PU Mattsiegel, Stammlack

UFI:

VMQF-N1PD-900N-JE2S

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

decorative paints/finishes

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

einzA Farben GmbH & Co KG

Junkersstraße 13

30179 Hannover

Telephone no. +49 (0)511 67490-0

Fax no. +49 (0)511 67490-20

e-mail info@einza.com

Information provided by / telephone

In emergencies, the country-specific emergency number can be found in the corresponding country-specific safety data sheets.

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

+49 (0)40 0511 - 674 90-0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Skin Sens. 1; H317

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS07

Signal word

Warning

Hazardous component(s) to be indicated on label:

1,2-benzisothiazol-3(2H)-one

Trade name: einza LawiPur 2-K-PU Mattsiegel, Stammlack

Product no.: 0079347

Current version: 1.0.1, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

Hazard statement(s)

H317 May cause an allergic skin reaction.

Hazard statements (EU)

EUH208 Contains formaldehyde, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1). May produce an allergic reaction.

Precautionary statement(s)

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P280 Wear protective gloves/eye protection.
 P501 Dispose of contents/container to a facility in accordance with local and national regulations.

UFI:

VMQF-N1PD-900N-JE2S

2.3 Other hazards

The product does not contain any components > 0.1% that meet the criteria for PBT and vPvB according to Regulation (EC) No. 1907/2006, Annex XIII, or that have been included in the list compiled in accordance with Article 59(1). This product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Hazardous ingredients

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration
			%
1	ammonia		
	1336-21-6 215-647-6 007-001-01-2 01-2119488876-14	Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT SE 3; H335 Aquatic Acute 1; H400	< 0,50 wt%
2	1,2-benzisothiazol-3(2H)-one		
	2634-33-5 220-120-9 613-088-00-6 -	Acute Tox. 4; H302 Skin Irrit. 2; H315 Skin Sens. 1A; H317 Eye Dam. 1; H318 Acute Tox. 2; H330 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	< 0,10 wt%
3	formaldehyde		
	50-00-0 200-001-8 605-001-00-5 01-2119488953-20	Acute Tox. 3; H301 Acute Tox. 3; H311 Acute Tox. 3; H331 Carc. 1B; H350 Muta. 2; H341 Skin Corr. 1B; H314 Skin Sens. 1; H317	< 0,10 wt%
4	pyridine-2-thiol 1-oxide, sodium salt		

Trade name: einza LawiPur 2-K-PU Mattsiegel, Stammlack

Product no.: 0079347

Current version: 1.0.1, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

	3811-73-2 223-296-5 613-344-00-7 -	EUH070 Acute Tox. 4; H302 Acute Tox. 3; H311 Acute Tox. 3; H331 Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Irrit. 2; H319 STOT RE 1; H372 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	< 0,10	wt%
5	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1)			
	55965-84-9 - 613-167-00-5 -	Acute Tox. 2; H310 Acute Tox. 2; H330 Acute Tox. 3; H301 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 Eye Dam. 1; H318 Skin Corr. 1C; H314 Skin Sens. 1A; H317	< 0,0015	wt%

Full text of H- and EUH-phrases, if not already mentioned in section 2.2: see section 16.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	B	STOT SE 3; H335: C >= 5%	-	-
2	-	Skin Sens. 1A; H317: C >= 0,036%	M = 1	M = 1
3	-	Skin Sens. 1; H317: C >= 0,2% Eye Irrit. 2; H319: C >= 5% STOT SE 3; H335: C >= 5% Skin Irrit. 2; H315: C >= 5% Skin Corr. 1B; H314: C >= 25%	-	-
4	-	-	M = 100	-
5	B	Skin Sens. 1A; H317: C >= 0,0015% Eye Irrit. 2; H319: C >= 0,06% Skin Irrit. 2; H315: C >= 0,06% Skin Corr. 1C; H314: C >= 0,6% Eye Dam. 1; H318: C >= 0,6%	M = 100	M = 100

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

No	Route, target organ, concrete effect
4	H372 -; nervous system; -

Acute toxicity estimate (ATE) values			
No	oral	dermal	inhalative
1	350 mg/kg bodyweight		
2	450 mg/kg bodyweight		
4	500 mg/kg bodyweight	790 mg/kg bodyweight	

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Trade name: einza LawiPur 2-K-PU Mattsiegel, Stammlack

Product no.: 0079347

Current version: 1.0.1, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO₂, powders, water spray

Unsuitable extinguishing media

water jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Do not allow to enter drains/watercourses/soil.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flattening] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

General protective and hygiene measures

Trade name: einza LawiPur 2-K-PU Mattsiegel, Stammlack

Product no.: 0079347

Current version: 1.0.1, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

No special measures necessary.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Comply with legal health and safety regulations; Storage in accordance with the Ordinance on Industrial Safety and Health. Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep from freezing.

Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Stoarge Class according TRGS 510

12 Non-combustible liquids that cannot be assigned to any of the above LGKs.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	formaldehyde	50-00-0	200-001-8
	TRGS 900		
	Formaldehyd		
	WEL long-term (8-hr TWA reference period)	0,37	mg/m ³ 0,3 ml/m ³
	Ceiling Limit	2 (I)	
	Skin resorption / sensibilisation	Sh	
	Notes	Y, X	
	2004/37/EC		
	Formaldehyde		
	WEL short-term (15 min reference period)	0,74	mg/m ³ 0,6 ppm
	WEL long-term (8-hr TWA reference period)	0,37	mg/m ³ 0,3 ppm
	Skin resorption / sensibilisation		dermal sensitisation (14)
2	pyridine-2-thiol 1-oxide, sodium salt	3811-73-2	223-296-5
	TRGS 900		
	Pyridin-2-thiol-1-oxid, Natriumsalz		
	einatembare Fraktion		
	WEL long-term (8-hr TWA reference period)	0,2 E	mg/m ³
	Ceiling Limit	2(II)	
	Skin resorption / sensibilisation	H	
	Notes	Y	

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name	CAS / EC no		
	Route of exposure	Exposure time	Effect	Value
1	ammonia	1336-21-6 215-647-6		
	dermal	Short term (acut)	systemic	6,8 mg/kg/day
	with reference to: CAS 7664-41-7			
	dermal	Long term (chronic)	systemic	6,8 mg/kg/day

EU safety data sheet



Trade name: einza LawiPur 2-K-PU Mattsiegel, Stammlack

Product no.: 0079347

Current version: 1.0.1, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

	with reference to: CAS 7664-41-7			
	inhalative	Short term (acut)	systemic	47,6 mg/m ³
	with reference to: CAS 7664-41-7			
	inhalative	Short term (acut)	local	36 mg/m ³
	with reference to: CAS 7664-41-7			
	inhalative	Long term (chronic)	systemic	47,6 mg/m ³
	with reference to: CAS 7664-41-7			
	inhalative	Long term (chronic)	local	14 mg/m ³
	with reference to: CAS 7664-41-7			
2	formaldehyde			50-00-0 200-001-8
	dermal	Long term (chronic)	systemic	240 mg/kg bw/day
	dermal	Long term (chronic)	local	37 µg/cm ²
	inhalative	Long term (chronic)	systemic	9 mg/m ³
	inhalative	Long term (chronic)	local	0,375 mg/m ³

DNEL value (consumer)

No	Substance name			CAS / EC no
	Route of exposure	Exposure time	Effect	Value
1	ammonia			1336-21-6 215-647-6
	oral	Short term (acut)	systemic	6,8 mg/kg/day
	with reference to: CAS 7664-41-7			
	oral	Long term (chronic)	systemic	6,8 mg/kg/day
	with reference to: CAS 7664-41-7			
	dermal	Short term (acut)	systemic	6,8 mg/kg/day
	with reference to: CAS 7664-41-7			
	dermal	Long term (chronic)	systemic	6,8 mg/kg/day
	with reference to: CAS 7664-41-7			
	inhalative	Short term (acut)	systemic	23,8 mg/m ³
	with reference to: CAS 7664-41-7			
	inhalative	Short term (acut)	local	7,2 mg/m ³
	with reference to: CAS 7664-41-7			
	inhalative	Long term (chronic)	systemic	23,8 mg/m ³
	with reference to: CAS 7664-41-7			
	inhalative	Long term (chronic)	local	2,8 mg/m ³
	with reference to: CAS 7664-41-7			
2	formaldehyde			50-00-0 200-001-8
	oral	Long term (chronic)	systemic	4,1 mg/kg bw/day
	dermal	Long term (chronic)	systemic	102 mg/kg bw/day
	dermal	Long term (chronic)	local	12 µg/cm ²
	inhalative	Long term (chronic)	systemic	3,2 mg/m ³
	inhalative	Long term (chronic)	local	0,1 mg/m ³

PNEC values

No	Substance name		CAS / EC no
	ecological compartment	Type	Value
1	ammonia		1336-21-6 215-647-6
	water	fresh water	0,001 mg/L
	with reference to: CAS: 7664-41-7		
	water	marine water	0,001 mg/L
	with reference to: CAS: 7664-41-7		
	water	Aqua intermittent	0,0068 mg/L
	with reference to: CAS: 7664-41-7		
	soil	-	0,022 mg/kg dry weight

8.2 Exposure controls

Appropriate engineering controls

Trade name: einza LawiPur 2-K-PU Mattsiegel, Stammlack

Product no.: 0079347

Current version: 1.0.1, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

Eye / face protection

Wear safety goggles to protect against splashes. Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material	In case of short-term contact / splash protection: nitrile rubber		
Material thickness	>	0,4	mm
Breakthrough time	>	120	min
Appropriate Material	In case of prolonged exposure: nitrile rubber		
Material thickness	>	0,4	mm
Breakthrough time	>	480	min

Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation	
liquid	
Form	
liquid	
Colour	
according to product name	
Odour	
characteristic	
pH value	
Value	7,5 - 8,5
Boiling point / boiling range	
Value	appr. 100 °C
Melting point/freezing point	
No data available	
Decomposition temperature	
No data available	
Flash point	
Not applicable	
Ignition temperature	

Trade name: einza LawiPur 2-K-PU Mattsiegel, Stammlack

Product no.: 0079347

Current version: 1.0.1, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

No data available

Oxidising properties

Not applicable

Flammability

Not applicable

Lower explosion limit

No data available

Upper explosion limit

No data available

Vapour pressure

Value	<	100	hPa
Reference temperature		50	°C

Relative vapour density

No data available

Relative density

No data available

Density

Value	1,05	-	1,07	g/cm ³
Reference temperature			20	°C
Method	DIN 51757			

Solubility in water

Comments miscible

Solubility

No data available

Partition coefficient n-octanol/water (log value)

No	Substance name	CAS no.	EC no.
1	formaldehyde	50-00-0	200-001-8
	log Pow		0,35
	Reference temperature		25 °C
	Method	QSAR	
	Source	ECHA	

Kinematic viscosity

Value	350	-	400	mPa*s
Reference temperature			20	
Method	DIN 53019			

Solvent separation test

Not applicable

Particle characteristics

No data available

9.2 Other information**Other information**

No data available.

SECTION 10: Stability and reactivity**10.1 Reactivity**

Stable under recommended storage and handling conditions (See section 7).

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Trade name: einza LawiPur 2-K-PU Mattsiegel, Stammlack

Product no.: 0079347

Current version: 1.0.1, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	ammonia	1336-21-6	215-647-6
LD50		350	mg/kg bodyweight
Species with reference to	rat		
Method	CAS 7664-41-7		
Source	OECD 401		
	ECHA		
2	1,2-benzisothiazol-3(2H)-one	2634-33-5	220-120-9
ATE		450	mg/kg bodyweight
Source	1272/2008/EC, Annex VI		
3	pyridine-2-thiol 1-oxide, sodium salt	3811-73-2	223-296-5
ATE		500	mg/kg bodyweight
Species	rat		
Source	1272/2008/EC, Annex VI		

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	pyridine-2-thiol 1-oxide, sodium salt	3811-73-2	223-296-5
ATE		790	mg/kg bodyweight
Species	rat		
Source	1272/2008/EC, Annex VI		

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	1,2-benzisothiazol-3(2H)-one	2634-33-5	220-120-9
ATE		0,21	mg/l
State of aggregation	Dust/mist		
Source	1272/2008/EC, Annex VI		
2	pyridine-2-thiol 1-oxide, sodium salt	3811-73-2	223-296-5
ATE		0,5	mg/l
State of aggregation	Dust/mist		
Species	rat		
Source	1272/2008/EC, Annex VI		

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	ammonia	1336-21-6	215-647-6
Duration of exposure		4	h
Species with reference to	rabbit		
Method	CAS 7664-41-7		
Source	OECD 404		
Evaluation	ECHA		
	corrosive		
2	formaldehyde	50-00-0	200-001-8
Species	rabbit		
Method	OECD 404		
Source	ECHA		

Trade name: einza LawiPur 2-K-PU Mattsiegel, Stammlack

Product no.: 0079347

Current version: 1.0.1, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

Evaluation	corrosive
Evaluation/classification	Based on available data, the classification criteria are met.

Serious eye damage/irritation
No data available

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	formaldehyde	50-00-0	200-001-8
Route of exposure		Skin	
Species		guinea pig	
Method		OECD 406	
Source		ECHA	
Evaluation		sensitizing	
Evaluation/classification		Based on available data, the classification criteria are met.	

Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	ammonia	1336-21-6	215-647-6
Duration of exposure		48 h	
Type of examination		Bacterial Reverse Mutation Test	
Species		Salmonella typhimurium TA98, TA100, TA1535, TA1537	
with reference to		CAS 7664-41-7	
Method		OECD 471	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
2	formaldehyde	50-00-0	200-001-8
Type of examination		in vitro gene mutation study in bacteria	
Species		Salmonella typhimurium	
Method		OECD 471	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are met.	

Reproduction toxicity
No data available

Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	formaldehyde	50-00-0	200-001-8
Route of exposure		inhalational	
Species		Human	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are met.	

STOT - single exposure
No data available

STOT - repeated exposure
No data available

Aspiration hazard
No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure
Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

11.2 Information on other hazards

Trade name: einza LawiPur 2-K-PU Mattsiegel, Stammlack

Product no.: 0079347

Current version: 1.0.1, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER**Endocrine disrupting properties**

No data available

Other information

No data available.

SECTION 12: Ecological information**12.1 Toxicity**

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	ammonia	1336-21-6	215-647-6
LC50		0,083	mg/l
Duration of exposure		96	h
Species	Oncorhynchus gorbuscha		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are met.		
2	formaldehyde	50-00-0	200-001-8
LC50		24,1	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	OECD 203		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Toxicity to fish (chronic)			
No data available			
Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	ammonia	1336-21-6	215-647-6
EC50		101	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	ASTM Standard E 729-80		
Source	ECHA		
2	formaldehyde	50-00-0	200-001-8
EC50		5,8	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Toxicity to Daphnia (chronic)			
No	Substance name	CAS no.	EC no.
1	ammonia	1336-21-6	215-647-6
NOEC		0,79	mg/l
Duration of exposure		21	day(s)
Species	Daphnia magna		
Method	EPA OPPTS 850.1300		
Source	ECHA		
Toxicity to algae (acute)			
No	Substance name	CAS no.	EC no.
1	formaldehyde	50-00-0	200-001-8
EC50		3,48	mg/l
Duration of exposure		72	h
Species	Desmodesmus subspicatus		
Method	OECD 201		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Trade name: einza LawiPur 2-K-PU Mattsiegel, Stammlack

Product no.: 0079347

Current version: 1.0.1, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

Toxicity to algae (chronic)
No data available

Bacteria toxicity
No data available

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	formaldehyde	50-00-0	200-001-8
Type	aerobic biodegradation		
Value		99	%
Duration		28	d
Method	OECD 301 A		
Source	ECHA		
Evaluation	readily biodegradable		

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	formaldehyde	50-00-0	200-001-8
log Pow		0,35	
Reference temperature		25	°C
Method	QSAR		
Source	ECHA		

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information
Do not allow to enter drains or water courses.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste code 08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company.

Allow paint/varnish to dry out completely in a well-ventilated area and dispose of in residual waste once completely solidified. Dispose of liquid or non-drying residues separately.

Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

SECTION 14: Transport information

14.1 UN number or ID number

Trade name: einzA LawiPur 2-K-PU Mattsiegel, Stammlack

Product no.: 0079347

Current version: 1.0.1, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

Not classified as dangerous in the meaning of transport regulations.

14.2 UN proper shipping name

Not classified as dangerous in the meaning of transport regulations.

14.3 Transport hazard class(es)

Not classified as dangerous in the meaning of transport regulations.

14.4 Packing group

Not classified as dangerous in the meaning of transport regulations.

14.5 Environmental hazards

Not classified as dangerous in the meaning of transport regulations.

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations****Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	1,2-benzisothiazol-3(2H)-one	2634-33-5	220-120-9	75
2	ammonia	1336-21-6	215-647-6	75
3	formaldehyde	50-00-0	200-001-8	75
4	octamethylcyclotetrasiloxane	556-67-2	209-136-7	75
5	pyridine-2-thiol 1-oxide, sodium salt	3811-73-2	223-296-5	75
6	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1)	55965-84-9	-	75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is not subject to Part 1 or 2 of Annex I.

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing productsrelevant VOC limit value as referred to in Annex II of Directive 2004/42/CE , Cat. : j, type: wb = 140 g/l
Max. VOC content (limit value) of the product in its ready for use condition = < 140 g/l**National regulations****Water Hazard Class (Germany)**

Class

2

Trade name: einza LawiPur 2-K-PU Mattsiegel, Stammlack

Product no.: 0079347

Current version: 1.0.1, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

Source

Classification according to AwSV (Regulation on facilities for handling substances that are hazardous to water).

Other regulations

GISCODE BSW20 Covering agents, solvent based

Other national regulations

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment. For example, TRGS (Technical Rules for Hazardous Substances) and the DGUV (German Social Accident Insurance) rules.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

EUH070	Toxic by eye contact.
EUH071	Corrosive to the respiratory tract.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

B	Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.
---	---

Creation of the safety data sheet

Trade name: einza LawiPur 2-K-PU Mattsiegel, Stammlack

Product no.: 0079347

Current version: 1.0.1, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

UMCO GmbH
Georg-Wilhelm-Str. 187, D-21107 Hamburg
Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.
The safety data sheet describes products with a view to safety requirements.
It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

This document is an English translation of the legally compliant safety data sheet of the region Germany. This document, including UFI and emergency telephone number, may only be used for placing on the market in the region Germany.

Copyright-protected document. Any changes or reproductions require the express consent of UMCO GmbH.

Prod-ID 773833