

Trade name: einZA LawiPur Versiegelung, farblos Stammlack

Product no.: 0070994

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

einZA LawiPur Versiegelung, farblos Stammlack

UFI:

XFTF-C1FG-D00Y-DPD1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

decorative paints/finishes

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

einZA Farben GmbH & Co KG

Junkersstraße 13

30179 Hannover

Telephone no. +49 (0)511 67490-0

Fax no. +49 (0)511 67490-20

e-mail info@einZA.com

Information provided by / telephone

In emergencies, the country-specific emergency number can be found in the corresponding country-specific safety data sheets.

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

+49 (0)40 0511 - 674 90-0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Skin Sens. 1; H317

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS07

Signal word

Warning

Hazardous component(s) to be indicated on label:

1,2-benzisothiazol-3(2H)-one

Trade name: einza LawiPur Versiegelung, farblos Stammlack

Product no.: 0070994

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

Hazard statement(s)

H317 May cause an allergic skin reaction.

Hazard statements (EU)

EUH208 Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H - isothiazol-3-one (3:1). May produce an allergic reaction.

Precautionary statement(s)

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P280 Wear protective gloves/eye protection.
 P501 Dispose of contents/container to a facility in accordance with local and national regulations.

UFI:

XFTF-C1FG-D00Y-DPD1

2.3 Other hazards

The product does not contain any components > 0.1% that meet the criteria for PBT and vPvB according to Regulation (EC) No. 1907/2006, Annex XIII, or that have been included in the list compiled in accordance with Article 59(1). This product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Hazardous ingredients

| No | Substance name | Additional information | |
|----|---|--|---------------|
| | CAS / EC / Index / REACH no | Classification (EC) 1272/2008 (CLP) | Concentration |
| | | | % |
| 1 | 2-dimethylaminoethanol | | |
| | 108-01-0 203-542-8 603-047-00-0 01-2119492298-24 | Acute Tox. 4; H302 Acute Tox. 4; H312 Acute Tox. 3; H331 Flam. Liq. 3; H226 Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT SE 3; H335 | < 0,50 wt% |
| 2 | 1,2-benzisothiazol-3(2H)-one | | |
| | 2634-33-5 220-120-9 613-088-00-6 - | Acute Tox. 4; H302 Skin Irrit. 2; H315 Skin Sens. 1A; H317 Eye Dam. 1; H318 Acute Tox. 2; H330 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 | < 0,10 wt% |
| 3 | pyridine-2-thiol 1-oxide, sodium salt | | |
| | 3811-73-2 223-296-5 613-344-00-7 - | EUH070 Acute Tox. 4; H302 Acute Tox. 3; H311 Acute Tox. 3; H331 Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Irrit. 2; H319 STOT RE 1; H372 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 | < 0,10 wt% |
| 4 | reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1) | | |

Trade name: einza LawiPur Versiegelung, farblos Stammlack

Product no.: 0070994

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

| | | | |
|--------------|-------------------------|----------|-----|
| 55965-84-9 | Acute Tox. 2; H310 | < 0,0015 | wt% |
| - | Acute Tox. 2; H330 | | |
| 613-167-00-5 | Acute Tox. 3; H301 | | |
| - | Aquatic Acute 1; H400 | | |
| | Aquatic Chronic 1; H410 | | |
| | EUH071 | | |
| | Eye Dam. 1; H318 | | |
| | Skin Corr. 1C; H314 | | |
| | Skin Sens. 1A; H317 | | |

Full text of H- and EUH-phrases, if not already mentioned in section 2.2: see section 16.

| No | Note | Specific concentration limits | M-factor (acute) | M-factor (chronic) |
|----|------|---|------------------|--------------------|
| 1 | - | STOT SE 3; H335: C \geq 5% | - | - |
| 2 | - | Skin Sens. 1A; H317: C \geq 0,036% | M = 1 | M = 1 |
| 3 | - | - | M = 100 | - |
| 4 | B | Skin Sens. 1A; H317: C \geq 0,0015% Eye Irrit. 2; H319: C \geq 0,06% Skin Irrit. 2; H315: C \geq 0,06% Skin Corr. 1C; H314: C \geq 0,6% Eye Dam. 1; H318: C \geq 0,6% | M = 100 | M = 100 |

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

| No | Route, target organ, concrete effect |
|----|--------------------------------------|
| 3 | H372 -; nervous system; - |

| Acute toxicity estimate (ATE) values | | | |
|--------------------------------------|-------------------------|-----------------------|------------|
| No | oral | dermal | inhalative |
| 1 | 1182,7 mg/kg bodyweight | 1219 mg/kg bodyweight | |

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Trade name: einza LawiPur Versiegelung, farblos Stammlack

Product no.: 0070994

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

Alcohol resistant foam, CO₂, powders, water spray

Unsuitable extinguishing media
water jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Do not allow to enter drains/watercourses/soil.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flattening] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

No special measures necessary.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Comply with legal health and safety regulations; Storage in accordance with the Ordinance on Industrial Safety and Health. Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep from freezing.

Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Storage Class according TRGS 510

12 Non-combustible liquids that cannot be assigned to any of the above LGKs.

7.3 Specific end use(s)

Trade name: einza LawiPur Versiegelung, farblos Stammlack

Product no.: 0070994

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

DNEL, DMEL and PNEC values

DNEL values (worker)

| No | Substance name | | | CAS / EC no | |
|----|------------------------|---------------------|----------|-----------------------|-------------------|
| | Route of exposure | Exposure time | Effect | Value | |
| 1 | 2-dimethylaminoethanol | | | 108-01-0 203-542-8 | |
| | dermal | Long term (chronic) | systemic | 0,25 | mg/kg bw/day |
| | inhalative | Long term (chronic) | systemic | 1,76 | mg/m ³ |
| | inhalative | Long term (chronic) | local | 1,76 | mg/m ³ |

PNEC values

| No | Substance name | | CAS / EC no | |
|----|------------------------|-----------------------|-----------------------|------------------|
| | ecological compartment | Type | Value | |
| 1 | 2-dimethylaminoethanol | | 108-01-0 203-542-8 | |
| | water | fresh water | 0,066 | mg/L |
| | water | marine water | 10 | mg/L |
| | water | fresh water sediment | 0,246 | mg/kg dry weight |
| | water | marine water sediment | 0,015 | mg/kg dry weight |
| | soil | - | 0,01 | mg/kg dry weight |

8.2 Exposure controls

Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

Eye / face protection

Wear safety goggles to protect against splashes. Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

| | | | |
|----------------------|---|-----|-----|
| Appropriate Material | In case of short-term contact / splash protection: nitrile rubber | | |
| Material thickness | > | 0,4 | mm |
| Breakthrough time | > | 120 | min |
| Appropriate Material | In case of prolonged exposure: nitrile rubber | | |
| Material thickness | > | 0,4 | mm |
| Breakthrough time | > | 480 | min |

Other

Trade name: einza LawiPur Versiegelung, farblos Stammlack

Product no.: 0070994

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

| | | | |
|--------------------------------------|-----------|------|-------------------|
| State of aggregation | | | |
| liquid | | | |
| Form | | | |
| liquid | | | |
| Colour | | | |
| according to product name | | | |
| Odour | | | |
| characteristic | | | |
| pH value | | | |
| Value | 7,8 | - | 8,5 |
| Boiling point / boiling range | | | |
| Value | appr. | 100 | °C |
| Melting point/freezing point | | | |
| No data available | | | |
| Decomposition temperature | | | |
| No data available | | | |
| Flash point | | | |
| Not applicable | | | |
| Ignition temperature | | | |
| No data available | | | |
| Oxidising properties | | | |
| Not applicable | | | |
| Flammability | | | |
| Not applicable | | | |
| Lower explosion limit | | | |
| No data available | | | |
| Upper explosion limit | | | |
| No data available | | | |
| Vapour pressure | | | |
| Value | < | 100 | hPa |
| Reference temperature | | 50 | °C |
| Relative vapour density | | | |
| No data available | | | |
| Relative density | | | |
| No data available | | | |
| Density | | | |
| Value | appr. | 1,03 | g/cm ³ |
| Reference temperature | | 20 | °C |
| Method | DIN 51757 | | |
| Solubility in water | | | |
| Comments | miscible | | |

Trade name: einza LawiPur Versiegelung, farblos Stammlack

Product no.: 0070994

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

| Solubility | |
|-------------------|--|
| No data available | |

| Partition coefficient n-octanol/water (log value) | |
|---|--|
| No data available | |

| Kinematic viscosity | | | |
|-----------------------|-----------|---|-----------|
| Value | 1500 | - | 1700 Pa*s |
| Reference temperature | | | 20 °C |
| Method | DIN 53019 | | |

| Solvent separation test | |
|-------------------------|--|
| Not applicable | |

| Particle characteristics | |
|--------------------------|--|
| No data available | |

9.2 Other information

| Other information | |
|--------------------|--|
| No data available. | |

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage and handling conditions (See section 7).

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

| Acute oral toxicity | | | |
|---------------------|------------------------|----------|------------------|
| No | Substance name | CAS no. | EC no. |
| 1 | 2-dimethylaminoethanol | 108-01-0 | 203-542-8 |
| LD50 | | 1182,7 | mg/kg bodyweight |
| Species | rat | | |
| Method | OECD 401 | | |

| Acute dermal toxicity | | | |
|-----------------------|------------------------|----------|------------------|
| No | Substance name | CAS no. | EC no. |
| 1 | 2-dimethylaminoethanol | 108-01-0 | 203-542-8 |
| LD50 | | 1219 | mg/kg bodyweight |
| Species | rabbit | | |
| Method | OECD 402 | | |

| Acute inhalational toxicity (result of the ATE calculation for the mixture) | |
|---|--|
| Product Name | |
| einza LawiPur Versiegelung, farblos Stammlack | |

Trade name: einza LawiPur Versiegelung, farblos Stammlack

Product no.: 0070994

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

| | |
|----------|--|
| Comments | The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE for inhalation: > 20.000 ppmV (gases), > 20 mg/l (vapours), > 5 mg/l (dusts/mists)). |
|----------|--|

| Acute inhalational toxicity | | | |
|-----------------------------|------------------------|----------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | 2-dimethylaminoethanol | 108-01-0 | 203-542-8 |
| LC50 | | 6,1 | mg/l |
| Duration of exposure | | 4 | h |
| State of aggregation | Vapour | | |
| Species | rat | | |
| Method | OECD 403 | | |

| Skin corrosion/irritation | | | |
|---------------------------|------------------------|----------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | 2-dimethylaminoethanol | 108-01-0 | 203-542-8 |
| Duration of exposure | | 24 | h |
| Species | rabbit | | |
| Method | OECD 404 | | |
| Evaluation | corrosive | | |

| Serious eye damage/irritation | | | |
|-------------------------------|------------------------|----------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | 2-dimethylaminoethanol | 108-01-0 | 203-542-8 |
| Species | rabbit | | |
| Method | OECD 405 | | |
| Evaluation | corrosive | | |

| Respiratory or skin sensitisation | | | |
|-----------------------------------|------------------------|----------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | 2-dimethylaminoethanol | 108-01-0 | 203-542-8 |
| Route of exposure | Skin | | |
| Species | guinea pig | | |
| Method | OECD 406 | | |
| Evaluation | non-sensitizing | | |

| Germ cell mutagenicity | | | |
|---------------------------|---|----------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | 2-dimethylaminoethanol | 108-01-0 | 203-542-8 |
| Evaluation/classification | Based on available data, the classification criteria are not met. | | |

| Reproduction toxicity | | | |
|---------------------------|---|----------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | 2-dimethylaminoethanol | 108-01-0 | 203-542-8 |
| Evaluation/classification | Based on available data, the classification criteria are not met. | | |

| Carcinogenicity | | | |
|---------------------------|---|----------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | 2-dimethylaminoethanol | 108-01-0 | 203-542-8 |
| Evaluation/classification | Based on available data, the classification criteria are not met. | | |

| STOT - single exposure | | | |
|------------------------|--|--|--|
| No data available | | | |

| STOT - repeated exposure | | | |
|--------------------------|--|--|--|
| No data available | | | |

| Aspiration hazard | | | |
|-------------------|--|--|--|
| No data available | | | |

| Delayed and immediate effects as well as chronic effects from short and long-term exposure | | | |
|--|--|--|--|
| | | | |

Trade name: einza LawiPur Versiegelung, farblos Stammlack

Product no.: 0070994

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

11.2 Information on other hazards

Endocrine disrupting properties

No data available

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)

| No | Substance name | CAS no. | EC no. |
|----------------------|------------------------|----------|-----------|
| 1 | 2-dimethylaminoethanol | 108-01-0 | 203-542-8 |
| LC50 | | 146,6 | mg/l |
| Duration of exposure | | 96 | h |
| Species | Leuciscus idus | | |
| Method | DIN 38412 | | |

Toxicity to fish (chronic)

No data available

Toxicity to Daphnia (acute)

| No | Substance name | CAS no. | EC no. |
|----------------------|------------------------|----------|-----------|
| 1 | 2-dimethylaminoethanol | 108-01-0 | 203-542-8 |
| EC50 | | 98,4 | mg/l |
| Duration of exposure | | 48 | h |
| Species | Daphnia magna | | |
| Method | EEC 78/831 | | |

Toxicity to Daphnia (chronic)

No data available

Toxicity to algae (acute)

| No | Substance name | CAS no. | EC no. |
|----------------------|-------------------------|----------|-----------|
| 1 | 2-dimethylaminoethanol | 108-01-0 | 203-542-8 |
| EC50 | | 66,08 | mg/l |
| Duration of exposure | | 72 | h |
| Species | Desmodesmus subspicatus | | |

Toxicity to algae (chronic)

No data available

Bacteria toxicity

| No | Substance name | CAS no. | EC no. |
|----------------------|------------------------|----------|-----------|
| 1 | 2-dimethylaminoethanol | 108-01-0 | 203-542-8 |
| EC20 | | > | 1000 mg/l |
| Duration of exposure | | 30 | min |
| Species | activated sludge | | |
| Method | OECD 209 | | |

12.2 Persistence and degradability

Biodegradability

| No | Substance name | CAS no. | EC no. |
|----|----------------|---------|--------|
|----|----------------|---------|--------|

Trade name: einza LawiPur Versiegelung, farblos Stammlack

Product no.: 0070994

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

| | | | |
|----------|-------------------------------|-----------------|------------------|
| 1 | 2-dimethylaminoethanol | 108-01-0 | 203-542-8 |
| Type | BOD | | |
| Value | | 60,5 | % |
| Duration | | 14 | d |
| Method | OECD 301 E | | |

12.3 Bioaccumulative potential

| Bioconcentration factor (BCF) | | | |
|-------------------------------|------------------------|---|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | 2-dimethylaminoethanol | 108-01-0 | 203-542-8 |
| Evaluation/classification | | Based on available data, the classification criteria are met. | |

12.4 Mobility in soil

| Mobility in soil | | | |
|---------------------------|------------------------|---|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | 2-dimethylaminoethanol | 108-01-0 | 203-542-8 |
| Evaluation/classification | | Based on available data, the classification criteria are not met. | |

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

| Other information |
|--|
| Do not allow to enter drains or water courses. |

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste code 08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company.

Allow paint/varnish to dry out completely in a well-ventilated area and dispose of in residual waste once completely solidified. Dispose of liquid or non-drying residues separately.

Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

SECTION 14: Transport information

14.1 UN number or ID number

Not classified as dangerous in the meaning of transport regulations.

14.2 UN proper shipping name

Not classified as dangerous in the meaning of transport regulations.

14.3 Transport hazard class(es)

Not classified as dangerous in the meaning of transport regulations.

14.4 Packing group

Not classified as dangerous in the meaning of transport regulations.

Trade name: einza LawiPur Versiegelung, farblos Stammlack

Product no.: 0070994

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER**14.5 Environmental hazards**

Not classified as dangerous in the meaning of transport regulations.

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations****Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

| No | Substance name | CAS no. | EC no. | No |
|----|---------------------------------------|-----------|-----------|--------|
| 1 | 1,2-benzisothiazol-3(2H)-one | 2634-33-5 | 220-120-9 | 75 |
| 2 | 2-(2-butoxyethoxy)ethanol | 112-34-5 | 203-961-6 | 55, 75 |
| 3 | 2-amino-2-methylpropanol | 124-68-5 | 204-709-8 | 75 |
| 4 | 2-dimethylaminoethanol | 108-01-0 | 203-542-8 | 75 |
| 5 | ammonia | 1336-21-6 | 215-647-6 | 75 |
| 6 | pyridine-2-thiol 1-oxide, sodium salt | 3811-73-2 | 223-296-5 | 75 |

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is not subject to Part 1 or 2 of Annex I.

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)

VOC content 0,64 %

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing productsrelevant VOC limit value as referred to in Annex II of Directive 2004/42/CE, Cat. : i, type: wb = 140 g/l
Max. VOC content (limit value) of the product in its ready for use condition = < 140 g/l**National regulations****Water Hazard Class (Germany)**Class
Source

2

Classification according to AwSV (Regulation on facilities for handling substances that are hazardous to water).

Other regulations

GISCODE BSW20 Covering agents, solvent based

Other national regulations

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment. For example, TRGS (Technical Rules for Hazardous Substances) and the DGUV (German Social Accident Insurance) rules.

Trade name: einza LawiPur Versiegelung, farblos Stammlack

Product no.: 0070994

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

| | |
|--------|---|
| EUH070 | Toxic by eye contact. |
| EUH071 | Corrosive to the respiratory tract. |
| H226 | Flammable liquid and vapour. |
| H301 | Toxic if swallowed. |
| H302 | Harmful if swallowed. |
| H310 | Fatal in contact with skin. |
| H311 | Toxic in contact with skin. |
| H312 | Harmful in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H330 | Fatal if inhaled. |
| H331 | Toxic if inhaled. |
| H335 | May cause respiratory irritation. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

| | |
|---|---|
| B | Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis. |
|---|---|

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

EU safety data sheet



Trade name: einZA LawiPur Versiegelung, farblos Stammlack

Product no.: 0070994

Current version: 1.0.0, Revision: 28.01.2026

Replaced version: -, Revision: -

Region:
GER

This document is an English translation of the legally compliant safety data sheet of the region Germany. This document, including UFI and emergency telephone number, may only be used for placing on the market in the region Germany.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.
Prod-ID 653573