

Trade name: einzA Härter Lawinit 2-K-Epoxi-Primer

**Product no.:** 0071542

Current version: 1.0.2, issued: 19.05.2020 Replaced version: 1.0.1, issued: 06.12.2018 Region: GB

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name

## einzA Härter Lawinit 2-K-Epoxi-Primer

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

decorative paints/finishes

#### Uses advised against

No data available.

#### 1.3 Details of the supplier of the safety data sheet

#### Address

einzA Farben GmbH & Co KG

Junkersstraße 13 30179 Hannover

Telephone no. +49 (0)511 67490-0 Fax no. +49 (0)511 67490-20 e-mail info@einzA.com

#### **Advice on Safety Data Sheet**

sdb info@umco.de

### 1.4 Emergency telephone number

For medical advice (in German and English): +49 (0)551 192 40 (Giftinformationszentrum Nord)

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

### Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Eye Irrit. 2; H319 Skin Sens. 1: H317

### Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

### 2.2 Label elements

### Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

### Hazard pictograms



#### Signal word

Warning

### Hazardous component(s) to be indicated on label:

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-

phenyleneoxymethylene)]bis[oxirane] and .alpha.-(oxiranylmethyl)-.omega.-(oxiranylmethoxy)poly[oxy(methyl-1,2-ethanediyl)]

### Hazard statement(s)



Trade name: einzA Härter Lawinit 2-K-Epoxi-Primer

**Product no.:** 0071542

Current version: 1.0.2, issued: 19.05.2020 Replaced version: 1.0.1, issued: 06.12.2018 Region: GB

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Precautionary statement(s)

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves/eye protection.

P501 Dispose of contents/container to a facility in accordance with local and national

regulations.

### 2.3 Other hazards

PBT assessment

The components of this product are not considered to be a PBT.

vPvB assessment

The components of this product are not considered to be a vPvB.

### **SECTION 3: Composition/information on ingredients**

### 3.1 Substances

Not applicable. The product is not a substance.

#### 3.2 Mixtures

### **Hazardous ingredients**

No	Substance name		Addit	ional informati	on	
	CAS / EC / Index /	Classification (EC) 1272/2008 (CLP)	Conc	entration		%
	REACH no					
1		hylethylidene)bis-, polymer with 2,2´-[(1-				
	methylethylidene)k	ois(4,1-phenyleneoxymethylene)]bis[oxirane]				
	and .alpha(oxiran	ylmethyl)omega				
	(oxiranylmethoxy)	poly[oxy(methyl-1,2-ethanediyl)]				
	69761-19-9	Eye Irrit. 2; H319	>=	25.00 - <	50.00	%-b.w.
	-	Skin Sens. 1; H317				
	-					
	-					

Full Text for all H-phrases and EUH-phrases: pls. see section 16

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

### **General information**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

#### After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

#### After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

#### After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

### After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

No data available.

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available.



Trade name: einzA Härter Lawinit 2-K-Epoxi-Primer

**Product no.:** 0071542

Current version: 1.0.2, issued: 19.05.2020 Replaced version: 1.0.1, issued: 06.12.2018 Region: GB

### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

#### Suitable extinguishing media

Alcohol resistant foam, CO2, powders, water spray

#### Unsuitable extinguishing media

water jet.

### 5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO2); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

### 5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

### For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

### 6.2 Environmental precautions

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

### 6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

#### 6.4 Reference to other sections

No data available.

### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

### Advice on safe handling

Due to the organic solvents' content of the mixture: Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flatting] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

### General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

### Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

### 7.2 Conditions for safe storage, including any incompatibilities

### Technical measures and storage conditions

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.



Trade name: einzA Härter Lawinit 2-K-Epoxi-Primer

**Product no.:** 0071542

Current version: 1.0.2, issued: 19.05.2020 Replaced version: 1.0.1, issued: 06.12.2018 Region: GB

### Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

#### Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

### 7.3 Specific end use(s)

No data available.

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

No parameters available for monitoring.

#### 8.2 Exposure controls

#### Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

### Personal protective equipment

### Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. Filter A2P2 (DIN EN 14387)

### Eye / face protection

Wear safety googles to protect against splashes. Safety glasses with side protection shield (EN 166)

#### Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material In case of short-term contact / splash protection: nitrile rubber

Material thickness>0.4mmBreakthrough time>120minAppropriate MaterialIn case of prolonged exposure: nitrile rubberMaterial thickness>0.4mmBreakthrough time>480min

#### Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

### **Environmental exposure controls**

Do not allow to enter drains or water courses.

### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Form/Colour			
liquid			
according to product name			

O	a	0	u	ļ

characteristic

#### **Odour threshold**

No data available



Trade name: einzA Härter Lawinit 2-K-Epoxi-Primer

**Product no.:** 0071542

Solvent separation test

Not applicable

Current version: 1.0.2, issued: 19.05.2020 Replaced version: 1.0.1, issued: 06.12.2018 Region: GB

pH value				
No data available				
Boiling point / boiling range	T	400	°C	
Value	appr.	100	C	
Melting point / melting range  No data available				
Decomposition point / decomposition range No data available	9			
Flash point				
Not applicable				
Auto-ignition temperature				
No data available				
Oxidising properties				
Not applicable				
Explosive properties				
No data available				
Flammability (solid, gas)				
Not applicable				
Lower flammability or explosive limits  No data available				
Upper flammability or explosive limits				
No data available				
Vapour pressure				
Value Reference temperature	<	100 50	hPa °C	
		50	C	
Vapour density No data available				
Evaporation rate  No data available				
Relative density				
No data available				
Density				
Value	1.11	- 1.12	g/cm³	
Reference temperature Method	DIN 51757	20	°C	
	וטווע טווטן			
Solubility in water Comments	miscible			
	THISCIDIE			
Solubility(ies)  No data available				
Partition coefficient: n-octanol/water				
No data available				
Viscosity				
Value	120	- 140	sec	
Reference temperature Method	DIN EN 2431 (	20 (4 mm)	°C	
Method	ווע בווע בייטן אווטן	<del>, -</del> 111111)		



Trade name: einzA Härter Lawinit 2-K-Epoxi-Primer

**Product no.:** 0071542

Current version: 1.0.2, issued: 19.05.2020 Replaced version: 1.0.1, issued: 06.12.2018 Region: GB

#### 9.2 Other information

#### Other information

No data available.

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

Stable under recommended storage and handling conditions (See section 7).

### 10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

### 10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

#### 10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

#### 10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

#### 10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

### **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

### Acute oral toxicity

No data available

### **Acute dermal toxicity**

No data available

### Acute inhalational toxicity

No data available

#### Skin corrosion/irritation

No data available

### Serious eye damage/irritation

No data available

### Respiratory or skin sensitisation

No data available

### Germ cell mutagenicity

No data available

#### Reproduction toxicity

No data available

### Carcinogenicity

No data available

## STOT - single exposure

No data available

#### STOT - repeated exposure

No data available

### **Aspiration hazard**

No data available

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney,



Trade name: einzA Härter Lawinit 2-K-Epoxi-Primer

**Product no.:** 0071542

Current version: 1.0.2, issued: 19.05.2020 Replaced version: 1.0.1, issued: 06.12.2018 Region: GB

liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. Based on the properties of the epoxy constituent(s) and considering toxicological data on similar mixtures, this mixture may be a skin sensitiser and an irritant. It contains low molecular weight epoxy constituents which are irritating to eyes, mucous membrane and skin. Repeated skin contact may lead to irritation and to sensitisation, possibly with cross-sensitisation to other epoxies. Skin contact with the mixture and exposure to spray mist and vapour should be avoided.

### **SECTION 12: Ecological information**

### 12.1 Toxicity

### Toxicity to fish (acute)

No data available

#### **Toxicity to fish (chronic)**

No data available

### Toxicity to Daphnia (acute)

No data available

### Toxicity to Daphnia (chronic)

No data available

#### Toxicity to algae (acute)

No data available

#### Toxicity to algae (chronic)

No data available

### **Bacteria toxicity**

No data available

### 12.2 Persistence and degradability

No data available.

### 12.3 Bioaccumulative potential

No data available.

#### 12.4 Mobility in soil

No data available.

#### 12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	The components of this product are not considered to be a PBT.
vPvB assessment	The components of this product are not considered to be a vPvB.

#### 12.6 Other adverse effects

No data available.

### 12.7 Other information

Other information	
Do not allow to enter drains or water courses.	

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

### **Product**

Waste code 08 04 09\* waste adhesives and sealants containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company. Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.



Trade name: einzA Härter Lawinit 2-K-Epoxi-Primer

**Product no.:** 0071542

Current version: 1.0.2, issued: 19.05.2020 Replaced version: 1.0.1, issued: 06.12.2018 Region: GB

#### **Packaging**

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

### **SECTION 14: Transport information**

### 14.1 Transport ADR/RID/ADN

The product is not subject to ADR/RID/ADN regulations.

### 14.2 Transport IMDG

The product is not subject to IMDG regulations.

### 14.3 Transport ICAO-TI / IATA

The product is not subject to ICAO-TI / IATA regulations.

#### 14.4 Other information

No data available.

#### 14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

#### 14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant

### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

### Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

#### REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

# Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances requiring authorisation as listed on Annex XVII of the REACH regulation (EC) 1907/2006.

### Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is not subject to Part 1 or 2 of Annex I.

### **National regulations**

### Other national regulations

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

### 15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

### **SECTION 16: Other information**

Sources of key data used to compile the data sheet:



Trade name: einzA Härter Lawinit 2-K-Epoxi-Primer

**Product no.: 0071542** 

Current version: 1.0.2, issued: 19.05.2020 Replaced version: 1.0.1, issued: 06.12.2018 Region: GB

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.

EC Directives 2000/39/EC, 2006/15/EC, 2009/161/EU

National Threshold Limit Values of the corresponding countries as amended in each case. Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

### Department issuing safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 653589