

Product no.: 0066944

Current version: 4.0.0, issued: 17.11.2020 Replaced version: 3.1.0, issued: 03.09.2020 Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

einzA Seidenmatt, RAL 8011 nußbraun einzA Seidenmatt 2010, RAL 8011 nußbraun

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

decorative paints/finishes

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

einzA Farben GmbH & Co KG

Junkersstraße 13 30179 Hannover

Telephone no. +49 (0)511 67490-0 Fax no. +49 (0)511 67490-20 e-mail info@einzA.com

Advice on Safety Data Sheet

sdb info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English): +49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Flam. Liq. 3; H226

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



Signal word

Warning

Hazard statement(s)

H226 Flammable liquid and vapour.

Hazard statements (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains COBALT BIS(2-ETHYLHEXANOATE). May produce an allergic reaction.



Trade name: einzA Seidenmatt, RAL 8011 nußbraun

Product no.: 0066944

Current version: 4.0.0, issued: 17.11.2020 Reglaced version: 3.1.0, issued: 03.09.2020 Region: GB

Precautionary statement(s)

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P370+P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide

to extinguish.

P501 Dispose of contents/container to a facility in accordance with local and national

regulations.

2.3 Other hazards

PBT assessment

The components of this product are not considered to be a PBT.

vPvB assessment

The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Hazardous ingredients

Substance name		Additi	onal infor	mation		
CAS / EC / Index /	Classification (EC) 1272/2008 (CLP)	Conce	entration		%	
REACH no						
	0-C13, n-alkanes, isoalkanes, cyclics, <2%					
aromatics						
-	Asp. Tox. 1; H304	>=	10.00 -	< 25.00	wt%	
918-481-9	EUH066					
-						
01-2119457273-39						
phosphoric acid sa						
-		<	2.50		wt%	
-	Skin Irrit. 2; H315					
-						
-						
strontium bis(2-eth	ylhexanoate)					
2457-02-5	Acute Tox. 4; H302	<	0.50		wt%	
219-536-3						
-						
COBALT BIS(2-ETH	HYLHEXANOATE)					
136-52-7	Aquatic Acute 1; H400	<	0.10		wt%	
205-250-6	Aquatic Chronic 3; H412					
-	Skin Sens. 1A; H317					
01-2119524678-29	Eye Irrit. 2; H319					
	Repr. 1B; H360					
	CAS / EC / Index / REACH no Hydrocarbons, C10 aromatics - 918-481-9 - 01-2119457273-39 phosphoric acid sa strontium bis(2-eth 2457-02-5 219-536-3 - 01-2120783571-49 COBALT BIS(2-ETH 136-52-7 205-250-6 - 01-2119524678-29	CAS / EC / Index / REACH no Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics - Asp. Tox. 1; H304 EUH066 - 01-2119457273-39 phosphoric acid salt (72243/00/2008.0040, Germany) - Eye Irrit. 2; H319 - Skin Irrit. 2; H315 - Skin Irrit. 2; H315 - Skin Irrit. 2; H315 - Cast Acute Tox. 4; H302 2457-02-5 Acute Tox. 4; H302 219-536-3 Skin Irrit. 2; H315 - Eye Dam. 1; H318 01-2120783571-49 Repr. 2; H361d COBALT BIS(2-ETHYLHEXANOATE) 136-52-7 Aquatic Acute 1; H400 - Aquatic Chronic 3; H412 - Skin Sens. 1A; H317 - Sye Irrit. 2; H319	CAS / EC / Index / REACH no Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics - Asp. Tox. 1; H304 EUH066 - 01-2119457273-39 phosphoric acid salt (72243/00/2008.0040, Germany) - Eye Irrit. 2; H319 Skin Irrit. 2; H315 - Strontium bis(2-ethylhexanoate) 2457-02-5 Acute Tox. 4; H302 Skin Irrit. 2; H315 - Eye Dam. 1; H318 01-2120783571-49 Repr. 2; H361d COBALT BIS(2-ETHYLHEXANOATE) 136-52-7 Aquatic Acute 1; H400 Aquatic Chronic 3; H412 Skin Sens. 1A; H317 01-2119524678-29 Repr. 1B; H360	CAS / EC / Index / REACH no REACH no	Cas EC Index REACH no	

Full Text for all H-phrases and EUH-phrases: pls. see section 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact



Trade name: einzA Seidenmatt, RAL 8011 nußbraun

Product no.: 0066944

Current version: 4.0.0, issued: 17.11.2020 Replaced version: 3.1.0, issued: 03.09.2020 Region: GB

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO2, powders, water spray

Unsuitable extinguishing media

water jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO2); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes.



Product no.: 0066944

Current version: 4.0.0, issued: 17.11.2020 Replaced version: 3.1.0, issued: 03.09.2020 Region: GB

Wet [sanding]/[flatting] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	strontium bis(2-ethylhexa	rontium bis(2-ethylhexanoate)			
				219-536-3	
	dermal	Long term (chronic)	systemic	0.41	mg/kg/day
	inhalative	Long term (chronic)	systemic	0.73	mg/m³

DNEL value (consumer)

No	Substance name			CAS / EC no	
	Route of exposure Exposure time		Effect	Value	
1	trontium bis(2-ethylhexanoate)			2457-02-5	
				219-536-3	
	oral	Long term (chronic)	systemic	0.21	mg/kg/day
	dermal	Long term (chronic)	systemic	0.21	mg/kg/day
	inhalative	Long term (chronic)	systemic	0.18	mg/m³

PNEC values

No	Substance name		CAS / EC no	
	ecological compartment	Туре	Value	
1	strontium bis(2-ethylhexanoate)		2457-02-5	
			219-536-3	
	water	fresh water	0.44	mg/L
	water	marine water	0.04	mg/L
	water	fresh water sediment	7.86	mg/kg dry
				weight
	water	marine water sediment	0.79	mg/kg dry
				weight
	soil	-	1.31	mg/kg dry



Product no.: 0066944

Current version: 4.0.0, issued: 17.11.2020 Reglaced version: 3.1.0, issued: 03.09.2020 Region: GB

				weight
sewage tr	eatment plant -	-	88.52	mg/L

8.2 Exposure controls

Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

Eye / face protection

Wear safety googles to protect against splashes. Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific workstation suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material In case of short-term contact / splash protection: nitrile rubber

Material thickness>0.4mmBreakthrough time>120minAppropriate MaterialIn case of prolonged exposure: nitrile rubberMaterial thickness>0.4mmBreakthrough time>480min

Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form/Colour	Form
liquid	liquid
according to product name	acco

Odour	
of solvents	

Odour threshold	
No data available	

pH value	
No data available	

Boiling point / boiling range					
Value	>	120	°C		
Reference substance	solvent mixture				

Melting point / melting range
No data available

Decomposition point / decomposition range	
No data available	



Trade name: einzA Seidenmatt, RAL 8011 nußbraun

Product no.: 0066944

Current version: 4.0.0, issued: 17.11.2020 Replaced version: 3.1.0, issued: 03.09.2020 Region: GB

Flash point			
Value	40 -	45	°C
Method	closed cup		
Ignition townsystems			
Ignition temperature Value	T	200	°C
	>	200	C
Reference substance	solvent mixture		
Auto-ignition temperature			
No data available			
Oxidising properties			
Not applicable			
Explosive properties			
No data available			
Flammability (solid, gas)			
Not applicable			
Lower flammability or explanity limits			
Lower flammability or explosive limits Value	>	0.6	% vol
Reference substance	solvent mixture	0.0	/0 VUI
Veterance annatation	Solvent mixture		
Upper flammability or explosive limits			
Value	<	7.5	% vol
Reference substance	solvent mixture		
	L		
Vapour pressure			
Value	<	100	hPa
Reference temperature		50	°C
Reference substance	solvent mixture		
Vapour density			
No data available			
Evaporation rate			
No data available			
Deletive density			
REISTIVE GENSITY			
Relative density No data available			
No data available			
No data available Density			
No data available Density Value	0.93 -	1.36	g/cm³
No data available Density Value Reference temperature		1.36 20	g/cm³ °C
No data available Density Value	0.93 - DIN 51757		g/cm³ °C
No data available Density Value Reference temperature Method			g/cm³ °C
No data available Density Value Reference temperature Method Solubility in water	DIN 51757		g/cm³ °C
No data available Density Value Reference temperature Method			g/cm³ °C
No data available Density Value Reference temperature Method Solubility in water Comments	DIN 51757		g/cm³ °C
No data available Density Value Reference temperature Method Solubility in water	DIN 51757		g/cm³ °C
No data available Density Value Reference temperature Method Solubility in water Comments Solubility(ies) No data available	DIN 51757		g/cm³ °C
No data available Density Value Reference temperature Method Solubility in water Comments Solubility(ies) No data available Partition coefficient: n-octanol/water	DIN 51757		g/cm³ °C
No data available Density Value Reference temperature Method Solubility in water Comments Solubility(ies) No data available	DIN 51757		g/cm³ °C
No data available Density Value Reference temperature Method Solubility in water Comments Solubility(ies) No data available Partition coefficient: n-octanol/water	DIN 51757		g/cm³ °C
No data available Density Value Reference temperature Method Solubility in water Comments Solubility(ies) No data available Partition coefficient: n-octanol/water No data available Viscosity	DIN 51757	20	g/cm³ °C
No data available Density Value Reference temperature Method Solubility in water Comments Solubility(ies) No data available Partition coefficient: n-octanol/water No data available Viscosity Value	DIN 51757		°C
No data available Density Value Reference temperature Method Solubility in water Comments Solubility(ies) No data available Partition coefficient: n-octanol/water No data available Viscosity	DIN 51757	20 60 20	°C sec
No data available Density Value Reference temperature Method Solubility in water Comments Solubility(ies) No data available Partition coefficient: n-octanol/water No data available Viscosity Value Reference temperature Method	DIN 51757	20 60 20	°C sec
No data available Density Value Reference temperature Method Solubility in water Comments Solubility(ies) No data available Partition coefficient: n-octanol/water No data available Viscosity Value Reference temperature Method Solvent separation test	DIN 51757 immiscible 55 - DIN EN 2431 (6 m	60 20 nm)	°C sec °C
No data available Density Value Reference temperature Method Solubility in water Comments Solubility(ies) No data available Partition coefficient: n-octanol/water No data available Viscosity Value Reference temperature Method	DIN 51757	20 60 20	°C sec

9.2 Other information

Other information



Product no.: 0066944

Current version: 4.0.0, issued: 17.11.2020 Reglaced version: 3.1.0, issued: 03.09.2020 Region: GB

No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage and handling conditions (See section 7).

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acu	Acute oral toxicity				
No	Substance name		CAS no.		EC no.
1	strontium bis(2-ethylhexanoate)		2457-02-5		219-536-3
LD5	LD50			500	mg/kg bodyweight
Species		rat			
Soul	Source				

Acu	Acute dermal toxicity					
No	Substance name		CAS no.		EC no.	
1	strontium bis(2-ethylhexanoate)		2457-02-5		219-536-3	
LD5	0	>		2000	mg/kg bodyweight	
Spe		rat				
Meth	Method					
Soul	rce	ECHA				

Acute inhalational toxicity No data available

Skin corrosion/irritation No data available

Seri	ous eye damage/irritation		
No	Substance name	CAS no.	EC no.
1	strontium bis(2-ethylhexanoate)	2457-02-5	219-536-3
Meth	nod	OECD 437	
Soul	rce	ECHA	
Eval	uation	Irreversible effects on the eye	

Res	Respiratory or skin sensitisation				
No	Substance name	CAS no.	EC no.		
1	strontium bis(2-ethylhexanoate)	2457-02-5	219-536-3		
Rou	ite of exposure	Skin			
Spe	cies	guinea pig			
Met	hod	OECD 406			
Sou	rce	ECHA			
Eva	luation	non-sensitizing			

Germ cell mutagenicity				
No	Substance name	CAS no.	EC no.	



Product no.: 0066944

Current version: 4.0.0, issued: 17.11.2020 Reglaced version: 3.1.0, issued: 03.09.2020 Region: GB

1	strontium bis(2-ethylhexanoate)	2457-02-5	219-536-3	
Metl	nod	OECD 474		
Sou	rce	ECHA		
Eval	uation/classification	Based on available data, the classificatio	n criteria are not met.	

Rep	Reproduction toxicity				
No	Substance name	CAS no.	EC no.		
1	strontium bis(2-ethylhexanoate)	2457-02-5	219-536-3		
Metl	hod	Value taken from the literature			
Sou	rce	ECHA			
Eval	luation/classification	Based on available data, the classification	on criteria are met.		

Carcinogenicity	
No data available	

1	STOT - single exposure
ļ	No data available

STOT - repeated exposure No data available

Aspiration hazard No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

SECTION 12: Ecological information

12.1 Toxicity

Tox	Toxicity to fish (acute)				
No	Substance name	CAS no.		EC no.	
1	strontium bis(2-ethylhexanoate)	2457-02-5		219-536-3	
LC5	0	>	100	mg/l	
Dura	ation of exposure		96	h	
Spe	cies	Oryzias latipes			
Met	hod	OECD 203			
Sou	rce	ECHA			

Toxicity to fish (chronic) No data available

Toxicity to Daphnia (acute) No data available

	exicity to Daphnia (chronic)					
No	Substance name	CAS no.		EC no.		
1	strontium bis(2-ethylhexanoate)	2457-02-5		219-536-3		
NOE	EC		25	mg/l		
Dura	ation of exposure		21	day(s)		
Spe	cies	Daphnia magna				
Metl	hod	OECD 211				
Sou	rce	ECHA				

Toxicity to algae (acute)			
No Substance name	CAS no.	EC no.	



Trade name: einzA Seidenmatt, RAL 8011 nußbraun

Product no.: 0066944

Current version: 4.0.0, issued: 17.11.2020 Reglaced version: 3.1.0, issued: 03.09.2020 Region: GB

1	strontium bis(2-ethylhexanoate)	2457-02-	-5	219-536-3	
ErC!	50	>	47.1	mg/l	
Dura	ation of exposure		72	h	
Spec	cies	Pseudokirchneriella su	bcapitata		
Meth	nod	OECD 201			
Soul	rce	ECHA			

Toxicity to algae (chronic)

No data available

Bacteria toxicity

No data available

12.2 Persistence and degradability

Biod	Biodegradability			
No	Substance name	CAS no.		EC no.
1	strontium bis(2-ethylhexanoate)	2457-02-5		219-536-3
Туре	e	aerobic biodegradation		
Valu	e	9	99	%
Dura	ation	2	28	day(s)
Method		OECD 301 E		
Source		ECHA		
Eval	uation	readily biodegradable		

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	The components of this product are not considered to be a PBT.
vPvB assessment	The components of this product are not considered to be a vPvB.

12.6 Other adverse effects

No data available.

12.7 Other information

Other information	
Do not allow to enter drains or water courses.	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste code 08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company. Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Packaging

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class 3
Classification code F1
Packing group III



Trade name: einzA Seidenmatt, RAL 8011 nußbraun

Product no.: 0066944

Current version: 4.0.0, issued: 17.11.2020 Reglaced version: 3.1.0, issued: 03.09.2020 Region: GB

Hazard identification no. 30
UN number UN1263
Proper shipping name PAINT
Tunnel restriction code D/E

Comments Containers with a capacity <= 450 ltrs are not subject to ADR-regulations (refer to

2.2.3.1.5.)

14.2 Transport IMDG

Class 3
Packing group III
UN number UN1263
Proper shipping name PAINT
EmS F-E+S-E

Label 3

Comments Containers with a capacity <= 450 ltrs are not subjected to IMDG regulations,

chapter 4.1, 5.2 and 6.1 (see IMDG-Code 2.3.2.5)

14.3 Transport ICAO-TI / IATA

Class 3
Packing group III
UN number UN1263
Proper shipping name Paint
Label 3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances subject to restriction as listed in Annex XVII of the REACH regulation (EC) 1907/2006.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances		
	This product is subject to Part I of Annex I, risk category:	P5c

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)

VOC content

25.94 %

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic



Product no.: 0066944

Current version: 4.0.0, issued: 17.11.2020 Replaced version: 3.1.0, issued: 03.09.2020 Region: GB

solvents in certain paints and varnishes and vehicle refinishing products

relevant VOC limit value as referred to in Annex II of Directive 2004/42/CE, Cat.: d, type: lb = 300 g/l Max. VOC content (limit value) of the product in its ready for use condition = < 300 g/l

National regulations

Other national regulations

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.

H360 May damage fertility or the unborn child H361d Suspected of damaging the unborn child.

H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 653508