

Trade name: einzA Nitroverdünnung

Product no.: 0100242

Current version : 5.0.0, issued: 11.09.2024

Replaced version: 4.0.0, issued: 21.04.2021

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name

einzA Nitroverdünnung**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses of the substance or mixture

Thinner

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

einzA Farben GmbH & Co KG

Junkersstraße 13

30179 Hannover

Telephone no. +49 (0)511 67490-0

Fax no. +49 (0)511 67490-20

e-mail info@einzA.com

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Aquatic Chronic 3; H412

Asp. Tox. 1; H304

Eye Irrit. 2; H319

Flam. Liq. 2; H225

Skin Irrit. 2; H315

STOT SE 3; H336

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)**

Hazard pictograms



GHS02



GHS07



GHS08

Signal word

Danger

Hazardous component(s) to be indicated on label:

ethyl-acetate

acetone

Reaction mass of xylene and ethylbenzene

Hazard statement(s)

H225

Highly flammable liquid and vapour.

H304

May be fatal if swallowed and enters airways.

H315

Causes skin irritation.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.

H412

Harmful to aquatic life with long lasting effects.

Precautionary statement(s)

Trade name: einza Nitroverdünnung

Product no.: 0100242

Current version : 5.0.0, issued: 11.09.2024

Replaced version: 4.0.0, issued: 21.04.2021

Region: GB

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P370+P378	In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.
P405	Store locked up.
P501	Dispose of contents/container to a facility in accordance with local and national regulations.

2.3 Other hazards

PBT assessment

The components of this product are not considered to be a PBT.

vPvB assessment

The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not applicable. The product is not a substance.

3.2 Mixtures**Hazardous ingredients**

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	ethyl-acetate		
	141-78-6 205-500-4 607-022-00-5 01-2119475103-46	EUH066 Eye Irrit. 2; H319 Flam. Liq. 2; H225 STOT SE 3; H336	>= 25.00 - < 50.00 wt%
2	acetone		
	67-64-1 200-662-2 606-001-00-8 01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	>= 25.00 - < 50.00 wt%
3	n-butyl acetate		
	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	EUH066 Flam. Liq. 3; H226 STOT SE 3; H336	>= 10.00 - < 25.00 wt%
4	Reaction mass of xylene and ethylbenzene		
	- 905-588-0 - 01-2119539452-40	Acute Tox. 4; H312 Acute Tox. 4; H332 Asp. Tox. 1; H304 Eye Irrit. 2; H319 Flam. Liq. 3; H226 Skin Irrit. 2; H315 STOT SE 3; H335 STOT RE 2; H373	>= 5.00 - < 10.00 wt%
5	ethanol		
	64-17-5 200-578-6 603-002-00-5 01-2119457610-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 5.00 - < 10.00 wt%
6	Hydrocarbons, C6, isoalkanes, <5% n-hexane		
	64742-49-0 931-254-9 - 01-2119484651-34	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	< 5.00 wt%
7	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics		
	- 927-510-4 - 01-2119475515-33	Aquatic Chronic 2; H411 Asp. Tox. 1; H304 Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336	< 5.00 wt%
8	propan-2-ol		

Trade name: einza Nitroverdünnung

Product no.: 0100242

Current version : 5.0.0, issued: 11.09.2024

Replaced version: 4.0.0, issued: 21.04.2021

Region: GB

	67-63-0 200-661-7 603-117-00-0 01-2119457558-25	Eye Irrit. 2; H319 Flam. Liq. 2; H225 STOT SE 3; H336	< 5.00	wt%
9	toluene			
	108-88-3 203-625-9 601-021-00-3 01-2119471310-51	Asp. Tox. 1; H304 Flam. Liq. 2; H225 Repr. 2; H361d Skin Irrit. 2; H315 STOT RE 2; H373i STOT SE 3; H336	< 2.50	wt%
10	butan-1-ol			
	71-36-3 200-751-6 603-004-00-6 01-2119484630-38	Acute Tox. 4; H302 Eye Dam. 1; H318 Flam. Liq. 3; H226 Skin Irrit. 2; H315 STOT SE 3; H335 STOT SE 3; H336	< 2.50	wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
5	-	Eye Irrit. 2; H319: C >= 50%	-	-

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO₂, powders, water spray

Unsuitable extinguishing media

water jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

Trade name: einza Nitroverdünnung

Product no.: 0100242

Current version : 5.0.0, issued: 11.09.2024

Replaced version: 4.0.0, issued: 21.04.2021

Region: GB

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage**7.1 Precautions for safe handling****Advice on safe handling**

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flattening] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities**Technical measures and storage conditions**

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limit values**

No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
	2017/164/EU		
	Ethyl acetate		
	WEL short-term (15 min reference period)	1468	mg/m ³ 400 ppm
	WEL long-term (8-hr TWA reference period)	734	mg/m ³ 200 ppm
	List of approved workplace exposure limits (WELs) / EH40		
	Ethyl acetate		
	WEL short-term (15 min reference period)		400 ppm
	WEL long-term (8-hr TWA reference period)		200 ppm
2	acetone	67-64-1	200-662-2
	2000/39/EC		
	Acetone		
	WEL long-term (8-hr TWA reference period)	1210	mg/m ³ 500 ppm
	List of approved workplace exposure limits (WELs) / EH40		
	Acetone		
	WEL short-term (15 min reference period)	3620	mg/m ³ 1500 ppm

EU safety data sheet



Trade name: einza Nitroverdünnung

Product no.: 0100242

Current version : 5.0.0, issued: 11.09.2024

Replaced version: 4.0.0, issued: 21.04.2021

Region: GB

	WEL long-term (8-hr TWA reference period)	1210	mg/m ³	500	ppm
3	n-butyl acetate	123-86-4		204-658-1	
	List of approved workplace exposure limits (WELs) / EH40				
	Butyl acetate				
	WEL short-term (15 min reference period)	966	mg/m ³	200	ppm
	WEL long-term (8-hr TWA reference period)	724	mg/m ³	150	ppm
	EU 2019/1831				
	n-Butyl acetate				
	WEL short-term (15 min reference period)	723	mg/m ³	150	ppm
	WEL long-term (8-hr TWA reference period)	241	mg/m ³	50	ppm
4	ethanol	64-17-5		200-578-6	
	List of approved workplace exposure limits (WELs) / EH40				
	Ethanol				
	WEL long-term (8-hr TWA reference period)	1920	mg/m ³	1000	ppm
5	propan-2-ol	67-63-0		200-661-7	
	List of approved workplace exposure limits (WELs) / EH40				
	Propan-2-ol				
	WEL short-term (15 min reference period)	1250	mg/m ³	500	ppm
	WEL long-term (8-hr TWA reference period)	999	mg/m ³	400	ppm
6	toluene	108-88-3		203-625-9	
	2006/15/EC				
	Toluene				
	WEL short-term (15 min reference period)	384	mg/m ³	100	ppm
	WEL long-term (8-hr TWA reference period)	192	mg/m ³	50	ppm
	Skin resorption / sensibilisation	Skin			
	List of approved workplace exposure limits (WELs) / EH40				
	Toluene				
	WEL short-term (15 min reference period)	384	mg/m ³	100	ppm
	WEL long-term (8-hr TWA reference period)	191	mg/m ³	50	ppm
	Comments	Sk			
7	butan-1-ol	71-36-3		200-751-6	
	List of approved workplace exposure limits (WELs) / EH40				
	Butan-1-ol				
	WEL short-term (15 min reference period)	154	mg/m ³	50	ppm
	Comments	Sk			

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	ethyl-acetate			141-78-6	
				205-500-4	
	dermal	Long term (chronic)	systemic	63	mg/kg/day
	inhalative	Long term (chronic)	systemic	734	mg/m ³
	inhalative	Short term (acute)	systemic	1468	mg/m ³
	inhalative	Long term (chronic)	local	734	mg/m ³
	inhalative	Short term (acute)	local	1468	mg/m ³
2	acetone			67-64-1	
				200-662-2	
	dermal	Long term (chronic)	systemic	186	mg/kg/day
	inhalative	Short term (acute)	local	2420	mg/m ³
	inhalative	Short term (acute)	systemic	1210	mg/m ³
3	n-butyl acetate			123-86-4	
				204-658-1	
	dermal	Long term (chronic)	systemic	11	mg/kg/day
	dermal	Short term (acute)	systemic	11	mg/kg/day
	inhalative	Long term (chronic)	systemic	300	mg/m ³
	inhalative	Short term (acute)	systemic	600	mg/m ³
	inhalative	Long term (chronic)	local	300	mg/m ³
	inhalative	Short term (acute)	local	600	mg/m ³
4	Reaction mass of xylene and ethylbenzene			-	
				905-588-0	
	dermal	Long term (chronic)	systemic	212	mg/kg/day
	inhalative	Short term (acute)	systemic	442	mg/m ³
	inhalative	Short term (acute)	local	442	mg/m ³
	inhalative	Long term (chronic)	systemic	221	mg/m ³
	inhalative	Long term (chronic)	local	221	mg/m ³

EU safety data sheet



Trade name: einza Nitroverdünnung

Product no.: 0100242

Current version : 5.0.0, issued: 11.09.2024

Replaced version: 4.0.0, issued: 21.04.2021

Region: GB

5	ethanol			64-17-5 200-578-6
	dermal	Long term (chronic)	systemic	8238 mg/kg/day
	inhalative	Long term (chronic)	systemic	380 mg/m ³
6	Hydrocarbons, C6, isoalkanes, <5% n-hexane			64742-49-0 931-254-9
	dermal	Long term (chronic)	systemic	13964 mg/kg/day
	inhalative	Long term (chronic)	systemic	5306 mg/m ³
7	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics			- 927-510-4
	dermal	Long term (chronic)	systemic	300 mg/kg/day
	inhalative	Long term (chronic)	systemic	2085 mg/m ³
8	propan-2-ol			67-63-0 200-661-7
	dermal	Long term (chronic)	systemic	888 mg/kg/day
	inhalative	Long term (chronic)	systemic	500 mg/m ³
9	toluene			108-88-3 203-625-9
	dermal	Long term (chronic)	systemic	384.00 mg/kg/day
	inhalative	Long term (chronic)	systemic	192.00 mg/m ³
	inhalative	Short term (acute)	systemic	384.00 mg/m ³
	inhalative	Long term (chronic)	local	192.00 mg/m ³
	inhalative	Short term (acute)	local	384.00 mg/m ³
10	butan-1-ol			71-36-3 200-751-6
	inhalative	Long term (chronic)	local	310 mg/m ³

DNEL value (consumer)

No	Substance name			CAS / EC no
	Route of exposure	Exposure time	Effect	Value
1	ethyl-acetate			141-78-6 205-500-4
	oral	Long term (chronic)	systemic	4.5 mg/kg/day
	dermal	Long term (chronic)	systemic	37 mg/kg/day
	inhalative	Long term (chronic)	systemic	367 mg/m ³
	inhalative	Short term (acute)	systemic	734 mg/m ³
	inhalative	Long term (chronic)	local	367 mg/m ³
	inhalative	Short term (acute)	local	734 mg/m ³
2	acetone			67-64-1 200-662-2
	oral	Long term (chronic)	systemic	62 mg/kg/day
	dermal	Long term (chronic)	systemic	62 mg/kg/day
	inhalative	Long term (chronic)	systemic	200 mg/m ³
3	n-butyl acetate			123-86-4 204-658-1
	oral	Long term (chronic)	systemic	2 mg/kg/day
	oral	Short term (acute)	systemic	2 mg/kg/day
	dermal	Long term (chronic)	systemic	6 mg/kg/day
	dermal	Short term (acute)	systemic	6 mg/kg/day
	inhalative	Long term (chronic)	systemic	35.7 mg/m ³
	inhalative	Short term (acute)	systemic	300 mg/m ³
	inhalative	Long term (chronic)	local	35.7 mg/m ³
	inhalative	Short term (acute)	local	300 mg/m ³
4	Reaction mass of xylene and ethylbenzene			- 905-588-0
	oral	Long term (chronic)	systemic	12.5 mg/kg/day
	dermal	Long term (chronic)	systemic	125 mg/kg/day
	inhalative	Short term (acute)	systemic	260 mg/m ³
	inhalative	Long term (chronic)	systemic	65.3 mg/m ³
	inhalative	Short term (acute)	local	260 mg/m ³
	inhalative	Long term (chronic)	local	65.3 mg/m ³
5	ethanol			64-17-5 200-578-6
	inhalative	Long term (chronic)	systemic	114 mg/m ³
6	Hydrocarbons, C6, isoalkanes, <5% n-hexane			64742-49-0 931-254-9
	oral	Long term (chronic)	systemic	1301 mg/kg/day
	dermal	Long term (chronic)	systemic	1377 mg/kg/day
	inhalative	Long term (chronic)	systemic	1131 mg/m ³

EU safety data sheet



Trade name: einza Nitroverdünnung

Product no.: 0100242

Current version : 5.0.0, issued: 11.09.2024

Replaced version: 4.0.0, issued: 21.04.2021

Region: GB

7	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics			-	
	oral	Long term (chronic)	systemic	927-510-4	
	dermal	Long term (chronic)	systemic	149	mg/kg/day
	inhalative	Long term (chronic)	systemic	149	mg/kg/day
	inhalative	Long term (chronic)	systemic	447	mg/m ³
8	propan-2-ol			67-63-0	
	oral	Long term (chronic)	systemic	200-661-7	
	dermal	Long term (chronic)	systemic	26	mg/kg/day
	dermal	Long term (chronic)	systemic	319	mg/kg/day
	inhalative	Long term (chronic)	systemic	89	mg/m ³
9	toluene			108-88-3	
	oral	Long term (chronic)	systemic	203-625-9	
	dermal	Long term (chronic)	systemic	8.13	mg/kg/day
	dermal	Long term (chronic)	systemic	226.00	mg/kg/day
	inhalative	Long term (chronic)	systemic	56.50	mg/m ³
	inhalative	Short term (acute)	systemic	226.00	mg/m ³
	inhalative	Long term (chronic)	local	56.50	mg/m ³
	inhalative	Short term (acute)	local	226.00	mg/m ³
10	butan-1-ol			71-36-3	
	oral	Long term (chronic)	systemic	200-751-6	
	dermal	Long term (chronic)	systemic	1.562	mg/kg/day
	dermal	Long term (chronic)	systemic	3.125	mg/kg/day
	inhalative	Long term (chronic)	systemic	55.357	mg/m ³
	inhalative	Long term (chronic)	local	155	mg/m ³

PNEC values

No	Substance name		CAS / EC no
	ecological compartment	Type	Value
1	ethyl-acetate		141-78-6
			205-500-4
	water	fresh water	0.24 mg/L
	water	marine water	0.024 mg/L
	water	fresh water sediment	1.15 mg/kg dry weight
	water	marine water sediment	0.115 mg/kg dry weight
	soil	-	0.148 mg/kg dry weight
	sewage treatment plant	-	650 mg/L
	secondary poisoning with reference to: food	-	0.2 g/kg
2	acetone		67-64-1
			200-662-2
	water	fresh water	10.6 mg/L
	water	Aqua intermittent	21 mg/L
	water	marine water	1.06 mg/L
	water	fresh water sediment	30.4 mg/kg
	water	marine water sediment	3.04 mg/kg
	soil	-	29.5 mg/kg
	sewage treatment plant	-	100 mg/L
3	n-butyl acetate		123-86-4
			204-658-1
	water	fresh water	0.18 mg/L
	water	marine water	0.018 mg/L
	water	fresh water sediment	0.981 mg/kg dry weight
	water	marine water sediment	0.098 mg/kg dry weight
	soil	-	0.09 mg/kg
	sewage treatment plant	-	35.6 mg/L
4	Reaction mass of xylene and ethylbenzene		-
			905-588-0
	water	fresh water	0.327 mg/L
	water	marine water	0.327 mg/L
	water	Aqua intermittent	0.327 mg/L
	water	fresh water sediment	12.46 mg/kg
	water	marine water sediment	12.46 mg/kg
	soil	-	2.31 mg/kg dry weight
	sewage treatment plant	-	6.58 mg/L
5	ethanol		64-17-5
			200-578-6
	water	fresh water	0.96 mg/L
	water	marine water	0.79 mg/L
	water	fresh water sediment	3.6 mg/kg dry weight

Trade name: einza Nitroverdünnung

Product no.: 0100242

Current version : 5.0.0, issued: 11.09.2024

Replaced version: 4.0.0, issued: 21.04.2021

Region: GB

	water	marine water sediment	2.9	mg/L
	soil	-	0.63	mg/kg dry weight
	sewage treatment plant	-	580	mg/L
	secondary poisoning	-	0.38	g/kg
	with reference to: food			
6	propan-2-ol		67-63-0 200-661-7	
	soil	-	28	mg/kg
	sewage treatment plant	-	2251	mg/L
	secondary poisoning	-	160	mg/kg
	with reference to: food			
7	toluene		108-88-3 203-625-9	
	water	fresh water	0.68	mg/L
	water	marine water	0.68	mg/L
	water	Aqua intermittent	0.68	mg/L
	water	fresh water sediment	16.39	mg/kg
	with reference to: dry weight			
	water	marine water sediment	16.39	mg/kg
	with reference to: dry weight			
	soil	-	2.89	mg/kg
	with reference to: dry weight			
	sewage treatment plant	-	13.61	mg/L
8	butan-1-ol		71-36-3 200-751-6	
	water	fresh water	0.082	mg/L
	water	marine water	0.008	mg/L
	water	Aqua intermittent	2.25	mg/L
	water	fresh water sediment	0.324	mg/kg dry weight
	water	marine water sediment	0.032	mg/kg dry weight
	soil	-	0.017	mg/kg dry weight
	sewage treatment plant	-	2476	mg/L

8.2 Exposure controls

Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

Eye / face protection

Wear safety goggles to protect against splashes. Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material In case of short-term contact / splash protection: nitrile rubber

Material thickness > 0.4 mm

Breakthrough time > 120 min

Appropriate Material In case of prolonged exposure: nitrile rubber

Material thickness > 0.4 mm

Breakthrough time > 480 min

Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

EU safety data sheet



Trade name: einza Nitroverdünnung

Product no.: 0100242

Current version : 5.0.0, issued: 11.09.2024

Replaced version: 4.0.0, issued: 21.04.2021

Region: GB

State of aggregation			
liquid			
Form			
liquid			
Colour			
colourless			
Odour			
characteristic			
pH value			
No data available			
Boiling point / boiling range			
Value	56	- 145	°C
Melting point/freezing point			
No data available			
Decomposition temperature			
No data available			
Flash point			
Value	appr.	-15	°C
Ignition temperature			
No data available			
Auto-ignition temperature			
Value		240	°C
Oxidising properties			
Not applicable			
Flammability			
Not applicable			
Lower explosion limit			
Value		0.7	% vol
Upper explosion limit			
Value		19.2	% vol
Vapour pressure			
No data available			
Relative vapour density			
No data available			
Relative density			
No data available			
Density			
Value	appr.	0.828	g/cm³
Reference temperature		20	°C
Solubility in water			
Comments	partially miscible		
Solubility			
No data available			
Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
log Pow		0.68	
Reference temperature		25	°C
Source	ECHA		
2	acetone	67-64-1	200-662-2
log Pow		-0.23	
Method	QSAR		
Source	ECHA		
3	n-butyl acetate	123-86-4	204-658-1
log Pow		2.3	
Reference temperature		25	°C
Method	OECD 117		
Source	ECHA		

Trade name: einza Nitroverdünnung

Product no.: 0100242

Current version : 5.0.0, issued: 11.09.2024

Replaced version: 4.0.0, issued: 21.04.2021

Region: GB

4	Reaction mass of xylene and ethylbenzene	-	905-588-0
log Pow	appr.	3.49	
Reference temperature		30	°C
with reference to	pH >= 5 - <= 8		
Method	OECD 117		
Source	ECHA		
5	ethanol	64-17-5	200-578-6
log Pow		-0.35	
Reference temperature		24	°C
with reference to	pH 7,4		
Method	OECD 107		
Source	ECHA		
6	propan-2-ol	67-63-0	200-661-7
log Pow		0.05	
Reference temperature		25	°C
Source	ECHA		
7	toluene	108-88-3	203-625-9
log Pow		2.73	
Reference temperature		20	°C
Source	ECHA		
Kinematic viscosity			
Value	<	20.5	mm²/s
Reference temperature		40	°C
Type	kinematic		
Solvent separation test			
Value	<	3	%
Reference temperature		20	°C
Particle characteristics			
No data available			

9.2 Other information

Other information
No data available.

SECTION 10: Stability and reactivity**10.1 Reactivity**

Stable under recommended storage and handling conditions (See section 7).

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Acute oral toxicity (result of the ATE calculation for the mixture)			
Product Name			
einza Nitroverdünnung			
Comments		The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE oral > 2000 mg/kg).	
Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
LD50	>	5600	ma/ka bodyweight

Trade name: einzA Nitroverdünnung

Product no.: 0100242

Current version : 5.0.0, issued: 11.09.2024

Replaced version: 4.0.0, issued: 21.04.2021

Region: GB

Species	rat	
Source	ECHA	
2	acetone	67-64-1200-662-2
LD50	5800mg/kg bodyweight	
Species	rat	
Source	ECHA	
Evaluation/classification	Based on available data, the classification criteria are not met.	
3	n-butyl acetate	123-86-4204-658-1
LD50	10760mg/kg bodyweight	
Species	rat	
Method	OECD 423	
Source	ECHA	
4	Reaction mass of xylene and ethylbenzene	-905-588-0
LD50	3523mg/kg bodyweight	
Species	rat	
Method	EU Method B.1	
Source	ECHA	
Evaluation/classification	Based on available data, the classification criteria are not met.	
5	ethanol	64-17-5200-578-6
LD50	10470mg/kg bodyweight	
Species	rat	
with reference to	95% ethanol in water	
Method	OECD 401	
Source	ECHA	
Evaluation/classification	Based on available data, the classification criteria are not met.	
6	propan-2-ol	67-63-0200-661-7
LD50	5840mg/kg bodyweight	
Species	rat	
Method	OECD 401	
Source	ECHA	
Evaluation/classification	Based on available data, the classification criteria are not met.	
7	toluene	108-88-3203-625-9
LD50	5580mg/kg bodyweight	
Species	rat	
Method	OECD 423	
Source	ECHA	

Acute dermal toxicity (result of the ATE calculation for the mixture)**Product Name****einzA Nitroverdünnung****Comments**

The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE dermal > 2000 mg/kg).

Acute dermal toxicity

No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
LD50		>	20000
Species	rabbit		mg/kg bodyweight
Source	ECHA		
2	acetone	67-64-1	200-662-2
LD50		>	15800
Species	rabbit		mg/kg bodyweight
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	n-butyl acetate	123-86-4	204-658-1
LD50		>	14112
Species	rabbit		mg/kg bodyweight
Method	OECD 402		
Source	ECHA		
4	toluene	108-88-3	203-625-9
LD50		>	5000
Species	rabbit		mg/kg bodyweight
Source	ECHA		
5	butan-1-ol	71-36-3	200-751-6
LD50		appr.	3430
Species	rabbit		mg/kg bodyweight
Method	OECD 402		
Source	ECHA		

Trade name: einza Nitroverdünnung

Product no.: 0100242

Current version : 5.0.0, issued: 11.09.2024

Replaced version: 4.0.0, issued: 21.04.2021

Region: GB

Acute inhalational toxicity (result of the ATE calculation for the mixture)	
Product Name	
einza Nitroverdünnung	
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE for inhalation: > 20.000 ppmV (gases), > 20 mg/l (vapours), > 5 mg/l (dusts/mists).

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	acetone	67-64-1	200-662-2
LC50		76	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	ethanol	64-17-5	200-578-6
LC50		124.7	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Method	OECD 403		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	-	927-510-4
LC50	>	23.3	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Method	OECD 403		
Source	ECHA		
4	propan-2-ol	67-63-0	200-661-7
LC50	>	10000	ppmV
Duration of exposure		6	h
State of aggregation	Vapour		
Species	rat		
Method	OECD 403		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
5	toluene	108-88-3	203-625-9
LC50	>	20	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Method	OECD 403		
Source	ECHA		
6	butan-1-ol	71-36-3	200-751-6
LC50	>	17.76	mg/l
Duration of exposure		4	h
State of aggregation	Dust/mist		
Species	rat		
Method	OECD 403		
Source	ECHA		

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	low-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	acetone	67-64-1	200-662-2
Species	guinea pig		
Source	ECHA		
Evaluation	non-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	n-butyl acetate	123-86-4	204-658-1

Trade name: einzA Nitroverdünnung

Product no.: 0100242

Current version : 5.0.0, issued: 11.09.2024

Replaced version: 4.0.0, issued: 21.04.2021

Region: GB

Species	rabbit
Method	OECD 404
Source	ECHA
Evaluation	non-irritant
4	ethanol 64-17-5 200-578-6
Species	rabbit
Method	OECD 404
Source	ECHA
Evaluation	non-irritant
Evaluation/classification	Based on available data, the classification criteria are not met.
5	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics - 927-510-4
Species	rabbit
with reference to	CAS 64741-66-8
Method	OECD 404
Source	ECHA
Evaluation	irritant
6	propan-2-ol 67-63-0 200-661-7
Species	rabbit
Source	ECHA
Evaluation	non-irritant
Evaluation/classification	Based on available data, the classification criteria are not met.
7	toluene 108-88-3 203-625-9
Duration of exposure	4 h
Species	rabbit
Method	OECD 404
Source	ECHA
Evaluation	irritant
8	butan-1-ol 71-36-3 200-751-6
Species	rabbit
Source	ECHA
Evaluation	irritant
Serious eye damage/irritation	
No	Substance name CAS no. EC no.
1	ethyl-acetate 141-78-6 205-500-4
Species	rabbit
Method	OECD 405
Source	ECHA
Evaluation	low-irritant
2	acetone 67-64-1 200-662-2
Species	rabbit
Method	OECD 405
Source	ECHA
Evaluation	irritant
Evaluation/classification	Based on available data, the classification criteria are met.
3	n-butyl acetate 123-86-4 204-658-1
Species	rabbit
Method	OECD 405
Source	ECHA
Evaluation	non-irritant
4	ethanol 64-17-5 200-578-6
Species	rabbit
Method	OECD 405
Source	ECHA
Evaluation	irritant
Evaluation/classification	Based on available data, the classification criteria are met.
5	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics - 927-510-4
Species	rabbit
with reference to	CAS 64741-66-8
Method	EPA OPPTS 870.2400
Source	ECHA
Evaluation	non-irritant
6	propan-2-ol 67-63-0 200-661-7
Species	rabbit
Method	OECD 405
Source	ECHA
Evaluation	irritant
Evaluation/classification	Based on available data, the classification criteria are met.
7	butan-1-ol 71-36-3 200-751-6
Species	rabbit

Trade name: einza Nitroverdünnung

Product no.: 0100242

Current version : 5.0.0, issued: 11.09.2024

Replaced version: 4.0.0, issued: 21.04.2021

Region: GB

Method	OECD 405		
Source	ECHA		
Evaluation	strongly irritant		
Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
Route of exposure		Skin	
Species	guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		
2	acetone	67-64-1	200-662-2
Route of exposure		Skin	
Species	guinea pig		
Source	ECHA		
Evaluation	non-sensitizing		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	ethanol	64-17-5	200-578-6
Route of exposure		respiratory tract	
Source	ECHA		
Evaluation	non-sensitizing		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Route of exposure		Skin	
Species	mouse		
Source	ECHA		
Evaluation	non-sensitizing		
Evaluation/classification	Based on available data, the classification criteria are not met.		
4	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	-	927-510-4
Route of exposure		Skin	
Species	guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		
5	propan-2-ol	67-63-0	200-661-7
Route of exposure		Skin	
Species	guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		
Evaluation/classification	Based on available data, the classification criteria are not met.		
6	butan-1-ol	71-36-3	200-751-6
Route of exposure		Skin	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	acetone	67-64-1	200-662-2
Type of examination	in vitro gene mutation study in bacteria		
Species	Salmonella typhimurium		
Method	OECD 471		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Type of examination	In vitro Mammalian Chromosomal Aberration Test		
Species	Chinese hamster Ovary (CHO)		
Method	OECD 473		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Type of examination	in vitro gene mutation study in mammalian cells		
Species	Mouse lymphoma cells		
Method	OECD 476		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	n-butyl acetate	123-86-4	204-658-1
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	Reaction mass of xylene and ethylbenzene	-	905-588-0
Species	Chinese hamster Ovary (CHO)		
Method	EU Method B.10		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Trade name: einza Nitroverdünnung

Product no.: 0100242

Current version : 5.0.0, issued: 11.09.2024

Replaced version: 4.0.0, issued: 21.04.2021

Region: GB

4	ethanol	64-17-5	200-578-6
Type of examination	in vitro gene mutation study in bacteria		
Species	Salmonella typhimurium		
Method	OECD 471		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Type of examination	in vitro gene mutation study in mammalian cells		
Species	mouse lymphoma cells		
Method	OECD 476		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Type of examination	Genotoxicity in vivo		
Species	mouse		
Method	OECD 478		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
5	propan-2-ol	67-63-0	200-661-7
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
6	toluene	108-88-3	203-625-9
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
7	butan-1-ol	71-36-3	200-751-6
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	acetone	67-64-1	200-662-2
Route of exposure	inhalational		
NOAEC	2200		ppm
Type of examination	Prenatal Developmental Toxicity Study		
Species	rat		
Method	OECD 414		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	n-butyl acetate	123-86-4	204-658-1
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	ethanol	64-17-5	200-578-6
Route of exposure	oral		
NOAEL			
Type of examination	2 generation study		
Species	mouse		
Method	OECD 416		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Route of exposure	inhalational		
NOAEL	>= 20000		ppm
Type of examination	Prenatal Developmental Toxicity Study		
Species	rat		
Method	OECD 414		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
4	propan-2-ol	67-63-0	200-661-7
Route of exposure	oral		
NOAEL	1000		mg/kg bw/d
Type of examination	Two-Generation Reproduction Toxicity Study		
Species	rats (male/female)		
Method	OECD 416		
Source	ECHA		
Evaluation/classification	Based on the available data, the classification criteria are not met.		
5	butan-1-ol	71-36-3	200-751-6
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	acetone	67-64-1	200-662-2
Route of exposure	dermal		
Type of examination	Toxicity study		

Trade name: einza Nitroverdünnung

Product no.: 0100242

Current version : 5.0.0, issued: 11.09.2024

Replaced version: 4.0.0, issued: 21.04.2021

Region: GB

Species	mouse
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
2	Reaction mass of xylene and ethylbenzene - 905-588-0
Species	rats (male/female)
Method	EU Method B.32
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
3	ethanol 64-17-5 200-578-6
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
4	propan-2-ol 67-63-0 200-661-7
Route of exposure	inhalational
NOEL	5000 ppm
Species	rats (male/female)
Method	OECD 451
Source	ECHA
STOT - single exposure	
No	Substance name CAS no. EC no.
1	ethyl-acetate 141-78-6 205-500-4
Route of exposure	inhalational
NOEC	350 ppm
Species	rat
Source	ECHA
Effects	May cause drowsiness or dizziness.
Evaluation/classification	Based on available data, the classification criteria are met.
2	toluene 108-88-3 203-625-9
Species	Human
Evaluation/classification	Based on available data, the classification criteria are met.
STOT - repeated exposure	
No	Substance name CAS no. EC no.
1	acetone 67-64-1 200-662-2
Route of exposure	oral
NOAEL	10000 ppm
Species	rat
Method	OECD 408
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
Route of exposure	inhalational
NOAEC	19000 ppm
Species	rat
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
2	n-butyl acetate 123-86-4 204-658-1
Route of exposure	inhalational
NOAEC	500 ppm
Duration of exposure	90 day(s)
Species	rat
Method	EPA OTS 798.2450
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
3	ethanol 64-17-5 200-578-6
Route of exposure	oral
Duration of exposure	14 week/s
Species	rat
Target organ	kidneys
Method	OECD 408
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
4	propan-2-ol 67-63-0 200-661-7
Route of exposure	inhalational
NOAEC	12500 mg/m ³
Species	rat
Method	OECD 451
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
5	toluene 108-88-3 203-625-9
Route of exposure	inhalational

Trade name: einza Nitroverdünnung

Product no.: 0100242

Current version : 5.0.0, issued: 11.09.2024

Replaced version: 4.0.0, issued: 21.04.2021

Region: GB

Target organ	central nervous system
Evaluation/classification	Based on available data, the classification criteria are met.
Aspiration hazard	
No data available	
Endocrine disrupting properties	
No data available	
Delayed and immediate effects as well as chronic effects from short and long-term exposure	
Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.	

11.2 Information on other hazards**Other information**

No data available.

SECTION 12: Ecological information**12.1 Toxicity**

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
LC50		220	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Source	ECHA		
2	acetone	67-64-1	200-662-2
LC50		5540	mg/l
Duration of exposure		96	h
Species	Oncorhynchus mykiss		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	n-butyl acetate	123-86-4	204-658-1
LC50		18	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	OECD 203		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
4	ethanol	64-17-5	200-578-6
LC50		14200	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	EPA		
Source	ECHA		
5	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	-	927-510-4
LL50		13.4	mg/l
Duration of exposure		96	h
Species	Oncorhynchus mykiss		
Method	OECD 203		
Source	ECHA		
6	propan-2-ol	67-63-0	200-661-7
LC50		9640	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	OECD 203		
Source	ECHA		
7	toluene	108-88-3	203-625-9
LC50		5.5	mg/l
Duration of exposure		96	h
Species	Oncorhynchus kisutch		
Source	ECHA		
8	butan-1-ol	71-36-3	200-751-6
LC50		1376	mg/l

Trade name: einza Nitroverdünnung

Product no.: 0100242

Current version : 5.0.0, issued: 11.09.2024

Replaced version: 4.0.0, issued: 21.04.2021

Region: GB

Duration of exposure	96	h
Species	Pimephales promelas	
Method	OECD 203	
Source	ECHA	

Toxicity to fish (chronic)

No data available

Toxicity to Daphnia (acute)

No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
EC50		3090	mg/l
Duration of exposure		24	h
Species	Daphnia magna		
Source	ECHA		
2	acetone	67-64-1	200-662-2
EC50		8800	mg/l
Duration of exposure		48	h
Species	Daphnia pulex		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	n-butyl acetate	123-86-4	204-658-1
EC50		44	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
4	ethanol	64-17-5	200-578-6
EC50		5012	mg/l
Duration of exposure		48	h
Species	Ceriodaphnia dubia		
Method	ASTM Standard E 729-80		
Source	ECHA		
5	toluene	108-88-3	203-625-9
EC50		3.78	mg/l
Duration of exposure		48	h
Species	Ceriodaphnia dubia		
Source	ECHA		
6	butan-1-ol	71-36-3	200-751-6
EC50		1328	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		

Toxicity to Daphnia (chronic)

No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
NOEC		2.4	mg/l
Species	Daphnia magna		
Method	OECD 211		
2	n-butyl acetate	123-86-4	204-658-1
NOEC		23	mg/l
Duration of exposure		21	day(s)
Species	Daphnia magna		
with reference to	CAS 110-19-0		
Method	OECD 211		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	ethanol	64-17-5	200-578-6
NOEC		9.6	mg/l
Duration of exposure		9	day(s)
Species	Daphnia magna		
Source	ECHA		
4	butan-1-ol	71-36-3	200-751-6
NOEC		4.1	mg/l
Duration of exposure		21	day(s)
Species	Daphnia magna		
Method	OECD 211		
Source	ECHA		

Toxicity to algae (acute)

Trade name: einza Nitroverdünnung

Product no.: 0100242

Current version : 5.0.0, issued: 11.09.2024

Replaced version: 4.0.0, issued: 21.04.2021

Region: GB

No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
EC50		397	mg/l
Duration of exposure		72	h
Species	Selenastrum capricornutum		
Method	OECD 201		
Source	ECHA		
2	ethanol	64-17-5	200-578-6
EC50		275	mg/l
Duration of exposure		72	h
Species	Chlorella vulgaris		
Method	OECD 201		
Source	ECHA		
3	butan-1-ol	71-36-3	200-751-6
EC50		225	mg/l
Duration of exposure		72	h
Species	Pseudokirchneriella subcapitata		
Method	OECD 201		
Source	ECHA		

Toxicity to algae (chronic)

No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
NOEC	>	100	mg/l
Species	Desmodismus subspicatus		
Method	OECD 201		
Source	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
NOEC		196	mg/l
Duration of exposure		72	h
Species	Raphidocelis subcapitata		
Method	OECD 201		
Source	ECHA		
3	butan-1-ol	71-36-3	200-751-6
NOEC		129	mg/l
Species	Raphidocelis subcapitata		
Method	OECD 201		
Source	ECHA		

Bacteria toxicity

No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
IC50		356	mg/l
Duration of exposure		40	h
Species	Tetrahymena pyriformis (Protozoa)		
Source	ECHA		
2	butan-1-ol	71-36-3	200-751-6
EC50		4390	mg/l
Duration of exposure		17	h
Species	Pseudomonas putida		
Method	DIN 38412		
Source	ECHA		

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
Type	COD		
Value		1.69	g O2/g
Source	ECHA		
Evaluation	readily biodegradable		
2	acetone	67-64-1	200-662-2
Type	aerobic biodegradation		
Value		90.9	%
Duration		28	day(s)
Method	OECD 301 B		
Source	ECHA		
Evaluation	readily biodegradable		
3	n-butyl acetate	123-86-4	204-658-1
Type	aerobic biodegradation		
Value		83	%

Trade name: einzA Nitroverdünnung

Product no.: 0100242

Current version : 5.0.0, issued: 11.09.2024

Replaced version: 4.0.0, issued: 21.04.2021

Region: GB

Duration	28		day(s)
Method	OECD 301 D		
Source	ECHA		
Evaluation	readily biodegradable		
4	Reaction mass of xylene and ethylbenzene	-	905-588-0
Type	aerobic biodegradation		
Value	98	%	
Duration	28	d	
Method	OECD 301 F		
Source	ECHA		
Evaluation	readily biodegradable		
5	ethanol	64-17-5	200-578-6
Type	aerobic biodegradation		
Value	appr.	84	%
Duration		20	day(s)
Source	ECHA		
Evaluation	readily biodegradable		
6	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	-	927-510-4
Type	aerobic biodegradation		
Value	83	%	
Duration	28	day(s)	
Method	OECD 301 F		
Source	ECHA		
Evaluation	readily biodegradable		
7	propan-2-ol	67-63-0	200-661-7
Type	BOD/COD		
Value	53	%	
Duration	5	day(s)	
Source	ECHA		
Evaluation	readily biodegradable		
8	toluene	108-88-3	203-625-9
Type	aerobic biodegradation		
Method	OECD 301 C		
Source	ECHA		
Evaluation	readily biodegradable		
9	butan-1-ol	71-36-3	200-751-6
Type	DOC decrease		
Value	92	%	
Duration	20	day(s)	
Method	OECD		
Source	ECHA		
Evaluation	readily biodegradable		
Abiotic Degradation			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
Type	Photolysis		
Half-life	3.3	day(s)	
Reference temperature	25	°C	
Source	ECHA		

12.3 Bioaccumulative potential

Bioconcentration factor (BCF)			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
BCF		15.3	
Method		Calculation model used (Q)SAR	
Source		ECHA	
Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
log Pow		0.68	
Reference temperature		25 °C	
Source		ECHA	
2	acetone	67-64-1	200-662-2
log Pow		-0.23	
Method		QSAR	
Source		ECHA	
3	n-butyl acetate	123-86-4	204-658-1

Trade name: einzA Nitroverdünnung

Product no.: 0100242

Current version : 5.0.0, issued: 11.09.2024

Replaced version: 4.0.0, issued: 21.04.2021

Region: GB

log Pow	2.3	
Reference temperature	25	°C
Method	OECD 117	
Source	ECHA	
4	Reaction mass of xylene and ethylbenzene	905-588-0
log Pow	appr. 3.49	
Reference temperature	30	°C
with reference to	pH >= 5 - <= 8	
Method	OECD 117	
Source	ECHA	
5	ethanol	200-578-6
log Pow	-0.35	
Reference temperature	24	°C
with reference to	pH 7,4	
Method	OECD 107	
Source	ECHA	
6	propan-2-ol	200-661-7
log Pow	0.05	
Reference temperature	25	°C
Source	ECHA	
7	toluene	203-625-9
log Pow	2.73	
Reference temperature	20	°C
Source	ECHA	

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
Product Name	
einzA Nitroverdünnung	
PBT assessment	The components of this product are not considered to be a PBT.
vPvB assessment	The components of this product are not considered to be a vPvB.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information
Do not allow to enter drains or water courses.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Waste code 07 01 04* other organic solvents, washing liquids and mother liquors

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company.

Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

SECTION 14: Transport information**14.1 UN number or ID number**

ADR/RID/ADN	UN1263
IMDG	UN1263
ICAO-TI / IATA	UN1263

14.2 UN proper shipping name

ADR/RID/ADN	PAINT RELATED MATERIAL
IMDG	PAINT RELATED MATERIAL
ICAO-TI / IATA	Paint related material

Trade name: einza Nitroverdünnung

Product no.: 0100242

Current version : 5.0.0, issued: 11.09.2024

Replaced version: 4.0.0, issued: 21.04.2021

Region: GB

14.3 Transport hazard class(es)

ADR/RID/ADN - Class	3
Label	3
Classification code	F1
Tunnel restriction code	D/E
Hazard identification no.	33
Special Provision 640	640D
IMDG - Class	3
Label	3
ICAO-TI / IATA - Class	3
Label	3

14.4 Packing group

ADR/RID/ADN	II
IMDG	II
ICAO-TI / IATA	II

14.5 Environmental hazards

EmS	F-E, S-E
-----	----------

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations****Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3, 40
The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	acetone	67-64-1	200-662-2	75
2	butan-1-ol	71-36-3	200-751-6	75
3	ethyl-acetate	141-78-6	205-500-4	75
4	propan-2-ol	67-63-0	200-661-7	75
5	toluene	108-88-3	203-625-9	48, 75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category: P5b

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)

VOC content 100 %

National regulations**Other national regulations**

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

Trade name: einza Nitroverdünnung

Product no.: 0100242

Current version : 5.0.0, issued: 11.09.2024

Replaced version: 4.0.0, issued: 21.04.2021

Region: GB

National Threshold Limit Values of the corresponding countries as amended in each case.
Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure
H373i	May cause damage to organs through prolonged or repeated exposure if inhaled.
H411	Toxic to aquatic life with long lasting effects.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCÖ GmbH.

Prod-ID 671342