

Trade name: einZA XXL Wandfarbe

Product no.: 0069541

Current version: 1.0.1, Revision: 01.04.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

einZA XXL Wandfarbe

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

decorative paints/finishes

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

einZA Farben GmbH & Co KG

Junkersstraße 13

30179 Hannover

Telephone no. +49 (0)511 67490-0

Fax no. +49 (0)511 67490-20

e-mail info@einZA.com

Information provided by / telephone

In emergencies, the country-specific emergency number can be found in the corresponding country-specific safety data sheets.

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

+49 (0)40 0511 - 674 90-0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

This product does not meet the classification criteria given in the Regulation (EC) No 1272/2008 (CLP).

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms

-

Signal word

-

Hazard statement(s)

-

Hazard statements (EU)

EUH208

Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

EUH210

Safety data sheet available on request.

Precautionary statement(s)

Trade name: einZA XXL Wandfarbe

Product no.: 0069541

Current version: 1.0.1, Revision: 01.04.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER**Labelling information**

The labelling (EU hazard statements) meets the criteria of annex II of Directive (EC) Nr. 1272/2008 (CLP).

2.3 Other hazards

The product does not contain any components > 0.1% that meet the criteria for PBT and vPvB according to Regulation (EC) No. 1907/2006, Annex XIII, or that have been included in the list compiled in accordance with Article 59(1). This product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not applicable. The product is not a substance.

3.2 Mixtures**Hazardous ingredients**

No	Substance name		Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration	%
1	bronopol			
	52-51-7 200-143-0 603-085-00-8 01-2119980938-15	Acute Tox. 4; H302 Acute Tox. 4; H312 Eye Dam. 1; H318 Skin Irrit. 2; H315 STOT SE 3; H335 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	< 0,10	wt%
2	1,2-benzisothiazol-3(2H)-one			
	2634-33-5 220-120-9 613-088-00-6 -	Acute Tox. 4; H302 Skin Irrit. 2; H315 Skin Sens. 1A; H317 Eye Dam. 1; H318 Acute Tox. 2; H330 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	< 0,10	wt%
3	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1)			
	55965-84-9 - 613-167-00-5 -	Acute Tox. 2; H310 Acute Tox. 2; H330 Acute Tox. 3; H301 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 Eye Dam. 1; H318 Skin Corr. 1C; H314 Skin Sens. 1A; H317	< 0,0015	wt%
4	2-methyl-2H-isothiazol-3-one			
	2682-20-4 220-239-6 613-326-00-9 -	Acute Tox. 2; H330 Acute Tox. 3; H301 Acute Tox. 3; H311 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 Eye Dam. 1; H318 Skin Corr. 1B; H314 Skin Sens. 1A; H317	< 0,10	wt%

Full text of H- and EUH-phrases, if not already mentioned in section 2.2: see section 16.

Trade name: einza XXL Wandfarbe

Product no.: 0069541

Current version: 1.0.1, Revision: 01.04.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	-	-	M = 10	-
2	-	Skin Sens. 1A; H317: C \geq 0,036%	M = 1	M = 1
3	B	Skin Sens. 1A; H317: C \geq 0,0015% Eye Irrit. 2; H319: C \geq 0,06% Skin Irrit. 2; H315: C \geq 0,06% Skin Corr. 1C; H314: C \geq 0,6% Eye Dam. 1; H318: C \geq 0,6%	M = 100	M = 100
4	-	Skin Sens. 1A; H317: C \geq 0,0015%	M = 10	M = 1

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

Acute toxicity estimate (ATE) values			
No	oral	dermal	inhalative
1	305 mg/kg bodyweight		
2	450 mg/kg bodyweight		

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Not combustible under normal conditions. Extinguishing measures to suit surroundings.

Unsuitable extinguishing media

No data available.

5.2 Special hazards arising from the substance or mixture

None known.

5.3 Advice for firefighters

Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Trade name: einZA XXL Wandfarbe

Product no.: 0069541

Current version: 1.0.1, Revision: 01.04.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

For non-emergency personnel

Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Do not allow to enter drains/watercourses/soil.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Avoid inhalation of dust from sanding. For personal protection see section 8.

General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

No special measures necessary.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Comply with legal health and safety regulations; Storage in accordance with the Ordinance on Industrial Safety and Health. Prevent unauthorised access. No smoking. Keep from freezing.

Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Storage Class according TRGS 510

12 Non-combustible liquids that cannot be assigned to any of the above LGKs.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	bronopol			52-51-7 200-143-0	
	dermal	Long term (chronic)	systemic	2,3	mg/kg/day
	dermal	Short term (acute)	systemic	7	mg/kg/day
	dermal	Long term (chronic)	local	13	µg/cm ²

Trade name: einZA XXL Wandfarbe

Product no.: 0069541

Current version: 1.0.1, Revision: 01.04.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

dermal	Short term (acut)	local	13	µg/cm ²
inhalative	Long term (chronic)	systemic	4,1	mg/m ³
inhalative	Short term (acut)		12,3	mg/m ³
inhalative	Long term (chronic)	local	4.2	mg/m ³
inhalative	Short term (acut)	local	4,2	mg/m ³

DNEL value (consumer)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	bronopol			52-51-7 200-143-0	
	oral	Long term (chronic)	systemic	0,35	mg/kg/day
	oral	Short term (acut)	systemic	1,1	mg/kg/day
	dermal	Long term (chronic)	systemic	1,4	mg/kg/day
	dermal	Short term (acut)	systemic	4,2	mg/kg/day
	dermal	Long term (chronic)	local	8	µg/cm ²
	dermal	Short term (acut)	local	8	µg/cm ²
	inhalative	Long term (chronic)	systemic	1,2	mg/m ³
	inhalative	Short term (acut)	systemic	3,7	mg/m ³
	inhalative	Long term (chronic)	local	1,3	mg/m ³
	inhalative	Short term (acut)	local	1,3	mg/m ³

PNEC values

No	Substance name		CAS / EC no	
	ecological compartment	Type	Value	
1	bronopol		52-51-7 200-143-0	
	water	fresh water	0,01	mg/L
	water	marine water	0,001	mg/L
	water	fresh water sediment	0,041	mg/kg dry weight
	water	marine water sediment	0,003	mg/kg dry weight
	soil	-	0,5	mg/kg dry weight
	sewage treatment plant	-	0,43	mg/L

8.2 Exposure controls

Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal protective equipment

Respiratory protection

Not necessary. When applied by spraying: Filter A2P2 (DIN EN 14387)

Eye / face protection

Wear safety goggles to protect against splashes. Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material In case of short-term contact / splash protection: nitrile rubber

Material thickness > 0,4 mm

Breakthrough time > 120 min

Appropriate Material In case of prolonged exposure: nitrile rubber

Material thickness > 0,4 mm

Breakthrough time > 480 min

Other

Trade name: einZA XXL Wandfarbe

Product no.: 0069541

Current version: 1.0.1, Revision: 01.04.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

Light protective clothing

Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation	
liquid	
Form	
liquid	
Colour	
according to product name	
Odour	
characteristic	
pH value	
Value	7,0 - 9,0
Boiling point / boiling range	
Value	100 °C
Melting point/freezing point	
No data available	
Decomposition temperature	
No data available	
Flash point	
Not applicable	
Ignition temperature	
No data available	
Oxidising properties	
Not applicable	
Flammability	
Not applicable	
Lower explosion limit	
No data available	
Upper explosion limit	
No data available	
Vapour pressure	
Value	< 100 hPa
Reference temperature	50 °C
Relative vapour density	
No data available	
Relative density	
No data available	
Density	
Value	1,30 - 1,70 g/cm ³
Reference temperature	25 °C
Method	DIN 51757
Solubility in water	
Comments	miscible

Trade name: einZA XXL Wandfarbe

Product no.: 0069541

Current version: 1.0.1, Revision: 01.04.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

Solubility	
No data available	
Partition coefficient n-octanol/water (log value)	
No data available	
Kinematic viscosity	
Value	5000 - 15000 mPa*s
Reference temperature	25 °C
Method	DIN 53019
Solvent separation test	
Not applicable	
Particle characteristics	
No data available	

9.2 Other information

Other information
No data available.

SECTION 10: Stability and reactivity**10.1 Reactivity**

Stable under recommended storage and handling conditions (See section 7).

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	bronopol	52-51-7	200-143-0
LD50		305	mg/kg bodyweight
Species	rat		
Source	ECHA		
2	1,2-benzisothiazol-3(2H)-one	2634-33-5	220-120-9
ATE		450	mg/kg bodyweight
Source	1272/2008/EC, Annex VI		
Acute dermal toxicity			
No data available			
Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	bronopol	52-51-7	200-143-0
LC50	>=	0,588	mg/l
Duration of exposure		4	h
State of aggregation	Dust/mist		
Species	rat		

Trade name: einZA XXL Wandfarbe

Product no.: 0069541

Current version: 1.0.1, Revision: 01.04.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

Source	ECHA
2	1,2-benzisothiazol-3(2H)-one 2634-33-5 220-120-9
ATE	0,21 mg/l
State of aggregation	Dust/mist
Source	1272/2008/EC, Annex VI

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	bronopol	52-51-7	200-143-0
Duration of exposure		4	h
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	irritant		

Serious eye damage/irritation
No data available

Respiratory or skin sensitisation
No data available

Germ cell mutagenicity
No data available

Reproduction toxicity
No data available

Carcinogenicity
No data available

STOT - single exposure
No data available

STOT - repeated exposure
No data available

Aspiration hazard
No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure
The liquid splashed in the eyes may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

11.2 Information on other hazards

Endocrine disrupting properties
No data available

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	bronopol	52-51-7	200-143-0
LC50		35,7	mg/l
Duration of exposure		96	h
Species	Lepomis macrochirus		
Method	EPA OPP 72-1		
Source	ECHA		

Toxicity to fish (chronic)			
No	Substance name	CAS no.	EC no.

Trade name: einza XXL Wandfarbe

Product no.: 0069541

Current version: 1.0.1, Revision: 01.04.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

1	bronopol	52-51-7	200-143-0
NOEC		21,5	mg/l
Duration of exposure		49	day(s)
Species	Oncorhynchus mykiss		
Method	OECD 210		
Source	ECHA		

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	bronopol	52-51-7	200-143-0
EC50		1,4	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		

Toxicity to Daphnia (chronic)			
No	Substance name	CAS no.	EC no.
1	bronopol	52-51-7	200-143-0
NOEC		0,27	mg/l
Duration of exposure		21	day(s)
Species	Daphnia magna		
Method	OECD 211		
Source	ECHA		

Toxicity to algae (acute)	
No data available	

Toxicity to algae (chronic)	
No data available	

Bacteria toxicity	
No data available	

12.2 Persistence and degradability

No data available.

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information
Do not allow to enter drains or water courses.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Waste code 08 01 12 waste paint and varnish other than those mentioned in 08 01 11

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company.

Allow paint/varnish to dry out completely in a well-ventilated area and dispose of in residual waste once completely solidified. Dispose of liquid or non-drying residues separately.

Trade name: einZA XXL Wandfarbe

Product no.: 0069541

Current version: 1.0.1, Revision: 01.04.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

SECTION 14: Transport information**14.1 UN number or ID number**

Not classified as dangerous in the meaning of transport regulations.

14.2 UN proper shipping name

Not classified as dangerous in the meaning of transport regulations.

14.3 Transport hazard class(es)

Not classified as dangerous in the meaning of transport regulations.

14.4 Packing group

Not classified as dangerous in the meaning of transport regulations.

14.5 Environmental hazards

Not classified as dangerous in the meaning of transport regulations.

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations****Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	1,2-benzisothiazol-3(2H)-one	2634-33-5	220-120-9	75
2	2-(2-butoxyethoxy)ethanol	112-34-5	203-961-6	75
3	bronopol	52-51-7	200-143-0	75
4	Calcium carbonate	471-34-1	207-439-9	75
5	Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6	75
6	Limestone	1317-65-3	215-279-6	75
7	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1)	55965-84-9	-	75
8	titanium dioxide	13463-67-7	236-675-5	75
9	triiron-tetraoxide	1317-61-9	215-277-5	75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

Trade name: einza XXL Wandfarbe

Product no.: 0069541

Current version: 1.0.1, Revision: 01.04.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

This product is not subject to Part 1 or 2 of Annex I.
--

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products
--

relevant VOC limit value as referred to in Annex II of Directive 2004/42/CE , Cat. : a, type: Ib = 30 g/l Max. VOC content (limit value) of the product in its ready for use condition = < 30 g/l
--

National regulations**Water Hazard Class (Germany)**

Class	1
Source	Classification according to AwSV (Regulation on facilities for handling substances that are hazardous to water).

Other regulations

GISCODE BSW20 Covering agents, solvent based

Other national regulations

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment. For example, TRGS (Technical Rules for Hazardous Substances) and the DGUV (German Social Accident Insurance) rules.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

EUH071	Corrosive to the respiratory tract.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

This product does not meet the classification criteria given in the Regulation (EC) No 1272/2008 (CLP).

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

Trade name: einZA XXL Wandfarbe

Product no.: 0069541

Current version: 1.0.1, Revision: 01.04.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

B Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

This document is an English translation of the legally compliant safety data sheet of the region Germany. This document, including UFI and emergency telephone number, may only be used for placing on the market in the region Germany.

Copyright-protected document. Any changes or reproductions require the express consent of UMCO GmbH.

Prod-ID 655290