

**Trade name:** einzA mineralit Sol Fassadenfarbe**Product no.:** 0030903**Current version:** 2.0.1, Revision: 28.07.2026**Replaced version:** 2.0.0, Revision: 10.06.2026**Region:**  
GER**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name****einza mineralit Sol Fassadenfarbe****1.2 Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses of the substance or mixture**

coating material

**Uses advised against**

No data available.

**1.3 Details of the supplier of the safety data sheet****Address**

einza Farben GmbH &amp; Co KG

Junkersstraße 13

30179 Hannover

Telephone no. +49 (0)511 67490-0

Fax no. +49 (0)511 67490-20

e-mail info@einza.com

**Information provided by / telephone**

In emergencies, the country-specific emergency number can be found in the corresponding country-specific safety data sheets.

**Advice on Safety Data Sheet**

sdb\_info@umco.de

**1.4 Emergency telephone number**

+49 (0)40 0511 - 674 90-0

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Aquatic Chronic 3; H412

**Classification information**

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)****Hazard pictograms**

-

**Signal word**

-

**Hazard statement(s)**

H412

Harmful to aquatic life with long lasting effects.

**Hazard statements (EU)**

EUH208

Contains 2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.

**Precautionary statement(s)**

P501

Dispose of contents/container to a facility in accordance with local and national regulations.

Trade name: einzA mineralit Sol Fassadenfarbe

Product no.: 0030903

Current version: 2.0.1, Revision: 28.07.2026

Replaced version: 2.0.0, Revision: 10.06.2026

Region:  
GER**2.3 Other hazards**

The product does not contain any components > 0.1% that meet the criteria for PBT and vPvB according to Regulation (EC) No. 1907/2006, Annex XIII, or that have been included in the list compiled in accordance with Article 59(1). This product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**SECTION 3: Composition/information on ingredients****3.1 Substances**

Not applicable. The product is not a substance.

**3.2 Mixtures****Hazardous ingredients**

| No | Substance name                                   | Classification (EC) 1272/2008 (CLP)                                                                                                                                                           | Additional information |     |
|----|--------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|-----|
|    | CAS / EC / Index / REACH no                      |                                                                                                                                                                                               | Concentration          | %   |
| 1  | <b>potassium silicate</b>                        |                                                                                                                                                                                               |                        |     |
|    | 1312-76-1<br>215-199-1<br>-<br>01-2119456888-17  | STOT SE 3; H335<br>Skin Irrit. 2; H315<br>Eye Irrit. 2; H319                                                                                                                                  | < 5,00                 | wt% |
| 2  | <b>Kieselguhr, soda ash flux-calcined</b>        |                                                                                                                                                                                               |                        |     |
|    | 68855-54-9<br>272-489-0<br>-<br>01-2119488518-22 | STOT RE 2; H373i                                                                                                                                                                              | < 5,00                 | wt% |
| 3  | <b>pyrithione zinc</b>                           |                                                                                                                                                                                               |                        |     |
|    | 13463-41-7<br>236-671-3<br>613-333-00-7<br>-     | Acute Tox. 3; H301<br>Acute Tox. 2; H330<br>Eye Dam. 1; H318<br>Repr. 1B; H360D<br>STOT RE 1; H372<br>Aquatic Acute 1; H400<br>Aquatic Chronic 1; H410                                        | < 0,10                 | wt% |
| 4  | <b>terbutryn</b>                                 |                                                                                                                                                                                               |                        |     |
|    | 886-50-0<br>212-950-5<br>-<br>-                  | Aquatic Acute 1; H400<br>Aquatic Chronic 1; H410<br>Acute Tox. 4; H302<br>Skin Sens. 1; H317                                                                                                  | < 0,025                | wt% |
| 5  | <b>2-octyl-2H-isothiazol-3-one</b>               |                                                                                                                                                                                               |                        |     |
|    | 26530-20-1<br>247-761-7<br>613-112-00-5<br>-     | Acute Tox. 3; H301<br>Acute Tox. 3; H311<br>Skin Corr. 1; H314<br>Skin Sens. 1A; H317<br>Eye Dam. 1; H318<br>Acute Tox. 2; H330<br>Aquatic Chronic 1; H410<br>Aquatic Acute 1; H400<br>EUH071 | < 0,10                 | wt% |

Full text of H- and EUH-phrases, if not already mentioned in section 2.2: see section 16.

| No | Note | Specific concentration limits     | M-factor (acute) | M-factor (chronic) |
|----|------|-----------------------------------|------------------|--------------------|
| 3  | -    | -                                 | M = 1000         | M = 10             |
| 4  | -    | -                                 | M = 100          | M = 100            |
| 5  | -    | Skin Sens. 1A; H317: C >= 0,0015% | M = 100          | M = 100            |

| No | Route, target organ, concrete effect |
|----|--------------------------------------|
| 2  | H373i<br>inhalational; -; -          |

**Trade name:** einzA mineralit Sol Fassadenfarbe**Product no.:** 0030903**Current version:** 2.0.1, Revision: 28.07.2026**Replaced version:** 2.0.0, Revision: 10.06.2026**Region:**  
GER

| Acute toxicity estimate (ATE) values |                      |                      |            |
|--------------------------------------|----------------------|----------------------|------------|
| No                                   | oral                 | dermal               | inhalative |
| 3                                    | 221 mg/kg bodyweight |                      |            |
| 4                                    | 500 mg/kg bodyweight |                      |            |
| 5                                    | 125 mg/kg bodyweight | 311 mg/kg bodyweight |            |

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

#### After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

#### After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

#### After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

#### After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

No data available.

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Not combustible under normal conditions. Extinguishing measures to suit surroundings.

#### Unsuitable extinguishing media

No data available.

### 5.2 Special hazards arising from the substance or mixture

None known.

### 5.3 Advice for firefighters

Do not allow run-off from fire fighting to enter drains or water courses.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

#### For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

### 6.2 Environmental precautions

If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Do not allow to enter drains/watercourses/soil.

### 6.3 Methods and material for containment and cleaning up

**Trade name:** einza mineralit Sol Fassadenfarbe**Product no.:** 0030903**Current version:** 2.0.1, Revision: 28.07.2026**Replaced version:** 2.0.0, Revision: 10.06.2026**Region:**  
GER

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

**6.4 Reference to other sections**

No data available.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling****Advice on safe handling**

Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Avoid inhalation of dust from sanding. For personal protection see section 8.

**General protective and hygiene measures**

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

**Advice on protection against fire and explosion**

No special measures necessary.

**7.2 Conditions for safe storage, including any incompatibilities****Technical measures and storage conditions**

Comply with legal health and safety regulations; Storage in accordance with the Ordinance on Industrial Safety and Health. Prevent unauthorised access. No smoking. Keep from freezing.

**Requirements for storage rooms and vessels**

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

**Incompatible products**

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

**Storage Class according TRGS 510**

12 Non-combustible liquids that cannot be assigned to any of the above storage classes.

**7.3 Specific end use(s)**

No data available.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Occupational exposure limit values**

| No | Substance name                            | CAS no.    | EC no.            |
|----|-------------------------------------------|------------|-------------------|
| 1  | Kieselguhr, soda ash flux-calcined        | 68855-54-9 | 272-489-0         |
|    | TRGS 900                                  |            |                   |
|    | Kieselgur, gebrannt                       |            |                   |
|    | WEL long-term (8-hr TWA reference period) | 0,3 A      | mg/m <sup>3</sup> |
|    | Notes                                     | Y, 1       |                   |
| 2  | 2-octyl-2H-isothiazol-3-one               | 26530-20-1 | 247-761-7         |
|    | TRGS 900                                  |            |                   |
|    | 2-Octyl-2H-isothiazol-3-on                |            |                   |
|    | WEL long-term (8-hr TWA reference period) | 0,05 E     | mg/m <sup>3</sup> |
|    | Ceiling Limit                             | 2 (I)      |                   |
|    | Skin resorption / sensibilisation         | H          |                   |
|    | Notes                                     | Y          |                   |

**DNEL, DMEL and PNEC values****DNEL values (worker)**

| No | Substance name    | CAS / EC no |
|----|-------------------|-------------|
|    | Route of exposure | Value       |
|    | Exposure time     |             |
|    | Effect            |             |

Trade name: einza mineralit Sol Fassadenfarbe

Product no.: 0030903

Current version: 2.0.1, Revision: 28.07.2026

Replaced version: 2.0.0, Revision: 10.06.2026

Region:  
GER

|   |                                           |                     |          |                                       |                   |
|---|-------------------------------------------|---------------------|----------|---------------------------------------|-------------------|
| 1 | <b>potassium silicate</b>                 |                     |          | <b>1312-76-1</b><br><b>215-199-1</b>  |                   |
|   | dermal                                    | Long term (chronic) | systemic | 1,49                                  | mg/kg/day         |
|   | inhalative                                | Long term (chronic) | systemic | 5,61                                  | mg/m <sup>3</sup> |
| 2 | <b>Kieselguhr, soda ash flux-calcined</b> |                     |          | <b>68855-54-9</b><br><b>272-489-0</b> |                   |
|   | inhalative                                | Long term (chronic) | systemic | 0,05                                  | mg/m <sup>3</sup> |

**DNEL value (consumer)**

| No | Substance name                            |                     |          | CAS / EC no                           |                   |
|----|-------------------------------------------|---------------------|----------|---------------------------------------|-------------------|
|    | Route of exposure                         | Exposure time       | Effect   | Value                                 |                   |
| 1  | <b>potassium silicate</b>                 |                     |          | <b>1312-76-1</b><br><b>215-199-1</b>  |                   |
|    | oral                                      | Long term (chronic) | systemic | 0,74                                  | mg/kg/day         |
|    | dermal                                    | Long term (chronic) | systemic | 0,74                                  | mg/kg/day         |
|    | inhalative                                | Long term (chronic) | systemic | 1,38                                  | mg/m <sup>3</sup> |
| 2  | <b>Kieselguhr, soda ash flux-calcined</b> |                     |          | <b>68855-54-9</b><br><b>272-489-0</b> |                   |
|    | oral                                      | Long term (chronic) | systemic | 18,7                                  | mg/kg bw/day      |
|    | inhalative                                | Long term (chronic) | systemic | 0,05                                  | mg/m <sup>3</sup> |

**PNEC values**

| No | Substance name                            |                   | CAS / EC no                           |      |
|----|-------------------------------------------|-------------------|---------------------------------------|------|
|    | ecological compartment                    | Type              | Value                                 |      |
| 1  | <b>potassium silicate</b>                 |                   | <b>1312-76-1</b><br><b>215-199-1</b>  |      |
|    | water                                     | fresh water       | 7,5                                   | mg/L |
|    | water                                     | marine water      | 1                                     | mg/L |
|    | water                                     | Aqua intermittent | 7,5                                   | mg/L |
|    | sewage treatment plant                    | -                 | 348                                   | mg/L |
| 2  | <b>Kieselguhr, soda ash flux-calcined</b> |                   | <b>68855-54-9</b><br><b>272-489-0</b> |      |
|    | sewage treatment plant                    | -                 | 100                                   | mg/L |

**8.2 Exposure controls****Appropriate engineering controls**

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

**Personal protective equipment****Respiratory protection**

Not necessary. When applied by spraying: Filter A2P2 (DIN EN 14387)

**Eye / face protection**

Wear safety goggles to protect against splashes. Safety glasses with side protection shield (EN 166)

**Hand protection**

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material In case of short-term contact / splash protection: nitrile rubber

Material thickness > 0,4 mm

Breakthrough time > 120 min

Appropriate Material In case of prolonged exposure: nitrile rubber

Material thickness > 0,4 mm

Breakthrough time > 480 min

**Other**

Light protective clothing

**Environmental exposure controls**

Trade name: einza mineralit Sol Fassadenfarbe

Product no.: 0030903

Current version: 2.0.1, Revision: 28.07.2026

Replaced version: 2.0.0, Revision: 10.06.2026

Region:  
GER

Do not allow to enter drains or water courses.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

|                                      |             |     |            |
|--------------------------------------|-------------|-----|------------|
| <b>State of aggregation</b>          |             |     |            |
| liquid                               |             |     |            |
| <b>Form</b>                          |             |     |            |
| liquid                               |             |     |            |
| <b>Colour</b>                        |             |     |            |
| according to product name            |             |     |            |
| <b>Odour</b>                         |             |     |            |
| characteristic                       |             |     |            |
| <b>pH value</b>                      |             |     |            |
| Value                                | 10,4 - 11,4 |     |            |
| <b>Boiling point / boiling range</b> |             |     |            |
| Value                                | 100 °C      |     |            |
| <b>Melting point/freezing point</b>  |             |     |            |
| No data available                    |             |     |            |
| <b>Decomposition temperature</b>     |             |     |            |
| No data available                    |             |     |            |
| <b>Flash point</b>                   |             |     |            |
| Not applicable                       |             |     |            |
| <b>Ignition temperature</b>          |             |     |            |
| No data available                    |             |     |            |
| <b>Oxidising properties</b>          |             |     |            |
| Not applicable                       |             |     |            |
| <b>Flammability</b>                  |             |     |            |
| Not applicable                       |             |     |            |
| <b>Lower explosion limit</b>         |             |     |            |
| No data available                    |             |     |            |
| <b>Upper explosion limit</b>         |             |     |            |
| No data available                    |             |     |            |
| <b>Vapour pressure</b>               |             |     |            |
| Value                                | <           | 100 | hPa        |
| Reference temperature                |             | 50  | °C         |
| <b>Relative vapour density</b>       |             |     |            |
| No data available                    |             |     |            |
| <b>Relative density</b>              |             |     |            |
| No data available                    |             |     |            |
| <b>Density</b>                       |             |     |            |
| Value                                | 1,30        | -   | 1,70 g/cm³ |
| Reference temperature                |             | 25  | °C         |
| Method                               | DIN 51757   |     |            |
| <b>Solubility in water</b>           |             |     |            |
| Comments                             | miscible    |     |            |
| <b>Solubility</b>                    |             |     |            |
| No data available                    |             |     |            |

Trade name: einzA mineralit Sol Fassadenfarbe

Product no.: 0030903

Current version: 2.0.1, Revision: 28.07.2026

Replaced version: 2.0.0, Revision: 10.06.2026

Region:  
GER

| Partition coefficient n-octanol/water (log value)                        |                |                    |           |
|--------------------------------------------------------------------------|----------------|--------------------|-----------|
| No                                                                       | Substance name | CAS no.            | EC no.    |
| 1                                                                        | terbutryn      | 886-50-0           | 212-950-5 |
| log Pow                                                                  |                | 3,74               |           |
|                                                                          |                |                    |           |
| Kinematic viscosity                                                      |                |                    |           |
| Value                                                                    |                | 5000 - 15000 mPa*s |           |
| Reference temperature                                                    |                | 25 °C              |           |
| Method                                                                   |                | DIN 53019          |           |
|                                                                          |                |                    |           |
| Solvent separation test                                                  |                |                    |           |
| Not applicable                                                           |                |                    |           |
|                                                                          |                |                    |           |
| Particle characteristics                                                 |                |                    |           |
| No data available                                                        |                |                    |           |
|                                                                          |                |                    |           |
| Microplastics                                                            |                |                    |           |
| This product does not contain synthetic polymer microparticles >= 0.01%. |                |                    |           |

**9.2 Other information**

| Other information  |
|--------------------|
| No data available. |

**SECTION 10: Stability and reactivity****10.1 Reactivity**

Stable under recommended storage and handling conditions (See section 7).

**10.2 Chemical stability**

Stable under recommended storage and handling conditions (See section 7).

**10.3 Possibility of hazardous reactions**

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**10.4 Conditions to avoid**

Heat, naked flames and other ignition sources.

**10.5 Incompatible materials**

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**10.6 Hazardous decomposition products**

None if stored, handled and transported properly. In case of fire: see section 5.

**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

| Acute oral toxicity       |                                                               |            |           |
|---------------------------|---------------------------------------------------------------|------------|-----------|
| No                        | Substance name                                                | CAS no.    | EC no.    |
| 1                         | Kieselguhr, soda ash flux-calcined                            | 68855-54-9 | 272-489-0 |
| LD50                      | > 2000 mg/kg bodyweight                                       |            |           |
| Species                   | rat                                                           |            |           |
| Method                    | OECD 420                                                      |            |           |
| Source                    | ECHA                                                          |            |           |
| 2                         | pyrithione zinc                                               | 13463-41-7 | 236-671-3 |
| ATE                       | 221 mg/kg bodyweight                                          |            |           |
| Species                   | rat                                                           |            |           |
| Source                    | 1272/2008/EC, Annex VI                                        |            |           |
| 3                         | terbutryn                                                     | 886-50-0   | 212-950-5 |
| LD50                      | appr. 500 mg/kg bodyweight                                    |            |           |
| Species                   | rat                                                           |            |           |
| Evaluation/classification | Based on available data, the classification criteria are met. |            |           |
| 4                         | 2-octyl-2H-isothiazol-3-one                                   | 26530-20-1 | 247-761-7 |
| ATE                       | 125 mg/kg bodyweight                                          |            |           |

Trade name: einza mineralit Sol Fassadenfarbe

Product no.: 0030903

Current version: 2.0.1, Revision: 28.07.2026

Replaced version: 2.0.0, Revision: 10.06.2026

Region:  
GER

|         |                        |
|---------|------------------------|
| Species | rat                    |
| Source  | 1272/2008/EC, Annex VI |

| Acute dermal toxicity     |                                                                   |            |           |
|---------------------------|-------------------------------------------------------------------|------------|-----------|
| No                        | Substance name                                                    | CAS no.    | EC no.    |
| 1                         | terbutryn                                                         | 886-50-0   | 212-950-5 |
| LD50                      | > 2000 mg/kg bodyweight                                           |            |           |
| Species                   | rat                                                               |            |           |
| Evaluation/classification | Based on available data, the classification criteria are not met. |            |           |
| 2                         | 2-octyl-2H-isothiazol-3-one                                       | 26530-20-1 | 247-761-7 |
| ATE                       | 311 mg/kg bodyweight                                              |            |           |
| Species                   | rabbit                                                            |            |           |
| Source                    | 1272/2008/EC, Annex VI                                            |            |           |

| Acute inhalational toxicity |                                                                   |            |           |
|-----------------------------|-------------------------------------------------------------------|------------|-----------|
| No                          | Substance name                                                    | CAS no.    | EC no.    |
| 1                           | Kieselguhr, soda ash flux-calcined                                | 68855-54-9 | 272-489-0 |
| LC50                        | > 2,6 mg/l                                                        |            |           |
| Duration of exposure        | 4 h                                                               |            |           |
| State of aggregation        | Dust                                                              |            |           |
| Species                     | rat                                                               |            |           |
| Method                      | OECD 403                                                          |            |           |
| Source                      | ECHA                                                              |            |           |
| 2                           | pyrithione zinc                                                   | 13463-41-7 | 236-671-3 |
| ATE                         | 0,14 mg/l                                                         |            |           |
| State of aggregation        | Dust/mist                                                         |            |           |
| Species                     | rat                                                               |            |           |
| Source                      | 1272/2008/EC, Annex VI                                            |            |           |
| 3                           | terbutryn                                                         | 886-50-0   | 212-950-5 |
| LC50                        | > 5,21 mg/l                                                       |            |           |
| Duration of exposure        | 4 h                                                               |            |           |
| State of aggregation        | Dust/mist                                                         |            |           |
| Species                     | rat                                                               |            |           |
| Evaluation/classification   | Based on available data, the classification criteria are not met. |            |           |
| 4                           | 2-octyl-2H-isothiazol-3-one                                       | 26530-20-1 | 247-761-7 |
| ATE                         | 0,27 mg/l                                                         |            |           |
| Duration of exposure        | 4 h                                                               |            |           |
| State of aggregation        | Dust/mist                                                         |            |           |
| Species                     | rat                                                               |            |           |
| Source                      | 1272/2008/EC, Annex VI                                            |            |           |

| Skin corrosion/irritation |                                    |            |           |
|---------------------------|------------------------------------|------------|-----------|
| No                        | Substance name                     | CAS no.    | EC no.    |
| 1                         | Kieselguhr, soda ash flux-calcined | 68855-54-9 | 272-489-0 |
| Method                    | OECD 431                           |            |           |
| Source                    | ECHA                               |            |           |
| Evaluation                | non-irritant                       |            |           |

| Serious eye damage/irritation |                                    |            |           |
|-------------------------------|------------------------------------|------------|-----------|
| No                            | Substance name                     | CAS no.    | EC no.    |
| 1                             | Kieselguhr, soda ash flux-calcined | 68855-54-9 | 272-489-0 |
| Source                        | ECHA                               |            |           |
| Evaluation                    | non-irritant                       |            |           |

| Respiratory or skin sensitisation |                                    |            |           |
|-----------------------------------|------------------------------------|------------|-----------|
| No                                | Substance name                     | CAS no.    | EC no.    |
| 1                                 | Kieselguhr, soda ash flux-calcined | 68855-54-9 | 272-489-0 |
| Route of exposure                 | Skin                               |            |           |
| Species                           | mouse                              |            |           |
| Method                            | OECD 429                           |            |           |
| Source                            | ECHA                               |            |           |
| Evaluation                        | non-sensitizing                    |            |           |

Trade name: einzA mineralit Sol Fassadenfarbe

Product no.: 0030903

Current version: 2.0.1, Revision: 28.07.2026

Replaced version: 2.0.0, Revision: 10.06.2026

Region:  
GER**Germ cell mutagenicity**

No data available

**Reproduction toxicity**

No data available

**Carcinogenicity**

No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration hazard**

No data available

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

The liquid splashed in the eyes may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

**11.2 Information on other hazards****Endocrine disrupting properties**

No data available

**Other information**

No data available.

**SECTION 12: Ecological information****12.1 Toxicity****Toxicity to fish (acute)**

| No                        | Substance name                                                                                                               | CAS no.    | EC no.    |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------|------------|-----------|
| 1                         | potassium silicate                                                                                                           | 1312-76-1  | 215-199-1 |
| LC50                      |                                                                                                                              | 146        | mg/l      |
| Duration of exposure      |                                                                                                                              | 96         | h         |
| Species                   | Leuciscus idus                                                                                                               |            |           |
| Method                    | OECD 203                                                                                                                     |            |           |
| Source                    | ECHA                                                                                                                         |            |           |
| 2                         | Kieselguhr, soda ash flux-calcined                                                                                           | 68855-54-9 | 272-489-0 |
| LC50                      |                                                                                                                              | > 100      | mg/l      |
| Duration of exposure      |                                                                                                                              | 96         | h         |
| Species                   | Oncorhynchus mykiss                                                                                                          |            |           |
| Method                    | OECD 203                                                                                                                     |            |           |
| Source                    | ECHA                                                                                                                         |            |           |
| Evaluation/classification | The tested concentration is above the limit of solubility. Based on available data, the classification criteria are not met. |            |           |
| 3                         | terbutryn                                                                                                                    | 886-50-0   | 212-950-5 |
| LC50                      |                                                                                                                              | 1,8        | mg/l      |
| Duration of exposure      |                                                                                                                              | 96         | h         |
| Species                   | fish                                                                                                                         |            |           |

**Toxicity to fish (chronic)**

No data available

**Toxicity to Daphnia (acute)**

| No                   | Substance name     | CAS no.   | EC no.    |
|----------------------|--------------------|-----------|-----------|
| 1                    | potassium silicate | 1312-76-1 | 215-199-1 |
| EC50                 |                    | 146       | mg/l      |
| Duration of exposure |                    | 24        | h         |
| Species              | Daphnia magna      |           |           |
| Method               | OECD 202           |           |           |

Trade name: einza mineralit Sol Fassadenfarbe

Product no.: 0030903

Current version: 2.0.1, Revision: 28.07.2026

Replaced version: 2.0.0, Revision: 10.06.2026

Region:  
GER

| Source                                      | ECHA                                                                                                                         |
|---------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| <b>2 Kieselguhr, soda ash flux-calcined</b> | <b>68855-54-9 272-489-0</b>                                                                                                  |
| EC50                                        | > 100 mg/l                                                                                                                   |
| Duration of exposure                        | 48 h                                                                                                                         |
| Species                                     | Daphnia magna                                                                                                                |
| Method                                      | OECD 202                                                                                                                     |
| Source                                      | ECHA                                                                                                                         |
| Evaluation/classification                   | The tested concentration is above the limit of solubility. Based on available data, the classification criteria are not met. |
| <b>3 terbutryn</b>                          | <b>886-50-0 212-950-5</b>                                                                                                    |
| EC50                                        | 7,1 mg/l                                                                                                                     |
| Duration of exposure                        | 48 h                                                                                                                         |
| Species                                     | Daphnia                                                                                                                      |

**Toxicity to Daphnia (chronic)**

No data available

**Toxicity to algae (acute)**

| No                        | Substance name                                                                                                               | CAS no.           | EC no.           |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------|
| <b>1</b>                  | <b>Kieselguhr, soda ash flux-calcined</b>                                                                                    | <b>68855-54-9</b> | <b>272-489-0</b> |
| EC50                      | >                                                                                                                            | 100 mg/l          |                  |
| Duration of exposure      |                                                                                                                              | 72 h              |                  |
| Species                   | Desmodesmus subspicatus                                                                                                      |                   |                  |
| Method                    | OECD 201                                                                                                                     |                   |                  |
| Source                    | ECHA                                                                                                                         |                   |                  |
| Evaluation/classification | The tested concentration is above the limit of solubility. Based on available data, the classification criteria are not met. |                   |                  |
| <b>2</b>                  | <b>terbutryn</b>                                                                                                             | <b>886-50-0</b>   | <b>212-950-5</b> |
| EC50                      |                                                                                                                              | 0,0055 mg/l       |                  |
| Duration of exposure      |                                                                                                                              | 72 h              |                  |
| Species                   | Scenedesmus capricornutum                                                                                                    |                   |                  |
| Evaluation/classification | Based on available data, the classification criteria are met.                                                                |                   |                  |

**Toxicity to algae (chronic)**

No data available

**Bacteria toxicity**

No data available

**12.2 Persistence and degradability**

| Biodegradability |                           |                 |                  |
|------------------|---------------------------|-----------------|------------------|
| No               | Substance name            | CAS no.         | EC no.           |
| <b>1</b>         | <b>terbutryn</b>          | <b>886-50-0</b> | <b>212-950-5</b> |
| Evaluation       | not readily biodegradable |                 |                  |

**12.3 Bioaccumulative potential**

| Bioconcentration factor (BCF)                     |                  |                 |                  |
|---------------------------------------------------|------------------|-----------------|------------------|
| No                                                | Substance name   | CAS no.         | EC no.           |
| <b>1</b>                                          | <b>terbutryn</b> | <b>886-50-0</b> | <b>212-950-5</b> |
| BCF                                               |                  | 103             |                  |
| Partition coefficient n-octanol/water (log value) |                  |                 |                  |
| No                                                | Substance name   | CAS no.         | EC no.           |
| <b>1</b>                                          | <b>terbutryn</b> | <b>886-50-0</b> | <b>212-950-5</b> |
| log Pow                                           |                  | 3,74            |                  |

**12.4 Mobility in soil**

No data available.

**12.5 Results of PBT and vPvB assessment**

No data available.

**12.6 Endocrine disrupting properties**

**Trade name:** einzA mineralit Sol Fassadenfarbe**Product no.:** 0030903**Current version:** 2.0.1, Revision: 28.07.2026**Replaced version:** 2.0.0, Revision: 10.06.2026**Region:**  
GER

No data available.

**12.7 Other adverse effects**

No data available.

**12.8 Other information****Other information**

Do not allow to enter drains or water courses.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Product**

Waste code 08 01 12 waste paint and varnish other than those mentioned in 08 01 11

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company. Allow paint/varnish to dry out completely in a well-ventilated area and dispose of in residual waste once completely solidified. Dispose of liquid or non-drying residues separately.

Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

**Packaging**

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

**SECTION 14: Transport information****14.1 UN number or ID number**

Not classified as dangerous in the meaning of transport regulations.

**14.2 UN proper shipping name**

Not classified as dangerous in the meaning of transport regulations.

**14.3 Transport hazard class(es)**

Not classified as dangerous in the meaning of transport regulations.

**14.4 Packing group**

Not classified as dangerous in the meaning of transport regulations.

**14.5 Environmental hazards**

Not classified as dangerous in the meaning of transport regulations.

**14.6 Special precautions for user**

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments**

Not relevant

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations****Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

**REACH candidate list of substances of very high concern (SVHC) for authorisation**

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Trade name: einza mineralit Sol Fassadenfarbe

Product no.: 0030903

Current version: 2.0.1, Revision: 28.07.2026

Replaced version: 2.0.0, Revision: 10.06.2026

Region:  
GER**Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES**

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

| No | Substance name                                         | CAS no.    | EC no.    | No |
|----|--------------------------------------------------------|------------|-----------|----|
| 1  | 1,2-benzisothiazol-3(2H)-one                           | 2634-33-5  | 220-120-9 | 75 |
| 2  | 2-octyl-2H-isothiazol-3-one                            | 26530-20-1 | 247-761-7 | 75 |
| 3  | Distillates (petroleum), hydrotreated light naphthenic | 64742-53-6 | 265-156-6 | 75 |
| 4  | pyrithione zinc                                        | 13463-41-7 | 236-671-3 | 75 |
| 5  | titanium dioxide                                       | 13463-67-7 | 236-675-5 | 75 |
| 6  | toluene                                                | 108-88-3   | 203-625-9 | 75 |

**Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances**

This product is not subject to Part 1 or 2 of Annex I.

**Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products**

relevant VOC limit value as referred to in Annex II of Directive 2004/42/CE, Cat. : c, type: wb = 100 g/l  
 Max. VOC content (limit value) of the product in its ready for use condition = < 100 g/l

**National regulations****Water Hazard Class (Germany)**

Class 2  
 Source Classification according to AwSV (Regulation on facilities for handling substances that are hazardous to water).

**Other regulations**

GISCODE BSW40 Covering agents, water based, alkaline

**Other national regulations**

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment. For example, TRGS (Technical Rules for Hazardous Substances) and the DGUV (German Social Accident Insurance) rules.

**15.2 Chemical safety assessment**

A chemical safety assessment has not been carried out for this mixture.

**SECTION 16: Other information****Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

**Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)**

|        |                                          |
|--------|------------------------------------------|
| EUH071 | Corrosive to the respiratory tract.      |
| H301   | Toxic if swallowed.                      |
| H302   | Harmful if swallowed.                    |
| H311   | Toxic in contact with skin.              |
| H314   | Causes severe skin burns and eye damage. |
| H315   | Causes skin irritation.                  |
| H317   | May cause an allergic skin reaction.     |
| H318   | Causes serious eye damage.               |
| H319   | Causes serious eye irritation.           |
| H330   | Fatal if inhaled.                        |
| H335   | May cause respiratory irritation.        |
| H360D  | May damage the unborn child.             |

**Trade name:** einza mineralit Sol Fassadenfarbe

**Product no.:** 0030903

**Current version:** 2.0.1, Revision: 28.07.2026

**Replaced version:** 2.0.0, Revision: 10.06.2026

**Region:**  
GER

|       |                                                                               |
|-------|-------------------------------------------------------------------------------|
| H372  | Causes damage to organs through prolonged or repeated exposure.               |
| H373i | May cause damage to organs through prolonged or repeated exposure if inhaled. |
| H400  | Very toxic to aquatic life.                                                   |
| H410  | Very toxic to aquatic life with long lasting effects.                         |

## Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

## Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: [umco@umco.de](mailto:umco@umco.de)

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

This document is an English translation of the legally compliant safety data sheet of the region Germany. This document, including UFI and emergency telephone number, may only be used for placing on the market in the region Germany.

Copyright-protected document. Any changes or reproductions require the express consent of UMCO GmbH.

Prod-ID 772861