

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 2 Stammlack

Product no.: 0071306

Current version: 1.1.0, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

einza mix Lawidur hgl 2K-PU-Buntlack, Basis 2 Stammlack

UFI:

E9NG-Q16Y-M001-G2JX

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

decorative paints/finishes

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

einza Farben GmbH & Co KG

Junkersstraße 13

30179 Hannover

Telephone no. +49 (0)511 67490-0

Fax no. +49 (0)511 67490-20

e-mail info@einza.com

Information provided by / telephone

In emergencies, the country-specific emergency number can be found in the corresponding country-specific safety data sheets.

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

+49 (0)40 0511 - 674 90-0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Aquatic Chronic 3; H412

Flam. Liq. 3; H226

STOT SE 3; H335

STOT SE 3; H336

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02



GHS07

Signal word

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 2 Stammlack

Product no.: 0071306

Current version: 1.1.0, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

Warning

Hazardous component(s) to be indicated on label:

Hydrocarbons, C9, aromatics

Hazard statement(s)

H226 Flammable liquid and vapour.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Hazard statements (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statement(s)

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 Use only outdoors or in a well-ventilated area.
P370+P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.
P405 Store locked up.
P501 Dispose of contents/container to a facility in accordance with local and national regulations.

UFI:

E9NG-Q16Y-M001-G2JX

2.3 Other hazards

The product does not contain any components > 0.1% that meet the criteria for PBT and vPvB according to Regulation (EC) No. 1907/2006, Annex XIII, or that have been included in the list compiled in accordance with Article 59(1). This product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not applicable. The product is not a substance.

3.2 Mixtures**Hazardous ingredients**

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	Hydrocarbons, C9, aromatics	pls. refer to footnote (2)	
	64742-95-6 918-668-5 649-356-00-4 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H335 STOT SE 3; H336 Aquatic Chronic 2; H411 Asp. Tox. 1; H304 EUH066	>= 10,00 - < 25,00 wt%
2	2-ethoxy-1-methylethyl acetate		
	54839-24-6 259-370-9 603-177-00-8 01-2119475116-39	Flam. Liq. 3; H226 STOT SE 3; H336	>= 5,00 - < 10,00 wt%
3	Reaction mass of xylene and ethylbenzene		

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 2 Stammlack

Product no.: 0071306

Current version: 1.1.0, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

	- 905-588-0 - 01-2119488216-32	Acute Tox. 4; H312 Acute Tox. 4; H332 Asp. Tox. 1; H304 Eye Irrit. 2; H319 Flam. Liq. 3; H226 Skin Irrit. 2; H315 STOT RE 2; H373 STOT SE 3; H335	< 5,00	wt%
4	n-butyl acetate			
	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	EUH066 Flam. Liq. 3; H226 STOT SE 3; H336	< 2,50	wt%
5	barium sulfate, natural			
	7727-43-7 231-784-4 - 01-2119491274-35	-	< 2,50	wt%
6	2-methoxy-1-methylethyl acetate			
	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336	< 2,50	wt%

Full text of H- and EUH-phrases, if not already mentioned in section 2.2: see section 16.

(2) According to the latest state of knowledge and applying the criteria set out in annex I to Regulation (EC) No 1272/2008, the aforementioned classification is required. This classification goes beyond the classification set out in table 3, Annex VI to Regulation (CE) No 1272/2008.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	P	-	-	-
3	-	STOT RE 2; H373: C ≥ 10%	-	-

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 2 Stammlack

Product no.: 0071306

Current version: 1.1.0, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO₂, powders, water spray

Unsuitable extinguishing media

water jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Do not allow to enter drains/watercourses/soil.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flatting] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 2 Stammlack**Product no.:** 0071306**Current version:** 1.1.0, Revision: 25.02.2026**Replaced version:** 1.0.0, Revision: 28.01.2026**Region:**
GER

Comply with legal health and safety regulations; Storage in accordance with the Ordinance on Industrial Safety and Health. Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Stoarge Class according TRGS 510

3 Flammable liquids

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limit values**

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
	TRGS 900		
	Kohlenwasserstoffgemische, Verwendung als Lösemittel (Lösemittelkohlenwasserstoffe), additiv-frei: C9-C15 Aromaten		
	WEL long-term (8-hr TWA reference period)	100	mg/m ³
	Ceiling Limit	2 (II)	
2	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9
	TRGS 900		
	2-Ethoxy-1-methylethylacetat		
	WEL long-term (8-hr TWA reference period)	120	mg/m ³ 20 ml/m ³
	Ceiling Limit	2(II)	
	Skin resorption / sensibilisation	H	
	Notes	Y, 14	
3	n-butyl acetate	123-86-4	204-658-1
	TRGS 900		
	n-Butylacetat		
	WEL long-term (8-hr TWA reference period)	300	mg/m ³ 62 ml/m ³
	Ceiling Limit	2(I)	
	Notes	Y	
	EU 2019/1831		
	n-Butyl acetate		
	WEL short-term (15 min reference period)	723	mg/m ³ 150 ppm
	WEL long-term (8-hr TWA reference period)	241	mg/m ³ 50 ppm
4	barium sulfate, natural	7727-43-7	231-784-4
	2006/15/EC		
	Barium (soluble compounds as Ba)		
	WEL long-term (8-hr TWA reference period)	0,5	mg/m ³
5	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
	TRGS 900		
	2-Methoxy-1-methylethylacetat		
	WEL long-term (8-hr TWA reference period)	270	mg/m ³ 50 ml/m ³
	Ceiling Limit	1(I)	
	Notes	Y	
	2000/39/EC		
	2-Methoxy-1-methylethylacetate		
	WEL short-term (15 min reference period)	550	mg/m ³ 100 ppm
	WEL long-term (8-hr TWA reference period)	275	mg/m ³ 50 ppm
	Skin resorption / sensibilisation	Skin	

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 2 Stammlack

Product no.: 0071306

Current version: 1.1.0, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER**DNEL, DMEL and PNEC values****DNEL values (worker)**

No	Substance name			CAS / EC no
	Route of exposure	Exposure time	Effect	Value
1	Hydrocarbons, C9, aromatics			64742-95-6 918-668-5
	inhalative	Long term (chronic)	systemic	0,64 mg/m ³
	inhalative	Short term (acut)	systemic	1286,4 mg/m ³
	inhalative	Long term (chronic)	local	837,5 mg/m ³
	inhalative	Short term (acut)	local	1066,67 mg/m ³
2	2-ethoxy-1-methylethyl acetate			54839-24-6 259-370-9
	dermal	Long term (chronic)	systemic	103 mg/kg/day
	inhalative	Long term (chronic)	systemic	152 mg/m ³
	inhalative	Short term (acut)	systemic	2366 mg/m ³
3	Reaction mass of xylene and ethylbenzene			- 905-588-0
	dermal	Long term (chronic)	systemic	212,00 mg/kg/day
	inhalative	Short term (acut)	systemic	442,00 mg/m ³
	inhalative	Short term (acut)	local	442,00 mg/m ³
	inhalative	Long term (chronic)	systemic	221,00 mg/m ³
	inhalative	Long term (chronic)	local	221,00 mg/m ³
4	n-butyl acetate			123-86-4 204-658-1
	dermal	Long term (chronic)	systemic	11 mg/kg/day
	dermal	Short term (acut)	systemic	11 mg/kg/day
	inhalative	Long term (chronic)	systemic	300 mg/m ³
	inhalative	Short term (acut)	systemic	600 mg/m ³
	inhalative	Long term (chronic)	local	300 mg/m ³
	inhalative	Short term (acut)	local	600 mg/m ³
5	2-methoxy-1-methylethyl acetate			108-65-6 203-603-9
	dermal	Long term (chronic)	systemic	796 mg/kg/day
	inhalative	Long term (chronic)	systemic	275 mg/m ³
	inhalative	Short term (acut)	local	550 mg/m ³

DNEL value (consumer)

No	Substance name			CAS / EC no
	Route of exposure	Exposure time	Effect	Value
1	Hydrocarbons, C9, aromatics			64742-95-6 918-668-5
	inhalative	Long term (chronic)	systemic	0,113 mg/m ³
	inhalative	Short term (acut)	systemic	1,152 mg/m ³
	inhalative	Long term (chronic)	local	178,57 mg/m ³
	inhalative	Short term (acut)	local	640 mg/m ³
2	2-ethoxy-1-methylethyl acetate			54839-24-6 259-370-9
	oral	Long term (chronic)	systemic	13,1 mg/kg/day
	dermal	Long term (chronic)	systemic	62 mg/kg/day
	inhalative	Long term (chronic)	systemic	181 mg/m ³
	inhalative	Short term (acut)	systemic	1420 mg/m ³
3	Reaction mass of xylene and ethylbenzene			- 905-588-0
	oral	Long term (chronic)	systemic	5 mg/kg/day
	dermal	Long term (chronic)	systemic	125,00 mg/kg/day
	inhalative	Short term (acut)	systemic	260,00 mg/m ³
	inhalative	Long term (chronic)	systemic	65,30 mg/m ³
	inhalative	Short term (acut)	local	260,00 mg/m ³
	inhalative	Long term (chronic)	local	65,30 mg/m ³

EU safety data sheet



Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 2 Stammlack

Product no.: 0071306

Current version: 1.1.0, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

4	n-butyl acetate			123-86-4 204-658-1
	oral	Long term (chronic)	systemic	2 mg/kg/day
	oral	Short term (acut)	systemic	2 mg/kg/day
	dermal	Long term (chronic)	systemic	6 mg/kg/day
	dermal	Short term (acut)	systemic	6 mg/kg/day
	inhalative	Long term (chronic)	systemic	35,7 mg/m ³
	inhalative	Short term (acut)	systemic	300 mg/m ³
	inhalative	Long term (chronic)	local	35,7 mg/m ³
	inhalative	Short term (acut)	local	300 mg/m ³
5	2-methoxy-1-methylethyl acetate			108-65-6 203-603-9
	oral	Long term (chronic)	systemic	36 mg/kg/day
	oral	Short term (acut)	systemic	500 mg/kg/day
	dermal	Long term (chronic)	systemic	320 mg/kg/day
	inhalative	Long term (chronic)	systemic	33 mg/m ³
	inhalative	Long term (chronic)	local	33 mg/m ³

PNEC values

No	Substance name		CAS / EC no
	ecological compartment	Type	Value
1	2-ethoxy-1-methylethyl acetate		54839-24-6 259-370-9
	water	fresh water	2 mg/L
	water	marine water	0,2 mg/L
	water	Aqua intermittent	2 mg/L
	water	fresh water sediment	8,2 mg/kg dry weight
	water	marine water sediment	0,82 mg/kg dry weight
	soil	-	0,67 mg/kg dry weight
	sewage treatment plant	-	62,5 mg/L
	secondary poisoning	-	117 mg/kg food
2	Reaction mass of xylene and ethylbenzene		- 905-588-0
	water	fresh water	0,1 mg/L
	water	marine water	0,01 mg/L
	water	fresh water sediment	13,7 mg/kg
	water	marine water sediment	1,37 mg/kg
	soil	-	2,68 mg/kg dry weight
	sewage treatment plant	-	9,6 mg/L
	secondary poisoning	-	0,02 g/kg
3	n-butyl acetate		123-86-4 204-658-1
	water	fresh water	0,18 mg/L
	water	marine water	0,018 mg/L
	water	fresh water sediment	0,981 mg/kg dry weight
	water	marine water sediment	0,098 mg/kg dry weight
	soil	-	0,09 mg/kg
	sewage treatment plant	-	35,6 mg/L
4	2-methoxy-1-methylethyl acetate		108-65-6 203-603-9
	water	fresh water	0,635 mg/L
	water	marine water	0,064 mg/L
	water	fresh water sediment	3,29 mg/kg
	with reference to: dry weight		
	water	marine water sediment	0,329 mg/kg

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 2 Stammlack**Product no.:** 0071306**Current version:** 1.1.0, Revision: 25.02.2026**Replaced version:** 1.0.0, Revision: 28.01.2026**Region:**
GER

	with reference to: dry weight			
	soil	-	0,29	mg/kg
	with reference to: dry weight			
	sewage treatment plant	-	100	mg/L

8.2 Exposure controls

Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

Eye / face protection

Wear safety goggles to protect against splashes. Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material In case of short-term contact / splash protection: nitrile rubber

Material thickness > 0,4 mm

Breakthrough time > 120 min

Appropriate Material In case of prolonged exposure: nitrile rubber

Material thickness > 0,4 mm

Breakthrough time > 480 min

Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation

liquid

Form

liquid

Colour

according to product name

Odour

like solvents

pH value

reason for missing pH

substance/mixture is non-soluble (in water)

Boiling point / boiling range

Value > 120 °C

Reference substance solvent mixture

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 2 Stammlack

Product no.: 0071306

Current version: 1.1.0, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

Melting point/freezing point			
No data available			
Decomposition temperature			
No data available			
Flash point			
Value	40	- 42	°C
Method	closed cup		
Ignition temperature			
Value	>	200	°C
Reference substance	solvent mixture		
Oxidising properties			
Not applicable			
Flammability			
Not applicable			
Lower explosion limit			
Value	>	0,6	% vol
Reference substance	solvent mixture		
Upper explosion limit			
Value	<	7,5	% vol
Reference substance	solvent mixture		
Vapour pressure			
Value	<	100	hPa
Reference temperature		50	°C
Reference substance	solvent mixture		
Relative vapour density			
No data available			
Relative density			
No data available			
Density			
Value	1,17	- 1,22	g/cm³
Reference temperature		20	°C
Method	DIN 51757		
Solubility in water			
Comments	immiscible		
Solubility			
No data available			
Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9
log Pow		0,76	
Reference temperature		22	°C
with reference to		pH 7	
Source		ECHA	
2	n-butyl acetate	123-86-4	204-658-1
log Pow		2,3	
Reference temperature		25	°C
Method		OECD 117	
Source		ECHA	
3	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
log Pow		1,2	
Reference temperature		20	°C
Method		OECD 117	

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 2 Stammlack**Product no.:** 0071306**Current version:** 1.1.0, Revision: 25.02.2026**Replaced version:** 1.0.0, Revision: 28.01.2026**Region:**
GER

Source	ECHA
--------	------

Kinematic viscosity			
Value	40	- 55	sec
Reference temperature		20	°C
Method	DIN EN 2431 (6 mm)		

Solvent separation test			
Value	<	3	%
Reference temperature		20	°C

Particle characteristics	
No data available	

9.2 Other information

Other information
No data available.

SECTION 10: Stability and reactivity**10.1 Reactivity**

Stable under recommended storage and handling conditions (See section 7).

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
LD50		10760	mg/kg bodyweight
Species	rat		
Method	OECD 423		
Source	ECHA		
2	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
LD50		5155	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		

Acute dermal toxicity (result of the ATE calculation for the mixture)	
Product Name	
einza mix Lawidur hgl 2K-PU-Buntlack, Basis 2 Stammlack	
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE dermal > 2000 mg/kg).

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 2 Stammlack

Product no.: 0071306

Current version: 1.1.0, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
LD50	>	14112	mg/kg bodyweight
Species	rabbit		
Method	OECD 402		
Source	ECHA		
2	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
LD50	>	5000	mg/kg bodyweight
Species	rat		
Method	OECD 402		
Source	ECHA		

Acute inhalational toxicity (result of the ATE calculation for the mixture)	
Product Name	
einza mix Lawidur hgl 2K-PU-Buntlack, Basis 2 Stammlack	
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE for inhalation: > 20.000 ppmV (gases), > 20 mg/l (vapours), > 5 mg/l (dusts/mists).

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9
LC50	>	6,99	mg/l
Duration of exposure		4	h
State of aggregation	Dust/mist		
Species	rat		
Method	OECD 403		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9
Duration of exposure		4	h
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	n-butyl acetate	123-86-4	204-658-1
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		
3	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	non-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 2 Stammlack

Product no.: 0071306

Current version: 1.1.0, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

2	Reaction mass of xylene and ethylbenzene	-	905-588-0
Species	rabbit		
Source	ECHA		
Evaluation	irritant		
Evaluation/classification	Based on available data, the classification criteria are met.		
3	n-butyl acetate	123-86-4	204-658-1
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	non-irritant		
4	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	non-irritant		

Respiratory or skin sensitisation

No	Substance name	CAS no.	EC no.
1	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9
Route of exposure	Skin		
Species	guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
Route of exposure	Skin		
Species	guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		

Germ cell mutagenicity

No	Substance name	CAS no.	EC no.
1	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9
Type of examination	in vitro gene mutation study in bacteria		
Species	Salmonella typhimurium		
Method	OECD 471		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	n-butyl acetate	123-86-4	204-658-1
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
Type of examination	in vitro gene mutation study in bacteria		
Method	OECD 471		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Reproduction toxicity

No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Carcinogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No	Substance name	CAS no.	EC no.
----	----------------	---------	--------

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 2 Stammlack

Product no.: 0071306

Current version: 1.1.0, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

1	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9
Route of exposure	dermal		
Duration of exposure		3	months
Species	rabbit		
Method	OECD 411		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are met.		
2	n-butyl acetate	123-86-4	204-658-1
Route of exposure	inhalational		
NOAEC		500	ppm
Duration of exposure		90	day(s)
Species	rat		
Method	EPA OTS 798.2450		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
Route of exposure	oral		
Species	rats (male/female)		
Method	OECD 422		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Aspiration hazard

No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

11.2 Information on other hazards**Endocrine disrupting properties**

No data available

Other information

No data available.

SECTION 12: Ecological information**12.1 Toxicity**

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
LL50		10	mg/l
Duration of exposure		96	h
Species	Oncorhynchus mykiss		
Method	OECD 203		
Source	ECHA		
2	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9
LC50		140	mg/l
Duration of exposure		96	h
Species	Oncorhynchus mykiss		
Method	OECD 203		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 2 Stammlack

Product no.: 0071306

Current version: 1.1.0, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

3	n-butyl acetate	123-86-4	204-658-1
LC50		18	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	OECD 203		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
4	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
LC50	100	- 180	mg/l
Duration of exposure		96	h
Species	Oncorhynchus mykiss		
Method	OECD 203		
Source	ECHA		

Toxicity to fish (chronic)

No data available

Toxicity to Daphnia (acute)

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
EL50		4,5	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		
2	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9
EC50		110	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	n-butyl acetate	123-86-4	204-658-1
EC50		44	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
4	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
EC50	>	500	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	EU Method C.2		
Source	ECHA		

Toxicity to Daphnia (chronic)

No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
NOEC		23	mg/l
Duration of exposure		21	day(s)
Species	Daphnia magna		
with reference to	CAS 110-19-0		
Method	OECD 211		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
NOEC	>=	100	mg/l
Duration of exposure		21	day(s)
Species	Daphnia magna		
Method	OECD 211		
Source	ECHA		

Toxicity to algae (acute)

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 2 Stammlack

Product no.: 0071306

Current version: 1.1.0, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
EL50		3,1	mg/l
Duration of exposure		72	h
Species	Raphidocelis subcapitata		
Method	OECD 201		
Source	ECHA		
2	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9
EC50		>	100
Duration of exposure		72	mg/l h
Species	Desmodesmus subspicatus		
Method	OECD 201		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	n-butyl acetate	123-86-4	204-658-1
EC50		397	mg/l
Duration of exposure		72	h
Species	Selenastrum capricornutum		
Method	OECD 201		
Source	ECHA		
4	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
EC50		>	1000
Duration of exposure		96	mg/l h
Species	Raphidocelis subcapitata		
Method	OECD 201		
Source	ECHA		

Toxicity to algae (chronic)

No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
NOEC		196	mg/l
Duration of exposure		72	h
Species	Raphidocelis subcapitata		
Method	OECD 201		
Source	ECHA		

Bacteria toxicity

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
EC50		>	99
Duration of exposure		10	mg/l min
Species	activated sludge		
Method	OECD 209		
Source	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
IC50		356	mg/l
Duration of exposure		40	h
Species	Tetrahymena pyriformis (Protozoa)		
Source	ECHA		
3	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
EC10		>	1000
Duration of exposure		30	mg/l min
Species	activated sludge		
Method	OECD 209		
Source	ECHA		

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
Type	BSB		
Value		78	%

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 2 Stammlack

Product no.: 0071306

Current version: 1.1.0, Revision: 25.02.2026

Replaced version: 1.0.0, Revision: 28.01.2026

Region:
GER

Duration	28	d
Method	OECD 301 F	
Source	ECHA	
Evaluation	readily biodegradable	
2	2-ethoxy-1-methylethyl acetate	54839-24-6 259-370-9
Type	aerobic biodegradation	
Value	100	%
Duration	28	d
Method	OECD 301 D	
Source	ECHA	
Evaluation	readily biodegradable	
3	n-butyl acetate	123-86-4 204-658-1
Type	aerobic biodegradation	
Value	83	%
Duration	28	day(s)
Method	OECD 301 D	
Source	ECHA	
Evaluation	readily biodegradable	
4	2-methoxy-1-methylethyl acetate	108-65-6 203-603-9
Type	aerobic biodegradation	
Value	83	%
Duration	28	day(s)
Method	OECD 301 F	
Source	ECHA	
Evaluation	readily biodegradable	

Abiotic Degradation

No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
Type	Photolysis		
Half-life	3,3	day(s)	
Reference temperature	25	°C	
Source	ECHA		

12.3 Bioaccumulative potential

Bioconcentration factor (BCF)			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
BCF	15,3		
Method	Calculation model used (Q)SAR		
Source	ECHA		

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9
log Pow	0,76		
Reference temperature	22	°C	
with reference to	pH 7		
Source	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
log Pow	2,3		
Reference temperature	25	°C	
Method	OECD 117		
Source	ECHA		
3	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
log Pow	1,2		
Reference temperature	20	°C	
Method	OECD 117		
Source	ECHA		

12.4 Mobility in soil

No data available.

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 2 Stammlack**Product no.:** 0071306**Current version:** 1.1.0, Revision: 25.02.2026**Replaced version:** 1.0.0, Revision: 28.01.2026**Region:**
GER**12.5 Results of PBT and vPvB assessment**

Results of PBT and vPvB assessment		
No	Substance name	CAS no. EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6 918-668-5
PBT assessment		The substance is not PBT.
vPvB assessment		The substance is not vPvB.
Source		ECHA

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information
Do not allow to enter drains or water courses.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Waste code 08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company.

Allow paint/varnish to dry out completely in a well-ventilated area and dispose of in residual waste once completely solidified. Dispose of liquid or non-drying residues separately.

Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

SECTION 14: Transport information**14.1 UN number or ID number**

ADR/RID/ADN UN1263
IMDG UN1263
ICAO-TI / IATA UN1263

14.2 UN proper shipping name

ADR/RID/ADN PAINT
IMDG PAINT
ICAO-TI / IATA Paint

14.3 Transport hazard class(es)

ADR/RID/ADN - Class 3
Label 3
Classification code F1
Tunnel restriction code D/E
Hazard identification no. 30
Comments (ADR/RID/ADN) Containers with a capacity <= 450 ltrs are not subject to ADR-regulations (refer to 2.2.3.1.5.)

IMDG - Class 3
Label 3
Comments (IMDG) Containers with a capacity <= 450 ltrs are not subjected to IMDG regulations, chapter 4.1, 5.2 and 6.1 (see IMDG-Code 2.3.2.5)

ICAO-TI / IATA - Class 3

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 2 Stammlack**Product no.:** 0071306**Current version:** 1.1.0, Revision: 25.02.2026**Replaced version:** 1.0.0, Revision: 28.01.2026**Region:**
GER

Label 3

14.4 Packing group

ADR/RID/ADN	III
IMDG	III
ICAO-TI / IATA	III

14.5 Environmental hazards

EmS F-E+S-E

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations****Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3, 40
--	----------

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	2-methoxypropyl acetate	70657-70-4	274-724-2	75
2	2-methylpropan-1-ol	78-83-1	201-148-0	75
3	propylene carbonate	108-32-7	203-572-1	75
4	titanium dioxide	13463-67-7	236-675-5	75
5	xylene	1330-20-7	215-535-7	75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:	P5c
--	-----

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)

VOC content	40,66 %
-------------	---------

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products

relevant VOC limit value as referred to in Annex II of Directive 2004/42/CE, Cat. : j, type: Ib = 500 g/l
Max. VOC content (limit value) of the product in its ready for use condition = < 500 g/l

National regulations**Water Hazard Class (Germany)**

Class	2
Source	Classification according to AwSV (Regulation on facilities for handling substances that are hazardous to water).

Other regulations

GISCODE	PU50	PU systems, containing solvents, harmful, sensitising
---------	------	---

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 2 Stammlack**Product no.:** 0071306**Current version:** 1.1.0, Revision: 25.02.2026**Replaced version:** 1.0.0, Revision: 28.01.2026**Region:**
GER**Other national regulations**

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment. For example, TRGS (Technical Rules for Hazardous Substances) and the DGUV (German Social Accident Insurance) rules.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects.

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

P	The harmonised classification as a carcinogen applies unless the full refining history is known and it can be shown that the substance from which it is produced is not a carcinogen, in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.
---	--

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

This document is an English translation of the legally compliant safety data sheet of the region Germany. This document, including UFI and emergency telephone number, may only be used for placing on the market in the region Germany.

Copyright-protected document. Any changes or reproductions require the express consent of UMCO GmbH.

Prod-ID 653577