

Product no.: 0071709

Current version: 4.1.0, issued: 03.01.2024 Replaced version: 4.0.0. issued: 04.07.2023 Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1 1 **Product identifier**

Trade name

einzA mix Lawinol, Basis ME seidenglänzend

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

decorative paints/finishes

Uses advised against

No data available

1.3 Details of the supplier of the safety data sheet

Address

einzA Farben GmbH & Co KG

Junkersstraße 13 30179 Hannover

+49 (0)511 67490-0 Telephone no. +49 (0)511 67490-20 Fax no info@einzA.com

Advice on Safety Data Sheet

sdb info@umco.de

Emergency telephone number

For medical advice (in German and English): +49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Flam. Liq. 3; H226 STOT SE 3: H336

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC)

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms





Signal word Warning

Hazardous component(s) to be indicated on label:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hazard statement(s)

H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness.



Product no.: 0071709

Current version: 4.1.0, issued: 03.01.2024 Replaced version: 4.0.0, issued: 04.07.2023 Region: GB

Hazard statements (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.
EUH208 Contains phthalic-anhydride. May produce an allergic reaction.

Precautionary statement(s)

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P271 Use only outdoors or in a well-ventilated area.

P370+P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to

extinguish.

P405 Store locked up.

P501 Dispose of contents/container to a facility in accordance with local and national

regulations.

2.3 Other hazards

PBT assessment

The components of this product are not considered to be a PBT.

vPvB assessment

The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Hazardous ingredients

No	Substance name		Addit	tional information	
	CAS / EC / Index /	Classification (EC) 1272/2008 (CLP)	Conc	entration	%
	REACH no				
1	Hydrocarbons, C9-	C11, n-alkanes, isoalkanes, cyclics, <2%			
	aromatics				
	64742-48-9	Asp. Tox. 1; H304	>=	25.00 - < 50	.00 wt%
	919-857-5	EUH066			
	-	Flam. Liq. 3; H226			
	01-2119463258-33	STOT SE 3; H336			
2	Hydrocarbons, C10	0-C13, n-alkanes, isoalkanes, cyclics, <2%			
	aromatics				
	-	Asp. Tox. 1; H304	>=	10.00 - < 25	.00 wt%
	918-481-9	EUH066			
	-				
	01-2119457273-39				
3	aluminium powder	(stabilised)			
	7429-90-5	Flam. Sol. 1; H228	<	5.00	wt%
	231-072-3				
	013-002-00-1				
	01-2119529243-45				
4	phthalic-anhydride				
	85-44-9	Acute Tox. 4*; H302	<	0.50	wt%
	201-607-5	Eye Dam. 1; H318			
	607-009-00-4	Resp. Sens. 1; H334			
	-	Skin Irrit. 2; H315			
		Skin Sens. 1; H317			
		STOT SE 3; H335			

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(*,**,***,****) Detailed explanation pls. refer to CLP regulation No. 1272/2008, annex VI, 1.2

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
3	T	<u>-</u>	-	-



Trade name: einzA mix Lawinol, Basis ME seidenglänzend

Product no.: 0071709

Current version: 4.1.0, issued: 03.01.2024 Replaced version: 4.0.0, issued: 04.07.2023 Region: GB

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO2, powders, water spray

Unsuitable extinguishing media

water jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO2); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.



Product no.: 0071709

Current version: 4.1.0, issued: 03.01.2024 Replaced version: 4.0.0, issued: 04.07.2023 Region: GB

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flatting] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.		EC no.		
1	aluminium powder (stabilised)	7429-90-5		231-072-3		
	List of approved workplace exposure limits (WELs) / EH40					
	Aluminium metal					
	total inhalable dust					
	WEL long-term (8-hr TWA reference period)	10	mg/m³			
	List of approved workplace exposure limits (WELs) / E	H40				
	Aluminium metal					
	respirable dust	•	•			
	WEL long-term (8-hr TWA reference period)	4	mg/m³			

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name			CAS / EC no
	Route of exposure	Exposure time	Effect	Value



Trade name: einzA mix Lawinol, Basis ME seidenglänzend

Product no.: 0071709

Current version: 4.1.0, issued: 03.01.2024 Replaced version: 4.0.0, issued: 04.07.2023 Region: GB

1				64742-48-9 919-857-5	
	dermal	Long term (chronic)	systemic	77	mg/kg/day
	inhalative	Long term (chronic)	systemic	871	mg/m³
2	aluminium powder (stabilised)			7429-90-5	
			231-072-3		
	inhalative	Long term (chronic)	local	3.72	mg/m³

DNEL value (consumer)

No	Substance name				
	Route of exposure	Exposure time	Effect	Value	
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			64742-48-9	
				919-857-5	
	oral	Long term (chronic)	systemic	46	mg/kg/day
	dermal	Long term (chronic)	systemic	46	mg/kg/day
	inhalative	Long term (chronic)	systemic	185	mg/m³
2	aluminium powder (stabilised)			7429-90-5	
				231-072-3	
	oral	Long term (chronic)	systemic	3.95	mg/kg/day

PNFC values

No	Substance name		CAS / EC no	
	ecological compartment	Туре	Value	
1	aluminium powder (stabilised)		7429-90-5	
			231-072-3	
	water	fresh water	74.9	μg/L
	sewage treatment plant	-	20	mg/L

8.2 Exposure controls

Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

Eye / face protection

Wear safety googles to protect against splashes. Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific workstation suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material In case of short-term contact / splash protection: nitrile rubber

Material thickness>0.4mmBreakthrough time>120minAppropriate MaterialIn case of prolonged exposure: nitrile rubberMaterial thickness>0.4mmBreakthrough time>480min

Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls

Do not allow to enter drains or water courses.



Product no.: 0071709

Current version: 4.1.0, issued: 03.01.2024 Replaced version: 4.0.0, issued: 04.07.2023 Region: GB

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation			
Form			
liquid			
Colour			
according to product name			
Odour			
like solvents			
pH value			
No data available			
Boiling point / boiling range			
Value Reference substance	>	120	°C
	solvent mixture		
Melting point/freezing point No data available			
Decomposition temperature			
No data available			
Flash point			
Value		40	°C
Method	closed cup		
Ignition temperature			
Value Reference substance	> solvent mixture	200	°C
	Solvent mixture		
Oxidising properties Not applicable			
Flammability			
Not applicable			
Lower explosion limit			
Value	>	0.6	% vol
Reference substance	solvent mixture		
Upper explosion limit			
Value Reference substance	<pre></pre>	7.5	% vol
	solvent mixture		
Vapour pressure Value	 	100	hPa
Reference temperature		50	nPa °C
Reference substance	solvent mixture		
Relative vapour density			
No data available			
Relative density			
No data available			
Density			
Value	appr.	0.95	g/cm³
Reference temperature Method	DIN 51757	20	°C
	12		
Solubility in water			



Product no.: 0071709

Current version: 4.1.0, issued: 03.01.2024 Replaced version: 4.0.0, issued: 04.07.2023 Region: GB

Comments	immiscible
Solubility	
No data available	

Part	Partition coefficient n-octanol/water (log value)							
No	Substance name		CAS no.			EC	no.	
1	1 Hydrocarbons, C10-C13, n-alkanes, isoalkanes,		-			918	3-481-9	
	cyclics, <2% aromatics							
log F	Pow	3.17		-	7.22			
Meth	nod	QSAR						
Soul	rce	ECHA						

Kinematic viscosity					
Value	57 - 63 sec				
Reference temperature	20 °C				
Method	DIN EN 2431 (6 mm)				

Solvent separation test				
Value	<	3	%	
Reference temperature		20	°C	

Particle characteristics	
No data available	

9.2 Other information

Other information	
No data available.	

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage and handling conditions (See section 7).

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acu	Acute oral toxicity						
No	Substance name		CAS no.		EC no.		
1	Hydrocarbons, C9-C11, n-alkanes, isoalk cyclics, <2% aromatics	anes,	64742-48-9		919-857-5		
LD5	0	>		5000	mg/kg bodyweight		
Spec	cies	rat					
Meth	nod	OECD 401					
Soul	rce	ECHA					
2	Hydrocarbons, C10-C13, n-alkanes, isoa	lkanes,	-		918-481-9		
	cyclics, <2% aromatics						
LD5	0	>		15000	mg/kg bodyweight		
Spec	cies	rat					



Trade name: einzA mix Lawinol, Basis ME seidenglänzend

Product no.: 0071709

Current version: 4.1.0, issued: 03.01.2024 Replaced version: 4.0.0, issued: 04.07.2023 Region: GB

MethodOECD 401SourceECHAEvaluation/classificationBased on available data, the classification criteria are not met.

Acu	Acute dermal toxicity							
No	Substance name		CAS no.		EC no.			
1	Hydrocarbons, C9-C11, n-alkanes, isoalk	anes,	64742-48-9		919-857-5			
	cyclics, <2% aromatics							
LD5	0	>		2000	mg/kg bodyweight			
Spe	cies	rabbit						
Meth	nod	OECD 402						
Soul	rce	ECHA						

Acu	Acute inhalational toxicity							
No	Substance name		CAS no.		EC no.			
1	aluminium powder (stabilised)		7429-90-5		231-072-3			
LC5	0			0.888	mg/l			
Dura	ation of exposure			4	h			
Stat	e of aggregation	Dust						
		rat						
Sou	rce	ECHA						

Skir	Skin corrosion/irritation								
No	Substance name		CAS no.	EC no.					
1	Hydrocarbons, C9-C11, n-alkanes, isoalka cyclics, <2% aromatics	anes,	64742-48-9	919-857-5					
Spe	cies	rabbit							
Meth	nod	OECD 404							
Sou	Source								
Eval	Evaluation								

Seri	Serious eye damage/irritation						
No	Substance name		CAS no.	EC no.			
1	Hydrocarbons, C9-C11, n-alkanes, isoalk	anes,	64742-48-9	919-857-5			
	cyclics, <2% aromatics						
Spe	cies	rabbit					
Meth	Method						
Sou	rce	ECHA					
Eval	Evaluation						

Res	Respiratory or skin sensitisation							
No	Substance name		CAS no.	EC no.				
1	Hydrocarbons, C9-C11, n-alkanes, isoalk	anes,	64742-48-9	919-857-5				
	cyclics, <2% aromatics							
Rou	te of exposure	Skin						
Spec	cies	guinea pig						
Meth			OECD 406					
Soul	Source							
Eval	uation	non-sensitizir	ng					

Germ cell mutagenicity		
No Substance name	CAS no.	EC no.
1 Hydrocarbons, C10-C13, n-alkanes,	isoalkanes, -	918-481-9
cyclics, <2% aromatics		
Type of examination	in vitro gene mutation stud	dy in bacteria
Species	S. typhimurium TA 1535,	TA 1537, TA 98 and TA 100S. typhimurium
	TA 1535, TA 1537, TA 98,	TA 100, TA 102
Method	OECD 471	
Source	ECHA	
Evaluation/classification	Based on available data, t	the classification criteria are not met.
Route of exposure	oral	
Type of examination	In vivo mammalian somat	ic cell study: cytogenicity / erythrocyte
	micronucleus	
Species	mouse	



Product no.: 0071709

Current version: 4.1.0, issued: 03.01.2024 Replaced version: 4.0.0, issued: 04.07.2023 Region: GB

Method
Source
Evaluation/classification

OECD 474
ECHA
Based on available data, the classification criteria are not met.

Reproduction toxicity
No data available

Carcinogenicity
No data available

STOT - single exposure
No data available

STOT - repeated exposure							
No	Substance name		CAS no.		EC no.		
1	Hydrocarbons, C10-C13, n-alkanes, isoal cyclics, <2% aromatics	lkanes,	-		918-481-9		
Rout	te of exposure	oral					
NOA	EL	>=		500	mg/kg bw/d		
Spec	cies	rat					
Method		OECD 408					
Source		ECHA					
Eval	uation/classification	Based on ava	ailable data, th	e classificatio	n criteria are not met.		

Aspiration hazard
No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

11.2 Information on other hazards

Endocrine disrupting properties

No data available.

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Tox	Toxicity to fish (acute)							
No	Substance name		CAS no.		EC no.			
1	Hydrocarbons, C9-C11, n-alkanes, isoalk	anes,	64742-48-9		919-857-5			
	cyclics, <2% aromatics							
LL5	0	>		1000	mg/l			
Dura	ation of exposure			96	h			
Species		Rainbow trout						
Met	hod	OECD 203						
Sou	rce	ECHA						

loxicity	to fish ((chronic)

No data available

Tox	icity to Daphnia (acute)		
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	919-857-5



Product no.: 0071709

Current version: 4.1.0, issued: 03.01.2024 Replaced version: 4.0.0, issued: 04.07.2023 Region: GB

EL50	>	1000	mg/l
Duration of exposure		48	h
Species	cies Daphnia magna		
with reference to	WAF (water accommodated fractions)		
Method	OECD 202		
Source	ECHA		

Toxicity to Daphnia (chronic)

No data available

Toxi	Toxicity to algae (acute)					
No	Substance name		CAS no.		EC no.	
1	Hydrocarbons, C9-C11, n-alkanes, isoalk	anes,	64742-48-9		919-857-5	
	cyclics, <2% aromatics					
EL50)	>		1000	mg/l	
Dura	ation of exposure			72	h	
Species		Pseudokirchr	eriella subcapita	ata		
with reference to		WAF (water a	ccommodated f	ractions)		
Method		OECD 201				
Source		ECHA				

Toxicity to algae (chronic)

No data available

Bacteria toxicity No data available

12.2 Persistence and degradability

Biod	Biodegradability				
No	Substance name	CAS no.	EC no.		
1	Hydrocarbons, C9-C11, n-alkanes, isoalk	anes, 64742-48-9	919-857-5		
	cyclics, <2% aromatics				
Meth	nod	OECD 301 F			
Soul	ce	ECHA			
Evaluation		readily biodegradable			

12.3 Bioaccumulative potential

Part	Partition coefficient n-octanol/water (log value)						
No	Substance name		CAS no.			EC no.	
1	Hydrocarbons, C10-C13, n-alkanes, isoal cyclics, <2% aromatics	lkanes,	-			918-481-9	
log F	Pow	3.17		-	7.22		
Meth	nod	QSAR					
Soul	rce	ECHA					

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment			
PBT assessment	The components of this product are not considered to be a PBT.		
vPvB assessment	The components of this product are not considered to be a vPvB.		

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information	
Do not allow to enter drains or water courses.	

SECTION 13: Disposal considerations



Trade name: einzA mix Lawinol, Basis ME seidenglänzend

Product no.: 0071709

Current version: 4.1.0, issued: 03.01.2024 Replaced version: 4.0.0, issued: 04.07.2023 Region: GB

13.1 Waste treatment methods

Product

Waste code 08 01 11* waste paint and varnish containing organic solvents or other hazardous

substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company. Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class 3
Classification code F1
Packing group III
Hazard identification no. 30
UN number UN1263
Proper shipping name PAINT

Tunnel restriction code D/E label 3

Comments Containers with a capacity <= 450 ltrs are not subject to ADR-regulations (refer to

2.2.3.1.5.)

14.2 Transport IMDG

Class 3
Packing group III
UN number UN1263
Proper shipping name PAINT

EmS F-E+S-E

Label 3

Comments Containers with a capacity <= 450 ltrs are not subjected to IMDG regulations,

chapter 4.1, 5.2 and 6.1 (see IMDG-Code 2.3.2.5)

14.3 Transport ICAO-TI / IATA

Class 3
Packing group III
UN number UN1263
Proper shipping name Paint
Label 3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU regulations</u>

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)



Trade name: einzA mix Lawinol, Basis ME seidenglänzend

Product no.: 0071709

Current version: 4.1.0, issued: 03.01.2024 Replaced version: 4.0.0, issued: 04.07.2023 Region: GB

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3, 40

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	2-(2-butoxyethoxy)ethanol	112-34-5	203-961-6	75
2	2-methylpentane-2,4-diol	107-41-5	203-489-0	75
3	aluminium powder (stabilised)	7429-90-5	231-072-3	75
4	phthalic-anhydride	85-44-9	201-607-5	75
5	propylene carbonate	108-32-7	203-572-1	75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances This product is subject to Part I of Annex I, risk category: P5c

Directive 2010/75/EU on industrial emissions	(integrated pollution prevention and control)
VOC content	48.38 %

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products

relevant VOC limit value as referred to in Annex II of Directive 2004/42/CE, Cat.: i, type: lb = 500 g/l Max. VOC content (limit value) of the product in its ready for use condition = < 500 g/l

National regulations

Other national regulations

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H228 Flammable solid. H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)



Trade name: einzA mix Lawinol, Basis ME seidenglänzend

Product no.: 0071709

Current version: 4.1.0, issued: 03.01.2024 Replaced version: 4.0.0, issued: 04.07.2023 Region: GB

Т

This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be included in the safety data sheet.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH. Prod-ID 663488