Current version : 8.4.0. issued: 21.12.2023

Replaced version: 8.3.1, issued: 07.08.2023

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 **Product identifier**

Trade name

### einzA mix Novatrol Alpenöl Silvershine, Basis ME

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture decorative paints/finishes

Uses advised against No data available.

### 1.3 Details of the supplier of the safety data sheet

#### Address

einzA Farben GmbH & Co KG Junkersstraße 13 30179 Hannover

 Telephone no.
 +49 (0)511 67490-0

 Fax no.
 +49 (0)511 67490-20

 e-mail
 info@einzA.com

Advice on Safety Data Sheet sdb\_info@umco.de

#### 1.4 Emergency telephone number

For medical advice (in German and English): +49 (0)551 192 40 (Giftinformationszentrum Nord)

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

#### **Classification information**

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

This product does not meet the classification criteria given in the Regulation (EC) No 1272/2008 (CLP).

### 2.2 Label elements

### Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

#### Hazard pictograms

Signal word

Hazard statement(s)

Hazard statements (EU)

Contains 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

EUH210

EUH208

Safety data sheet available on request.

#### Precautionary statement(s)

#### Labelling information

The labelling (EU hazard statements) meets the criteria of annex II of Directive (EC) Nr. 1272/2008 (CLP).

Product no.: 0074053

Current version : 8.4.0, issued: 21.12.2023

Region: GB

2.3 Other hazards

PBT assessment

The components of this product are not considered to be a PBT.

### vPvB assessment

The components of this product are not considered to be a vPvB.

**SECTION 3: Composition/information on ingredients** 

### 3.1 Substances

Not applicable. The product is not a substance.

### 3.2 Mixtures

#### Hazardous ingredients

No	No Substance name Additional information				
110	CAS / EC / Index /	Classification (EC) 1272/2008 (CLP)	Concentration	%	
	REACH no		Concontration	70	
1	2-butoxyethanol				
	111-76-2	Acute Tox. 4; H302	< 2.50	wt%	
	203-905-0	Acute Tox. 4; H332	2.00	wer/o	
	603-014-00-0	Eye Irrit. 2; H319			
	01-2119475108-36	Skin Irrit. 2; H315			
2	1,2-benzisothiazol-		pls. refer to footnote (1)		
	2634-33-5	Acute Tox. 4*; H302	< 0.05	wt%	
	220-120-9	Eye Dam. 1; H318			
	613-088-00-6	Skin Irrit. 2; H315			
	-	Skin Sens. 1; H317			
		Acute Tox. 2; H330			
		Aquatic Acute 1; H400			
		Aquatic Chronic 2; H411			
3	pyridine-2-thiol 1-o				
	3811-73-2	EUH070	< 0.10	wt%	
	223-296-5	Acute Tox. 4; H302			
	613-344-00-7	Acute Tox. 3; H311			
	-	Acute Tox. 3; H331			
		Skin Irrit. 2; H315			
		Skin Sens. 1; H317			
		Eye Irrit. 2; H319			
		STOT RE 1; H372			
		Aquatic Acute 1; H400			
		Aquatic Chronic 2; H411			
4	3-iodo-2-propynyl k	outylcarbamate			
	55406-53-6	Acute Tox. 3; H331	<	0.10 wt%	
	259-627-5	Acute Tox. 4; H302			
	616-212-00-7	Aquatic Acute 1; H400			
	-	Aquatic Chronic 1; H410			
		Eye Dam. 1; H318			
		Skin Sens. 1; H317			
		STOT RE 1; H372			
5	2-methyl-2H-isothia				
1	2682-20-4	Acute Tox. 2; H330	< 0.10	wt%	
	220-239-6	Acute Tox. 3; H301			
	613-326-00-9	Acute Tox. 3; H311			
	-	Aquatic Acute 1; H400			
		Aquatic Chronic 1; H410			
		EUH071			
		Eye Dam. 1; H318			
1		Skin Corr. 1B; H314			
		Skin Sens. 1A; H317			

Replaced version: 8.3.1, issued: 07.08.2023

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(\*,\*\*,\*\*\*\*) Detailed explanation pls. refer to CLP regulation No. 1272/2008, annex VI, 1.2





### Product no.: 0074053

Current version : 8.4.0. issued: 21.12.2023

Replaced version: 8.3.1, issued: 07.08.2023

(1) Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
2	-	Skin Sens. 1; H317: C >= 0.05%	-	-
3	-	-	M = 100	-
4	-	-	M = 10	M = 1
5	-	Skin Sens. 1A; H317: C >= 0.0015%	M = 10	M = 1

#### No Route, target organ, concrete effect 3 H372 -; nervous system; -

4 H372

-; larynx;	-

Acu	Acute toxicity estimate (ATE) values				
No	oral	dermal	inhalative		
1	1200 mg/kg bodyweight				

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

#### After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

### After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

#### After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

#### After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

# **4.2 Most important symptoms and effects, both acute and delayed** No data available.

### **4.3 Indication of any immediate medical attention and special treatment needed** No data available.

### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

### Suitable extinguishing media

Alcohol resistant foam, CO2, powders, water spray

# Unsuitable extinguishing media water jet.

### 5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO2); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

### 5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

### **SECTION 6: Accidental release measures**

### Product no.: 0074053

Replaced version: 8.3.1, issued: 07.08.2023

### 6.1 Personal precautions, protective equipment and emergency procedures

### For non-emergency personnel

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

### For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

### 6.2 Environmental precautions

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

### 6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

### 6.4 Reference to other sections

No data available.

### SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

### Advice on safe handling

Due to the organic solvents' content of the mixture: Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flatting] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

### General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

### Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

### 7.2 Conditions for safe storage, including any incompatibilities

### Technical measures and storage conditions

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

### Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

### Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

### 7.3 Specific end use(s)

No data available.

### SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

### Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	2-butoxyethanol	111-76-2	203-905-0
	2000/39/EC		

### Product no.: 0074053

Current version : 8.4.0, issued: 21.12.2023

Replaced version: 8.3.1, issued: 07.08.2023

Region: GB

2-Butoxyethanol				
WEL short-term (15 min reference period)	246	mg/m³	50	ppm
WEL long-term (8-hr TWA reference period)	98	mg/m³	20	ppm
Skin resorption / sensibilisation	Skin			
List of approved workplace exposure limits (WE	ELs) / EH40			
2-Butoxyethanol				
WEL short-term (15 min reference period)	246	mg/m³	50	ppm
WEL long-term (8-hr TWA reference period)	123	mg/m³	25	ppm
Comments	Sk, BMG	SV		

### **DNEL, DMEL and PNEC values**

#### DNEL values (worker)

No	Substance name		CAS / EC n	CAS / EC no	
	Route of exposure Exposure time Effect		Value		
1	2-butoxyethanol			111-76-2	
				203-905-0	
	inhalative	Long term (chronic)	systemic	98.00	mg/m³
	inhalative	Short term (acut)	systemic	1091.00	mg/m³
	inhalative	Long term (chronic)	local	246.00	mg/m³

#### DNEL value (consumer)

No	Substance name			No Substance name CAS / EC no		no
	Route of exposure Exposure time		Effect	Value		
1	2-butoxyethanol			111-76-2	111-76-2	
				203-905-0		
	oral	Long term (chronic)	systemic	6.30	mg/kg/day	
	oral	Short term (acut)	systemic	26.70	mg/kg/day	
	inhalative	Long term (chronic)	systemic	59.00	mg/m³	
	inhalative	Short term (acut)	systemic	426.00	mg/m³	
	inhalative	Long term (chronic)	local	147.00	mg/m³	

### PNEC values

No	Substance name		CAS / EC	no	
	cological compartment Type		Value		
1	2-butoxyethanol		111-76-2 203-905-0		
	water	fresh water	8.80	mg/L	
	water	marine water	0.88	mg/L	
	water	fresh water sediment	34.60	mg/kg	
	with reference to: dry weight		·		
	water	marine water sediment	3.46	mg/kg	
	water	Aqua intermittent	26.4	mg/L	
	soil	-	2.33	mg/kg dry weight	
	sewage treatment plant	-	463.00	mg/L	
	secondary poisoning	-	0.02	g/kg	

### 8.2 Exposure controls

#### Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

#### Personal protective equipment

#### **Respiratory protection**

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

Product no.: 0074053

Current version : 8.4.0, issued: 21.12.2023

Region: GB

### Eye / face protection

Wear safety googles to protect against splashes. Safety glasses with side protection shield (EN 166)

#### Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Replaced version: 8.3.1, issued: 07.08.2023

Appropriate Material	In case of short-term c	ontact / spla	sh protection: nitrile rubber
Material thickness	>	0.4	mm
Breakthrough time	>	120	min
Appropriate Material	In case of prolonged ex	kposure: nitr	ile rubber
Material thickness	>	0.4	mm
Breakthrough time	>	480	min

### Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

#### **Environmental exposure controls**

Do not allow to enter drains or water courses.

### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

State of aggregation			
Form liquid			
Colour according to product name			
Odour characteristic			
pH value Value	7.9 -	8.3	
Boiling point / boiling range           Value         a	appr.	100	°C
Melting point/freezing point No data available			
Decomposition temperature No data available			
Flash point Not applicable			
Ignition temperature No data available			
Oxidising properties Not applicable			
Flammability Not applicable			
Lower explosion limit No data available			
Upper explosion limit No data available			



<

appr.

DIN 51757

miscible

### Product no.: 0074053

Vapour pressure

Reference temperature **Relative vapour density** No data available **Relative density** No data available

Value

Density

Value

Method

Comments

Solubility

9.2

Solubility in water

Current version: 8.4.0, issued: 21,12,2023

<b>2010</b>	idility				
No d	lata available				
Part	ition coefficient n-octanol/water (log value	e)			
	Substance name	c)	CAS no.		EC no.
1	2-butoxyethanol		111-76-2		203-905-0
log F				0.81	
-	erence temperature			25	°C
Sour		ECHA			
		·			
Kine	ematic viscosity				
Valu	e	appr.	25	sec	
Refe	erence temperature		20	°C	
Meth	nod	DIN EN 243	81 (4 mm)		
• •					
Solv	rent separation test				
Not a	applicable				
Part	icle characteristics				
	lata available				
NO U					
2 (	Other information				
Othe	er information				
No d	ata available.				

Replaced version: 8.3.1, issued: 07.08.2023

hPa

a/cm<sup>3</sup>

°C

100

1.00

50

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

Stable under recommended storage and handling conditions (See section 7).

#### 10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

#### 10.3 Possibility of hazardous reactions Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

#### 10.4 Conditions to avoid Heat, naked flames and other ignition sources.

### 10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

#### 10.6 Hazardous decomposition products None if stored, handled and transported properly. In case of fire: see section 5.

### **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Acute oral toxicity (result of the ATE calculation for the mixture)



Region:	GB
---------	----

### Product no.: 0074053

Current version : 8.4.0, issued: 21.12.2023

Replaced version: 8.3.1, issued: 07.08.2023

No	Product Name				
1	einzA mix Novatrol Alpenöl Silvershine, I	Basis ME			
Com	ments	European Re 3 of Annex I of this mixture	gulation (EC) is outside the v	1272/2008 (C alues that imp able 3.1.1 det	od according to the LP), Paragraph 3.1.3.6, Part oly a classification / labelling fining the respective
Acu	te oral toxicity				
No	Substance name		CAS no.		EC no.
1	2-butoxyethanol		111-76-2		203-905-0
ATE				1200	mg/kg bodyweight
Spec Sour		rat 1272/2008/E	C, Annex VI		
Acu	te dermal toxicity				
	Substance name		CAS no.		EC no.
1	2-butoxyethanol		111-76-2		203-905-0
LD5		>		2000	mg/kg bodyweight
Species Method		guinea pig OECD 402			
Sour	ce	ECHA			
Aou	to inhalational toxicity (recult of the ATE o	algulation fo	r the mixture)		
No	te inhalational toxicity (result of the ATE c Product Name	alculation to	r the mixture)		
1	einzA mix Novatrol Alpenöl Silvershine, I	Rasis MF			
-	ments		the applied cal	sulation moth	od according to the
Com		European Re 3 of Annex I of this mixture categories (A	gulation (EC) f is outside the v e according to t	1272/2008 (C alues that imp able 3.1.1 de n: > 20.000 p	LP), Paragraph 3.1.3.6, Part oly a classification / labelling fining the respective opmV (gases), > 20 mg/l
Acut	te inhalational toxicity				
	lata available				
Skin	corrosion/irritation				
No	Substance name		CAS no.		EC no.
1	2-butoxyethanol		111-76-2		203-905-0
	tion of exposure			4	h
Spec		rabbit			
Meth		EU B.4			
Sour		ECHA			
⊏val	uation	irritant			
	ous eye damage/irritation				
No	Substance name		CAS no.		EC no.

No	Substance name	CAS no.		EC no.
1	2-butoxyethanol	111-76-2		203-905-0
Dura	ation of exposure		24	h
Spee	cies	rabbit		
Meth	nod	OECD 405		
Sour	rce	ECHA		
Eval	uation	Irritating to eyes		

Respiratory or skin sensitisation				
No	Substance name	CAS no.	EC no.	
1	2-butoxyethanol	111-76-2	203-905-0	
Rout	te of exposure	Skin		
Spee	cies	guinea pig		
		OECD 406		
Sour	rce	ECHA		
Evaluation		non-sensitizing		
	n cell mutagenicity			
No	Substance name	CAS no.	EC no.	

ei

#### Pr ~

nt version : 8.4.0, issued: 21.12.2023	Replaced version: 8.3.1, issued: 0	07.08.2023 <b>Regi</b>
2-butoxyethanol	111-76-2	203-905-0
/lethod	OECD 471	
Source	ECHA	
valuation/classification	Based on available data, the classif	fication criteria are not met.
Reproduction toxicity		
lo data available		
Carcinogenicity		
lo Substance name	CAS no.	EC no.
2-butoxyethanol	111-76-2	203-905-0
Species	rat	
/ethod	OECD 451	
Source	ECHA	
valuation/classification	Based on available data, the classif	fication criteria are not met.
TOT - single exposure		
lo data available		
lo data available		
lo data available TOT - repeated exposure	CAS no	EC no
lo data available STOT - repeated exposure lo Substance name	CAS no.	EC no.
lo data available STOT - repeated exposure lo Substance name 2-butoxyethanol	111-76-2	EC no. 203-905-0
lo data available TOT - repeated exposure Io Substance name 2-butoxyethanol Source	111-76-2 ECHA	203-905-0
lo data available STOT - repeated exposure lo Substance name 2-butoxyethanol	111-76-2	203-905-0
Io data available         STOT - repeated exposure         Io       Substance name         2-butoxyethanol         Source         Evaluation/classification	111-76-2 ECHA	203-905-0
lo data available TOT - repeated exposure Io Substance name 2-butoxyethanol Source	111-76-2 ECHA	203-905-0
Io data available         STOT - repeated exposure         Io       Substance name         2-butoxyethanol         Source         Evaluation/classification         Aspiration hazard         Io data available	111-76-2 ECHA Based on available data, the classid	203-905-0 fication criteria are not met.
lo data available TOT - repeated exposure Io Substance name 2-butoxyethanol Source Evaluation/classification Aspiration hazard Io data available Delayed and immediate effects as well as	111-76-2 ECHA Based on available data, the classif	203-905-0 fication criteria are not met. erm exposure
Io data available         STOT - repeated exposure         Io       Substance name         2-butoxyethanol         Source         Evaluation/classification         Aspiration hazard         Io data available         Delayed and immediate effects as well as exposure to component solvents vapours component solventsolventsolvent solvents vapours component solventsolve	111-76-2         ECHA         Based on available data, the classif         s chronic effects from short and long-tee         oncentration in excess of the stated occup	203-905-0 fication criteria are not met. erm exposure pational exposure limit may resu
Io data available         STOT - repeated exposure         Io       Substance name         2-butoxyethanol         Source         Evaluation/classification         Aspiration hazard         Io data available         Delayed and immediate effects as well as exposure to component solvents vapours con adverse health effects such as mucous means	111-76-2         ECHA         Based on available data, the classif         s chronic effects from short and long-tee         oncentration in excess of the stated occup         nembrane and respiratory system irritation	203-905-0 fication criteria are not met. erm exposure pational exposure limit may resu and adverse effects on kidney,
Io data available         STOT - repeated exposure         Io       Substance name         2-butoxyethanol         Source         Evaluation/classification         Aspiration hazard         Io data available         Delayed and immediate effects as well as exposure to component solvents vapours con adverse health effects such as mucous mixer and central nervous system. Symptoms	111-76-2         ECHA         Based on available data, the classif         s chronic effects from short and long-tee         oncentration in excess of the stated occup         nembrane and respiratory system irritation         s and signs include headache, dizziness, f	203-905-0 fication criteria are not met. erm exposure pational exposure limit may resu and adverse effects on kidney, fatigue, muscular weakness,
Io data available         STOT - repeated exposure         Io       Substance name         2-butoxyethanol         Source         Evaluation/classification         Aspiration hazard         Io data available         Delayed and immediate effects as well as exposure to component solvents vapours con adverse health effects such as mucous mover and central nervous system. Symptoms provisiness and in extreme cases, loss of context	111-76-2         ECHA         Based on available data, the classif         s chronic effects from short and long-tee         oncentration in excess of the stated occup         nembrane and respiratory system irritation         s and signs include headache, dizziness, to         ponsciousness. Solvents may cause some	203-905-0 fication criteria are not met. erm exposure pational exposure limit may resu and adverse effects on kidney, fatigue, muscular weakness, of the above effects by absorptio
Io data available         STOT - repeated exposure         Io       Substance name         2-butoxyethanol         Source         Evaluation/classification         Aspiration hazard         Io data available         Delayed and immediate effects as well as exposure to component solvents vapours con adverse health effects such as mucous mover and central nervous system. Symptoms frowsiness and in extreme cases, loss of contrough the skin. Repeated or prolonged control	111-76-2         ECHA         Based on available data, the classif         s chronic effects from short and long-te         oncentration in excess of the stated occup         nembrane and respiratory system irritation         s and signs include headache, dizziness, to         onsciousness. Solvents may cause some         ntact with the mixture may cause removal	203-905-0 fication criteria are not met. erm exposure pational exposure limit may resu and adverse effects on kidney, fatigue, muscular weakness, of the above effects by absorption of natural fat from the skin
Io data available         STOT - repeated exposure         Io       Substance name         2-butoxyethanol         Source         Evaluation/classification         Aspiration hazard         Io data available         Delayed and immediate effects as well as exposure to component solvents vapours con adverse health effects such as mucous mover and central nervous system. Symptoms frowsiness and in extreme cases, loss of contrough the skin. Repeated or prolonged contesulting in non-allergic contact dermatitis and solvents and the streme cases of the solvents and the streme cases of the solvents and the s	111-76-2         ECHA         Based on available data, the classif         s chronic effects from short and long-te         oncentration in excess of the stated occup         nembrane and respiratory system irritation         s and signs include headache, dizziness, to         onsciousness. Solvents may cause some         ntact with the mixture may cause removal         nd absorption through the skin. The liquid	203-905-0 fication criteria are not met. erm exposure pational exposure limit may resu and adverse effects on kidney, fatigue, muscular weakness, of the above effects by absorptio of natural fat from the skin splashed in the eyes may cause
Io data available         STOT - repeated exposure         Io       Substance name         2-butoxyethanol         Source         Evaluation/classification         Aspiration hazard         Io data available         Delayed and immediate effects as well as exposure to component solvents vapours or a diverse health effects such as mucous mixer and central nervous system. Symptoms frowsiness and in extreme cases, loss of comough the skin. Repeated or prolonged comesulting in non-allergic contact dermatitis and rittation and reversible damage. Ingestion non-allergic contact dermatitis and rittation and reversible damage. Ingestion non-allergic contact dermatitis and rittation and reversible damage.	111-76-2         ECHA         Based on available data, the classif         s chronic effects from short and long-te         oncentration in excess of the stated occup         nembrane and respiratory system irritation         s and signs include headache, dizziness, to         onsciousness. Solvents may cause some         ntact with the mixture may cause removal         nd absorption through the skin. The liquid         nay cause nausea, diarrhoea and vomiting	203-905-0 fication criteria are not met. erm exposure pational exposure limit may resu and adverse effects on kidney, fatigue, muscular weakness, of the above effects by absorption of natural fat from the skin splashed in the eyes may cause g. This takes into account, where
Io data available         STOT - repeated exposure         Io       Substance name         2-butoxyethanol         Source         Evaluation/classification         Aspiration hazard         Io data available         Delayed and immediate effects as well as exposure to component solvents vapours con adverse health effects such as mucous mover and central nervous system. Symptoms frowsiness and in extreme cases, loss of contrough the skin. Repeated or prolonged contesulting in non-allergic contact dermatitis and solvents and the streme cases of the solvents and the streme cases of the solvents and the s	111-76-2         ECHA         Based on available data, the classif         s chronic effects from short and long-te         oncentration in excess of the stated occup         nembrane and respiratory system irritation         s and signs include headache, dizziness, to         onsciousness. Solvents may cause some         ntact with the mixture may cause removal         nd absorption through the skin. The liquid         nay cause nausea, diarrhoea and vomiting         also chronic effects of components from s	203-905-0 fication criteria are not met. erm exposure pational exposure limit may resu and adverse effects on kidney, fatigue, muscular weakness, of the above effects by absorption of natural fat from the skin splashed in the eyes may caus g. This takes into account, wher

Endocrine disrupting properties No data available.

Other information No data available.

### **SECTION 12: Ecological information**

### 12.1 Toxicity

Toxi	Toxicity to fish (acute)				
No	Substance name	CAS no.		EC no.	
1	2-butoxyethanol	111-76-2		203-905-0	
LC5	0		1474	mg/l	
Dura	ation of exposure		96	h	
Spee	cies	Oncorhynchus mykiss			
Meth	nod	OECD 203			
Sou	rce	ECHA			
Toxi	city to fish (chronic)				
No	Substance name	CAS no.		EC no.	
1	2-butoxyethanol	111-76-2		203-905-0	
NOE	C	>	100	mg/l	
Dura	ation of exposure		21	day(s)	
Spee	cies	Danio rerio			

GB



### Product no.: 0074053

Method Source Toxicity to Daphnia (acute) No Substance name	OECD 204 ECHA		
Toxicity to Daphnia (acute)			
	CAS no.	EC no.	
1 2-butoxyethanol	111-76-2	203-905-0	
EC50		1550 mg/l	
Duration of exposure		18 h	
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		
Toxicity to Daphnia (chronic)			
No Substance name	CAS no.	EC no.	
1 2-butoxyethanol	111-76-2	203-905-0	
NOEC		00 mg/l	
Duration of exposure		day(s)	
Species	Daphnia magna	, , , , , , , , , , , , , , , , , , ,	
Method	OECD 211		
Source	ECHA		
Toxicity to algae (acute)			
No Substance name	CAS no.	EC no.	
1 2-butoxyethanol	111-76-2	203-905-0	
EC50	ç	911 mg/l	
Duration of exposure	7	′2 h	
Species	Pseudokirchneriella subcapitata	à	
Method	OECD 201		
Source	ECHA		
Toxicity to algae (chronic)			
No data available			
Bacteria toxicity			
No data available			

DIOC	legradability				
No	Substance name	CAS no.		EC no.	
1	2-butoxyethanol	111-76-2		203-905-0	
Туре	9	aerobic biodegradation			
Valu			90.4	%	
Dura	ation		28	day(s)	
Meth	nod	OECD 301 B			
Sour	rce	ECHA			
Eval	uation	readily biodegradable			

### 12.3 Bioaccumulative potential

Part	Partition coefficient n-octanol/water (log value)				
No	Substance name	CAS no.		EC no.	
1	2-butoxyethanol	111-76-2		203-905-0	
log F	Pow		0.81		
Refe	erence temperature		25	°C	
Sou	се	ECHA			

### 12.4 Mobility in soil

No data available.

### 12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	The components of this product are not considered to be a PBT.
vPvB assessment	The components of this product are not considered to be a vPvB.

### **12.6 Endocrine disrupting properties**



### Product no.: 0074053

Current version : 8.4.0, issued: 21.12.2023

Replaced version: 8.3.1, issued: 07.08.2023

No data available.

### 12.7 Other adverse effects

## No data available.

### 12.8 Other information

### Other information

Do not allow to enter drains or water courses.

SEC	TION 13: Disposal considerations
	Waste treatment methods

Product Waste code

S 1

08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company. Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

#### Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

### **SECTION 14: Transport information**

#### 14.1 Transport ADR/RID/ADN

The product is not subject to ADR/RID/ADN regulations.

#### 14.2 Transport IMDG

The product is not subject to IMDG regulations.

#### 14.3 Transport ICAO-TI / IATA

The product is not subject to ICAO-TI / IATA regulations.

- **14.4 Other information** No data available.
- **14.5** Environmental hazards Information on environmental hazards, if relevant, please see 14.1 - 14.3.

#### 14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments Not relevant

### **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU regulations</u>

#### Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

#### REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

#### Product no.: 0074053

No Substance name

annex XVII.

1

Current version : 8.4.0, issued: 21.12.2023

1,2-benzisothiazol-3(2H)-one
2-butoxyethanol

2	2-butoxyethanol	111-76-2	203-905-0	75	
3	2-Hydroxyethyl methacrylate	868-77-9	212-782-2	75	
4	3-iodo-2-propynyl butylcarbamate	55406-53-6	259-627-5	75	
5	aluminium powder (stabilised)	7429-90-5	231-072-3	75	
6	pyridine-2-thiol 1-oxide, sodium salt	3811-73-2	223-296-5	75	

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006

Replaced version: 8.3.1, issued: 07.08.2023

EC no.

220-120-9

CAS no.

2634-33-5

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances This product is not subject to Part 1 or 2 of Annex I.

THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

 Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)

 VOC content
 1.89 %

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products

relevant VOC limit value as referred to in Annex II of Directive 2004/42/CE , Cat. : e, type: wb = 130 g/l Max. VOC content (limit value) of the product in its ready for use condition = < 130 g/l

#### National regulations

#### Other national regulations

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

#### 15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

### **SECTION 16: Other information**

### Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

## Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

360110113/	
EUH070	Toxic by eye contact.
EUH071	Corrosive to the respiratory tract.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

### Creation of the safety data sheet

UMCO GmbH

Region: GB



No

75

## EU safety data sheet

### Trade name: einzA mix Novatrol Alpenöl Silvershine, Basis ME

Product no.: 0074053

Current version : 8.4.0, issued: 21.12.2023

Replaced version: 8.3.1, issued: 07.08.2023

Region: GB

6

Georg-Wilhelm-Str. 187, D-21107 Hamburg Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience. The safety data sheet describes products with a view to safety requirements. It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH. Prod-ID 739888