Trade name: einzA mix Samtacryl Seidenglanzlack, Basis 3 Product no.: 0171754

Current version : 7.1.1, issued: 21.06.2022

Replaced version: 7.1.0, issued: 10.03.2022

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 **Product identifier**

Trade name

einzA mix Samtacryl Seidenglanzlack, Basis 3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture decorative paints/finishes

Uses advised against No data available.

1.3 Details of the supplier of the safety data sheet

Address

einzA Farben GmbH & Co KG Junkersstraße 13 30179 Hannover

 Telephone no.
 +49 (0)511 67490-0

 Fax no.
 +49 (0)511 67490-20

 e-mail
 info@einzA.com

Advice on Safety Data Sheet sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English): +49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

This product does not meet the classification criteria given in the Regulation (EC) No 1272/2008 (CLP).

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms

Signal word

EUH210

Hazard statement(s)

Hazard statements (EU) EUH208

Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1), 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

Safety data sheet available on request.

Precautionary statement(s)

Labelling information

The labelling (EU hazard statements) meets the criteria of annex II of Directive (EC) Nr. 1272/2008 (CLP).



Product no.: 0171754

Current version : 7.1.1, issued: 21.06.2022

Replaced version: 7.1.0, issued: 10.03.2022

e

2.3 Other hazards

PBT assessment

The components of this product are not considered to be a PBT.

vPvB assessment

The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Hazardous ingredients

No	Substance name		Additional information	
	CAS / EC / Index /	Classification (EC) 1272/2008 (CLP)	Concentration	%
	REACH no		Concentration	70
1		YLETHOXY)PROPANOL		
-	34590-94-8	-	< 2.50	wt%
	252-104-2			
	-			
	01-2119450011-60			
2	triethylamine			
	121-44-8	Flam. Liq. 2; H225	< 1.00	wt%
	204-469-4	Acute Tox. 4; H302		
	612-004-00-5	Acute Tox. 3; H311		
	01-2119475467-26	Skin Corr. 1A; H314		
		Acute Tox. 3; H331		
		STOT SE 3; H335		
3	1,2-benzisothiazol-		pls. refer to footnote (1)	
	2634-33-5	Acute Tox. 4*; H302	< 0.05	wt%
	220-120-9	Eye Dam. 1; H318		
	613-088-00-6	Skin Irrit. 2; H315		
	-	Skin Sens. 1; H317		
		Acute Tox. 2; H330		
		Aquatic Acute 1; H400		
		Aquatic Chronic 2; H411		
4	pyridine-2-thiol 1-o			
	3811-73-2	Acute Tox. 4; H302	< 0.10	wt%
	223-296-5	Acute Tox. 4; H332		
	-	Aquatic Acute 1; H400		
	-	Aquatic Chronic 2; H411		
		Eye Dam. 1; H318		
5		-chloro-2-methyl-4-isothiazolin-3-one and 2-		
	methyl-2H -isothiaz			
	55965-84-9	Acute Tox. 2; H310	< 0.0015	wt%
	-	Acute Tox. 2; H330		
	613-167-00-5	Acute Tox. 3; H301		
	-	Aquatic Acute 1; H400		
		Aquatic Chronic 1; H410		
		EUH071		
		Eye Dam. 1; H318		
		Skin Corr. 1C; H314		
		Skin Sens. 1A; H317		
6	2-methyl-2H-isothia	azol-3-one		

Product no.: 0171754

Current version : 7.1.1, issued: 21.06.2022

Replaced version: 7.1.0, issued: 10.03.2022

	2682-20-4 220-239-6 613-326-00-9 -	Acute Tox. 2; H330 Acute Tox. 3; H301 Acute Tox. 3; H311 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 Eye Dam. 1; H318 Skin Corr. 1B; H314 Skin Sens. 1A; H317	<	0.10	wt%
7	propane-1,2-diol				
	57-55-6	-	<	2.50	wt%
	200-338-0				
	-				
	01-2119456809-23				

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(*,**,***,****) Detailed explanation pls. refer to CLP regulation No. 1272/2008, annex VI, 1.2

(1) Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
2	-	STOT SE 3; H335: C >= 1%	-	-
3	-	Skin Sens. 1; H317: C >= 0.05%	-	-
4	-	-	M = 100	-
5	В	Skin Sens. 1A; H317: C >= 0.0015% Eye Irrit. 2; H319: C >= 0.06% Skin Irrit. 2; H315: C >= 0.06% Skin Corr. 1C; H314: C >= 0.6% Eye Dam. 1; H318: C >= 0.6%	M = 100	M = 100
6	-	Skin Sens. 1A; H317: C >= 0.0015%	M = 10	M = 1

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

Acu	Acute toxicity estimate (ATE) values			
No	oral	dermal	inhalative	
2	730 mg/kg bodyweight	580 mg/kg bodyweight		

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

- **4.2 Most important symptoms and effects, both acute and delayed** No data available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No data available.

Product no.: 0171754

Current version : 7.1.1, issued: 21.06.2022

Replaced version: 7.1.0. issued: 10.03.2022

Region: GB

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO2, powders, water spray

Unsuitable extinguishing media water jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO2); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Due to the organic solvents' content of the mixture: Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flatting] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

Requirements for storage rooms and vessels

Product no.: 0171754

Current version : 7.1.1, issued: 21.06.2022

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Replaced version: 7.1.0, issued: 10.03.2022

Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.		EC no.	
1	propane-1,2-diol	57-55-6		200-338	-0
	List of approved workplace exposure limits (WELs) / EH40				
	Propane-1,2-diol				
	vapour & particulates				
	WEL long-term (8-hr TWA reference period)	474	mg/m³	150	ppm
	List of approved workplace exposure limits (WELs	s) / EH40			
	Propane-1,2-diol particulates				
	WEL long-term (8-hr TWA reference period)	10	mg/m³		
2	(2-METHOXYMETHYLETHOXY)PROPANOL	34590-94	4-8	252-104	-2
	2000/39/EC				
	(2-Methoxymethylethoxy)-propanol				
	WEL long-term (8-hr TWA reference period)	308	mg/m³	50	ppm
	Skin resorption / sensibilisation	Skin			
	List of approved workplace exposure limits (WELs	s) / EH40			
	(2-Methoxymethylethoxy) propanol				
	WEL long-term (8-hr TWA reference period)	308	mg/m³	50	ppm
	Comments	Sk			
3	triethylamine	121-44-8		204-469	-4
	2000/39/EC				
	Triethylamine				
	WEL short-term (15 min reference period)	12.6	mg/m³	3	ppm
	WEL long-term (8-hr TWA reference period)	8.4	mg/m³	2	ppm
	Skin resorption / sensibilisation	Skin			
	List of approved workplace exposure limits (WELs	s) / EH40			
	Triethylamine				
	WEL short-term (15 min reference period)	17	mg/m³	4	ppm
	WEL long-term (8-hr TWA reference period)	8	mg/m³	2	ppm
	Comments	Sk			

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name			CAS / EC	no
	Route of exposure	Exposure time	Effect	Value	
1	triethylamine			121-44-8	
				204-469-	4
	dermal	Long term (chronic)	systemic	12.1	mg/kg/day
	inhalative	Long term (chronic)	systemic	8.4	mg/m³
	inhalative	Short term (acut)	systemic	12.6	mg/m³
	inhalative	Long term (chronic)	local	8.4	mg/m³
	inhalative	Short term (acut)	local	12.6	mg/m³
PNEC values					
No	Substance name			CAS / EC	; no
	ecological compartment	Туре		Value	

Region: GB

Product no.: 0171754

Current version : 7.1.1, issued: 21.06.2022

Replaced version: 7.1.0. issued: 10.03.2022

Region: GB

1	triethylamine		121-44-8 204-469-4	ŀ
	water	fresh water	0.11	mg/L
	water	marine water	0.011	mg/L
	water	Aqua intermittent	0.08	mg/L
	water	fresh water sediment	1.575	mg/kg dry weight
	water	marine water sediment	0.158	mg/kg dry weight
	soil	-	0.25	mg/kg dry weight
	sewage treatment plant	-	100	mg/L

8.2 Exposure controls

Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

Eye / face protection

Wear safety googles to protect against splashes. Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific workstation suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material	In case of short-term of	contact / spla	ash protection: nitrile rubber
Material thickness	>	0.4	mm
Breakthrough time	>	120	min
Appropriate Material	In case of prolonged e	exposure: nit	rile rubber
Material thickness	>	0.4	mm
Breakthrough time	>	480	min

Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation
liquid
Form/Colour
liquid
according to product name
Odour
characteristic
pH value



Trade name: einzA mix Samtacryl Seidenglanzlack, Basis 3

rent version : 7.1.1, issued: 21.06.2022	Replaced version: 7.1.0, issued: 10.03.2022	Regior
Value	7.3 - 8.8	
Boiling point / boiling range		
Value	appr. 100 °C	
Melting point/freezing point		
No data available		
Decomposition temperature		
No data available		
Flash point		
Not applicable		
Ignition temperature No data available		
Oxidising properties Not applicable		
Flammability Not applicable		
Lower explosion limit No data available		
Upper explosion limit No data available		
Vapour pressure Value	< 100 hPa	
Reference temperature	50 °C	
Relative vapour density		
No data available		
Relative density		
No data available		
Density		
Value	1.01 - 1.26 g/cm ³	
Reference temperature Method	20 °C DIN 51757	
	Bin Straf	
Solubility in water Comments	miscible	
Solubility No data available		
Partition coefficient n-octanol/water	(log value) CAS no. EC n	•
1 triethylamine	121-44-8 204-4	
log Pow	1.45	
Source	ECHA	
Kinematic viscosity		
Value	1500 - 2400 Pa*s 20 °C	
Reference temperature Method	20 °C DIN 53019	
Solvent separation test Not applicable		
Particle characteristics No data available		

9.2 Other information

Other information

Trade name: einzA mix Samtacryl Seidenglanzlack, Basis 3

Product no.: 0171754

Current version: 7.1.1, issued: 21.06.2022

Replaced version: 7.1.0. issued: 10.03.2022

Region: GB

No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage and handling conditions (See section 7).

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

- **10.3 Possibility of hazardous reactions** Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- **10.4 Conditions to avoid** Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute of	oral toxicity				
No Su	ubstance name	CAS no.		EC no.	
1 trie	ethylamine	121-44-8		204-469-4	
LD50			730	mg/kg bodyweight	
Species	3	rat			
Method		OECD 401			
Source		ECHA			
	dermal toxicity (result of the ATE calcul	ation for the mixture)			
	oduct Name				
	nzA mix Samtacryl Seidenglanzlack, Ba				
Comme	ents	The result of the applied ca			
				CLP), Paragraph 3.1.3.6, Part	
				ply a classification / labelling	
		of this mixture according to	table 3.1.1 de	fining the respective	
		categories (ATE dermal > 2	000 mg/kg).		
Acuto					
	dermal toxicity	010		50	
	ubstance name	CAS no.		EC no.	
	ethylamine	121-44-8		204-469-4	
LD50			580	mg/kg bodyweight	
Species		rabbit			
Method		OECD 402			
Source		ECHA			
Acute i	nhalational toxicity (result of the ATE of	alculation for the mixture			
	oduct Name				
	nzA mix Samtacryl Seidenglanzlack, Ba	acie 3			
Comme		The result of the applied ca	lculation meth	od according to the	
Comme				CLP), Paragraph 3.1.3.6, Part	
				ply a classification / labelling	
		of this mixture according to			
		categories (ATE for inhalati			
		(vapours), > 5 mg/l (dusts/n		ppint (gases), > 20 mg/l	
L	(vapouloj, < 0 mg/l (uusio/misio).				
Acute i	nhalational toxicity				
No data	No data available				
Skin co	Skin corrosion/irritation				

Product no.: 0171754

Current version: 7.1.1

rrent version : 7.1.1, issued: 21.06.2022	Replaced version: 7.1.0, issued: 10.03.2022
No data available	
Serious eye damage/irritation	
No data available	
Respiratory or skin sensitisation	
No data available	
Germ cell mutagenicity	

No data available

Reproduction toxicity No data available

Carcinogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure No data available

Aspiration hazard No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

11.2 Information on other hazards

Endocrine disrupting properties No data available.

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

o. 169-4 mg/l h		
mg/l		
•		
h		
•		
h		
Toxicity to fish (chronic) No data available Toxicity to Daphnia (acute) No Substance name CAS no. EC no. 1 triethylamine 121-44-8 204-469-4 EC50 200 mg/l Duration of exposure 48 h Species Daphnia magna OECD 202		



Region: GB

Trade name: einzA mix Samtacryl Seidenglanzlack, Basis 3

Product no.: 0171754

Current version: 7.1.	1. issued: 21.06.2022

Replaced version: 7.1.0, issued: 10.03.2022

e

Region: GB

Sou	rce	ECHA		
	Toxicity to Daphnia (chronic)			
No	data available			
Tox	icity to algae (acute)			
No	Substance name	CAS no.	EC no.	
1	triethylamine	121-44-8	204-469-4	
EC5	60	8	mg/l	
Dur	ation of exposure	72	h	
Spe	Species Pseudokirchneriella subcapitata			
Met	Method OECD 201			
Sou	rce	ECHA		
Toy	Toxicity to algae (obranic)			
Toxicity to algae (chronic) No data available				
Bacteria toxicity				
No	No data available			

12.2 Persistence and degradability

Biodegradability			
Substance name	CAS no.	EC no.	
triethylamine	121-44-8	204-469-4	
)	aerobic biodegradation		
e	8	30.3 %	
Ition		29 day(s	;)
nod	OECD 301 B		
ce	ECHA		
uation	readily biodegradable		
	Substance name triethylamine e ation nod rce	Substance nameCAS no.triethylamine121-44-8aerobic biodegradationeaerobic biodegradatione2nodOECD 301 BrceECHA	Substance nameCAS no.EC no.triethylamine121-44-8204-469-4eaerobic biodegradatione80.3%ation29day(snodOECD 301 BrceECHA

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	triethylamine	121-44-8	204-469-4
log F	Pow		1.45
Sou	rce	ECHA	

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessn	nent
PBT assessment	The components of this product are not considered to be a PBT.
vPvB assessment	The components of this product are not considered to be a vPvB.

12.6 Endocrine disrupting properties No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information Do not allow to enter drains or water courses.

08 01 11*

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste code

waste paint and varnish containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company.

Trade name: einzA mix Samtacryl Seidenglanzlack, Basis 3

Product no.: 0171754

Current version : 7.1.1. issued: 21.06.2022

Region: GB

Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

The product is not subject to ADR/RID/ADN regulations.

14.2 Transport IMDG

The product is not subject to IMDG regulations.

14.3 Transport ICAO-TI / IATA The product is not subject to ICAO-TI / IATA regulations.

14.4 Other information No data available.

14.5 Environmental hazards Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006

	ex XVII.			
No	Substance name	CAS no.	EC no.	No
1	1,2-benzisothiazol-3(2H)-one	2634-33-5	220-120-9	75
2	pyridine-2-thiol 1-oxide, sodium salt	3811-73-2	223-296-5	75
3	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3- one and 2-methyl-2H -isothiazol-3-one (3:1)	55965-84-9	-	75
4	triethylamine	121-44-8	204-469-4	75
Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances This product is not subject to Part 1 or 2 of Annex I.				
Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)				
VOC	Content	3.23 %		

Product no.: 0171754

Current version : 7.1.1, issued: 21.06.2022

Replaced version: 7.1.0. issued: 10.03.2022

Region: GB

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products

relevant VOC limit value as referred to in Annex II of Directive 2004/42/CE , Cat. : d, type: wb = 130 g/l Max. VOC content (limit value) of the product in its ready for use condition = < 130 g/l

National regulations

Other national regulations

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

Sections)	
EUH071	Corrosive to the respiratory tract.
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

В

Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

Creation of the safety data sheet

UMCO GmbH Georg-Wilhelm-Str. 187, D-21107 Hamburg Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Product no.: 0171754

Current version : 7.1.1, issued: 21.06.2022

Replaced version: 7.1.0, issued: 10.03.2022

ein

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH. Prod-ID 653654