

**Trade name:** einzA silikon Grundfestiger**Product no.:** 0035939**Current version :** 4.0.0, issued: 04.06.2025**Replaced version:** 3.0.1, issued: 29.08.2024**Region:** GB**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name****einzA silikon Grundfestiger****1.2 Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses of the substance or mixture**

Coatings and paint, filling agent, levelling compounds, thinners

**Uses advised against**

No data available.

**1.3 Details of the supplier of the safety data sheet****Address**

einzA Farben GmbH &amp; Co KG

Junkersstraße 13

30179 Hannover

Telephone no. +49 (0)511 67490-0

Fax no. +49 (0)511 67490-20

e-mail info@einzA.com

**Advice on Safety Data Sheet**

sdb\_info@umco.de

**1.4 Emergency telephone number**

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Eye Irrit. 2; H319

Flam. Liq. 2; H225

Skin Irrit. 2; H315

STOT RE 2; H373

STOT SE 3; H335

STOT SE 3; H336

**Classification information**

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)****Hazard pictograms**

GHS02



GHS07



GHS08

**Signal word**

Danger

**Hazardous component(s) to be indicated on label:**

2-methoxy-1-methylethyl acetate

n-butyl acetate

Reaction mass of xylene and ethylbenzene

**Hazard statement(s)**

H225

Highly flammable liquid and vapour.

H315

Causes skin irritation.

H319

Causes serious eye irritation.

H335

May cause respiratory irritation.

H336

May cause drowsiness or dizziness.

H373

May cause damage to organs through prolonged or repeated exposure

**Precautionary statement(s)**

Trade name: einzA silikon Grundfestiger

Product no.: 0035939

Current version : 4.0.0, issued: 04.06.2025

Replaced version: 3.0.1, issued: 29.08.2024

Region: GB

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P370+P378	In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container to a facility in accordance with local and national regulations.

### 2.3 Other hazards

PBT assessment

According to the information provided in the supply chain: The product contains no components with &gt; 0.1% that are considered PBT.

vPvB assessment

According to the information provided in the supply chain: The product contains no components with &gt; 0.1% that are considered vPvB.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable. The product is not a substance.

### 3.2 Mixtures

#### Hazardous ingredients

No	Substance name	Classification (EC) 1272/2008 (CLP)	Additional information	%
	CAS / EC / Index / REACH no		Concentration	
1	<b>2-methoxy-1-methylethyl acetate</b>			
	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336	>= 25.00 - < 50.00	wt%
2	<b>n-butyl acetate</b>			
	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	EUH066 Flam. Liq. 3; H226 STOT SE 3; H336	>= 25.00 - < 50.00	wt%
3	<b>Reaction mass of xylene and ethylbenzene</b>			
	- 905-588-0 - 01-2119539452-40	Acute Tox. 4; H312 Acute Tox. 4; H332 Asp. Tox. 1; H304 Eye Irrit. 2; H319 Flam. Liq. 3; H226 Skin Irrit. 2; H315 STOT SE 3; H335 STOT RE 2; H373	>= 10.00 - < 25.00	wt%

Full text of H- and EUH-phrases, if not already mentioned in section 2.2: see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

#### After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

#### After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

#### After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

#### After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

No data available.

**Trade name:** einzA silicon Grundfestiger

**Product no.:** 0035939

**Current version :** 4.0.0, issued: 04.06.2025

**Replaced version:** 3.0.1, issued: 29.08.2024

**Region:** GB

## 4.3 Indication of any immediate medical attention and special treatment needed

No data available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Alcohol resistant foam, CO<sub>2</sub>, powders, water spray

#### Unsuitable extinguishing media

water jet.

### 5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO<sub>2</sub>); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

### 5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

#### For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

### 6.2 Environmental precautions

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

### 6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

### 6.4 Reference to other sections

No data available.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flattening] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

#### General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

#### Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Technical measures and storage conditions

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

#### Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

#### Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

### 7.3 Specific end use(s)

No data available.

Trade name: einza silicon Grundfestiger

Product no.: 0035939

Current version : 4.0.0, issued: 04.06.2025

Replaced version: 3.0.1, issued: 29.08.2024

Region: GB

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Occupational exposure limit values**

No	Substance name	CAS no.		EC no.	
1	2-methoxy-1-methylethyl acetate	108-65-6		203-603-9	
	List of approved workplace exposure limits (WELs) / EH40				
	1-Methoxypropylacetate				
	WEL short-term (15 min reference period)	548	mg/m³	100	ppm
	WEL long-term (8-hr TWA reference period)	274	mg/m³	50	ppm
	Comments	Sk			
	2000/39/EC				
	2-Methoxy-1-methylethylacetate				
	WEL short-term (15 min reference period)	550	mg/m³	100	ppm
	WEL long-term (8-hr TWA reference period)	275	mg/m³	50	ppm
	Skin resorption / sensibilisation	Skin			
2	n-butyl acetate	123-86-4		204-658-1	
	List of approved workplace exposure limits (WELs) / EH40				
	Butyl acetate				
	WEL short-term (15 min reference period)	966	mg/m³	200	ppm
	WEL long-term (8-hr TWA reference period)	724	mg/m³	150	ppm
	EU 2019/1831				
	n-Butyl acetate				
	WEL short-term (15 min reference period)	723	mg/m³	150	ppm
	WEL long-term (8-hr TWA reference period)	241	mg/m³	50	ppm

**DNEL, DMEL and PNEC values****DNEL values (worker)**

No	Substance name	CAS / EC no
	Route of exposure	Value
1	2-methoxy-1-methylethyl acetate	108-65-6 203-603-9
	dermal	Long term (chronic) systemic 796 mg/kg/day
	inhalative	Long term (chronic) systemic 275 mg/m <sup>3</sup>
	inhalative	Short term (acute) local 550 mg/m <sup>3</sup>
2	n-butyl acetate	123-86-4 204-658-1
	dermal	Long term (chronic) systemic 11 mg/kg/day
	dermal	Short term (acute) systemic 11 mg/kg/day
	inhalative	Long term (chronic) systemic 300 mg/m <sup>3</sup>
	inhalative	Short term (acute) systemic 600 mg/m <sup>3</sup>
	inhalative	Long term (chronic) local 300 mg/m <sup>3</sup>
	inhalative	Short term (acute) local 600 mg/m <sup>3</sup>
3	Reaction mass of xylene and ethylbenzene	- 905-588-0
	dermal	Long term (chronic) systemic 212 mg/kg/day
	inhalative	Short term (acute) systemic 442 mg/m <sup>3</sup>
	inhalative	Short term (acute) local 442 mg/m <sup>3</sup>
	inhalative	Long term (chronic) systemic 221 mg/m <sup>3</sup>
	inhalative	Long term (chronic) local 221 mg/m <sup>3</sup>

**DNEL value (consumer)**

No	Substance name	CAS / EC no
	Route of exposure	Value
1	2-methoxy-1-methylethyl acetate	108-65-6 203-603-9
	oral	Long term (chronic) systemic 36 mg/kg/day
	oral	Short term (acute) systemic 500 mg/kg/day
	dermal	Long term (chronic) systemic 320 mg/kg/day
	inhalative	Long term (chronic) systemic 33 mg/m <sup>3</sup>
	inhalative	Long term (chronic) local 33 mg/m <sup>3</sup>
2	n-butyl acetate	123-86-4 204-658-1
	oral	Long term (chronic) systemic 2 mg/kg/day
	oral	Short term (acute) systemic 2 mg/kg/day

Trade name: einza silicon Grundfestiger

Product no.: 0035939

Current version : 4.0.0, issued: 04.06.2025

Replaced version: 3.0.1, issued: 29.08.2024

Region: GB

	dermal	Long term (chronic)	systemic	6	mg/kg/day
	dermal	Short term (acute)	systemic	6	mg/kg/day
	inhalative	Long term (chronic)	systemic	35.7	mg/m <sup>3</sup>
	inhalative	Short term (acute)	systemic	300	mg/m <sup>3</sup>
	inhalative	Long term (chronic)	local	35.7	mg/m <sup>3</sup>
	inhalative	Short term (acute)	local	300	mg/m <sup>3</sup>
3	Reaction mass of xylene and ethylbenzene			-	
				905-588-0	
	oral	Long term (chronic)	systemic	12.5	mg/kg/day
	dermal	Long term (chronic)	systemic	125	mg/kg/day
	inhalative	Short term (acute)	systemic	260	mg/m <sup>3</sup>
	inhalative	Long term (chronic)	systemic	65.3	mg/m <sup>3</sup>
	inhalative	Short term (acute)	local	260	mg/m <sup>3</sup>
	inhalative	Long term (chronic)	local	65.3	mg/m <sup>3</sup>

## PNEC values

No	Substance name		CAS / EC no
	ecological compartment	Type	Value
1	2-methoxy-1-methylethyl acetate		108-65-6 203-603-9
	water	fresh water	0.635 mg/L
	water	marine water	0.064 mg/L
	water	fresh water sediment	3.29 mg/kg
	with reference to: dry weight		
	water	marine water sediment	0.329 mg/kg
	with reference to: dry weight		
	soil	-	0.29 mg/kg
	with reference to: dry weight		
	sewage treatment plant	-	100 mg/L
2	n-butyl acetate		123-86-4 204-658-1
	water	fresh water	0.18 mg/L
	water	marine water	0.018 mg/L
	water	fresh water sediment	0.981 mg/kg dry weight
	water	marine water sediment	0.098 mg/kg dry weight
	soil	-	0.09 mg/kg
	sewage treatment plant	-	35.6 mg/L
3	Reaction mass of xylene and ethylbenzene		- 905-588-0
	water	fresh water	0.327 mg/L
	water	marine water	0.327 mg/L
	water	Aqua intermittent	0.327 mg/L
	water	fresh water sediment	12.46 mg/kg
	water	marine water sediment	12.46 mg/kg
	soil	-	2.31 mg/kg dry weight
	sewage treatment plant	-	6.58 mg/L

## 8.2 Exposure controls

## Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

## Personal protective equipment

## Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

## Eye / face protection

Wear safety goggles to protect against splashes. Safety glasses with side protection shield (EN 166)

## Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material nitrile rubber

Trade name: einzA silicon Grundfestiger

Product no.: 0035939

Current version : 4.0.0, issued: 04.06.2025

Replaced version: 3.0.1, issued: 29.08.2024

Region: GB

Material thickness		0.4	mm
Breakthrough time	>=	480	min

**Other**

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

**Environmental exposure controls**

Do not allow to enter drains or water courses.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

<b>State of aggregation</b>			
liquid			
<b>Form</b>			
liquid			
<b>Colour</b>			
yellow			
<b>Odour</b>			
characteristic			
<b>pH value</b>			
reason for missing pH		substance/mixture is non-soluble (in water)	
<b>Boiling point / boiling range</b>			
Value	>	35.1	°C
<b>Melting point/freezing point</b>			
not determined			
<b>Decomposition temperature</b>			
No data available			
<b>Flash point</b>			
Value	appr.	-17	°C
Method	DIN 51755 Part 1		
<b>Ignition temperature</b>			
No data available			
<b>Oxidising properties</b>			
not fire-propagating			
<b>Explosive properties</b>			
not explosive			
<b>Flammability</b>			
Not applicable			
<b>Lower explosion limit</b>			
No data available			
<b>Upper explosion limit</b>			
No data available			
<b>Vapour pressure</b>			
Value	<	1100	hPa
Reference temperature		20	°C
<b>Relative vapour density</b>			
No data available			
<b>Relative density</b>			
No data available			
<b>Density</b>			
Value	appr.	0.939	g/cm³
Reference temperature		20	°C
<b>Solubility in water</b>			
Comments	miscible		
<b>Solubility</b>			
No data available			
<b>Partition coefficient n-octanol/water (log value)</b>			
No	Substance name	CAS no.	EC no.

Trade name: einzA silicon Grundfestiger

Product no.: 0035939

Current version : 4.0.0, issued: 04.06.2025

Replaced version: 3.0.1, issued: 29.08.2024

Region: GB

1	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
log Pow		1.2	
Reference temperature		20	°C
Method	OECD 117		
Source	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
log Pow		2.3	
Reference temperature		25	°C
Method	OECD 117		
Source	ECHA		
3	Reaction mass of xylene and ethylbenzene	-	905-588-0
log Pow	appr.	3.49	
Reference temperature		30	°C
with reference to	pH >= 5 - <= 8		
Method	OECD 117		
Source	ECHA		
Kinematic viscosity			
Value	>	21	mm <sup>2</sup> /s
Reference temperature		40	°C
Type	kinematic		
Solvent separation test			
Value	<	3	%
Reference temperature		20	°C
Particle characteristics			
No data available			

## 9.2 Other information

Other information
No data available.

## SECTION 10: Stability and reactivity

## 10.1 Reactivity

Stable under recommended storage and handling conditions (See section 7).

## 10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

## 10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

## 10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

## 10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

## 10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

## SECTION 11: Toxicological information

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
LD50		5155	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
LD50		10760	mg/kg bodyweight
Species	rat		
Method	OECD 423		
Source	ECHA		
3	Reaction mass of xylene and ethylbenzene	-	905-588-0
LD50		3523	mg/kg bodyweight
Species	rat		
Method	EU Method B.1		

Trade name: einza silicon Grundfestiger

Product no.: 0035939

Current version : 4.0.0, issued: 04.06.2025

Replaced version: 3.0.1, issued: 29.08.2024

Region: GB

Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
<b>Acute dermal toxicity (result of the ATE calculation for the mixture)</b>	
<b>Product Name</b>	
<b>einza silicon Grundfestiger</b>	
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE dermal > 2000 mg/kg).
<b>Acute dermal toxicity</b>	
<b>No</b>	<b>Substance name</b>
<b>1</b>	<b>2-methoxy-1-methylethyl acetate</b>
	<b>CAS no.</b>
	<b>108-65-6</b>
	<b>EC no.</b>
	<b>203-603-9</b>
LD50	> 5000 mg/kg bodyweight
Species	rat
Method	OECD 402
Source	ECHA
<b>2</b>	<b>n-butyl acetate</b>
	<b>123-86-4</b>
	<b>204-658-1</b>
LD50	> 14112 mg/kg bodyweight
Species	rabbit
Method	OECD 402
Source	ECHA
<b>Acute inhalational toxicity (result of the ATE calculation for the mixture)</b>	
<b>Product Name</b>	
<b>einza silicon Grundfestiger</b>	
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE for inhalation: > 20.000 ppmV (gases), > 20 mg/l (vapours), > 5 mg/l (dusts/mists).
<b>Acute inhalational toxicity</b>	
No data available	
<b>Skin corrosion/irritation</b>	
<b>No</b>	<b>Substance name</b>
<b>1</b>	<b>2-methoxy-1-methylethyl acetate</b>
	<b>CAS no.</b>
	<b>108-65-6</b>
	<b>EC no.</b>
	<b>203-603-9</b>
Species	rabbit
Method	OECD 404
Source	ECHA
Evaluation	non-irritant
<b>2</b>	<b>n-butyl acetate</b>
	<b>123-86-4</b>
	<b>204-658-1</b>
Species	rabbit
Method	OECD 404
Source	ECHA
Evaluation	non-irritant
<b>Serious eye damage/irritation</b>	
<b>No</b>	<b>Substance name</b>
<b>1</b>	<b>2-methoxy-1-methylethyl acetate</b>
	<b>CAS no.</b>
	<b>108-65-6</b>
	<b>EC no.</b>
	<b>203-603-9</b>
Species	rabbit
Method	OECD 405
Source	ECHA
Evaluation	non-irritant
<b>2</b>	<b>n-butyl acetate</b>
	<b>123-86-4</b>
	<b>204-658-1</b>
Species	rabbit
Method	OECD 405
Source	ECHA
Evaluation	non-irritant
<b>Respiratory or skin sensitisation</b>	
<b>No</b>	<b>Substance name</b>
<b>1</b>	<b>2-methoxy-1-methylethyl acetate</b>
	<b>CAS no.</b>
	<b>108-65-6</b>
	<b>EC no.</b>
	<b>203-603-9</b>
Route of exposure	Skin
Species	guinea pig
Method	OECD 406
Source	ECHA
Evaluation	non-sensitizing
<b>Germ cell mutagenicity</b>	



Trade name: einza silicon Grundfestiger

Product no.: 0035939

Current version : 4.0.0, issued: 04.06.2025

Replaced version: 3.0.1, issued: 29.08.2024

Region: GB

No	Substance name	CAS no.	EC no.
1	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
	Type of examination	in vitro gene mutation study in bacteria	
	Method	OECD 471	
	Source	ECHA	
	Evaluation/classification	Based on available data, the classification criteria are not met.	
2	n-butyl acetate	123-86-4	204-658-1
	Source	ECHA	
	Evaluation/classification	Based on available data, the classification criteria are not met.	
3	Reaction mass of xylene and ethylbenzene	-	905-588-0
	Species	Chinese hamster Ovary (CHO)	
	Method	EU Method B.10	
	Source	ECHA	
	Evaluation/classification	Based on available data, the classification criteria are not met.	

**Reproduction toxicity**

No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
	Source	ECHA	
	Evaluation/classification	Based on available data, the classification criteria are not met.	

**Carcinogenicity**

No	Substance name	CAS no.	EC no.
1	Reaction mass of xylene and ethylbenzene	-	905-588-0
	Species	rats (male/female)	
	Method	EU Method B.32	
	Source	ECHA	
	Evaluation/classification	Based on available data, the classification criteria are not met.	

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No	Substance name	CAS no.	EC no.
1	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
	Route of exposure	oral	
	Species	rats (male/female)	
	Method	OECD 422	
	Source	ECHA	
	Evaluation/classification	Based on available data, the classification criteria are not met.	
2	n-butyl acetate	123-86-4	204-658-1
	Route of exposure	inhalational	
	NOAEC	500	ppm
	Duration of exposure	90	day(s)
	Species	rat	
	Method	EPA OTS 798.2450	
	Source	ECHA	
	Evaluation/classification	Based on available data, the classification criteria are not met.	

**Aspiration hazard**

No data available

**Endocrine disrupting properties****Product Name**

einza silicon Grundfestiger

No additional information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

**11.2 Information on other hazards****Other information**

No data available.

**SECTION 12: Ecological information**

Trade name: einza silicon Grundfestiger

Product no.: 0035939

Current version : 4.0.0, issued: 04.06.2025

Replaced version: 3.0.1, issued: 29.08.2024

Region: GB

## 12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
LC50		100	- 180
Duration of exposure			96
Species	Oncorhynchus mykiss		
Method	OECD 203		
Source	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
LC50			18
Duration of exposure			96
Species	Pimephales promelas		
Method	OECD 203		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Toxicity to fish (chronic)			
No data available			
Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
EC50		>	500
Duration of exposure			48
Species	Daphnia magna		
Method	EU Method C.2		
Source	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
EC50			44
Duration of exposure			48
Species	Daphnia magna		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Toxicity to Daphnia (chronic)			
No	Substance name	CAS no.	EC no.
1	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
NOEC		>=	100
Duration of exposure			21
Species	Daphnia magna		
Method	OECD 211		
Source	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
NOEC			23
Duration of exposure			21
Species	Daphnia magna		
with reference to	CAS 110-19-0		
Method	OECD 211		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Toxicity to algae (acute)			
No	Substance name	CAS no.	EC no.
1	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
EC50		>	1000
Duration of exposure			96
Species	Raphidocelis subcapitata		
Method	OECD 201		
Source	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
EC50			397
Duration of exposure			72
Species	Selenastrum capricornutum		
Method	OECD 201		
Source	ECHA		
Toxicity to algae (chronic)			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
NOEC			196

Trade name: einza silicon Grundfestiger

Product no.: 0035939

Current version : 4.0.0, issued: 04.06.2025

Replaced version: 3.0.1, issued: 29.08.2024

Region: GB

Duration of exposure	72	h
Species	Raphidocelis subcapitata	
Method	OECD 201	
Source	ECHA	

Bacteria toxicity			
No	Substance name	CAS no.	EC no.
1	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
EC10	>	1000	mg/l
Duration of exposure		30	min
Species	activated sludge		
Method	OECD 209		
Source	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
IC50		356	mg/l
Duration of exposure		40	h
Species	Tetrahymena pyriformis (Protozoa)		
Source	ECHA		

## 12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
Type	aerobic biodegradation		
Value		83	%
Duration		28	day(s)
Method	OECD 301 F		
Source	ECHA		
Evaluation	readily biodegradable		
2	n-butyl acetate	123-86-4	204-658-1
Type	aerobic biodegradation		
Value		83	%
Duration		28	day(s)
Method	OECD 301 D		
Source	ECHA		
Evaluation	readily biodegradable		
3	Reaction mass of xylene and ethylbenzene	-	905-588-0
Type	aerobic biodegradation		
Value		98	%
Duration		28	d
Method	OECD 301 F		
Source	ECHA		
Evaluation	readily biodegradable		

Abiotic Degradation			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
Type	Photolysis		
Half-life		3.3	day(s)
Reference temperature		25	°C
Source	ECHA		

## 12.3 Bioaccumulative potential

Bioconcentration factor (BCF)			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
BCF		15.3	
Method	Calculation model used (Q)SAR		
Source	ECHA		

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
log Pow		1.2	
Reference temperature		20	°C
Method	OECD 117		
Source	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
log Pow		2.3	
Reference temperature		25	°C
Method	OECD 117		

Trade name: einza silicon Grundfestiger

Product no.: 0035939

Current version : 4.0.0, issued: 04.06.2025

Replaced version: 3.0.1, issued: 29.08.2024

Region: GB

Source	ECHA		
3	Reaction mass of xylene and ethylbenzene	-	905-588-0
log Pow	appr.	3.49	
Reference temperature with reference to		30	°C
Method	pH >= 5 - <= 8		
Source	OECD 117		
	ECHA		

**12.4 Mobility in soil**

No data available.

**12.5 Results of PBT and vPvB assessment**

Results of PBT and vPvB assessment	
Product Name	
einza silicon Grundfestiger	
PBT assessment	According to the information provided in the supply chain: The product contains no components with > 0.1% that are considered PBT.
vPvB assessment	According to the information provided in the supply chain: The product contains no components with > 0.1% that are considered vPvB.

**12.6 Endocrine disrupting properties**

Endocrine disrupting properties	
Product Name	
einza silicon Grundfestiger	
No additional information is available.	

**12.7 Other adverse effects**

No data available.

**12.8 Other information**

Other information
Do not allow to enter drains or water courses.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Product**

Waste code 08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company.

Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

**Packaging**

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

**SECTION 14: Transport information****14.1 UN number or ID number**

ADR/RID/ADN UN1263  
IMDG UN1263  
ICAO-TI / IATA UN1263

**14.2 UN proper shipping name**

ADR/RID/ADN PAINT  
IMDG PAINT  
ICAO-TI / IATA Paint

**14.3 Transport hazard class(es)**

ADR/RID/ADN - Class 3  
Label 3  
Classification code F1  
Tunnel restriction code D/E  
Hazard identification no. 33  
Special Provision 640 640D  
IMDG - Class 3  
Label 3  
ICAO-TI / IATA - Class 3

Trade name: einza silicon Grundfestiger

Product no.: 0035939

Current version : 4.0.0, issued: 04.06.2025

Replaced version: 3.0.1, issued: 29.08.2024

Region: GB

Label	3
<b>14.4 Packing group</b>	
ADR/RID/ADN	II
IMDG	II
ICAO-TI / IATA	II
<b>14.5 Environmental hazards</b>	
EmS	F-E, S-E
<b>14.6 Special precautions for user</b>	
Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	
<b>14.7 Maritime transport in bulk according to IMO instruments</b>	
Not relevant	

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations****Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

**REACH candidate list of substances of very high concern (SVHC) for authorisation**

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

**Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES**

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3, 40
--	----------

**Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances**

This product is subject to Part I of Annex I, risk category:	P5b
--	-----

**Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)**

VOC-value	739 g/l
-----------	---------

**National regulations****Other national regulations**

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

**15.2 Chemical safety assessment**

A chemical safety assessment has not been carried out for this mixture.

**SECTION 16: Other information****Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

**Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)**

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.

**Creation of the safety data sheet**

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

**Trade name:** einza silicon Grundfestiger

**Product no.:** 0035939

**Current version :** 4.0.0, issued: 04.06.2025

**Replaced version:** 3.0.1, issued: 29.08.2024

**Region:** GB

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCÖ GmbH.

Prod-ID 671222